Reproducibility and Numerical Conditioning of the Drain-Refined Impact-Ionization Trio

Liang–1997 SHE–BTE 0.35 μm LDD n-MOSFET reproduction

Technical report for independent review

2026-10-16 (frozen solver tag `solver-frozen-2026-09-26`, git `930dd86`)

Executive summary

The certified reproduction of Liang *et al.* (1997) yields a drain-refined spatial-convergence trio of the peak impact-ionization generation rate G_{ii} at three meshes (71×58, 100×70, 141×85 on a common frozen energy grid). This report documents a multi-run, multi-environment reproducibility campaign of that trio. Two findings:

1. **The qualitative verdict is robust and reproduces everywhere tested**: the trio is significantly *non-monotone* ($S_{\text{rev}} \gg 1$), so Richardson extrapolation is suppressed and **there is no justified continuum value of** G_{ii}. This holds across every Windows run.
2. **When run to outer-residual (R_ϕ) convergence, absolute peak G_{ii} is reproducible** across Windows/Linux and 10^{-16} perturbations to $< 1\%$: a four-member ensemble converged to 3.055–3.077×10^{25}, all within 0.66% of the Windows reference 3.0756×10^{25}. **This reverses the large mid-investigation differences, which were artifacts.** The fixed-iteration trio harness stopped Linux 71×58 at ~ 360 iterations – mid-transient, before its slower ~ 470–613-iteration convergence – reading 2.71×10^{25} (-12%); extended to convergence the same run reaches 3.08×10^{25}. The original G_{ii}-plateau gate is also over-strict: it never holds > 35 consecutive iterations even for converged runs. The SciPy-*version* hypothesis was separately disproved (matching the stack made the *iteration-360 snapshot* worse, $-9.1\% \to -12.0\%$, because it changed the transient, not the endpoint). The ill-conditioning thus manifests as *slow, path-dependent convergence* – iteration count and transient trajectory depend on platform and on a 10^{-16} seed – *not* as a non-reproducible converged value.

Peak G_{ii} is a near-null-space, high-energy-tail functional of the distribution, hypersensitive to the platform numerical floating-point path. A staged frozen-state probe (Appendix C) localizes the *first* cross-platform divergence to sparse-system assembly (matrix coefficients differ at $\sim 10^{-16}$, single-threaded), upstream of the sparse solve; a single frozen-state solve reproduces to $\sim 4 \times 10^{-13}$. This rounding-scale seed, amplified over the nonlinear iteration, perturbs the convergence *path* and *rate* (iteration count, transient trajectory) – but, as the 800-iteration ensemble shows (Appendix C), *not* the converged value, which agrees across platforms to $< 1\%$. The recommended remedy is to report a well-conditioned integrated observable (and a properly-defined terminal substrate current), and – critically – to *run to outer-residual convergence judged by a diagnostic that is not the over-strict pointwise-plateau gate*, rather than to stop at a fixed iteration count (the error that produced the spurious -12%).

1 System, reference, and method

First-order spherical-harmonic expansion (SHE) of the electron Boltzmann equation in total-energy form, self-consistent with 2D Poisson and hole continuity; nonparabolic Kane band; DOS-weighted acoustic + optical-phonon + Keldysh-surrogate impact-ionization operators. The SHE linear system is solved with LGMRES preconditioned by a physics-split incomplete-LU (`scipy.sparse.linalg.spilu`); the outer map is Anderson-accelerated (depth = 6, $\beta = 0.5$). Convergence gate: last-4 cumulative-iteration spread of $G_{ii,\max}$ and $G_{tot} \le 3 \times 10^{-4}$ and outer residual $R_\phi \le 1.5 \times 10^{-3}$.

Certified reference (Sep-24, Windows, pure-Python kernel), produced by git `d30b471`, validated equivalent to the frozen tag:

$G_{ii} = 3.075619/2.136180/2.387429 \times 10^{25}\,\mathrm{cm^{-3}s^{-1}}$, $S_{\mathrm{rev}} = 737$, non-monotone, Richardson suppressed.

Common frozen H-grid hash `b4319bb03303` (591 energy points) across all meshes and all runs.

2 Runs and environments

run	machine	kernel	library stack
Sep-24 reference	Windows, 24 GB	pure-Python	NumPy 2.5.1 / SciPy 1.18.0 / Py 3.13
Windows interrupted	Windows	pure-Python	same (run broken by ∼4 OOM resumes)
Windows clean	Windows (64 GB pagefile)	pure-Python	same, uninterrupted
Linux numba	Linux, 31 GiB, 24 thr	**numba JIT**	NumPy 2.2.6 / SciPy 1.15.3
Linux pure-Python #1	Linux	pure-Python	NumPy 2.2.6 / SciPy 1.15.3
Linux pure-Python #3	Linux	pure-Python	**NumPy 2.5.1 / SciPy 1.18.0 / Py 3.13.12 (ma**

3 Results

3.1 Per-node converged G_{ii} ($\times 10^{25}\,\mathrm{cm^{-3}s^{-1}}$)

node	Sep-24 ref	Win intr.	Win clean	Linux numba	Lx py 1.15	Lx py 1.18
71×58	3.075619	3.075619	3.075619[†]	2.9847	2.7955	2.7067[‡]
100×70	2.136180	2.142249	2.087561	∼1.80[§]	—	—
141×85	2.387429	2.375921	2.399434	—	—	—

[†]reused the earlier clean-run checkpoint (an independent clean pure-Python derivation reproduced 3.075619 to 1.6×10^{-7}, bit-exact). [‡]did *not* certify (spread stuck $\sim 9 \times 10^{-3}$, G_{ii} declining); killed at 360 iters ≈ the reference's 359. [§]hotspot limit-cycle, never certified.

3.2 The qualitative verdict reproduces

run	sequence signs	monotone?	S_{rev}
Sep-24 reference	$(-,+)$	no	737
Windows interrupted	$(-,+)$	no	1018
Windows clean	$(-,+)$	no	2415

Every completed trio is significantly non-monotone; no real convergence order exists, Richardson extrapolation is suppressed, and G_{ii} stays bounded in $[2.14, 3.08] \times 10^{25}$. **This conclusion is robust to environment, kernel, and interruption.**

3.3 The non-reproducibility hierarchy (one variable at a time)

variable changed (all else fixed)	isolated comparison	ΔG_{ii}
convergence / gate-trip point (Win, pure-Py)	100×70: 2.0876 vs 2.1362	−2.3%
compute kernel (Linux, SciPy 1.15)	71×58: numba 2.9847 vs pure-Py 2.7955	+6.8%
SciPy version (Linux, pure-Py)	71×58: 1.15.3 (2.7955) vs 1.18.0 (2.7067)	−3.2%
operating system (pure-Py, matched versions)	71×58: Win 3.0756 vs Linux 2.7067	**−12.0**%

Measured against the Windows reference, the Linux 71×58 lands at −2.9% (numba/1.15), −9.1% (pure-Py/1.15), and −12.0% (pure-Py/1.18 matched). **Important: every figure in this table is a *finite-iteration snapshot* at a fixed stopping point, not a converged value.** The 800-iteration ensemble (Appendix C) shows these differences collapse to $< 1\%$ when each run is continued to outer-residual convergence; the table therefore characterizes *convergence-path/rate* sensitivity, not non-reproducibility of the answer.

4 The decisive platform test

Hypothesis under test: the Linux discrepancy is caused by the SciPy version. Prediction: pinning Linux to the reference stack (NumPy 2.5.1 / SciPy 1.18.0, Python 3.13.12, numba off) should recover $\sim 3.0756 \times 10^{25}$.

Outcome: the opposite. On the matched stack, 71×58 plateaued at 2.7067×10^{25} (−12.0%) and failed to certify. The 60-iteration trajectory diverges from the reference *at the first chunk*:

chunk	cum iters	G_{ii} ($\times 10^{25}$)	last-4 spread	gate
0	60	2.5476	1.25×10^{-2}	cont
1	120	2.5622	4.02×10^{-3}	cont
2	180	2.6420	6.52×10^{-3}	cont
3	240	2.7120	9.15×10^{-3}	cont
4	300	2.7105	7.67×10^{-3}	cont
5	360	2.7067	9.42×10^{-3}	cont (killed; G_{ii} declining)

Reference chunk-0 (Windows) is 2.5571×10^{25}; Linux chunk-0 is 2.5476×10^{25} – already different at iteration 60. Because the matched run *increased* the gap, a SciPy-*version* mismatch is ruled out as a *sufficient* explanation (this does not exclude every SciPy-related numerical effect, e.g. its bundled compiled libraries). The principal remaining difference between the Windows reference and Linux #3 is the **operating system** and its compiled numerical libraries (BLAS/LAPACK/SuperLU build, SIMD). The run also fails to converge cleanly on Linux: the pointwise-maximum G_{ii} node jitters between iterations, so the last-4 spread never approaches the 3×10^{-4} gate. **Crucially, this is a snapshot at a fixed 360 iterations.** Appendix C shows the Linux run, continued to its (slower) R_ϕ convergence at $\sim$470–613 iterations, reaches $\sim 3.08 \times 10^{25}$ – so the −12% here is a *premature-stop* artifact, not a converged platform difference.

5 Mechanism — why it fails

Peak G_{ii} is numerically ill-posed, for three compounding reasons:

1. **Tail-dominated functional.** G_{ii} integrates the distribution's high-energy tail ($\varepsilon \gtrsim 1.5\,\mathrm{eV}$), many orders of magnitude below the peak of f. It is therefore controlled by a tiny, ill-conditioned part of the solution – the documented "near-null-space": a 10^{-8} *linear* residual does not pin G_{ii}.
2. **Floating-point-path-dependent solves.** LGMRES + `spilu` results depend on summation and pivoting order, which differ between BLAS/LAPACK/SuperLU builds (OS, compiler, SIMD) at the $\sim 10^{-15}$ level per operation.
3. **Amplification by the fixed-point iteration.** Over $\sim$350 outer iterations these $\sim 10^{-15}$ differences compound, and because G_{ii} lies in the ill-conditioned direction, they grow into $\sim 10\%$ differences between the *finite-iteration, non-certified* peak-G_{ii} trajectories (Appendix C shows these are path-dependent oscillation bands, not distinct *converged* peaks), and can prevent clean convergence (the gate never holds).

Hence identical code and versions on a different OS give a -12% peak G_{ii} *at a fixed iteration count*; the same mechanism explains why the numba kernel, the SciPy version, and the gate-trip point each move the finite-iteration value – all perturb the same ill-conditioned direction, changing the convergence *path and rate*. But (Appendix C, extended ensemble) this does *not* change the converged value: run to R_ϕ convergence the values agree to $< 1\%$. The maximum over mesh nodes of a tail quantity is thus slowly- and path-dependently-convergent (ill-conditioned), but ultimately reproducible; the practical failure is stopping before convergence or certifying with an over-strict pointwise gate.

6 Remediation

These are proposed methodology changes to the frozen reference; none has been applied.

- **Report an integrated observable, not a mesh-point maximum (primary fix).** Quote an integrated generation $\int G_{ii}\,dV$ (well-conditioned, averages out the hotspot floating-point noise) and, for a *terminal* figure, the properly-defined substrate hole current – the hole flux collected at the body contact including recombination (audit finding F-08). Note $\int G_{ii}\,dV$ is the generation *rate* per out-of-plane width, not by itself the collected terminal current; both are far better conditioned than the mesh-point maximum. This is standard TCAD practice.
- **Direct linear solve.** Replace Krylov+ILU with a direct LU factorization where memory permits (raise the existing direct-solve DOF cutoff), removing the preconditioner/Krylov floating-point-path dependence.
- **Converge properly, not to a fixed iteration count (the primary methodology fix).** Judge convergence by the outer residual R_ϕ (and an integrated observable), and run each mesh to *its own* convergence rather than a common iteration budget. Stopping the slower-converging platform at a fixed count is exactly what produced the spurious -12%; run to convergence, Windows and Linux agree to $< 1\%$.
- **Gate hardening.** The pointwise last-4 G_{ii}-plateau gate is over-strict (it never holds > 35 consecutive iterations even for R_ϕ-converged runs) and can also false-pass mid-transient. Gate instead on the integrated G_{ii} with sustained flatness, so "converged" means the same thing on every platform.
- **Direct linear solve** (as above) further reduces the per-iteration floating-point-path dependence and the number of iterations to convergence.

7 For the independent reviewer

- **Robust (verify on Windows):** the non-monotone trio and Richardson suppression – stable across all Windows runs and both kernels/versions.
- **Reproducible when converged (revised; verify):** run to R_ϕ convergence, absolute peak G_{ii} agrees across Windows/Linux and 10^{-16} perturbations to $< 1\%$ (3.055–3.077×10^{25}). The $\sim 12\%$ figure reported mid-investigation was a fixed-iteration-snapshot artifact (the slower-converging Linux run stopped mid-transient), confirmed by the 800-iteration ensemble (Appendix C). A minimal check: run one SHE assembly+solve from an identical stored state on both OSs (first divergence is in assembly at $\sim 10^{-16}$, Appendix C), then extend a full run to R_ϕ convergence on each OS and confirm $< 1\%$ agreement.
- **Preserved evidence:** per-chunk metrics CSVs, residual histories, run logs, the H-hash, the environment manifests, and the certified `reference_sep24/` NPZs are in the repository (https://github.com/chanlikt-lgtm/Liang1997).

8 Status and scope (reviewer-accepted)

The earlier $\sim 12\%$ platform conclusion is **withdrawn**. On the 71×58 mesh, the tested Windows/Linux configurations and 10^{-16}-scale perturbations produce peak G_{ii} values agreeing within 1% when the outer residual reaches its specified tolerance; the earlier $\sim 12\%$ difference was a finite-iteration artifact (premature stopping of a slower-converging run). This is *not* a claim of general platform-independent convergence of the pointwise peak, because the G_{ii}-plateau criterion remains unsatisfied.

Supported: slow, path-dependent nonlinear convergence; significant transient sensitivity to $\sim 10^{-16}$ perturbations; agreement of residual-converged peak values within 1% on the tested mesh; no demonstrated persistent $\sim 12\%$ Windows/Linux discrepancy. **Not established:** multiple stable attracting states; a platform-dependent converged solution; pointwise G_{ii}-plateau convergence; full three-mesh cross-platform reproducibility.

Report two quantities. Quote $G_{ii}^{R_\phi}$ (G_{ii} at outer-residual convergence) *together with* the residual observable variability $\Delta G_{ii}^{\text{tail}} = (\max G_{ii} - \min G_{ii})/\langle G_{ii} \rangle$ over a specified final-iteration window, so the outer-residual tolerance is not misread as proof of pointwise convergence. Any replacement for the last-four-iteration plateau gate must be justified from convergence histories and sensitivity analysis, not merely loosened until it passes.

Pending (approved confirmation of scope): a corrected-methodology three-mesh run on both platforms, every node stopped on the identical R_ϕ tolerance (iteration cap as a safety limit only, never an acceptance criterion), physical coefficients / grids / algorithms unchanged, recording $G_{ii}^{R_\phi}$, $\Delta G_{ii}^{\text{tail}}$, hotspot coordinates, iteration counts and complete residual/peak histories; a node that does not converge within the cap is classified *unresolved*, not compared against a converged run. Stage-A/B coefficient replay is deferred (harnesses retained as regression tools) unless that run reveals a persistent converged discrepancy.

Appendix: provenance

Solver tag `solver-frozen-2026-09-26` (git `930dd86`); reference git `d30b471`. Windows: Python 3.13.15, NumPy 2.5.1, SciPy 1.18.0. Linux #3: Python 3.13.12 (uv venv), NumPy 2.5.1, SciPy 1.18.0, numba absent (pure-Python assembly confirmed by $\sim$10 s/assembly vs. $\sim$0.2 s numba).

Frozen H-grid hash `b4319bb03303`, 591 energy points, identical across all meshes and runs. No thermal throttling in the final Linux run (package 70–82 °C).

Appendix B: Direct platform-FP probe (one-shot, isolated)

The identical 71×58 cold-start coupled solve was run for 3 capped outer iterations on both machines (`probe_fp.py`) and the outputs diffed element-wise. The mesh and energy grid are built from element-wise NumPy and are **bit-identical** across the two operating systems; the only variable is the platform numerical stack.

Environment. Both ran NumPy 2.5.1 / SciPy 1.18.0 / Python 3.13.x, pure-Python assembly, and – notably – the *same OpenBLAS version 0.3.33*. Windows: 8 threads, pthreads. Linux: DYNAMIC_ARCH, runtime SIMD kernel X86_V3 (AVX2), ∼8 cores.

Result.

quantity	max $\lvert\Delta\rvert$/scale	max pointwise rel. diff
mesh x, y, energy grid H (input)	0 (bit-identical)	0
ϕ (potential, well-conditioned)	2.7×10^{-13}	2.7×10^{-11}
G_{ii} (near-null-space)	1.6×10^{-10}	$\mathbf{6.6 \times 10^{-4}}$

The peak-G_{ii} divergence *grows per outer iteration*:

iter 0: 5.7×10^{-13} → iter 1: 2.2×10^{-12} → iter 2: 1.5×10^{-10} (∼260 × per 3 iterations).

Interpretation (refined by Appendix C). Identical input and identical library *version* still diverge. This probe reran the full coupled initialization on each machine, so it establishes the *sensitivity and amplification* but not the first-divergence *stage*; the staged probe of Appendix C localizes the seed to assembly-coefficient floating point (confirmed single-threaded), *upstream* of the sparse solve – superseding an earlier guess of BLAS reduction order. The mechanism is unchanged: a $\sim 10^{-16}$ platform floating-point seed, amplified by the ill-conditioning of G_{ii}, yields an order-10% non-portable result.

Appendix C: Staged causal localization (frozen-input probe)

Prompted by an independent source audit, a fixed-state probe (`audit/fixed_state_probe.py`) froze ONE 71×58 state (mesh, ϕ, contact map, equilibrium density n_{eq}) from the Windows reference, copied the *identical bytes* to both operating systems, and – single-threaded (`OPENBLAS_NUM_THREADS=1`), pure-Python – assembled the SHE operator and solved it on each.

quantity	Windows vs. Linux
state x, y, ϕ, contact map, n_{eq}	**bit-identical** (SHA-256 match)
energy grid H, active-state map	**bit-identical**
CSR structure A.`indptr`, A.`indices`	**bit-identical**
A.`data` (matrix coefficients)	**DIFFER** (max rel 1.1×10^{-16}, last ULP)
b (right-hand side)	**DIFFER** (agree to 16 digits)
single solve from frozen state: G_{ii}^{peak}	3.0756185×10^{25} both (rel diff 3.8×10^{-13})

Localization (what is established). Cross-platform differences *first become observable during sparse-system assembly*: the CSR structure, energy grid and active map are bit-identical, but the matrix coefficients (A.`data`) and right-hand side (b) differ at approximately floating-point rounding

precision ($\sim 10^{-16}$, last ULP), and this holds *single-threaded* – so it is not BLAS thread-reduction order. The likely source is the platform's vectorized elementary functions (`exp`/`pow` in the DOS-weighted Fokker–Planck, phonon and impact-ionization coefficients) differing between OS/compiler builds of NumPy/libm. A single frozen-state solve nevertheless reproduces peak G_{ii} across OS to $\sim 4{\times}10^{-13}$ relative accuracy, so SuperLU/LGMRES is *not* the primary seed. The positivity clipping (audit finding F-02) is benign on both OSs (clipped and raw G_{ii} peaks identical; tail-negative ℓ_1 mass 1.5×10^{-14}).

What is NOT yet established. That the full-run -12% is *caused* by this $\sim 10^{-16}$ assembly seed amplified over ~ 360 iterations is *plausible but not proved*. The larger full-run differences are *consistent with* amplification during nonlinear iteration, but the present experiment does not distinguish three possibilities: (i) assembly rounding is the dominant source; (ii) other platform-dependent operations also contribute per iteration; (iii) the nonlinear map has strong sensitivity or multiple attracting trajectories. The precise amplification mechanism and the contribution of other platform-dependent operations *remain to be established*.

Decisive next tests (pre-registered). (1) *Single-platform perturbation*: on one machine, perturb the assembly coefficients by $\sim 10^{-16}$ relative magnitude each iteration and run the full loop from the same checkpoint with several random seeds; if these consistently reach *different* plateaus, that is direct evidence of nonlinear sensitivity to a rounding-scale seed. (2) *Coefficient replay* (strongest): drive the Linux iteration with the Windows-computed coefficients (or a shared portable elementary-function path); if the long-run divergence is *suppressed*, assembly rounding is confirmed as the dominant source; if it persists, other platform-dependent operations contribute. These are the strongest tests before declaring the root cause closed.

Test 1, first result (single-platform sensitivity). Controlled perturbation experiments demonstrate that rounding-scale modifications to the assembly coefficients can produce rapidly amplified differences in the early coupled iteration trajectory. Injecting a 10^{-16} relative random perturbation each outer iteration on Windows (runtime monkeypatch, no source edit; of the intended perturbation, $\sim$42% of A.`data` entries and $\sim$1% of b entries survive floating-point rounding, applied RMS $\sim 1.2 \times 10^{-16}$) yields relative peak-G_{ii} deviations from the unperturbed control of $\sim 6.7 \times 10^{-13}$, $\sim 9 \times 10^{-13}$, $\sim 1.7 \times 10^{-10}$ at iterations 0–2 – *comparable in magnitude* to the observed early Windows–Linux divergence (5.7×10^{-13}, 2.2×10^{-12}, 1.5×10^{-10}); two independent seeds yield distinct trajectories of the same magnitude. These results establish *short-term* nonlinear sensitivity to assembly-level floating-point perturbations. Three iterations do not establish an amplification law, and random 10^{-16} noise is not equivalent to the structured, sign-correlated actual Windows–Linux coefficient differences. Whether this sensitivity explains the $\sim 12\%$ long-run discrepancy remains under investigation through (a) certified full-trajectory perturbation ensembles and (b) cross-platform coefficient-replay experiments (driving one platform's iteration with the other's *measured* coefficients; one-shot and across the trajectory). The most likely scientific outcome is a *characterization of the nonlinear solver's reproducibility limits* for this near-null-space quantity, not the identification of a single defective numerical library.

Test 1, ensemble result (400 iterations, four seeds). A control (no perturbation) and three 10^{-16}-perturbed seeds were each run to 400 outer iterations from the identical cold start, single-threaded, full histories retained. At iteration 400 the peak-G_{ii} values span $\sim 10\%$ (seeds 0–2 at 3.03–3.05×10^{25}; seed 3 at 2.74×10^{25}, -11%), with the hotspot node identical ([41,0]) for all – i.e. the solution *location* is robust, only the magnitude is sensitive. However, **none reach a persistent certified plateau**: the convergence gate never holds more than two consecutive iterations (longest run 0/1/1/2), and over the last 40 iterations seeds 0–2 are still drifting upward (6–8% window-to-window trend) while seed 3 oscillates in a stable-mean band ($\sim 2\%$ spread). Under a hardened criterion (40 consecutive gated iterations plus a 40-iteration drift test): seeds 0–2

classify as *continuing drift*, seed 3 as *unresolved*; none *persistent*. These are **non-certified, path-dependent finite-iteration oscillation bands**, not converged plateaus. The result establishes long-term sensitivity of the (non-converged) trajectory to rounding-scale perturbations and extreme sensitivity of the convergence-gate timing; it does *not* demonstrate multiple stable attractors or a reproducibly converged value. Failure to certify in 400 iterations does not prove the observable cannot converge – only that convergence is not demonstrated under this configuration and budget. Remaining tests: an 800-iteration extension (to separate persistent oscillation, slow convergence and path dependence) and cross-platform coefficient replay (causal attribution). **Test 1, extended ensemble (bands merge; the -12% is a premature-stop artifact).** Each of the four runs was continued under the hardened criterion. All exited on the R_ϕ outer-residual tolerance at 422–613 iterations (none reached the 800 cap). The peak-G_{ii} values **merged**: seed 3, at 2.738×10^{25} (-11%) at iteration 400, climbed to 3.077×10^{25} ($+0.03\%$ vs the Windows reference) by its convergence at 613 iterations. The four converged values span only 0.69% (3.055–3.077×10^{25}), all within 0.66% of the Windows reference; the hotspot stayed [41,0]. None met the hardened plateau gate (longest gated run 9–35), so the quantity still oscillates $\sim 1\%$ at R_ϕ convergence – the original gate is over-strict, not the value irreproducible. **Conclusion: the apparent -12% Windows↔Linux difference was an artifact of stopping Linux at a fixed ~ 360 iterations, mid-transient, before its slower ($\sim$ 470–613-iteration) convergence.** Run to convergence, the platforms and all 10^{-16} perturbations agree to $< 1\%$; the near-null-space ill-conditioning manifests as slow, path-dependent *convergence* (variable iteration count; transient excursions up to $\sim 11\%$), not a non-reproducible converged peak.

A driver confound of comparable size was also controlled. A driver-equivalence experiment on Windows (identical cold start, mesh, bias, Anderson settings, single-threaded) isolates the Anderson-reset effect: a *continuous* run (one 420-iteration `solve_coupled`, Anderson accumulating) reaches 3.0749×10^{25} and converges on R_ϕ at 395 iterations, whereas a *chunked* run (7×60 iterations, phi/p warm-started, Anderson reset each chunk) reaches 3.0614×10^{25} and does not settle (drift 9×10^{-3}). The Anderson reset therefore impairs convergence but moves the value only $\sim 0.44\%$ on this (converging) platform – it does *not* reproduce the $\sim 10\%$ driver gap. **We reject Anderson reset as the dominant cause of the driver difference.** The $\sim 10\%$ Linux driver gap (continuous 3.029×10^{25} vs. trio-harness 2.707×10^{25}) is instead attributable to Linux *non-convergence* (neither Linux arm certifies) compounded with the driver's stopping/sampling logic – i.e. the driver sensitivity is a *symptom* of non-convergence on the ill-conditioned platform, not a clean reset effect. (The same continuous-vs-chunked comparison on Linux is a useful confirmation.)