

Derivation and Numerical Reproduction of Liang, Goldsman, Mayergoyz & Oldiges (1997): 2-D Deterministic SHE-Boltzmann MOSFET Simulation

*Complete report, Revision 3 — coupled state with quantitative comparison against
Liang's figures*

Reproduction study (code commit 0994290+overlays; Python 3.13.14, NumPy 2.5.1, SciPy 1.18.0)

August 15, 2026

Abstract

This report derives and numerically reproduces the deterministic spherical-harmonic (SHE) Boltzmann device solver of Liang *et al.*, *IEEE Trans. Electron Devices* **44**(2), 257–267 (1997). Revision 2 superseded the earlier one-way/post-processed description: impact ionization is now *inside* the assembled electron collision operator (primary depletion + secondary redistribution), the self-consistent SHE $\leftrightarrow$ Poisson $\leftrightarrow$ hole-continuity loop is *demonstrated and observably converging*, global number- and terminal-current-conservation diagnostics are in place, and a physics-split preconditioner removes the previous solver bottleneck (~ 10 min $\rightarrow \sim 15$ s on the 40×34 problem). Established results: core transport (n , $|v|$, T_e) is validated and spatially robust; the self-consistent feedback materially suppresses avalanche generation and drain current while leaving T_e comparatively stable; conservation holds across one-way, refined, and coupled runs. Open items are stated precisely: the impact-ionization magnitude is *not spatially converged* — a 2×2 grid $\times$ coupling study drives $G_{ii,\max}$ multiplicatively from 1.35×10^{27} to 5.24×10^{26} cm $^{-3}$ s $^{-1}$ (the finest-tested coupled value, not a continuum estimate), while a one-way energy refinement to $\Delta H = 6.25$ meV moves it only -2.4% (negligible beside the spatial error); the T_e/G_{ii} peak offset is unresolved; and the device has been recalibrated to $V_{th} = 0.614$ V for the quantitative Liang overlays. The robust reproductions are the transport moments and the ($\sim 37\%$) self-consistent G_{ii} -feedback fraction — the latter now *confirmed* on the recalibrated $V_{th} = 0.614$ V device (-36%), where the higher overdrive raises the absolute (still grid-unconverged) generation to 1.34×10^{27} . **Revision 3** adds the quantitative overlays themselves (§10): placed on Liang's *own* published Fig. 7 contour levels, the recalibrated coupled fields reach $T_{e,\max} = 3598$ K (72% of Liang's top 5000 K contour) and $G_{ii,\max} = 1.34 \times 10^{27}$ (58% of the top 2.3×10^{27}), both drain-localized with the correct structure (T_e region much broader than G_{ii}), while the drift-diffusion terminal I-V reproduces the Fig. 8 triode $\rightarrow$ saturation form and V_{gs} ordering; a per-plot comparison table is given for each of Liang's Figs. 2–8. Every model element is classified as *paper-specified*, *reconstruction*, *surrogate*, or *not-yet-converged*.

Contents

1	Overview and audit provenance	2
I	Method derivation and validated foundation	2
2	First-order SHE equation	2

3	Reconstructed device, taxonomy, foundation	3
II	The 2-D SHE core, impact ionization, and self-consistency	3
4	Assembled operator, impact ionization, and moments	3
5	Numerics: physics-split preconditioner	4
6	Numerical audit of the one-way baseline	4
7	Grid refinement (40×34 vs 60×50 , one-way)	4
8	Self-consistent SHE $\leftrightarrow$ Poisson $\leftrightarrow$ hole loop	5
9	G_{ii} convergence matrix and device recalibration	5
10	Quantitative comparison with Liang’s published figures	6
III	Assessment	9
11	Conclusions, classified	9
A	Numerical and model specifications	11
B	Provenance and audit history	11

1 Overview and audit provenance

Liang *et al.* solve, self-consistently, three coupled equations on a 2-D MOSFET cross-section: Poisson, the electron BTE (first-order SHE), and hole continuity with an impact-ionization pair-generation source. This reproduction has passed through four external audit rounds and three code patches (Appendix B); the present revision documents the resulting coupled state and its quantitative comparison against Liang’s figures.

Honesty note. Model substitutions carried throughout and classified in Table 1: the doping profile is a *reconstruction*; the band is a 1-parameter Kane *surrogate* (paper: 2-band Fiegna/Brunetti); the impact-ionization rate is a Keldysh *surrogate*; the momentum time τ_1 is a single calibrated surrogate (not a summed Table-I model); and the device V_{th} , initially an over-high 1.64 V, is recalibrated to 0.614 V (§9) for the quantitative overlays (§10).

Part I

Method derivation and validated foundation

2 First-order SHE equation

With $\mathbf{E} = -\nabla_{\mathbf{r}}\phi$, expand $f = f_0(\mathbf{r}, \varepsilon) + \hat{\Omega} \cdot \mathbf{f}_1(\mathbf{r}, \varepsilon)$ (all $\ell \geq 2$ discarded). Projection gives the current relation and the conservative augmented-space balance

$$\mathbf{f}_1 = -\tau_1 v (\nabla_{\mathbf{r}} f_0 - q \mathbf{E} \partial_{\varepsilon} f_0), \quad \nabla_{\mathbf{r}} \cdot \mathbf{j}_x + \partial_{\varepsilon} j_{\varepsilon} = Z \mathcal{Q}[f_0] + Z S_{\text{gen}}, \quad (1)$$

$\mathbf{j}_x = -ZD(\nabla_{\mathbf{r}}f_0 - q\mathbf{E}\partial_{\varepsilon}f_0)$, $D = \frac{1}{3}v^2\tau_1$. In total energy $H = \varepsilon - q\phi$ this becomes pure spatial diffusion at fixed H , the collision operator coupling $H \leftrightarrow H \pm E_{op}$ locally in space, over the global mesh $-q\phi_{max} \leq H \leq \varepsilon_{max} - q\phi_{min}$ with mask $0 \leq H + q\phi \leq \varepsilon_{max}$; $\varepsilon = 0$ reflecting, ε_{max} absorbing. The DOS-weighted acoustic operator $\mathcal{Q}_{ac} = Z^{-1}\partial_{\varepsilon}[ZA(\partial_{\varepsilon} + 1/k_BT)f_0]$ (Scharfetter–Gummel) makes the collision term irreducible; it is number-conserving (defect 7.6×10^{-17}) with the Maxwellian as its exact null.

3 Reconstructed device, taxonomy, foundation

The 0.35 μm LDD NMOS uses error-function junctions ($x_j = 0.170 \mu\text{m}$ metallurgical). Foundation checks (all at $T = 300 \text{ K}$): equilibrium Poisson (built-in $+0.586 / -0.44 \text{ V}$, quadratic Newton); nonparabolic $N_c = 2.857 \times 10^{19}$ (0.1% of the independent value; parabolic limit 0.09% of closed form); bulk scattering engine detailed-balance 2×10^{-5} , zero-field $T_e \rightarrow 309.7 \text{ K}$, monotone heating. The DD solve at $V_{gs} = V_{ds} = 3 \text{ V}$ gives the operating-point potential driving the SHE.

Table 1: Modelling taxonomy (Rev. 2 adds a *not-yet-converged* class).

Element	Class	Basis / status
Method eqs., SHE reduction, moments	paper	Liang <i>et al.</i>
Table-I params, spherical band	paper	paper Sec. II
$L_{\text{eff}}, t_{ox}, x_j, N_D^{\pm}$	paper	paper text
1-param Kane $\gamma(\varepsilon)$	surrogate	paper: 2-band Fiegna/Brunetti
LDD doping shape, mesh	reconstruction	ref. [7] unavailable
Channel $N_A, \Phi_{gate}, \tau_1, c_{op}, 1/\tau_{ii}$	surrogate	calibrated; disclosed
$G_{ii, \text{max}}$ magnitude	not-yet-converged	spatially unconverged; 5.24×10^{26}
T_e/G_{ii} peak offset	not-yet-converged	(coupled 60×50), still dropping
	not-yet-converged	unresolved at present mesh

Part II

The 2-D SHE core, impact ionization, and self-consistency

4 Assembled operator, impact ionization, and moments

The solver discretizes the $(\mathbf{r}, H)$ equation by box integration; contributions (spatial diffusion $\times \Delta H$, optical in/out $\times A_{ij} \Delta H$, acoustic SG flux $\times A_{ij}$) share units and form a positive-diagonal system. Contacts inject a Maxwellian $f_0 = n_{\text{contact}} e^{-\varepsilon/k_BT} / \int Z e^{-\varepsilon/k_BT} dH$.

Impact ionization in the electron BTE. An event removes a primary electron at rate $1/\tau_{ii}(\varepsilon)$ (Keldysh surrogate, $\varepsilon_{th} = 1.1 \text{ eV}$) and deposits two secondaries at $\varepsilon' = (\varepsilon - \varepsilon_{th})/2$, linearly distributed onto the neighbouring H nodes, with net electron gain $+1$ per event. This is *assembled into the electron collision operator* (primary depletion + secondary redistribution), so f_0 is directly shaped by avalanche; $G_{ii} = \int Z f_0 / \tau_{ii} d\varepsilon$ is a moment of that II-affected distribution. The equal kinetic-energy split of the two secondaries, and the fact that this scattering-in term leaves the f_0 shape essentially unchanged, follow Liang *et al.* (§IV) directly. The absorb-

ing ε_{max} cutoff acts on spatial, acoustic, and optical fluxes. Moments n , $\langle \mathbf{v} \rangle$, T_e , G_{ii} , and the terminal currents are reconstructed from the *same finite-volume face fluxes* as the operator.

5 Numerics: physics-split preconditioner

The large-grid system is solved by a multiplicative physics-split preconditioner. Because DOFs are numbered with H fastest, same-spatial-cell couplings (acoustic + optical + II redistribution + spatial diagonal) form contiguous local energy blocks — the **E block** — factored cheaply; the diagonal plus cross-cell couplings form the fixed- H real-space **S block**. One application does $E^{-1} \rightarrow S^{-1} \rightarrow E^{-1}$ with a fresh residual between stages; the solved matrix is never shifted (shifts touch only preconditioner factors). On the 328 544-DOF 40×34 problem this solves to 10^{-10} in ~ 15 s (raw scaled residual 1.22×10^{-11}), where the previous global ILU did not finish its setup in 120 s. The legacy path is retained as `method="legacy_ilu"` for regression.

6 Numerical audit of the one-way baseline

Table 2 is the extracted audit of the locked one-way reference (commit `f016e3c`); it is preserved as a regression benchmark.

Table 2: Clean 40×34 numerical audit (impact ionization in the collision operator).

Quantity	Value	Location / note
$n_{\max}$	$1.0516 \times 10^{20} \text{ cm}^{-3}$	source n^+ (0.082, 0.043)
$T_{e,\max}$	3232.9 K	drain (0.595, 0.005)
$G_{ii,\max}$	$1.3513 \times 10^{27} \text{ cm}^{-3} \text{ s}^{-1}$	drain (0.595, 0.009)
$ v _{\max}$	$9.732 \times 10^6 \text{ cm/s}$	drain surface (0.554, 0)
$T_e - G_{ii}$ peak separation	5 nm (~ 1 cell)	co-located within mesh
SHE currents I_{src}/I_{drn}	$-1.7044/ + 1.7071 \times 10^{-4} \text{ A}/\mu\text{m}$	mismatch 0.16%
global continuity residual	-5.70×10^{-6} (relative)	—
orphan states	0	no artificial sinks
f_0 pre-clip min	-3.3×10^{-11}	46/328544 tiny negatives

7 Grid refinement (40×34 vs 60×50 , one-way)

Refining the spatial mesh at fixed $\Delta H = 12.5 \text{ meV}$:

Quantity	40×34	60×50	converged?
$n_{\max}$	1.0516×10^{20}	1.0473×10^{20}	yes (-0.4%)
$ v _{\max}$	9.73×10^6	10.0×10^6	yes ($+2.7\%$)
$T_{e,\max}$ [K]	3232.9	3423.0	moderate ($+5.9\%$)
$G_{ii,\max}$	1.3513×10^{27}	8.26×10^{26}	no (-40%)
T_e/G_{ii} separation	1 cell	2 cells	grid-scale (unresolved)
current mismatch / residual	0.16% / 5.7×10^{-6}	0.07% / 7.6×10^{-6}	conserved

Transport (n , $|v|$, T_e) is spatially robust; G_{ii} is *not* grid-converged (it depends on the high-energy tail); and the peak separation tracks the mesh, so it is unresolved, not a reproduced physical offset.




Figure 1: One-way SHE moments (40×34). n (Fig. 3), velocity field saturating at 9.73×10^6 cm/s (Fig. 4; masked where $n < 10^{13}$ cm $^{-3}$), T_e (Fig. 7 dashed, drain-localized), G_{ii} (Fig. 7 solid, drain-localized).

8 Self-consistent SHE $\leftrightarrow$ Poisson $\leftrightarrow$ hole loop

A damped outer iteration solves the SHE (with impact ionization) on the current potential, drives hole continuity with G_{ii} as pair generation (holding n_{SHE}), updates Poisson from the SHE density, damps, and repeats; n is recomputed from the SHE after each potential update (not constitutively from DD). Over 12 iterations (Fig. 2) the maximum potential update falls monotonically $17.7 \rightarrow 4.0$ mV, and the physical observables plateau: $G_{ii,\text{max}}$ is suppressed 37% ($1.35 \rightarrow 0.85 \times 10^{27}$) and the drain current 29% ($1.71 \rightarrow 1.21 \times 10^{-4}$ A/ μm), while $T_{e,\text{max}}$ stays ~ 3240 K. This is the physically expected negative feedback: the SHE electrons and the G_{ii} -generated holes reshape the potential, lowering the peak drain field and throttling avalanche. Final conservation is clean (relative number balance 2.4×10^{-5} , currents balance 0.14%).

Honesty note. The loop is *demonstrated and observably converging*, not converged to the prescribed tolerance: the plateaued observables are meaningful, but $\max |\Delta\phi| \approx 4$ mV remains above the chosen 2 mV stopping criterion. Tighter convergence needs more iterations or reduced damping.

9 G_{ii} convergence matrix and device recalibration

Combining one-way and coupled runs at both grids isolates how the impact-ionization magnitude responds to spatial refinement and to self-consistency (Table 3). The spatial ratios ($8.26/13.5 = 0.612$ one-way, $5.24/8.50 = 0.616$ coupled) and the coupling ratios ($8.50/13.5 = 0.630$ at 40×34 , $5.24/8.26 = 0.634$ at 60×50) agree to $\sim 1\%$ (ratio-of-ratios 1.0085): the two effects are *multiplicatively separable to that precision* over the tested meshes, and $1.35 \times 10^{27} \times 0.612 \times 0.630 =$




Figure 2: Self-consistent loop (40×34). Potential update converges $17.7 \rightarrow 4.0$ mV; feedback suppresses G_{ii} 37% and I_d 29% (both plateauing) while T_e stays stable.

5.20×10^{26} predicts the observed 5.24×10^{26} . The coupled result is *still* spatially unconverged (coupled $40 \times 34 \rightarrow 60 \times 50$: -38% , no plateau), and, like the 40×34 loop, the coupled 60×50 outer iteration ended above the 2 mV $\max|\Delta\phi|$ criterion (observably converging, not formally converged).

Table 3: $G_{ii,\max}$ [$\text{cm}^{-3}\text{s}^{-1}$] over grid $\times$ coupling (original device).

	one-way	self-consistent
40×34	1.35×10^{27}	8.50×10^{26}
60×50	8.26×10^{26}	5.24×10^{26}

A *one-way* energy refinement to $\Delta H = 6.25$ meV ($E_{op} = 8$) moves $G_{ii,\max}$ only -2.4% ($T_e -0.19\%$) — *negligible beside* the -38 – 40% spatial error — so the dominant numerical uncertainty is resolving the drain-side high-field/high-energy hotspot in real space rather than the energy axis. (The energy test was performed one-way, not on the coupled configuration in which the spatial sensitivity was measured, so we state energy insensitivity, not a proof of purely-spatial error.) 5.24×10^{26} is thus the *finest-tested coupled value*, not an estimate of the continuum limit: with a -38% change under the last spatial refinement there is no numerical basis to quote a converged G_{ii} . The robust results are the transport moments and the ($\sim 37\%$, grid-independent) feedback fraction.

Device recalibration. A rigid gate offset $\Phi_{gate} = -0.74$ V ($dV_{th}/d\Phi_{gate} \approx +1$) recalibrates the extracted threshold to $V_{th} = 0.614$ V (was 1.64 V); the $V_g = 3$ V overdrive becomes 2.39 V. The coupled 60×50 operating point on this device converges the observables ($n_{\max} = 1.01 \times 10^{20}$, $T_{e,\max} = 3598$ K, $I_d = 0.24$ mA/ μm , currents balance 0.02%, final $\max|\Delta\phi| = 7.5$ mV) and *preserves the G_{ii} -feedback fraction* (-36% vs. -37% on the old device; current suppression -55% at the higher overdrive). The higher overdrive raises the absolute $G_{ii,\max}$ to 1.34×10^{27} ($\sim 2.5\times$ the old-device coupled value, from more inversion/heating) — device-dependent and still grid-unconverged. This recalibrated operating point is the basis for the quantitative Liang overlays of §10.

10 Quantitative comparison with Liang’s published figures

The recalibrated coupled 60×50 solution (§9, $V_{th} = 0.614$ V) is compared to Liang *et al.*’s figures below, with *one comparison table per plot* (Figs. 2–8, Tables 4–10). Where Liang give labelled contour values (Fig. 7) the comparison is on those values; otherwise it is on peak magnitudes, locations, and structure. Liang’s Fig. 7 levels are $T_e \in \{500, 1000, 2000, 3000, 4500, 5000\}$ K (dashed) and $G_{ii} \in \{1.0, 2.3, 4.0\} \times 10^{26}, \{1.0, 1.7, 2.3\} \times 10^{27} \text{ cm}^{-3}\text{s}^{-1}$ (solid).




Figure 3: This work vs Liang Figs. 3 (n), 4 (velocity), 7 (T_e , G_{ii} at Liang's contour levels).




Figure 4: Quantitative Liang Fig. 7 overlay: our T_e (dashed) and G_{ii} (solid) on Liang's exact published levels; peaks reach 0.72 (T_e) and 0.58 (G_{ii}) of the top contours.




Figure 5: Potential ϕ (Liang Fig. 5) and hole concentration p (Liang Fig. 6), recalibrated coupled 60 $\times$ 50: ϕ rises smoothly source $\rightarrow$ drain; holes fill the p-body and are depleted in the n^+ S/D.




Figure 6: Energy distribution (Liang Fig. 2): a hot, non-Maxwellian tail localized at the drain surface, thermal in the bulk.




Figure 7: Terminal I-V (Liang Fig. 8), drift-diffusion proxy, per micron: (a) subthreshold transfer at $V_{ds} = 0.25, 0.5$ V; (b) output characteristic at $V_{gs} = 2.0, 2.5, 3.0$ V.

Per-plot comparison tables (columns: feature / this work / Liang / assessment).

Table 4: Liang Fig. 2 — carrier energy distribution / hot electrons (this work: Fig. 6).

Feature	This work	Liang	Assessment
Drain-surface T_e (tail temp.)	3300–3600 K	hot, non-Maxwellian tail	hot tail reproduced
Source / bulk T_e	300–330 K	thermal	thermal, matches
High-energy tail cutoff	$\varepsilon_{max} = 3.02$ eV (absorbing)	tail to high ε	bounded tail
Localization	drain-surface hot spot	near-drain surface	match

Table 5: Liang Fig. 3 — electron concentration $n(x, y)$ (this work: Fig. 3).

Feature	This work	Liang	Assessment
n_{max} (S/D)	$1.01 \times 10^{20} \text{ cm}^{-3}$ @ (0.10, 0.02)	$\sim 10^{20}$	match
Channel inversion (surface)	$3.1 \times 10^{19} \text{ cm}^{-3}$	inversion layer	match
Drain pinch-off	n decreases toward drain	pinch-off	match

Table 6: Liang Fig. 4 — average electron velocity (this work: Fig. 3).

Feature	This work	Liang	Assessment
$ v _{max}$	$1.01 \times 10^7 \text{ cm/s}$ @ drain (0.53, 0.05)	$\sim 10^7$ (sat.)	match
Field pattern	lateral in channel, downward into drain	source→drain, into drain	match
Saturation	velocity-saturated near drain	yes	match

Honesty note. The comparisons apply *our* model on Liang’s *levels*; they are not a pixel registration. With a reconstructed doping profile the absolute spatial positions of the hotspots need not coincide with Liang’s, so structural agreement (drain-localization, T_e broader than G_{ii} , order-of-magnitude levels) is the claim, not point-by-point overlap. $G_{ii,max}$ remains grid-unconverged (§9), so its 58%-of-top value is a mesh-tied lower bound, and the T_e/G_{ii} peak offset stays within one cell. The Fig. 5/6 and Fig. 8 comparisons are structural: the I-V is a drift-diffusion proxy reported per- μm , while Liang’s Fig. 8 solid lines are *experimental* data for a real device of unstated width, so only the per-width shape is comparable, not the absolute ampere magnitude.

Part III

Assessment

11 Conclusions, classified

- **Core SHE transport** shows a clean grid-sensitivity hierarchy: n strongly robust (0.4%), $|v|$ robust (2.7%), T_e *moderately grid-sensitive* (5.9%; robust but not converged), G_{ii} unconverged (40%).

Table 7: Liang Fig. 5 — electrostatic potential $\phi(x, y)$ (this work: Fig. 5).

Feature	This work	Liang	Assessment
ϕ swing	$-0.35 \rightarrow +3.59$ V (3.93 V)	$V_{ds}=3$ + built-ins	match
Source-surface ϕ	0.59 V (built-in)	built-in	match
Drain-surface ϕ	3.59 V (= V_{ds} +built-in)	$\approx V_{ds}$	match
Profile	smooth, monotone S→D	smooth 2-D	structural (reconstr. doping)

Table 8: Liang Fig. 6 — hole concentration $p(x, y)$ (this work: Fig. 5).

Feature	This work	Liang	Assessment
$p_{\max}$	$4.2 \times 10^{16} \text{ cm}^{-3}$ (p-body)	p-body / substrate	match (structural)
n^+ S/D holes	$\leq 4 \times 10^{13} \text{ cm}^{-3}$ (depleted)	hole-depleted	match
II holes near drain	elevated p from G_{ii} source	avalanche holes	present
Caveat	body-contact BC + reconstr. doping	—	structural, not point-wise

- **Impact ionization:** now part of the assembled electron collision operator, with explicit primary depletion and secondary redistribution (G_{ii} is a moment of the II-affected f_0); the equal-energy secondary split and negligible scattering-in shape change follow the paper.
- **Self-consistency:** SHE↔Poisson↔hole feedback *demonstrated and observably converging* (not to the 2 mV criterion); it materially suppresses avalanche generation and drain current while leaving T_e comparatively stable. The G_{ii} -suppression fraction is *confirmed* on the recalibrated $V_{th} = 0.614 \text{ V}$ device (−36%; current suppression is stronger, −55%, at the higher 2.39-V overdrive).
- **Quantitative overlays (this revision):** on Liang’s own Fig. 7 contour levels the recalibrated coupled fields reach 72% (T_e) and 58% (G_{ii}) of the top published contours, drain-localized and correctly structured (T_e region much broader than G_{ii}); the DD-proxy I-V reproduces the Fig. 8 triode→saturation shape and V_{gs} ordering. A per-plot comparison table is given for each of Liang’s Figs. 2–8 (§10, Tables 4–10).
- **Conservation:** validated across one-way, refined, and coupled calculations (number balance 10^{-5} – 10^{-7} ; terminal currents balance $< 0.2\%$).
- **Numerics:** physics-split preconditioning removes the previous practical solver bottleneck.
- G_{ii} : the earlier 1.37×10^{27} agreement with Liang was *demonstrably accidental* — spatial refinement and self-consistency each push it downward (multiplicatively separable to $\sim 1\%$). On the original device the coupled 60×50 run gives $5.24 \times 10^{26} \text{ cm}^{-3} \text{ s}^{-1}$, the *finest-tested coupled value* (not a continuum estimate: still −38% below coupled 40×34 , no plateau); a one-way energy refinement moves it only −2.4%. *No converged magnitude can be quoted* (Table 3).
- T_e/G_{ii} **offset:** unresolved at present mesh resolution; *no longer claimed reproduced*.
- **Device:** recalibrated to $V_{th} = 0.614 \text{ V}$ ($\Phi_{gate} = -0.74 \text{ V}$), replacing the earlier over-high 1.64 V.
- **Remaining gap:** a spatially-converged G_{ii} magnitude (and hence a resolved T_e/G_{ii} offset) via drain-local mesh refinement.

Table 9: Liang Fig. 7 — T_e (dashed) and G_{ii} (solid) contours (this work: Figs. 3,4).

Feature	This work	Liang	Assessment
$T_{e,\max}$	3598 K (72% of top)	to 5000 K	same order, drain-localized
$G_{ii,\max}$	1.34×10^{27} (58% of top)	to 2.3×10^{27}	lower, grid-unconverged
T_e vs G_{ii} extent	T_e region $\sim 30\times$ larger	T_e broader	match
Peak offset	≤ 1 cell (14 nm)	offset	unresolved at mesh

Table 10: Liang Fig. 8 — terminal I-V (this work: Fig. 7).

Feature	This work	Liang	Assessment
Output shape	triode $\rightarrow$ sat, V_{gs} -ordered	Fig. 8b	shape match (DD proxy)
$I_d(V_g = V_d = 3)$	0.54 mA/ μm (DD)	—	order-consistent w/ SHE 0.24
Subthreshold swing	~ 99 mV/dec	sub- μm NMOS	reasonable
Magnitude caveat	per- μm DD proxy	experimental total (unknown W)	shape only

A Numerical and model specifications

$T = 300$ K, Boltzmann, $m^* = 0.32m_0$, $g_v = 6$, $\alpha = 0.5 \text{ eV}^{-1}$, $v_s = 9.04 \times 10^3$ m/s; erfc doping per earlier revisions; SHE grid $\Delta H = 12.5$ meV ($E_{op}/\Delta H = 4$ integer), $\varepsilon = 0$ reflecting / ε_{max} absorbing. Optical $c_{op} = 4.69 \times 10^{-34}$ J m³/s, $\tau_1 = 10^{-14}$ s/ $(\sqrt{\gamma}\gamma')$, $\tau_{ac} = \tau_1$; impact ionization $1/\tau_{ii} = P[(\varepsilon - \varepsilon_{th})/\varepsilon_{th}]^2\Theta$, $P = 2 \times 10^{13}$ 1/s, $\varepsilon_{th} = 1.1$ eV, equal-split secondaries. Solve: physics-split E $\rightarrow$ S $\rightarrow$ E preconditioner, LGMRES tol 10^{-10} (audit) / 10^{-8} (coupled iterations). Coupled loop: ϕ -damping 0.25, ≤ 12 outer iterations, 2 mV stop. I-V proxy (§10): self-consistent drift-diffusion (Caughey–Thomas field-dependent mobility, SG continuity, SRH), 56×48 mesh, per- μm terminal current.

B Provenance and audit history

Base code commit 0994290; Python 3.13.14, NumPy 2.5.1, SciPy 1.18.0. Key commits: f016e3c (locked one-way audit), 7aad998 (60 $\times$ 50 refinement), 65461ad (physics-split solver), 047da93 (coupled loop), 0994290 (recalibrated coupled 60 $\times$ 50). Four audit rounds fixed: over-claims, missing specs, junction geometry, N_c convergence, the reducible-collision zero-field- T_e bug (acoustic operator), the global H -grid, the contact-Maxwellian normalization (report typo; code correct), boundary/velocity/current extraction, and finally delivered the real impact-ionization operator, the coupled driver, and the physics-split solver. Revision 3 adds the quantitative comparison against Liang’s published figures (§10): the recalibrated coupled fields on Liang’s Fig. 7 contour levels, plus potential/hole (Figs. 5/6) and terminal I-V (Fig. 8) plots (she2d.liang.compare.py, she2d.liang.overlay.py, she2d.liang.fig5.6.py, she2d.iv.py), with one comparison table per plot (Tables 4–10).

References

- [1] W. Liang, N. Goldsman, I. Mayergoyz, P. J. Oldiges, *IEEE Trans. Electron Devices* **44**(2), 257–267, 1997.
- [2] A. Gnudi, D. Ventura, G. Baccarani, F. Odeh, *Solid-State Electron.* **36**, 575, 1993.

- [3] Y.-J. Wu, N. Goldsman, *J. Appl. Phys.* **78**, 1995.
- [4] C. Jungemann, B. Meinerzhagen, *Hierarchical Device Simulation*. Springer, 2003.
- [5] D. L. Scharfetter, H. K. Gummel, *IEEE TED* **ED-16**, 64, 1969.