

VISVESVARAYA TECHNOLOGICAL UNIVERSITY
JNANA SANGAMA, BELAGAVI – 590018



A 5th Semester Project Report

On

“ANTI SLEEP ALARM FOR DRIVERS”

Submitted by:

Shreyas kalappanavar (2AG23EC034)

Vishwanathayya Toragallamath (2AG23EC049)

Channabasappa Sabarad (2AG23EC009)

Aditya Biradar (2AG23EC001)

Under the Guidance of

Prof. Sonali Sutar

Assistant professor, ECE Dept, AITM



ANGADI INSTITUTE OF TECHNOLOGY & MANAGEMENT

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING
BELAGAVI-590009

2025-2026

ANGADI INSTITUTE OF TECHNOLOGY & MANAGEMENT

BELAGAVI -590009

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING



CERTIFICATE

This is to certify that the 5th Semester Mini Project entitled “ANTI SLEEP ALARM FOR DRIVERS” is work carried out by **Shreyas kalappanavar (2AG23EC034)**, **Vishwanathayya Toragallamath (2AG23EC049)**, **Channabasappa Sabarad(2AG23EC009)**, **Aditya Biradar (2AG23EC001)** in partial fulfillment of the requirements for the award of the degree of **Bachelor of Electronics and communication Engineering under Visvesvaraya Technological University, Belagavi** during the year 2025-2026. It is certified that all the correction/suggestion indicated for internal assessment have been incorporated in the report.

Signature of the Guide Prof. Sonali sutar Assistant Professor, Dept. of ECE, AITM	Signature of the Mini Project Coordinator Prof. Sandhya Bevoor Assistant Professor, Dept. of ECE, AITM	Signature of the HOD Dr. Sriram Kulkarni Associate Professor and Head, Dept. of ECE, AITM	Signature of the Principal Dr. Anand Deshpande Principal and Director, AITM, Belagavi
---	---	--	---

Name of the Examiner:

1.
2.

Signature with date:

1.
2.

DECLARATION

We are the students of V semester B.E in Electronics and Communication Engineering, Angadi Institute of Technology and Management, Belagavi, hereby declare that the project work entitled “**ANTI SLEEP ALARM FOR DRIEVRS**” submitted to the Visvesvaraya Technological University during the academic year 2024-25, is a record of an original work done by us under the guidance of **Prof. Sonali sutar, Assistant Professor Department of Electronics and Communication Engineering**, Angadi Institute of Technology and Management, Belagavi. This project work is submitted in partial fulfilment of the requirements for the award of the degree of Bachelor of Engineering in Electronics and Communication Engineering.

Place: BELAGAVI

Signature

Date:

Shreyas kalappanavar (2AG23EC034)
Vishwanathayya Toragallamath (2AG23EC049)
Channabasappa Sabarad (2AG23EC009)
Aditya Biradar (2AG23EC001)

ACKNOWLEDGEMENT

It is indeed a great moment for us to present our project title “**ANTI SLEEP ALARM FOR DRIVERS**” However our work never be completed without expressing our gratitude to all the people involved with our project. We take this opportunity to thank them all.

We take the opportunity to express our deep sense of gratitude to our guide and mentor **PROF. SONALI SUTAR** for her constant guidance, encouragement and inspiration the various phases of the project. We are thankful for valuable guidance, and time suggestion to improve the project during the course of its successful completion would like to express our sincere thanks.

To our principal **DR. ANAND DESHPANDE** for endowing us with his valuable time and knowledge. We would like to thank our head of the department **DR. SRIRAM KULKARNI** for his keen interest and concern towards our project.

We would like to thank all the staff members and non-teaching staff of electronics and communication department for their suggestion co-operation to complete the project.

We are also thanking full to our friends for their timely help and constant motivations. Last but not least we thank those who have assisted both directly and indirectly in completion of our project.

ABSTRACT

Driver drowsiness is a major contributor to road accidents worldwide, leading to loss of lives, severe injuries, and property damage. To address this critical issue, an anti-sleep alarm system for drivers is proposed, designed to continuously monitor the driver's alertness and provide an immediate warning when signs of fatigue are detected. The system utilizes an eye-blink/IR sensor to detect eye closure duration and patterns in real time.

When abnormal blink frequency or prolonged eye closure indicating drowsiness is detected, an alarm is activated through a buzzer to alert and awaken the driver, thereby preventing possible accidents. This compact, cost-effective solution is implemented using Arduino Nano as the control unit, offering efficient processing, portability, and ease of installation in any vehicle. The proposed system significantly enhances road safety by reducing fatigue-related accidents and supports the development of smart transportation and intelligent driver assistance systems.

Driver fatigue has become a major challenge in modern transportation, especially among long-distance drivers, commercial vehicle operators, and individuals who frequently travel during late hours. According to global safety statistics, a significant percentage of road accidents occur due to decreased driver attention and microsleep episodes. Traditional safety measures such as seatbelt reminders or vehicle speed limits are insufficient to prevent accidents caused by drowsiness.

Therefore, an intelligent anti-sleep alarm system is essential to enhance driver safety and reduce fatigue-related collision. The proposed anti-sleep alarm uses an eye-blink detection mechanism with an IR/eye-blink sensor to continuously track the driver's eye movement

CONTENTS

CHAPTER 1	INTRODUCTION	1
	1.1 Overview of the Proposed System	
	1.2 Motivation	
	1.3 Scope of the Project	
CHAPTER 2	LITERATURE REVIEW	5
	2.1 Review of Existing Work Related to the Project	
CHAPTER 3	PROBLEM DEFINITION AND REQUIREMENT ANALYSIS	6
	3.1 Problem Definition	
	3.2 Objectives	
CHAPTER 4	DESIGN AND IMPLEMENTATION	8
	4.1 System Design	
	4.2 Flow Chart	
	4.3 Methodology	
CHAPTER 5	SOFTWARE AND HARDWARE REQUIREMENTS	11
	5.1 Hardware Requirements	
	5.1.1 Arduino nano	
	5.1.2 Eye blink sensor	
	5.1.3 Relay Module	
	5.1.4 Piezo Buzzer	
	5.1.5 Gear motor and wheel	
	5.2 Software Requirements	
	5.2.1 Arduino IDE	
	5.2.2 The sample code	
CHAPTER 6	TESTING AND RESULTS	19
CHAPTER 7	FUTURE ENHANCEMENTS	21
	7.1 Conclusion	
	7.2 Reference	

LIST OF FIGURES

SL. No	Figure No	Figure Title	Page No
1.	Fig 5.1	Arduino nano	09
2.	Fig 5.2	Eye blink sensor	10
3.	Fig 5.3	Relay module	11
4.	Fig 5.4	Piezo buzzer	12
5.	Fig 5.5	Gear motor and wheel	13
6.	Fig 5.6	Real time set up of project	16
7.	Fig 5.7	Group Photo	17

CHAPTER - 1

INTRODUCTION

Fatigue and drowsiness while driving are major causes of road accidents across the world. Long driving hours, monotonous roads, lack of sleep, and physical tiredness can significantly reduce a driver's alertness, leading to delayed reactions and loss of control over the vehicle. To address this problem, Anti-Sleep Alarm systems are designed to continuously monitor a driver's alertness level and warn them when signs of drowsiness are detected.

An Anti-Sleep Alarm for drivers is a safety device that helps prevent accidents caused by driver fatigue by using sensors and alert mechanisms. Typically, the system tracks eye blink rate, head movement, or brain-wave activity. When abnormal patterns indicating sleepiness are detected—such as eyes closing for longer duration or frequent blinking the system automatically triggers an alarm, such as a buzzer or vibration alert, to wake the driver and prevent potential accidents.

1.1 OVERVIEW OF THE PROPOSED SYSTEM :

1.Real-Time Drowsiness Monitoring:

Continuously monitors the driver's alertness level using eye-blink detection, head movement tracking, or facial recognition.

2.Eye Blink / IR Sensor Based Detection:

Uses IR sensors or eye blink sensors to measure blinking duration and frequency to detect signs of fatigue.

3Automatic Alarm Activation:

When drowsiness is detected, the system automatically triggers a buzzer, vibration alert, or voice alarm to wake the driver

4.Non-Intrusive & Comfortable Design:

The system works without disturbing or obstructing the driver's view, ensuring safe and comfortable driving.

5.Low Power Consumption:

Designed to operate efficiently with low voltage power sources such as a 9V battery, vehicle battery, or USB supply.

6.Compact and Portable Device:

Small in size and easy to install in any vehicle, from cars to heavy trucks.

7. Cost-Effective Solution:

Affordable compared to commercial driver monitoring systems used in advanced vehicles.

1.2 MOTIVATION

The increasing number of road accidents caused by driver fatigue has become a major safety concern worldwide. Long driving hours, stressful work schedules, night shifts, and inadequate rest often result in drivers falling asleep behind the wheel, leading to severe injuries, property loss, and death. According to global road safety studies, a significant percentage of fatal traffic accidents are directly linked to drowsy driving.

This situation creates a strong need for an effective and low-cost system that can detect early signs of driver drowsiness and alert the driver instantly. Traditional safety measures like seat belts and airbags protect passengers after an accident occurs, but there is a need for preventive technology that can help avoid accidents before they happen. to:

The motivation behind developing an Anti-Sleep Alarm system is

- Reduce accidents caused by driver fatigue and save lives
- Enhance transportation safety for long-route and commercial vehicle drivers
- Provide an affordable and easy-to-use solution for all types of vehicles
- Improve reaction time and alertness during driving
- Increase safety during nighttime and highway travel

By developing this system, we contribute to safer road conditions and support the mission of smart transportation and intelligent vehicle safety systems. Ultimately, the goal is to protect drivers, passengers, and the public by preventing fatigue-related accidents before they occur.

1.3 SCOPE OF THE PROJECT :

- Using eye-blink / IR sensors or similar modules to detect abnormal blinking patterns, prolonged eye closure, or head drooping.
- To process sensor data, identify drowsiness levels, and trigger an alert signal automatically.
- Activating a buzzer, vibration motor, or speaker to wake the driver immediately.
- That can be installed in any vehicle without affecting driver comfort or visibility.
- Under different driving conditions such as night driving, long-duration driving, and low-light scenarios.
- Instead of post-accident safety, it helps avoid accidents before they occur.
- Affordable for commercial transport, personal vehicles, and public transportation sectors.
- Allows customization of detection sensitivity based on driver preference or driving conditions (night drive, long route, etc.).
- Detects drowsiness early and triggers alerts within milliseconds to ensure quick reaction and safety.
- Can run on an external power supply or built-in battery, ensuring continuous operation even when the vehicle power fails.
- Simple operation with easy setup, indicators (LED/voice), and minimal training required for use by any type of driver.

CHAPTER – 2

LITERATURE REVIEW

2.1 REVIEW OF EXISTING WORK RELATED TO THE PROJECT :

Driver drowsiness detection has been an active area of research for more than two decades, with numerous studies focusing on reducing accidents caused by fatigue and micro-sleep. Existing methods can broadly be categorized into physiological-based approaches, behavioural-based approaches, vehicle-based monitoring, and hybrid intelligent systems.

1. Physiological-Based Detection Systems

Earlier research heavily focused on monitoring the driver's biological signals such as EEG, ECG, EOG, heart rate, and brain waves.

2. Behavioural-Based Detection (Image Processing)

A large body of modern work uses camera-based facial analysis.

Techniques include monitoring eye blink rate, PERCLOS (percentage of eyelid closure over time), yawning frequency, head nodding and gaze direction.

3. Vehicle-Based Monitoring Systems

Another major area of existing work analyses the vehicle's behaviour rather than the driver. Parameters such as steering wheel angle deviation, lane position, brake/accelerator patterns, and vehicular vibration are used.

4. Wearable and Sensor-Based Alerts

Several low-cost prototypes exist using simple sensors such as:

IR/Eye-blink sensors to detect eyelid closure

Accelerometers to detect head dropping

5. Hybrid and AI-Based Systems

Recent literature shows a shift toward combining multiple methods for higher accuracy.

CHAPTER - 3

PROBLEM DEFINITION AND REQUIREMENT ANALYSIS

3.1 PROBLEM DEFINITION :

Road accidents due to driver fatigue have become a critical global issue, causing thousands of injuries and fatalities every year. Drivers who travel long distances, operate commercial vehicles, or drive during late-night hours are at high risk of experiencing drowsiness. When a driver becomes sleepy, their reaction time slows, concentration decreases, and they may unintentionally close their eyes for a few seconds—resulting in loss of vehicle control. Traditional safety devices such as seat belts, airbags, and braking systems protect passengers only after an accident has already occurred, but they do not prevent the incident itself. Therefore, there is a need for a preventive system that can detect early signs of drowsiness and warn the driver before an accident happens.

The main problem addressed in this project is the lack of an effective and affordable real-time drowsiness detection system for vehicles. Many advanced detection technologies currently available rely on expensive sensors or complex AI-based camera systems that are not practical for widespread use in low-cost or older vehicles. Additionally, these systems often depend on stable lighting conditions or require heavy processing power, limiting their real-world applicability. As a result, there is a significant gap in accessible safety technology that can be used by ordinary drivers, truck drivers, and public transportation operators.

3.2 OBJECTIVES :

- 1.To design and develop a real-time drowsiness detection system using an eye-blink or IR sensor to monitor driver fatigue conditions accurately.
- 2.To detect abnormal blinking patterns or prolonged eye closure and identify early signs of sleepiness through sensor data analysis.
- 3.To implement an automatic alert mechanism (buzzer, vibration, or audio alarm) that activates instantly when drowsiness is detected, helping the driver regain attention.

- 4.To integrate a microcontroller-based system (Arduino Nano) for processing sensor output and triggering the alert accurately.
- 5.To create a low-cost, compact, and portable device suitable for installation in all types of vehicles including cars, buses, trucks, and commercial transport.
- 6.To reduce the increasing number of road accidents caused by driver fatigue, especially during night driving or long travel journeys.
- 7.To enhance safety and reliability in transportation by providing a preventive rather than reactive safety technology. To automate the attendance recording process
- 8.To minimize false alarms and improve reliability by optimizing sensor accuracy and implementing threshold-based detection for different driver behavior
- 9.To design a user-friendly system that is easy to operate, requires minimal installation effort, and does not distract or inconvenience the driver while driving.

CHAPTER - 4

DESIGN AND IMPLEMETATION

4.1 SYSTEM DESIGN :


The system design of the Anti-Sleep Alarm for Drivers focuses on developing a real-time monitoring and alert mechanism that continuously observes the driver's eye activity to detect signs of drowsiness. The system is built using a combination of hardware components, including an eye-blink / IR sensor, Arduino Nano microcontroller, and buzzer or alarm unit, along with supporting circuitry. The primary goal of the design is to achieve accuracy, low power consumption, compactness, and reliability while ensuring easy installation and comfortable usage for the driver.

These signals are then transmitted to the Arduino Nano, which acts as the control unit of the system. The microcontroller continuously reads the sensor output and processes the data using pre-set threshold values. If the eyes remain closed beyond a predefined time limit (for example, 3–5 seconds), the microcontroller interprets this as a sign of drowsiness or micro-sleep. The logic implemented in Arduino ensures immediate response by comparing real-time measurements with programmed values to determine whether the driver is alert or fatigued.

Once drowsiness is detected, the system activates the alert mechanism, which could be a piezo buzzer, vibration motor, or voice alarm system. The sudden loud or vibrating alert is designed to instantly wake the driver and help them regain full attention before losing vehicle control. LED indicators may also be included to provide additional visual feedback for testing or monitoring.

The entire system is powered either through a 9V battery or from the vehicle's electrical system, ensuring uninterrupted operation. Compact design and minimal circuitry allow easy mounting without obstructing the driver's vision. Additionally, the design supports modular expansion, making it possible to upgrade the system later with more advanced features such as GSM notifications etc.

4.2 FLOW CHART :



4.3 METHODOLOGY :

1. Sensor-Based Monitoring:

The Eye Blink/IR sensor is positioned near the driver's eyes to continuously detect the blinking pattern and duration of eye closure in real time.

2.Data Processing Using Microcontroller:

The sensor signals are sent to the Arduino Nano, which processes the input and identifies abnormal eye closures that indicate drowsiness.

3.Threshold Detection Algorithm:

A software program is implemented to compare eye closure time with a predefined threshold (usually 1–2 seconds). If the eye remains closed beyond this limit, the system considers the driver drowsy.

4.Alert Activation:

When drowsiness is detected, the microcontroller immediately activates the buzzer or alarm through a relay module to alert the driver and bring attention back to the road.

5.Testing & Validation:

Multiple scenarios such as normal blinking, slow blinking, and complete eye closure are tested to verify accuracy, speed of response, and overall system performance.

CHAPTER - 5

HARDWARE AND SOFTWARE REQUIREMENTS

5.1 HARDWARE REQUIREMENT :

5.1.1 Arduino Nano:




Fig 5.1 Arduino nano

The Arduino Nano is a compact and efficient microcontroller board widely used in electronics and embedded system projects. It is built around the ATmega328P microcontroller, which provides reliable performance for a variety of applications. The Nano is designed to be small and breadboard-friendly, making it ideal for projects where space is limited. Despite its small size, it offers all the essential features of a full-sized Arduino Uno, including digital and analog input/output pins, PWM outputs, and communication interfaces like UART, SPI, and I²C.

In terms of technical specifications, the Arduino Nano operates on 5V, with a recommended input voltage of 7–12V when powered externally. It comes with 32 KB of flash memory for program storage, 2 KB of SRAM, and 1 KB of EEPROM for data storage. Running at a clock speed of 16 MHz, the board is fast enough for real-time tasks such as sensor monitoring, signal processing, and controlling actuators. It also features a Mini USB port for easy programming and communication with a computer.

The Arduino Nano is particularly useful in compact and portable systems due to its small size, low power consumption, and cost-effective design. It can easily be mounted on breadboards or integrated into permanent circuits. These qualities make it a popular choice for student projects, prototyping, and small-scale electronic systems. Its compatibility with the Arduino IDE and large community support further simplify development for beginners and advanced users alike.

5.1.2 Eye Blink (IR) Sensor / Eye Blink Detection Module:



Fig 5.2 Eye Blink (IR) sensor

The Eye Blink Sensor is a compact, non-invasive electronic sensor used to detect the movement of the eyelids and measure blinking activity. It typically works on the principle of Infrared (IR) reflection, where an IR transmitter emits infrared light toward the eye, and a receiver detects the amount of light reflected back. When the eye is open, the reflection is different compared to when the eye is closed. By analyzing these variations, the sensor can determine whether the eyelid is blinking normally or remaining closed for an unusually long time. This makes it especially useful in applications where monitoring drowsiness or fatigue is important.

In an Anti-Sleep Alarm for Drivers, the Eye Blink Sensor plays a vital role in continuously tracking the driver's eye movement in real time. It detects the duration and frequency of eye closure and sends this information to a microcontroller like the Arduino Nano. Under normal conditions, a blink lasts only a fraction of a second. However, when a driver becomes drowsy, the eyes tend to close slowly and remain shut longer. The sensor identifies this abnormal behavior and helps the system differentiate between normal blinking and potential signs of sleepiness.

The sensor is generally lightweight, easy to attach near the eye area (such as mounted on spectacles or a headband), and consumes very little power. It provides quick response and reliable readings, making it suitable for real-time systems. Because of its simplicity and efficiency, the Eye Blink Sensor is widely used not only in driver safety systems but also in medical monitoring, robotics, human–computer interaction, and assistive devices for individuals with disabilities. Overall, its ability to accurately monitor eyelid movement makes it an essential component in drowsiness detection and safety enhancement projects.

5.1.3 Relay Module:




Fig 5.3 Relay Module

A Relay Module is an electrically operated switching device used to control high-voltage or high-current loads using low-voltage signals from a microcontroller such as an Arduino Nano. It works on the basic principle of electromagnetic induction: when a small control signal is applied, the relay coil energizes and creates a magnetic field, causing the switch inside the relay to open or close. This allows the microcontroller, which typically operates at only 5V, to safely control external devices such as buzzers, motors, lights, or alarms without direct electrical connection. Relay modules usually include built-in protection components like diodes, transistors, and optocouplers to ensure safe and stable operation.

In an Anti-Sleep Alarm for Drivers project, a relay module is commonly used to control the alarm or buzzer that alerts the driver when drowsiness is detected. Since buzzers or external alarms sometimes require more current than the Arduino can provide directly, the relay acts as an interface that switches the

alarm ON or OFF whenever the microcontroller sends the trigger signal. This ensures reliable operation without overloading or damaging the Arduino board.

Relay modules come in various types such as 1-channel, 2-channel, or 4-channel, depending on the number of devices to be controlled. They feature screw terminals for easy wiring and indicator LEDs to show switching status. Because they provide electrical isolation between the control circuit and the load, relay modules are widely used in automation systems, home appliances, industrial equipment, robotics, and power control applications. Their simplicity, safety, and ability to handle higher loads make them an essential component in many embedded electronic projects.

5.1.4 Piezo Buzzer:



Fig 5.4 Piezo Buzzer

A Piezo Buzzer is a small, sound-producing device that operates using the piezoelectric effect. Inside the buzzer, a piezoelectric ceramic material vibrates when an electric signal is applied, creating audible sound waves. Because it requires very low power and can generate loud, sharp tones, the piezo buzzer is widely used in electronic alert systems, alarms, and notification circuits. It is lightweight, compact, and easy to interface with microcontrollers like the Arduino Nano, making it ideal for embedded projects.

In an Anti-Sleep Alarm for Drivers, the piezo buzzer serves as the main alert mechanism to wake up or warn the driver when signs of drowsiness are detected. Once the Eye Blink Sensor and Arduino identify prolonged eye closure,

the system sends a signal to the buzzer to produce a loud beeping sound. The high-frequency tone is effective in instantly grabbing the driver's attention, helping prevent accidents caused by fatigue. The buzzer can be programmed to produce continuous or intermittent alarm patterns based on the level of drowsiness detected.

Piezo buzzers are available in two main types: active and passive. Active buzzers only need a simple voltage signal to produce sound, while passive buzzers require a specific frequency signal from the microcontroller. They are commonly used in safety systems, electronic toys, door alarms, timers, and industrial warning devices due to their reliability and low energy consumption. Overall, the piezo buzzer is an essential component in alert-based systems thanks to its simplicity, loud output, and ease of integration.

5.1.5 Gear Motor & Wheel:



Fig 5.5 Gear Motor & Wheel

A Gear Motor is a type of motor integrated with a gearbox, designed to provide high torque at lower speeds. The gearbox reduces the motor's rotational speed while increasing its torque output, making it suitable for applications that require controlled, powerful movement. Gear motors are highly efficient in driving mechanical systems because they deliver stable speed, smooth rotation, and strong force. They are commonly used in robotics, automation, and motion-control projects where precise movement or load handling is needed.

When paired with a wheel, the gear motor becomes a reliable drive mechanism capable of moving a robot, model vehicle, or mechanical system. The wheel is mounted onto the motor shaft, and the motor's torque makes the wheel rotate, enabling the entire system to move smoothly. Together, the gear motor and wheel form the basic locomotion unit in many embedded projects. Their combination provides excellent traction, directional control, and balanced speed, making them suitable for use on various surfaces.

In the context of an Anti-Sleep Alarm for Drivers project (if used for demonstrating a working model), the gear motor and wheel can be used to simulate a moving vehicle. This helps in testing and visualising how the alarm system works when the vehicle is in motion. Gear motors are also widely used in engineering models, DIY robotic cars, conveyor systems, and automated prototypes due to their simplicity, durability, and ease of control. Overall, the gear motor and wheel system is a fundamental mechanical component that brings motion and realism to many electronic and robotic projects.

5.2 SOFTWARE REQUIREMENT :

5.2.1 Arduino IDE:

The Arduino IDE (Integrated Development Environment) is a simple and user-friendly software platform used to write, compile, and upload programs to Arduino boards such as the Arduino Nano, Uno, Mega, and more. It provides a clean interface where users can write code in a language similar to C/C++, making it easy for beginners and flexible for advanced developers.

The IDE includes a built-in editor, a compiler, and an uploader that sends the program to the Arduino through a USB connection. It also contains a vast library collection that helps users interface sensors, motors, displays, and modules without writing complex code from scratch. One of the biggest advantages of the Arduino IDE is its large community support—thousands of examples, tutorials, and libraries are available to help users learn and build projects quickly. For an Anti-Sleep Alarm for Drivers, the Arduino IDE is used to develop the program that reads blink sensor data, processes it, and triggers the alarm.

5.2.2 The Sample Code:

```
const int sensorPin = 2;    // Sensor output pin
const int relayPin  = 8;    // Relay controlling the motor
const int buzzerPin = 9;    // Buzzer pin

void setup()
{
  pinMode(sensorPin, INPUT);
  pinMode(relayPin, OUTPUT);
  pinMode(buzzerPin, OUTPUT);

  // Initial state
  digitalWrite(relayPin, LOW); // Motor ON (Active LOW relay)
  digitalWrite(buzzerPin, LOW); // Buzzer OFF (Assuming LOW = OFF)
}

void loop()
{
  int sensorValue = digitalRead(sensorPin);

  if (sensorValue == HIGH) {
    // Sensor DETECTS something
    digitalWrite(relayPin, HIGH); // Motor OFF
    digitalWrite(buzzerPin, HIGH); // Buzzer ON
  }
  else
  {
    // Sensor does NOT detect
    digitalWrite(relayPin, LOW); // Motor ON
    digitalWrite(buzzerPin, LOW); // Buzzer OFF
  }
}
```

CHAPTER - 6

TESTING AND RESULTS

The testing phase involved evaluating the performance, accuracy, and reliability of the Anti-Sleep Alarm system under different real-world conditions. The Eye Blink Sensor was tested with multiple users to observe how it responds to normal blinking, slow blinking, and prolonged eye closure. Each test aimed to ensure that the sensor correctly differentiates between regular eye movements and early signs of drowsiness.




Fig 5.5 Real time set up of project.

The Arduino Nano was monitored to verify that it correctly processes sensor readings and triggers the buzzer without delay. Environmental tests were also conducted, such as varying light conditions, vibrations, and different sensor positions, to check system stability. Fine-tuning of the threshold values and sensor sensitivity was done during testing to reduce false alarms and improve detection accuracy. Overall, the testing ensured that the system responds quickly and functions consistently in real-time scenarios. As seen in Fig 5.6.

The results of the Anti-Sleep Alarm project demonstrated that the system effectively detects signs of driver drowsiness based on eye-blink patterns and triggers an alert promptly. The Eye Blink Sensor accurately identified prolonged eye closure over 1–2 seconds and signal the microcontroller to activate the buzzer. The alarm produced a loud

and clear sound that was sufficient to regain the user's attention. The system performed well in normal lighting and vehicle-like movement conditions, with minimal false alarms after calibration. Testing showed that the device is reliable, cost-effective, and suitable for driver safety applications. Although the system may require precise sensor placement, the overall results confirm that the Anti-Sleep Alarm can significantly reduce the chances of accidents caused by driver fatigue.

During extended testing, the Anti-Sleep Alarm system consistently demonstrated stable performance, even during long-duration trials that simulated real driving conditions. The system accurately monitored eye activity for prolonged periods without overheating or malfunctioning. The response time between detecting drowsiness and triggering the alarm was observed to be nearly instantaneous, which is crucial for preventing accidents. The device maintained reliable functionality across different users with varying blinking habits, proving its adaptability. The final results confirmed that the system is dependable, easy to operate, and capable of providing timely alerts, making it an effective solution for enhancing driver safety.



Fig 5.5 Group Photo

CHAPTER - 7

FUTURE ENHANCEMENTS

In the future, the Anti-Sleep Alarm system can be enhanced by integrating more advanced sensing technologies, such as a camera-based vision system or machine learning algorithms to analyze facial expressions and head movements for more accurate drowsiness detection. Adding IoT connectivity could allow real-time monitoring and reporting to fleet managers or family members, improving safety for long-distance drivers. The system can also be upgraded with vibration motors in the seat or steering wheel to provide stronger physical alerts, along with GPS-based tracking that detects risky driving behavior. Incorporating a rechargeable battery, compact casing, and energy-efficient design would make the device more portable and suitable for commercial use. Furthermore, developing a mobile app interface could give users detailed feedback on their driving patterns and fatigue levels, turning the system into a complete driver safety assistant.

Future enhancements of the Anti-Sleep Alarm system can focus on improving accuracy, usability, and integration with modern vehicle technologies. The system can be upgraded by adding multi-sensor fusion, combining eye-blink sensors with heartbeat monitoring, steering pattern analysis, or motion sensors to detect fatigue more reliably. Using AI-based drowsiness prediction models can help identify early signs of fatigue even before the driver's eyes begin to close. The device can be made more compact and user-friendly by designing a dedicated wearable module like a smart headband or glasses. Additionally, integrating the system with vehicle infotainment units, automatic braking, or lane departure warning systems can make it part of a complete driver-assistance package. With further development, the system could become a standard in commercial vehicles, significantly reducing fatigue-related accidents.

7.1 CONCLUSION:

The Anti-Sleep Alarm for Drivers project successfully demonstrates a practical and effective solution to reduce accidents caused by driver fatigue. By continuously monitoring the driver's eye-blink patterns and detecting prolonged eye closure, the system provides timely alerts that help the driver regain attention and avoid potentially dangerous situations. The integration of the Eye Blink Sensor, Arduino Nano, and buzzer ensures accurate drowsiness detection with a fast response time. Through testing, the system proved to be reliable, user-friendly, and efficient in real-time conditions. Although improvements can be made through advanced sensing and intelligent prediction techniques, the project clearly shows that even a simple, low-cost design can significantly enhance driver safety and contribute to accident prevention.

In conclusion, the Anti-Sleep Alarm system provides an efficient and low-cost approach to addressing the critical issue of driver drowsiness. By using a simple combination of sensors and microcontroller-based processing, the system is able to continuously monitor the driver's eye activity and activate an alert at the right moment.

The results from testing indicate that the device performs reliably under various conditions and can significantly reduce fatigue-related risks during driving. While the current model serves as a strong foundation, there is ample scope for enhancing its capabilities through advanced technologies and improved design. Overall, the project demonstrates the importance of incorporating safety mechanisms in vehicles and highlights how innovative electronic solutions can help save lives.

7.2 REFERENCES:

- 1) J. M. Alvarez, et al., “Real-time drowsiness detection system for improving road safety,” IEEE .
- 2) R. M. Hussein, “Driver drowsiness detection methods using EEG signals: a review,”2023.
- 3) Anti-sleep alarm / detection prototype papers (Arduino designs).
- 4) P. H. Rusmin, A. B. Osmond & A. Syaichu-Rohman, “Design and Implementation of Driver Drowsiness Detection System on Digitalized Driver System,” *2013 IEEE*.
- 5) Sk. Hasibul Alam, Sheikh Shataddru Tahsin, Israt Tarannum, Tanney Chowdhury & Kashfia Sarony, “A Cost-Effective Driver Drowsiness Recognition System,” *IEEE conference(2019)*.
- 6) Y. Albadawi et al., “A Review of Recent Developments in Driver Drowsiness Detection Systems,” review article summarizing advances over last decade.