

Introduction to Java



Java is a **high-level, class-based, object-oriented general-purpose programming language** created by **James Gosling** and his team at **Sun Microsystems** in **1995**.

At its core, Java was designed to be **secure, robust, portable and platform – independent**.

Java follows the principle of **WORA (Write Once, Run Anywhere)**, where **source code is compiled into bytecode** that can run on any system with a **Java Virtual Machine (JVM)**

Features of Java



- ⇒ High-Level Language
- ⇒ Object-Oriented Programming (OOP)
- ⇒ Statically Typed
- ⇒ Compiled and interpreted
- ⇒ Platform independent
- ⇒ Achieves WORA (Write Once, Run Anywhere)
- ⇒ Automatic Memory Management using the Garbage Collector (GC)

Applications of Java



- ⇒ Backend development
- ⇒ Desktop application development
- ⇒ Web application development
- ⇒ Data-driven applications
- ⇒ Enterprise applications
- ⇒ Android application development

System.out.println();



- **System** is a class in the **java.lang** package.
- **java.lang** package is automatically imported by the Java compiler.
- **out** is a **public static final PrintStream object** inside the **System class**.
- **println()** is a method of the **PrintStream** class that prints the data and moves the cursor to the next line.

System.out.print();



- **System** is a class in the **java.lang** package.
- **java.lang** package is automatically imported by the Java compiler.
- **out** is a **public static final PrintStream object** inside the **System class**.
- **print()** is a method of the **PrintStream** class that prints the given data and keeps the cursor on the **same line** after printing.

Tokens in Java



A **token** is the **smallest individual unit** of a Java program that has **meaningful information** to the Java compiler.

The main types of tokens are:

1. Reserved Words (Keywords)
2. Identifiers
3. Operators
4. Punctuators (Separators)
5. Literals

↳ Keywords:



keywords are reserved words that have predefined meaning and they are used to perform specific tasks.

Some examples of Java keywords are:

1. **if**
2. **while**
3. **class**
4. **public**
5. **static**
6. **void**
7. **return**

Note: **true**, **false**, and **null** are reserved literals, not keywords.

↳ Identifiers:



An identifier is a **user-defined name** given to variables, methods, classes, interfaces, packages, or other program elements to identify them uniquely.

Naming Rules for Identifiers in Java:

1. An identifier cannot start with a digit (0–9).
2. An identifier cannot contain spaces.
3. An identifier cannot contain special characters except the underscore (`_`) and dollar sign (`$`).
4. Java identifiers are case-sensitive.
5. An identifier cannot be a Java keyword (**reserved word**).

↳ Literals in Java:



Literals are **fixed values** that are directly assigned to variables or used in a Java program.

Examples of literals include:

- ✓ Numeric literals (e.g., 10, 3.14)
- ✓ Character literals (e.g., 'A')
- ✓ String literals (e.g., "Hello")
- ✓ Boolean literals (true, false)
- ✓ Null literal (null)

↳ Punctuators / (Separators):



Punctuators are special symbols in Java program used to **structure and organize the code**.

Common Punctuators in Java

- ; Semicolon (Statement Terminator)
- , Comma (Separator)
- . Dot (Member Access/Package Separator)
- () Parentheses (Method Calls, Parameters, Conditions)
- {} Curly Braces (Block of Code)
- [] Square Brackets (Arrays)
- : Colon (Used in Ternary Operator, Enhanced for-Loop, Switch Labels)

Public class in Java



public is an **access modifier** that makes a **class accessible from anywhere in the program**.

Class names should follow the PascalCase naming convention, where the **first letter of each word is capitalized**.

Example: - StudentLibraryManagement

↳ Rules of a public Class in Java:



- ✓ The **file name must exactly match the public class name**.
- ✓ A Java source file can contain **only one public class**.
- ✓ The public keyword must be written **before** the class keyword.
- ✓ The class name must be a **valid Java identifier**.

Example:

```
J Demo.java X README.md
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     ⚡
5 }
```

Main methods in Java



The **main()** method is the entry point of a Java application the JVM starts executing the program by **invoking the main()** method.

► Breakdown of the main() Method

1. public: is an access modifier that allows the **JVM** to access the **main()** method from anywhere.

2. static: means the **main()** method belongs to the class, so the **JVM** can call it **without creating an object** of the class.

3. void: is the **return type**, which indicates that the **main()** method does not return any value.

4. main: is the **predefined method name** that the **JVM** looks for as the starting point of a Java application.

5. String[] args: is an **array of strings** used to receive **command-line arguments** passed to the program.

Syntax:

```
public static void main(String[] args) {  
    //statements  
}
```

Example:

The screenshot shows an IDE with a file named 'Demo.java'. The code is as follows:

```
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         System.out.println("Hello, World!");  
6     }  
7 }
```

On the right, there is a 'Terminal' window showing the command prompt output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program  
Files\Eclipse Adoptium\jdk-25.0.3-hotspot\bin\java.exe' '-XX:  
+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDr  
ive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'  
Hello, World!  
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Variables in Java



A variable is a named **memory container** used to **store data** that can be **accessed and manipulated** during program execution.

In Java, variable names are **case-sensitive**.

Variable names should be valid **Java identifiers**.

```
J Demo.java 1 X README.md
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         int age = 10; // data type int, age is the actual variable or memory location, 22 is integer type of data.
6     }
7 }
```

Variable Declaration:



Variable declaration is the process of creating a variable by **specifying its data type and name**.

Example:

```
J Demo.java X README.md
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         int age;
6     }
7 }
```

Variable Initialization:



Variable initialization is the process of assigning a value to a variable.

Example:

```
J Demo.java X README.md
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         int age;
6         age = 22;
7         system.out.println("Age is: " + age);
8     }
9 }
```

Chat

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMess
ages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
Age is: 22
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Note: Java allows a variable to be declared and initialized in the same statement.

Many Values to Multiple Variables



Java allows multiple values to multiple variables within the same statement, but each variable must be explicitly assigned its value.

Syntax: datatype variable1 = value1, variable2 = value2, variable3 = value3;

Example:

```
1 package com.channa.JavaPractice;
2
3 public class Student {
4     Run | Debug
5     public static void main(String[] args) {
6         int num1 = 10, num2 = 20, num3 = 30;
7         System.out.println( num1);
8         System.out.println( num2);
9         System.out.println( num3);
10    }
```

```
PS C:\Users\chann\OneDrive\Desktop\Java> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\AppData\Roaming\Code\User\workspaceStorage\5e2c2e376685f5334087bb01b694a44c\re-dhat.java\jdt_ws\Java_e2daa7ee\bin' 'com.channa.JavaPractice.Student'
10
20
30
PS C:\Users\chann\OneDrive\Desktop\Java>
```

Single Value to Multiple Variables



Java allows a single value to be assigned to multiple variables in a single statement using chained assignment.

Example:

```
1 package com.channa.JavaPractice;
2
3 public class Student {
4     Run | Debug
5     public static void main(String[] args) {
6         // int num1 = num2 = num3 = 10; CTE
7         //Java does not allow declaration and chained assignment together
8
9         //Java allows chained assignment after the variables are declared.
10        int num1, num2, num3; // declaration
11        num1 = num2 = num3 = 10; // assignment
12        System.out.println( num1);
13        System.out.println( num2);
14        System.out.println( num3);
15    }
16 }
```

```
PS C:\Users\chann\OneDrive\Desktop\Java> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\AppData\Roaming\Code\User\workspaceStorage\5e2c2e376685f5334087bb01b694a44c\re-dhat.java\jdt_ws\Java_e2daa7ee\bin' 'com.channa.JavaPractice.Student'
10
10
10
PS C:\Users\chann\OneDrive\Desktop\Java>
```

Operators in Java



Operators are **predefined symbols** used to perform operations on operands (values or variables)

In Java, operators are classified into seven main types:

1. Arithmetic Operators
2. Assignment Operators
3. Relational (Comparison) Operators
4. Logical Operators
5. Ternary (Conditional) Operator
6. Unary Operators
7. Bitwise Operators

➤ Arithmetic Operators:



Arithmetic operators are predefined symbols used to perform mathematical operations on operands (values or variables).

Arithmetic Operators are classified into 5 types in java:

- ✓ Addition (+)
- ✓ Subtraction (-)
- ✓ Multiplication (*)
- ✓ Division (/) and
- ✓ Modulus (%).

Example program:

```
src > com > channa > JavaPractice > Demo.java > {} com.channa.JavaPractice
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num1 = 5;
6         int num2 = 10;
7         System.out.println("Addition: " + (num1 + num2));
8         System.out.println("Subtraction : " + (num1 - num2));
9         System.out.println("Multiplication : " + (num1 * num2));
10        System.out.println("Division: " + (num1 / num2));
11        System.out.println("Modulus: " + (num1 % num2));
12    }
13 }
14
```

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> cd src
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src> javac com\chann
a\JavaPractice\Demo.java
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src> java com.channa
.JavaPractice.Demo
Addition: 15
Subtraction :-5
Multiplication :50
Division: 0
Modulus: 5
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src>
```


➤ Assignment Operators in Java:



Assignment operators are used to assign values or the result of an expression to variables.

In Java, the basic assignment operators are:

- ✓ = Simple Assignment
- ✓ += Add and Assign
- ✓ -= Subtract and Assign
- ✓ *= Multiply and Assign
- ✓ /= Divide and Assign
- ✓ %= Modulus and Assign

Example program:

```
Demo.java | README.md
src > com > channa > JavaPractice > Demo.java | Demo | main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int laddus = 5;
6         laddus += 25;
7         laddus -= 20;
8         laddus *= 2;
9         System.out.println("Total laddus are: " + laddus);
10    }
11 }
```

```
Chat
Terminal
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> cd C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src> javac com\channa\JavaPractice\Demo.java
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src> java com.channa.JavaPractice.Demo
Total laddus are: 20
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\src>
```

➤ Relational Operators:



Relational operators are used to compare two operands and return a Boolean result like (true or false).

Types of Relational Operators:

- > Greater Than
- < Less Than
- >= Greater Than or Equal To
- <= Less Than or Equal To
- == Equal to
- != Not Equal to

Example program:

```
Demo.java | README.md
src > com > channa > JavaPractice > Demo.java | Demo | main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num1 = 10;
6         int num2 = 20;
7         System.out.println("> := " + (num1 > num2));
8         System.out.println("< := " + (num1 < num2));
9         System.out.println(">= := " + (num1 >= num2));
10        System.out.println("<= := " + (num1 <= num2));
11        System.out.println("== := " + (num1 == num2));
12        System.out.println("!= := " + (num1 != num2));
13    }
14 }
```

```
Chat
Terminal
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
> := false
< := true
>= := false
<= := true
== := false
!= := true
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ Unary Operators in Java:



Unary operators are used to operate on a single operand to perform a specific operation.

The main Types of Unary Operators are used in Java are:

- ++ Increment
- Decrement

➤ **Unary Increment Operator:** is used to increase the value by one.

Increment Operator have two types:

1. Pre-Increment Operator
2. Post-Increment Operator

➤ **Pre-Increment Operator:** means first increase the value by one then use it.

Example:

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num = 10;
6         int temp = ++num; // 10 increased by 1 then assigned to temp.
7         System.out.println(temp);
8         System.out.print(num);
9     }
10 }
11
```

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adopti
um\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp'
'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
11
11
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ **Post-Increment Operator:** means first use the value then Increase by one.

Example:

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num = 10;
6         int temp = num++; // 10 assigned to temp then increased by 1
7         System.out.println(temp);
8         System.out.print(num);
9     }
10 }
11
```

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adopti
um\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp'
'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
10
11
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

☞ **Unary Decrement Operator:** is used to decrease the value by one.

Decrement Operator have two types:

1. Pre-Decrement Operator
2. Post-Decrement Operator

☞ **Pre-Decrement Operator:** means first decrease the value by one then use it.

Example:

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num = 10;
6         int temp = --num; // 10 decreased by 1 then assigned to temp.
7         System.out.println(temp);
8         System.out.print(num);
9     }
10 }
```

☞ **Post-Decrement Operator:** means first use the value then decrease by one.

Example:

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num = 10;
6         int temp = num--; // 10 assigned to temp then decreased by 1.
7         System.out.println(temp);
8         System.out.print(num);
9     }
10 }
```

➤ Logical Operators in Java:



Logical operators are used to combine or negate conditional expressions. The result of a logical operation is **true or false**.

Operators:

&& (and) = true if both the conditions are true.

|| (or) = true if at least one condition is true.

! (not) = It reverses the result.

➤ **&& (Logical AND):** The logical AND operator returns true only if both the given conditions are true; otherwise, it returns false.

Truth table:

A	B	C
True	True	True
True	False	False
False	True	False
False	False	False

Example:


The screenshot shows the Eclipse IDE with a Java file named `Demo.java`. The code defines a `main` method that initializes two integers, `num1` (10) and `num2` (11). It then calculates a boolean result using the logical AND operator: `boolean result = num1++ > num2++ || num1++ < ++num2;`. The code is highlighted in green. The terminal on the right shows the command `PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'` and the output `true`.

➤ **|| (Logical OR):** The logical OR operator returns true if at least one of the given conditions is true.

Truth table:

A	B	C
True	True	True
True	False	True
False	True	True
False	False	False

Example:



```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num1 = 10;
6         int num2 = 11; // 10 assigned to temp then decreased by 1.
7         boolean result = num1++ > num2++ && num1++ < ++num2;
8         System.out.println(result);
9     }
10 }
```

Chat

Terminal


PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo' false
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>

! (Logical NOT): The logical NOT, is also known as negation operator, used to invert or negate a boolean value.

Truth table:

Expression	Result
True	False
False	True

Example:




```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int num1 = 10;
6         int num2 = 10; // 10 assigned to temp then decreased by 1.
7         boolean result = num1 == num2;
8         System.out.println(!result);
9     }
10 }
```

Chat

Terminal

PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo' false
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>


Ternary (Conditional) Operator in Java:



The **ternary operator** is a **conditional operator that evaluates** a condition and **returns one of two expressions** depending on whether the condition is **true or false**.

Syntax: (condition) ? expression1 : expression2;

Example:



```
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice;
2
3 public class Demo {
4     public static void main(String[] args){
5         int age = 18;
6         String result = (age >= 18)? "Channa is eligibal for vote" : "Channa is not eligibal for vote";
7         System.out.print("Result is: " + result);
8     }
9 }
```

Chat

Terminal

PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo' Result is: Channa is eligibal for vote
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>

Operator precedence in Java



Operator precedence determines **which operator is evaluated first** when an expression contains multiple operators.

Example: `int result = 10 + 5 * 2;`

Here, * has higher precedence than +, so multiplication happens first:
→ Higher precedence → evaluated first.

Note: if two operators have the **same precedence**, Java uses **associativity** to determine the evaluation direction.

↳ **Associativity in Operator precedence:**



Associativity determines the **direction in which operators with the same precedence are evaluated**.

Java has **two associativity directions**:

- ↳ **Left-to-right associativity**
- ↳ **Right-to-left associativity**

↳ **Left-to-right associativity**

+ and **-** have the **same precedence**, and their associativity is **left-to-right**.

Example: `int result = 20 - 5 + 2;`

Java evaluates: $(20 - 5) + 2$
 $15 + 2 = 17$

Note: **+**, **-**, *****, and **/** use **left-to-right associativity**.

➤ Right-to-left associativity

Example: `int a, b, c = 10;`

Java groups it **from right to left:** `a = (b = (c = 10))`

So:

1. `c = 10`
2. `b = 10`
3. `a = 10`

Therefore, **= assignment operator** has right-to-left associativity.

Java Operator Precedence — Highest – To – Lowest

Priority	Operators	Category	Associativity
1	<code>() [] .</code>	Postfix / access	Left to Right
2	<code>expr++, expr--</code>	Postfix	Left to Right
3	<code>++expr, --expr +, -, !, ~</code>	Unary	Right to Left
4	<code>*, /, %</code>	Multiplicative	Left to Right
5	<code>+, -</code>	Additive	Left to Right
6	<code><<, >>, >>></code>	Shift	Left to Right
7	<code><, >, <=, >= & instanceof</code>	Relational	Left to Right
8	<code>==, !=</code>	Equality	Left to Right
9	<code>& ^ </code>	Bitwise AND, XOR, OR	Left to Right
10	<code>&&, </code>	Logical AND, OR	Left to Right
11	<code>?:</code>	Ternary / Conditional	Right to Left
12	<code>=, +=, -=, *=, /=, %= etc.</code>	Assignment	Right to Left
13	<code>-></code>	Lambda	Right to Left

Note: In Java, parentheses () have the highest precedence. By grouping operators using parentheses, we can change the direction/order of evaluation.

Example:

```
1 package com.channa.JavaPractice;
2
3 public class Student {
4     public static void main(String[] args){
5         int num1 = 10;
6         int num2 = 5;
7         // without grouping expression will execute from left to right.
8         int result = num1 - (num2 - 2);
9         System.out.println("result is: " + result);
10    }
11 }
```

PS C:\Users\chann\OneDrive\Desktop\Java> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\AppData\Roaming\Code\User\workspaceStorage\5e2c2e376685f5334087bb01b694a44c\redhat.java\jdt_ws\Java_e2daa7ee\bin' 'com.channa.JavaPractice.Student'
result is: 7
PS C:\Users\chann\OneDrive\Desktop\Java>

Expression in Java

Expression in Java is a combination of variables, values, and operators that evaluates and produces a single value.

Example: `int result = 10 + 5 * 2;`

Here:

- 10, 5, 2 are values
- +, * are operators
- 10 + 5 * 2 is an expression

☞ The expression evaluates to 20 (**single value**)

Data types in Java

A data type specifies the type of data a variable can store, the amount of memory allocated, the range of values it can hold and what operations can be performed on that value.

In Java, data types are classified into two types:

1. Primitive Data Types.
2. Non-Primitive (Reference) Data Types: **Classes, objects, interfaces, strings etc.**

↳► Primitive data types in Java:



Primitive data types are **built-in data types** provided by Java that store single value.

In Java, **primitive data types** are classified into **8 types**:

Primitive Data Types	Size	Default value
byte	1 byte (8 bits)	0
short	2 bytes (16 bits)	0
char	2 bytes (16 bits)	'\u0000'
int	4 bytes (32 bits)	0
long	8 bytes (64 bits)	0L
float	4 bytes (32 bits)	0.0f
double	8 bytes (64 bits)	0.0d
boolean	JVM-dependent	false

↳► Bits and Bytes in Java:



↳► **Bit:** A **bit (binary digit)** is the smallest unit of data in a computer that can store either **0** or **1**.

↳► **Byte:** A **byte** is a unit of memory consisting of **8 bits**.

Quick Memory Trick

- 1 Bit = 0 or 1
- 8 Bits = 1 Byte
- 1024 Bytes = 1 KB
- 1024 KB = 1 MB
- 1024 MB = 1 GB
- 1024 GB = 1 TB

➤ ASCII Values:



ASCII (American Standard Code for Information Interchange)

It is a character encoding standard that assigns a unique numeric value to each character.

Why do we need ASCII?

Computers understand only **binary (0s and 1s)**, not characters like **A, B**, or **@**.

ASCII provides a numeric code for each character so the computer can store and process it.

ASCII values are:

Decimal	Character	Description
0	NUL	Null
1	SOH	Start of Heading
2	STX	Start of Text
3	ETX	End of Text
4	EOT	End of Transmission
5	ENQ	Enquiry
6	ACK	Acknowledge
7	BEL	Bell
8	BS	Backspace
9	TAB	Horizontal Tab
10	LF	Line Feed (New Line)
11	VT	Vertical Tab
12	FF	Form Feed
13	CR	Carriage Return
14	SO	Shift Out
15	SI	Shift In
16	DLE	Data Link Escape
17	DC1	Device Control 1

Decimal	Character	Description
18	DC2	Device Control 2
19	DC3	Device Control 3
20	DC4	Device Control 4
21	NAK	Negative Acknowledge
22	SYN	Synchronous Idle
23	ETB	End of Transmission Block
24	CAN	Cancel
25	EM	End of Medium
26	SUB	Substitute
27	ESC	Escape
28	FS	File Separator
29	GS	Group Separator
30	RS	Record Separator
31	US	Unit Separator
32	Space	Space
33	!	Exclamation Mark
34	"	Double Quote
35	#	Hash
36	\$	Dollar
37	%	Percent
38	&	Ampersand
39	'	Apostrophe
40	(	Left Parenthesis
41	)	Right Parenthesis
42	*	Asterisk
43	+	Plus
44	,	Comma
45	-	Hyphen
46	.	Period
47	/	Slash
48	0	Digit Zero
49	1	Digit One

Decimal	Character	Description
50	2	Digit Two
51	3	Digit Three
52	4	Digit Four
53	5	Digit Five
54	6	Digit Six
55	7	Digit Seven
56	8	Digit Eight
57	9	Digit Nine
58	:	Colon
59	;	Semicolon
60	<	Less Than
61	=	Equal
62	>	Greater Than
63	?	Question Mark
64	@	At Symbol
65–90	A–Z	Uppercase Letters
91	[	Left Square Bracket
92	\	Backslash
93	]	Right Square Bracket
94	^	Caret
95	_	Underscore
96	`	Backtick
97–122	a–z	Lowercase Letters
123	{	Left Curly Brace
124		Vertical Bar (Pipe)
125	}	Right Curly Brace
126	~	Tilde
127	DEL	Delete

Type Casting



Type casting is the process of converting a value or variable from one data type to another.

Java supports two types of type casting:

- ↳ Widening (**Implicit Type Casting**)
- ↳ Narrowing (**Explicit Type Casting**)

↳ Widening Type Casting (Implicit):



Widening is the **automatic conversion** of a **smaller data type** to a **larger compatible data type** without data loss.

Example:

```
src > com > channa > JavaPractice > Demo.java > Demo
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         int num1 = 10;
6         double num2 = num1;
7         System.out.print("Result: " + num2);
8     }
9 }
```

Terminal Output: PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo' Result: 10.0

↳ Narrowing Type Casting (Explicit):



Narrowing type casting is the **manual conversion** of a **larger data type** to a **smaller compatible data type** using the **cast operator ()**.

Example:

```
src > com > channa > JavaPractice > Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         double num1 = 10.99;
6         int num2 = (int) num1;
7         System.out.print("Result: " + num2);
8     }
9 }
```

Terminal Output: PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo' Result: 10

Note: Converting short to char and char to short are both narrowing conversions (explicit type casting).

Type Promotion in Java



Type promotion occurs when Java automatically promotes the smaller integer types, such as **byte**, **short**, **char**, to **int** during arithmetic operations.

Example:

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         byte num1 = 5;
6         short num2 = 6;
7         char num3 = 5;
8         int num4 = num1 + num2 + num3;
9         System.out.println("Result: " + num4);
10    }
11 }
```

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
Result: 16
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Control Statements in Java



Control statements are used to **control the flow of program execution** by making decisions, repeating code, or transferring control.

In Java, control statements are classified into three types:

1. **Selection (Decision-Making) Statements**
2. **Iteration (Looping) Statements**
3. **Transfer Control (Jump) Statements**

➤ Selection Statements:



Selection statements are used to **select and execute a block of code** based on a specified condition.

In Java, selection statements are classified into five types:


1. **if**
2. **if-else**
3. **else-if ladder**
4. **nested if**
5. **switch**

↳ **if Statement:** is a selection statement used to **select and execute the if block** if the specified condition evaluates to **true**.

Syntax: -

```
if (condition) {  
    // statements  
}
```

Example:



The screenshot shows an IDE with a Java file named Demo.java. The code is as follows:

```
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         boolean isAdult = true;  
6         if(isAdult){  
7             System.out.println("Eligibal");  
8         }  
9     }  
10 }
```


The terminal output shows the command to run the program and the output "Eligibal".

↳ **if – else Statement:** is a selection statement, it executes the **if block**, if the specified condition evaluates to **true** and **else block**, if the specified condition evaluates to **false**.

Syntax:

```
if (condition) {  
    // statements  
}  
else {  
    // statements  
}
```

Example:



The screenshot shows an IDE with a Java file named Demo.java. The code is as follows:

```
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         boolean isAdult = false;  
6         if(isAdult){  
7             System.out.println("Eligibal");  
8         } else {  
9             System.out.println("Not Eligibal");  
10        }  
11    }  
12 }
```


The terminal output shows the command to run the program and the output "Not Eligibal".

➤ **else-if ladder:** is a selection statement used to **check multiple conditions** and **execute the corresponding block** of code based on the **first condition** that evaluates to **true**.

Syntax:

```
if (condition1) {  
    // statements  
}  
else if (condition2) {  
    // statements  
}  
else if (condition3) {  
    // statements  
}  
else {  
    // statements  
}
```

Example:



The screenshot shows an IDE with a Java file named `Demo.java`. The code defines a `main` method that uses an else-if ladder to check the value of `marks` (88) and print the corresponding result. The terminal window on the right shows the command to run the program and the output: `Distinction`.

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])  
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         int marks = 88;  
6         if(marks < 0 || marks > 100){  
7             System.out.println("Invalid marks: Please provide valid marks.");  
8         } else if(marks <= 30){  
9             System.out.println("Fail");  
10        } else if(marks <= 50){  
11            System.out.println("Pass");  
12        } else if(marks <= 80){  
13            System.out.println("First class");  
14        } else {  
15            System.out.println("Distinction");  
16        }  
17    }  
18 }
```

Terminal
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMess
ages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
Distinction
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>


Note: Nested if statement means placing an if statement inside another if statement to check a condition inside another.

↳ ➤ **Switch Statement:** is a selection statement used to select and execute one block of code from multiple alternatives based on the value of a specified expression.

Syntax:


```
switch (expression) {  
    case value1: // statements break;  
  
    case value2: // statements break;  
  
    case value3: // statements break;  
  
    default: // statements  
}
```

Example:



The screenshot shows an IDE with a Java file named 'Demo.java'. The code defines a 'Demo' class with a 'main' method. Inside 'main', a variable 'choice' is set to 1. A 'switch' statement follows, with three cases: 'case 1' prints 'Vote for Namu', 'case 2' prints 'Vote for Pappu', and 'case 3' prints 'Vote for JDS'. A 'default' case prints 'Invalid choice'. The terminal output shows the execution of the program, displaying 'Vote for Namu'.

↳ ➤ **Iteration Statements:**



Iteration statements are used to repeatedly **execute a block of code** as long as a specified condition evaluates to **true**.

In Java, iteration statements are classified into four types:


1. while loop
2. do-while loop
3. for loop
4. enhanced for (for-each) loop (We learn in Arrays)

➤ **while loop:** Used to **repeatedly execute a block of code** as long as the specified condition evaluates to **true**, primarily used when the **number of iterations is unknown**.

Syntax:

```
while(Condition) {  
    //statements  
}
```

Example:



```
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         int name = 5;  
6         while (name > 0) {  
7             System.out.println("Channakeshavareddy");  
8             name --;  
9         }  
10    }  
11 }
```

Terminal Output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &  
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp  
ot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMess  
ages -cp 'C:\Users\chann\OneDrive\Desktop\Java\Jav  
aPrac\bin' 'com.channa.JavaPractice.Demo'  
Channakeshavareddy  
Channakeshavareddy  
Channakeshavareddy  
Channakeshavareddy  
Channakeshavareddy  
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```


➤ **do-while loop:** is an **exit-controlled iteration statement**, used to execute the loop body at least once, even if the specified condition evaluates to **false**.

Syntax:

```
do {  
    // statements  
} while (condition);
```

Note: The do-while loop ends with a semicolon (;).

Example:



```
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         int name = 5;  
6         do {  
7             System.out.println("Channakeshavareddy");  
8             name --;  
9         } while (name > 0);  
10    }  
11 }
```

Terminal Output:


```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &  
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp  
ot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMess  
ages -cp 'C:\Users\chann\OneDrive\Desktop\Java\Jav  
aPrac\bin' 'com.channa.JavaPractice.Demo'  
Channakeshavareddy  
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

↳ **for loop:** Used to **repeatedly execute a block of code** as long as the **specified condition evaluates to true**, primarily when the **number of iterations is known**.

Syntax:

```
for (initialization; condition; update) {  
    // statements  
}
```

Example:



The screenshot shows an IDE with a Java file named 'Demo.java'. The code defines a package 'com.channa.JavaPractice' and a class 'Demo' with a 'main' method. Inside the 'main' method, a 'for' loop is used to iterate from 1 to 5, printing each value. The terminal output shows the numbers 1, 2, 3, 4, and 5 printed on separate lines.

```
src > com > channa > JavaPractice > Demo.java > Demo > main(String[])  
1 package com.channa.JavaPractice; //package  
2  
3 public class Demo {  
4     public static void main(String[] args) {  
5         for(int i = 1; i <= 5; i++) {  
6             System.out.println(i);  
7         }  
8     }  
9 }
```

Terminal Output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &  
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp  
ot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMess  
ages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\jav  
aPrac\bin' 'com.channa.JavaPractice.Demo'  
1  
2  
3  
4  
5  
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ Transfer Control Statements:



Transfer control statements are used to alter the normal flow of program execution.

Transfer Control Statements are: -

1. break
2. continue
3. return

➤ **break:** Used to immediately terminates the execution of the nearest enclosing loop and transfers control to the next statement.

Example:

```
src > com > channa > JavaPractice > Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         for(int i = 1; i <= 5; i++) {
6             System.out.println(i);
7             if(i == 3){
8                 break;
9             }
10        }
11    }
12 }
```

Terminal output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMess
ages' -cp 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
1
2
3
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ **continue:** Used to skip the current iteration of the nearest enclosing loop and continue with the next iteration.

Example:

```
src > com > channa > JavaPractice > Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     public static void main(String[] args) {
5         for(int i = 1; i <= 5; i++) {
6             if(i == 3){
7                 continue;
8             }
9             System.out.println(i);
10        }
11    }
12 }
```

Terminal output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMess
ages' -cp 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
1
2
4
5
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ **return:** Used to immediately terminate the execution of the current method and optionally return a value to the caller.

Example:

```
src > com > channa > JavaPractice > Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2
3 public class Demo {
4     private static int add(){
5         return 10 + 5;
6     }
7     public static void main(String[] args) {
8         int sum = add();
9         System.out.println(sum);
10    }
11 }
```

Terminal output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMess
ages' -cp 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
15
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Scanner Class in Java



The **Scanner class** is a predefined class used to **read user input from the keyboard**.

The Scanner class belongs to the **java.util** package.

↳ **Creating a Scanner class Object:**


Syntax: Scanner scan = **new** Scanner(**System.in**);

Common Input Methods are:

nextByte()	Byte
nextShort()	Short
nextInt()	Int
nextLong()	Long
nextFloat()	Float
nextDouble()	Double
nextBoolean()	Boolean
next()	A single word (String)
nextLine()	An entire line (String)
next().charAt(0)	A single character

Basic Programs

Program 1: WAP to Print 1 to N natural Numbers?




```
src > com > channa > JavaPractice > Demo > main(String[])
2 import java.util.Scanner;
3 public class Demo {
4     public static void main(String[] args) {
5         Scanner scan = new Scanner(System.in);
6         System.out.print(s: "Enter a positive number: ");
7         int num = scan.nextInt();
8         for(int i = 1; i <= num; i++) {
9             System.out.println(i);
10        }
11    }
12 }
```

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMess
ages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
Enter a positive number: 10
1
2
3
4
5
6
7
8
9
10
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Program 2: WAP to Print N to 1 natural Numbers?



```
src > com > channa > JavaPractice > Demo > main(String[])
2 import java.util.Scanner;
3 public class Demo {
4     public static void main(String[] args) {
5         Scanner scan = new Scanner(System.in);
6         System.out.print(s: "Enter a positive number: ");
7         int num = scan.nextInt();
8         for(int i = num; i >= 1; i--) {
9             System.out.println(i);
10        }
11    }
12 }
```

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMess
ages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
Enter a positive number: 10
10
9
8
7
6
5
4
3
2
1
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Program 3: WAP to print sum of 1 to N natural Numbers?



```
src > com > channa > JavaPractice > Demo > main(String[])
2 import java.util.Scanner;
3 public class Demo {
4     public static void main(String[] args) {
5         Scanner scan = new Scanner(System.in);
6         System.out.print(s: "Enter a positive number: ");
7         int num = scan.nextInt();
8         int sum = 0;
9         for(int i = 1; i <= num; i++){
10             sum += i;
11        }
12        System.out.println("Sum of one to N natural numbers: " + sum);
13        scan.close();
14    }
15 }
```

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> &
'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotsp
ot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMess
ages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\Jav
aPrac\bin' 'com.channa.JavaPractice.Demo'
Enter a positive number: 5
Sum of one to N natural numbers: 15
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Program 4: WAP to print the factorial value of the given number?



```
src > com > channa > JavaPractice > Demo > main(String[])
2 import java.util.Scanner;
3 public class Demo {
4     public static void main(String[] args) {
5         Scanner scan = new Scanner(System.in);
6         System.out.print(s: "Enter a positive number: ");
7         int num = scan.nextInt();
8         int factorial = 1;
9         for(int i = 1; i <= num; i++){
10             factorial *= i;
11        }
12        System.out.println("Factorial value of the given number is: " + factorial);
13        scan.close();
14    }
15 }
```

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPra
c> & 'C:\Program Files\Eclipse Adoptium\jdk-25
.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDeta
ilsInExceptionMessages' '-cp' 'C:\Users\chann\O
neDrive\Desktop\Java\JavaPrac\bin' 'com.channa.
JavaPractice.Demo'
Enter a positive number: 5
Factorial value of the given number is: 120
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPra
c>
```

Methods in Java



A method is a reusable block of code that performs a specific task.

Syntax: **returnType methodName(parameters) {**
 // code
 }

Example:

```
public static void greet() {  
    System.out.println("Hello");  
}
```

Calling the method:

Method calling is the process of invoking a method to execute its defined task.

Example: -

```
public class Demo {  
    public static void greet() {  
        System.out.println("Hello");  
    }  
    public static void main(String[] args) {  
        greet();  
    }  
}
```

- **Parameters and method name** together are called the method signature.
- **Access modifier, return type, and method signature** together are called the method declaration.
- **Method declaration and method body** together are called the method definition.

Return Statement in Methods



The **return statement** is used to terminate a method and return a value to the caller based on return type.

void indicates that a **method does not return any value** to the caller.

In Java, methods are commonly classified into 4 types based on parameters and return type.

1. **Method with Parameters & Return Value .**
2. **Method without Parameters & without Return Value.**
3. **Method with Parameters & without Return Value.**
4. **Method without Parameters & Return Value.**

➤ Method with Parameters & Return Value:



A method **with parameters and a return value** accepts input through **parameters**, performs a specific task, and **returns a value** to the caller.

Syntax: **returnType methodName(parameter1, parameter2.....) {**
 // Method body
 return value;
 }

Example:

The screenshot shows an IDE with a Java file named 'Demo.java'. The code defines a package 'com.channa.JavaPractice', a class 'Demo', and a static method 'add' that takes two integers and returns their sum. The 'main' method calls 'add(10, 20)' and prints the result. The terminal on the right shows the command to run the program, which outputs '30'.

```
src > com > channa > JavaPractice > J Demo.java > {} com.channa.JavaPractice
1 package com.channa.JavaPractice; //package
2 public class Demo {
3
4     static int add(int a, int b) {
5         return a + b;
6     }
7
8     public static void main(String[] args) {
9         int sum = add(a: 10, b: 20);
10        System.out.println(sum);
11    }
}
```


Terminal Output:

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
30
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```


➤ Method without Parameters & without Return Value:

A method without parameters and without a return value performs a specific task without accepting any input or returning any value to the caller.

Example:



```
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice; //package
2 public class Demo {
3
4     static void greet() {
5         System.out.println("Hello, Java!");
6     }
7
8     Run | Debug
9     public static void main(String[] args) {
10         greet();
11     }
12 }
```

Chat


Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
Hello, Java!
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ Method with Parameters & without Return Value:

A method with parameters and without a return value accepts input through parameters but does not return any value to the caller.

Example:



```
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice; //package
2 public class Demo {
3
4     static void add(int a, int b) {
5         System.out.println(a + b);
6     }
7
8     Run | Debug
9     public static void main(String[] args) {
10         add(10, 20);
11     }
12 }
```

Chat


Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
30
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

➤ Method without Parameters & with Return Value:

A method without parameters and with a return value does not accept any input, performs a specific task, and returns a value to the caller.

Example:



```
src > com > channa > JavaPractice > J Demo.java > Demo
1 package com.channa.JavaPractice; //package
2 public class Demo {
3     static int getNumber() {
4         return 100;
5     }
6
7     Run | Debug
8     public static void main(String[] args) {
9         int number = getNumber();
10        System.out.println(number);
11    }
12 }
```

Chat

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
100
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

Method Arguments in Java



Method arguments in Java are classified into two types:

1. Positional arguments
2. Variable-length positional arguments (Varargs)

➤ Positional arguments



Positional arguments are arguments passed to a method based on the order or position of the parameters.

Example:

```
1 package com.channa.JavaPractice;
2
3 public class Student {
4     static void m1(int num, String name){
5         System.out.println("Age = " + num);
6         System.out.println("Name = " + name);
7     }
8     public static void main(String[] args){
9         m1(num: 22, name: "Channakeshavareddy G N");
10    }
11 }
```

```
PS C:\Users\chann\OneDrive\Desktop\Java> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\AppData\Roaming\Code\User\workspaceStorage\5e2c2e376685f5334087bb01b694a44c\redhat.java\jdt_ws\Java_e2daa7ee\bin' 'com.channa.JavaPractice.Student'
Age = 22
Name = Channakeshavareddy G N
PS C:\Users\chann\OneDrive\Desktop\Java>
```

➤ Variable-length positional arguments (Varargs...)



Variable-length positional arguments allow a method to accept any number of positional arguments.

Java methods use varargs (...) to accept any number of positional arguments.

Example:

```
package com.channa.JavaPractice;

public class Student {
    static void m1(int... nums) { // varargs parameter, internally treated as an array
        // it prints the array's default string representation
        System.out.println("varargs should not access like this: " + nums);

        System.out.println("\nvarargs can be access using index: \n" + nums[0]);
        System.out.println(nums[1]);
        System.out.println(nums[2]);
        System.out.println(nums[3]);
        System.out.println(nums[4]);
        System.out.println(nums[5]);
    }

    public static void main(String[] args){
        m1(...nums: 10,20,30,40,50,60);
    }
}
```

```
PS C:\Users\chann\OneDrive\Desktop\Java> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3-hotspot\bin\java.exe' -XX:+ShowCodeDetailsInExceptionMessages -cp 'C:\Users\chann\AppData\Roaming\Code\User\workspaceStorage\5e2c2e376685f5334087bb01b694a44c\redhat.java\jdt_ws\Java_e2daa7ee\bin' 'com.channa.JavaPractice.Student'

varargs should not access like this: [I@7ad041f3

varargs can be access using index:
10
20
30
40
50
60
PS C:\Users\chann\OneDrive\Desktop\Java>
```

Recursion in Java



Recursion is a programming technique in which a **method repeatedly calls itself** until it reaches the **base case**.

The **base case** is the **condition** that **stops the recursion**.

↳ **WAP to print the sum of 1 to N natural numbers using recursion technique?**

```
src > com > channa > JavaPractice > J Demo.java > Demo > sum(int)
1 package com.channa.JavaPractice; //package
2 public class Demo {
3     //sum method is Method with parameters and return value type
4     private static int sum(int num) {
5         if(num == 0){
6             return 0;
7         } else {
8             return num + sum(num - 1); // sum(num - 1); recursive call.
9         }
10    }
11
12    Run | Debug
13    public static void main(String[] args) {
14        int sum = sum(10); //method call by passing 10 as an argument
15        System.out.println(sum);
16    }
17 }
```

Chat

Terminal

```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
55
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

↳ **WAP to print the Factorial numbers using recursion technique?**

```
src > com > channa > JavaPractice > J Demo.java > Demo > main(String[])
1 package com.channa.JavaPractice; //package
2 public class Demo {
3     //factorial method is Method with parameters and return value type
4     private static int factorial(int num) {
5         if(num == 1){
6             return 1;
7         } else {
8             return num * factorial(num - 1); // sum(num - 1); recursive call.
9         }
10    }
11
12    Run | Debug
13    public static void main(String[] args) {
14        int factorial = factorial(10); //method call by passing 10 as an argument
15        System.out.println("Factorial value of n number is: " + factorial);
16    }
17 }
```

Chat

Terminal


```
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac> & 'C:\Program Files\Eclipse Adoptium\jdk-25.0.3.9-hotspot\bin\java.exe' '-XX:+ShowCodeDetailsInExceptionMessages' '-cp' 'C:\Users\chann\OneDrive\Desktop\Java\JavaPrac\bin' 'com.channa.JavaPractice.Demo'
Factorial value of n number is: 120
PS C:\Users\chann\OneDrive\Desktop\Java\JavaPrac>
```

JDK, JRE & JVM in Java



JAVA PROGRAM EXECUTION ARCHITECTURE

Java Program (.java)



1. Class Loader Subsystem

- ↳ **Bootstrap ClassLoader**
- ↳ **Extension ClassLoader**
- ↳ **Application ClassLoader**
- ↳ **Parent Delegation Model**

2. Runtime Memory Areas

- ↳ **Heap**
- ↳ **Stack**
- ↳ **Method Area**
- ↳ **PC Register**
- ↳ **Native Method Stack**


3. Execution Engine

- ↳ **Interpreter**
- ↳ **JIT Compiler**
- ↳ **Garbage Collector**

4. Java Native Interface (JNI)

5. Native Method Libraries

Complete Execution Flow:



↳ **JDK: Java Development Kit.**



JDK is known as **Java Development Kit**.

It is a **software development kit** used to develop and run Java programs.

JDK consists of:

1. **JRE** (Java Runtime Environment)

2. Development Tools:

↳ **javac** (Compiler)

↳ **java** (Launcher / Command-line tool)

↳ **javadoc** (Documentation Generator)

↳ **jar** (Java Archive Tool)

↳ **jdb** (Java Debugger)

↳ Other development tools

The relationship is that the JDK includes the JRE along with development tools.

1. What is javac in JDK?

javac is a Development tool inside JDK.

javac is a java compiler. It converts java **source code (.java)** into **bytecode (.class)**.

Without **javac**, Java source code cannot be compiled into bytecode.

2. What is java Launcher / Command line tool in JDK?

The java Launcher is a command-line tool in the JDK used to invoke (call) the JRE.

The JRE, starts the JVM to load and execute Java bytecode (.class).

Note: The JVM can be started by the java Launcher or by any other tool that invokes the JRE.

3.What is javadoc in JDK?

javadoc is documentation generation tool.

It is used to create documentation from java source code.

It reads comments in Java source file and generates HTML documentation.

javadoc works only with documentation comments.

Example: /**

```
This is class demonstrates
```

```
*/
```

```
public class Add {
```

```
/**
```

```
This is method add two numbers
```

```
*/
```

```
public static int add(int num1, int num2){
```

```
    return num1 + num2;
```

```
}
```

```
}
```

4.What is .jar in JDK?

jar is known as Java Archive.

It is a development tool used to package multiple **.class** files and resources into a single **.jar** file.

5. What is jdb in JDK?

jdb is a Java debugger tool provided by the JDK that is used to find and fix errors in Java programs.

Features:

- Set breakpoints.
- Inspect variable values.
- Control program execution

➤ JRE: Java Runtime Environment.



JRE is a software environment that provides the runtime environment to execute Java bytecode.

JRE consists of:

- JVM (Java Virtual Machine)
- Core Java Class Libraries
- Supporting files required to run Java programs.

↳ **JVM:** Java Virtual Machine.



JVM is an abstract machine that provides the runtime environment to execute Java bytecode.

JVM consists of:

- ↳ ClassLoader Subsystem
- ↳ Memory Areas
- ↳ Execution Engine
- ↳ Java Native Interface (JNI)
- ↳ Native Method Libraries

↳ **1. ClassLoader Subsystem in JVM?**

The **ClassLoader Subsystem** is a module of the **JVM** that loads Java bytecode (.class files) into JVM memory using different class loaders.

The main ClassLoaders are:

- ↳ **Bootstrap ClassLoader**
- ↳ **Platform ClassLoader**
- ↳ **Application ClassLoader**

1. What is the Bootstrap ClassLoader?

Bootstrap ClassLoader is the parent class loader that loads core Java classes into the **JVM**.

Examples:

- java.lang.String
- java.lang.Object
- java.lang.System

2. What is the Platform ClassLoader?

Platform ClassLoader is a **JVM class loader** that loads platform classes and Java platform modules into the **JVM**.

Examples:

- java.sql.DataSource
- java.sql.Driver
- java.xml.parsers.DocumentBuilder

3. What is the Application ClassLoader?

Application ClassLoader is a JVM class loader that loads user-defined classes into the JVM.

Examples:

- Main
- Student
- Hello

↳ Parent Delegation Model:

The **Parent Delegation Model** is a mechanism in which a **ClassLoader** first asks its **parent ClassLoader** to load a class before trying to load it itself.

The purpose of the **Parent Delegation Model** is to **ensure security, prevent duplicate class loading**, and maintain the class loading hierarchy in the JVM.

Flow of the Parent Delegation Model:

Step 1: Application ClassLoader receives the class loading request.

Step 2: It delegates the request to the Platform ClassLoader.

Step 3: The Platform ClassLoader delegates the request to the Bootstrap ClassLoader.

Step 4: The Bootstrap ClassLoader tries to load the class.

Step 5: If found → Class loaded.

Step 6: If not found, control returns to the Platform ClassLoader.

Step 7: The Platform ClassLoader tries to load the class.

Step 8: If found → Class loaded.

Step 9: If not found, control returns to the Application ClassLoader.

Step 10: The Application ClassLoader tries to load the class.

Step 11: If no ClassLoader can load the class, the JVM throws **ClassNotFoundException**.

↳ 2. Memory Areas in JVM:

JVM memory areas are the runtime memory regions where the JVM stores **objects, class information, method data, and execution information** during program execution.

The purpose of **JVM memory areas is to support the execution** of Java bytecode.

JVM has five main memory areas:

- **Heap**
- **Stack**
- **Method Area**
- **PC Register**
- **Native Method Stack**

1). What is Heap memory in JVM?

Heap memory is the runtime memory area in the JVM where **objects, arrays, and instance variables** are dynamically allocated.

2). What is Stack in JVM?

Stack memory is the runtime memory area in JVM that stores **method calls, Local variables, and references to objects in heap**, following **LIFO (Last in First Out) Order**.

3). What is the Method Area in the JVM?

Method Area is the runtime memory area in the JVM that stores **class-level information, including method bytecode, static variables, constants, and metadata**.

↳ What is metadata?

Metadata is runtime information about classes, methods, and fields used by the **JVM** during program execution.

4). What is PC – Register in JVM memory?

PC – Register stores the address of the current bytecode instruction for each thread in **JVM**.

5. What is the Native Method Stack in the JVM?

Native Method Stack is a **JVM memory area** that stores the **execution state, local variables, parameters, and call information of native methods** invoked by a Java program.

➤ 3. JVM Execution Engine:

Execution Engine is a **component of the JVM** that executes Java bytecode by converting it into machine code.

Execution Engine consists of:

- ↳ Interpreter
- ↳ JIT (Just-In-Time) Compiler
- ↳ Garbage Collector (GC)

1. What is the Interpreter in the JVM Execution Engine?

Interpreter is a component of the JVM Execution Engine that reads and executes **Java bytecode instruction by instruction (line by line)**.

The Interpreter is slower than the JIT Compiler because it executes bytecode one instruction at a time.

2. What is the JIT (Just-In-Time) Compiler in the JVM Execution Engine?

JIT Compiler is a component of the JVM Execution Engine; **it converts Java bytecode into native machine code at runtime for faster execution.**

JIT improves performance by executing frequently used code as native machine code.

3. What is the Garbage Collector (GC) in the JVM Execution Engine?

Garbage Collector (GC) is a component of the JVM Execution Engine that automatically removes unused or unreferenced objects from the heap memory to free memory.

↳➤ 4. Java Native Interface (JNI) in the JVM:

JNI is a bridge that allows Java programs to call native code written in languages such as C and C++.

It is mainly used to integrate Java with native libraries and access low-level system features.

↳➤ 5. Native Method Libraries in the JVM:

Native Method Libraries are collections of pre-compiled native code written in C or C++ that are accessed by Java programs through JNI.

They provide native functionality that Java uses through JNI to access low-level system features.

Final Summary: JVM executes Java programs using the **ClassLoader Subsystem, Memory Areas, Execution Engine, and Native Support (JNI & Native Method Libraries).**

↳➤ JRE Core Java Class Libraries:



Core Java Class Libraries are a collection of pre-defined packages and classes provided by the JRE that offer standard functionality such as

- data handling,
- input/output (I/O),
- collections,
- networking, and more.

These libraries are used by Java programs at runtime.

↳➤ JRE Supporting files:



Supporting files are non-Java files in JRE such as configuration, security and Native libraries that assist JVM and class libraries in executing java programs correctly.

 JAVA FUNDAMENTALS COMPLETED

Status : ✓ Completed

Foundation : ✓ Strong

Next Module : Object-Oriented Programming (OOP)

“Excellence in software starts with mastering the fundamentals”
