

Executive Report: The Evolution of Connected Worker Platforms, Industrial Wearables, and Automated Data Capture (AIDC)

1. The Connected Worker Ecosystem and Industrial Wearables Framework

The modern frontline operational environment is undergoing a structural transformation driven by the convergence of industrial Internet of Things (IoT), edge computing, and ergonomic human-machine interfaces¹. The Connected Worker ecosystem represents an integrated operational architecture that bridges frontline personnel with enterprise resource planning (ERP), warehouse management systems (WMS), and manufacturing execution systems (MES)¹. Rather than replacing human operators with full autonomy, the connected worker paradigm augments human physical and cognitive capabilities through digital contextualization, real-time process feedback, and automated hands-free data capture¹.

Within this structural topology, industrial wearable barcode scanners occupy the tactical tier at the edge of operational execution⁵. Historically, data capture functioned as an asynchronous, manual checkpoint that interrupted frontline material handling movement⁵. Wearable scanners—encompassing glove-mounted units, back-of-hand scanners, wrist-mounted displays, and retractable reel devices—reframe data capture as an ambient, friction-free byproduct of natural movement⁵. By embedding optical scan engines directly onto the worker's hand or wrist, these devices maintain continuous operational momentum while feeding high-fidelity transactional data directly into enterprise software infrastructure³.

The architectural flow of the connected worker ecosystem operates across three interconnected layers. At the foundational execution layer, frontline workers utilize wearable devices, such as the ProGlove MARK series or MARK Display, equipped with multi-range optical engines and bi-directional feedback mechanisms³. At the connectivity layer, these wearables transmit data via Bluetooth Low Energy (BLE 5.0) to local Android Enterprise terminals or specialized industrial gateways³. At the enterprise application layer, edge hosts route standardized scan payloads via Android Broadcast Intents, WebSockets, or MQTT brokers to cloud platforms and core enterprise software engines, including SAP EWM, Manhattan Associates, AWS IoT, and Microsoft Azure IoT¹.



The economic trajectory of this technology landscape reflects massive enterprise capital commitment. The global market for Automated Identification and Data Capture (AIDC) was valued at \$69.8 billion in 2024 and is projected to expand to \$136.9 billion by 2030, representing a Compound Annual Growth Rate (CAGR) of 11.7%¹³. Hardware components—comprising optical scanners, RFID readers, and mobile terminals—hold the dominant market revenue share at 63.0%¹³. Concurrently, the specialized market for wearable barcode scanners is accelerating at a CAGR of 8.7%, expanding from \$3.8 billion in 2025 to \$8.1 billion by 2034¹⁴. Regionally, North America represents the largest market share at 38.5% (\$26.8 billion in 2024), driven by deep enterprise penetration in omnichannel logistics and automated manufacturing¹³. The Asia-Pacific region demonstrates the fastest growth, with a projected CAGR between 12.4% and 13.5%, catalyzed by aggressive industrial digitization and smart infrastructure expansion across China, India, Japan, and Southeast Asia¹³. Leading market intelligence analysts highlight the strategic shift toward connected worker platforms. Gartner research indicates that frontline operational digitization has transitioned from an experimental initiative to a core pillar of corporate supply chain resilience. IDC research emphasizes that enterprise connected worker maturity is directly correlated with real-time operational visibility, noting that manual data capture delays create severe enterprise blind spots. ABI Research highlights an accelerating convergence between wearable devices and enterprise IoT analytics, projecting that industrial wearables represent the primary mechanism to eliminate human visibility black holes in manual warehousing. Furthermore, VDC Research demonstrates that high-throughput logistics facilities deploying hands-free data capture achieve double-digit productivity gains while substantially reducing onboarding periods for seasonal labor forces.

2. Paradigm Shift: Transition from Legacy Mobile Computers to Hands-Free Scanning

For decades, the standard tool for shop-floor data collection was the ruggedized pistol-grip mobile computer. While effective for static inventory audits, pistol-grip devices introduce severe operational friction in high-velocity picking, sorting, and assembly workflows⁵. Operators using pistol-grip computers are forced to execute a highly inefficient, non-value-added sequence for every pick: reach for the terminal, aim and scan the barcode, host or dock the terminal, pick up the physical item with one or two hands, place the item into a bin or pallet, and re-acquire the terminal⁵. This repetitive cycle introduces substantial scan latency and physical waste across millions of daily warehouse transactions⁵. Transitioning to hands-free wearable scanning—exemplified by lightweight units such as the ProGlove MARK 3—disrupts this legacy paradigm⁵. Wearables eliminate device handling time by keeping the worker's hands permanently free, allowing material handling and optical data capture to occur in a single continuous movement⁵.

Operational & Engineering Metric	Legacy Pistol-Grip Mobile Terminal	Hands-Free Wearable Scanner (e.g., ProGlove MARK 3)
Physical Device Weight	500g – 800g (Heavy form factor) ⁷	39g – 40g (Matchbox form factor) ⁷
Scan Latency & Cycle Time	4 – 6 seconds wasted per pick cycle in handling terminal ⁶	0 seconds handling latency; integrated into natural reaching motion ⁵
Ergonomic Strain Index	High risk of Carpal Tunnel and wrist strain ¹	Neutral wrist posture; zero grip strain; 40g ambient load ⁵
Shift Battery Performance	8 – 10 hours; frequent full-shift swap required ⁸	Up to 12,000 scans per charge (670 mAh); 2-hour full recharge ⁵
Drop Durability & Failure Rate	High screen/cradle breakage from frequent put-downs ⁵	IP65/IP54 rated; withstands 100+ drops from 2.0m onto concrete ⁵
Feedback &	4.0”–5.0” screen requiring full visual redirection ⁸	E-ink display (MARK Display) or

Contextualization		optical/acoustic/haptic feedback ⁵
Integration Architecture	Native heavy client; complex terminal emulation config ¹²	Android Broadcast Intent API, BLE WebSockets, Native SDK ³

The financial and operational impacts of this architectural shift unfold across primary, secondary, and tertiary operational levels. Reclaiming 4 to 6 seconds per scan cycle in a distribution center executing 50,000 daily picks saves 55 to 83 productive labor hours per day⁶. On a secondary level, eliminating the physical burden of lifting an 800-gram terminal thousands of times per shift dramatically lowers physical fatigue, directly reducing pick error rates by up to 33%⁵. On a tertiary level, mitigating repetitive micro-trauma to workers' wrists significantly decreases occupational injury claims and lowers employee turnover in an industry facing chronic labor shortages¹.

3. High-Throughput Industry Verticals and Operational Drivers

High-throughput industrial operations require high operational speed, sub-second error verification, and physical hardware resilience⁵. Specific verticals exhibit distinct operational friction points that accelerate the adoption of hands-free data capture solutions:

Industry Vertical	Primary Operational Friction Point	Wearable Data Capture Solution	Measured Operational KPI Impact
Automotive Manufacturing	Line-stop risk from Just-in-Sequence (JIS) assembly errors ¹	Hands-free scanning with instant acoustic/haptic error alerts ⁵	Prevents catastrophic assembly line downtime (\$20k+/min) ¹
3PL & E-Commerce	High SKU diversity and seasonal labor onboarding delays ⁵	Intuitive wearable display and Scan2Pair rapid staging ³	Reclaims 4–6s per pick; slashes worker onboarding time ⁶
Aerospace & Defense	Serialization tracking in tight, elevated assembly areas ⁵	Ultra-lightweight 40g scanner with extended multi-range optics ⁵	Ensures 3-point ladder safety contact while scanning ⁵

Cold Chain Logistics	Touchscreen failure and glove interference at -30°C ⁵	MARK 3 Freezer variant rated down to -30°C ⁵	Sustains 1,000 to 10,000 scans in extreme sub-zero conditions ⁵
-----------------------------	--	---	--

In automotive manufacturing and Tier-1 supply chains, operations run on strict Just-In-Time (JIT) and Just-In-Sequence (JIS) execution models¹. Operators in sequencing and kitting stations must select complex component variations under tight takt times⁵. A single incorrect part brought to the main assembly line can cause a total production halt, incurring line-stop costs that frequently exceed \$20,000 per minute¹. Industrial wearables equipped with multi-range optical engines and multi-sensory feedback (haptic vibration, acoustic beeps, and LED signals) immediately validate part correctness without requiring the operator to divert visual attention to a distant terminal screen⁵.

In third-party logistics (3PL) and e-commerce fulfillment, success depends on unit picking velocity and managing extreme seasonal order volume spikes⁵. Workers navigate high-density fulfillment aisles handling millions of distinct SKUs⁵. Hands-free scanning enables continuous item handling, allowing workers to move seamlessly between bin selection and carton loading⁵. Furthermore, during seasonal peak periods, simple wearable interfaces combined with rapid Scan2Pair onboarding reduce worker training periods from days to minutes, maximizing labor productivity²⁰.

In aerospace manufacturing, production involves long-cycle sub-assemblies where every tool, fastener, and structural bracket requires full serialization and lot-traceability⁵. Operators must scale staging ladders or navigate restricted airframe interiors where carrying traditional mobile devices poses safety and drop hazards⁵. Wearable glove scanners allow technicians to maintain required three-point contact on climbing equipment while capturing component barcodes hands-free⁵.

In cold chain logistics, frozen food and biopharmaceutical warehouses operate at temperatures ranging from -20°C to -30°C⁵. These extreme environments degrade standard mobile device battery chemistries, cause optical lens fogging, and make touchscreen navigation impossible for workers wearing thick thermal gloves⁵. Specialized wearable solutions—such as the ProGlove MARK 3 Freezer version—utilize low-temperature lithium-polymer cells capable of delivering up to 1,000 scans at -30°C and 10,000 scans at 0°C, enabling easy thumb-trigger operation without removing protective gear⁵.

4. Regulatory Frameworks, Health & Safety, and Supply Chain Traceability Mandates

Enterprise deployment of connected worker technologies is increasingly propelled by global regulatory compliance mandates and international supply chain standards:



Regulatory bodies such as the US Occupational Safety and Health Administration (OSHA) and the European Agency for Safety and Health at Work (EU-OSHA) have established strict regulatory guidelines addressing ergonomic risk factors in material handling¹. Directives targeting Upper Extremity Musculoskeletal Disorders (MSDs) explicitly flag repetitive wrist flexion, heavy pinch-grip forces, and sustained static loading as core drivers of long-term occupational injury¹. Wearable scanners address these regulatory requirements by completely eliminating the physical pinch-grip force required to operate pistol-grip units, maintaining the worker's hand in a neutral posture and aligning enterprise operations with EU-OSHA human-centric workplace standards¹.

Concurrently, global supply chain standard organizations are enforcing comprehensive traceability mandates. The GS1 Sunrise 2027 initiative marks a transition away from traditional 1D linear barcodes (UPC/EAN) toward multi-dimensional 2D symbologies, such as GS1 Data Matrix and QR codes. These 2D barcodes embed complex product data, including expiration dates, lot numbers, net weights, and unique serial IDs within a single compact symbol. Enterprise scanning infrastructure must deploy high-resolution 2D imager optics capable of parsing high-density 2D barcodes across variable distances (from 10 cm to 600 cm) without degrading read latency⁵.

In regulated life sciences logistics, the US Food and Drug Administration Unique Device Identification (FDA UDI) rule and the European Union Medical Device Regulation (EU MDR) require stringent end-to-end serialization across pharmaceutical and medical device supply chains¹. Distributors and healthcare logistics providers must record timestamped transactional scan logs at every distribution node¹. Deploying hands-free wearable scanners ensures compliant serialization tracking at high operational speeds without creating bottlenecks in distribution networks¹.

5. Technological Trends Reshaping Shop Floor Operations

The modern shop floor is experiencing a structural overhaul driven by four intersecting technology shifts:

Industry 4.0 to Industry 5.0

While Industry 4.0 prioritized hyper-automation, cyber-physical systems, and lights-out manufacturing environments, it frequently treated human workers as an unpredictable operational variable¹. Industry 5.0 re-centers the human operator at the core of industrial production¹. This emerging paradigm focuses on human-centricity, operational resilience, and sustainability². Industrial wearables embody Industry 5.0 principles by digitally augmenting frontline workers, granting them real-time process intelligence, ergonomic protection, and decision-support tools directly on the shop floor¹.

Edge Computing Integration

Modern industrial facilities are moving away from monolithic cloud architectures for real-time operational execution due to WAN latency and bandwidth constraints. Industrial edge gateways process scan data, perform local data formatting, and run validation rules on-site¹. Edge computing ensures that transactional validation occurs in sub-milliseconds, maintaining operational speed even during cloud connectivity disruptions¹.

Private 5G Networks

The deployment of Private 5G and Citizens Broadband Radio Service (CBRS) networks provides high-bandwidth, deterministic low-latency wireless coverage across sprawling warehouse facilities containing radio-frequency obstacles¹. Wearable scanners utilize low-power Bluetooth Low Energy (BLE 5.0) to connect to local host terminals or edge gateways, which then transmit data seamlessly over Private 5G backhauls to enterprise software platforms¹.


Android Enterprise Migration

The legacy operating systems that dominated industrial handhelds for decades (Windows CE and Windows Embedded Handheld) have reached complete end-of-life status. Enterprise fleets have transitioned entirely to Android Enterprise. Companion mobile software—such as ProGlove INSIGHT Mobile—installs natively on Android Enterprise hosts (including Zebra, Honeywell, and Samsung rugged devices), utilizing zero-code integration architectures like Android Broadcast Intents to replace legacy wedge software instantly⁹.

6. AI/ML Disruption and Sensor-Driven Motion Dynamics Analytics

Traditional industrial engineering relies on static time-motion studies, such as Methods-Time Measurement (MTM) or REBA ergonomic scoring, conducted periodically by engineers using stopwatches and visual observation checklists. These legacy methodologies suffer from severe

sampling bias, small dataset sizes, high manual execution costs, and the Hawthorne effect, where workers alter their natural behavior while under direct observation. Modern industrial wearables disrupt traditional time-motion studies by operating as continuous, passive IoT diagnostic sensors². Advanced wearable units—such as the ProGlove MARK series—integrate 3-axis accelerometers and Inertial Measurement Units (IMUs) that capture raw spatial motion dynamics alongside optical scan telemetry³. Cloud and edge analytics platforms, such as ProGlove INSIGHT, leverage machine learning models to analyze this continuous telemetry stream, converting raw motion data into actionable operational optimizations³.




Machine learning algorithms correlate scan timestamps with IMU acceleration patterns to segment pick cycles into precise micro-movements: walking time, searching time, reaching time, and scanning time³. By aggregating telemetry across an entire facility, the software flags subtle operational bottlenecks³. For example, if telemetry reveals an average 5-second delay between item selection and scan confirmation at a specific location, the analytics engine flags a potential lighting issue, damaged shelf barcode, or poor bin accessibility³. Furthermore, machine learning algorithms analyze wrist acceleration forces, repetitive twisting motions, and extreme reaching angles². Safety managers receive automated facility heatmaps highlighting specific workstations or storage racks that induce high physical strain³. This allows operations teams to adjust picking layouts, re-sequence pick paths, or modify shelf heights before physical repetitive strain injuries occur². Over the next five years, the integration of edge AI and compact computer vision engines into wearable form factors will create new hybrid data capture capabilities¹. Wearables combining miniaturized visual camera sensors with edge AI inference processors will enable ambient visual validation¹. Operators will touch or look at a package, and onboard vision models will simultaneously verify label data, assess physical package condition, check volumetric

dimensions, and confirm correct pallet placement without requiring a deliberate line-of-sight optical laser scan¹.

7. Technical Integration, Connectivity Protocols, and Enterprise Scalability

Deploying wearable data capture fleets across enterprise environments involves navigating complex physical radio frequency environments, software protocols, and device lifecycle management workflows³:

Protocol Tier	Frequency & Bandwidth	Transmission Range	Network Topology & Scalability	Primary Enterprise Use Case
Bluetooth Low Energy (BLE 5.0)	2.4 GHz; 1–2 Mbps throughput ³	40m (standard) up to 70m w/ Gateway ³	Star topology; Multi-pairing up to 5 scanners per Gateway ³	Local link from Wearable to Mobile Host or Gateway ³
Sub-1GHz (Legacy)	868 MHz (EU) / 915 MHz (US) ²¹	Long range, high physical barrier penetration ²¹	Unidirectional point-to-point via Access Point ³	Static desktop scan stations with basic host link ³
Wi-Fi / Private 5G	2.4/5GHz / CBRS Bands ¹	Facility-wide access point coverage ¹	Star/Mesh topology; Gateway acts as WebSocket/MQTT client ³	Network backhaul from Gateway to Cloud/WMS ¹





Selecting the appropriate software integration path depends on the host system architecture³:

1. **Android Broadcast Intents:** The standard integration pathway for Android Enterprise environments¹². The companion software (e.g., INSIGHT Mobile) intercepts the raw BLE scan payload and broadcasts a decoupled Android Intent containing data extras directly to target applications, such as industrial web browsers (Ivanti Velocity, StayLinked SmartTE) or native enterprise apps¹². The target application receives scan data without requiring source code modification¹². Key intent structures include:
 - *Intent Action:* com.proglove.api.BARCODE [cite: 12]
 - *Barcode Data Extra:* com.proglove.api.extra.BARCODE_DATA [cite: 12]
 - *Symbology Extra:* com.proglove.api.extra.BARCODE_SYMBOLGY [cite: 12]
2. **Software Keyboard Wedge:** Emulates system keystrokes directly into active text fields¹². While easy to deploy, it lacks granular control over data formatting, symbology parsing, or bi-directional worker feedback¹².
3. **Native Mobile SDK (Kotlin/Java):** For custom enterprise mobile applications, developers integrate native SDK libraries directly into source code¹⁸. This provides programmatic control over device pairing states, custom haptic vibration patterns, LED color sequences, and wrist display layouts (e.g., MARK Display)³.
4. **Hardware Gateway WebSockets/MQTT:** In fixed packing or sorting stations lacking

mobile terminals, wearable scanners pair directly to an industrial hardware gateway via BLE³. The gateway converts raw payloads into WebSocket or MQTT client messages, transmitting them over Wi-Fi or Ethernet directly to core WMS platforms like SAP EWM or Manhattan Associates³.

Managing wearable deployments at scale introduces operational orchestration challenges³. Manually configuring hundreds of Bluetooth devices is inefficient. Enterprise solutions utilize zero-touch staging mechanisms, such as Scan2Pair barcodes displayed on host terminals or charging stations, allowing workers to pair a wearable to a host in under two seconds³. Furthermore, enterprise deployment requires cloud-based device visibility platforms (such as ProGlove INSIGHT Webportal) integrated with Mobile Device Management (MDM) platforms³. This enables centralized over-the-air (OTA) firmware updates, battery health monitoring, and device tracking across global facilities without disrupting active shifts³.

8. Future Direction of Human-Centric Industrial Automation


The future trajectory of industrial automation is pivoting toward a hybrid model of human-machine collaboration². While fully autonomous systems, such as Autonomous Mobile Robots (AMRs), Automated Guided Vehicles (AGVs), and Automated Storage and Retrieval Systems (AS/RS), excel at high-volume bulk transport and structured vertical storage, human operators retain superior spatial reasoning, adaptability, and physical dexterity required for non-standard picking, kitting, and exception handling².



The future warehouse architecture integrates augmented workers directly into robotic orchestration loops². Industrial wearables function as the primary bi-directional interface between human workers and autonomous fleets². In a representative hybrid workflow, an AMR transports bulk inventory to a picking location, while an augmented worker—guided by pick instructions on a wearable wrist display—executes high-speed item selection with 100% verification accuracy using hands-free scanning⁵. This hybrid model delivers the throughput efficiency of automated transport alongside the operational flexibility of a human workforce².

9. Pre-Sales Engineering and Solution Architecture Execution

Aligning industrial wearable technologies with enterprise business objectives requires solution architects to execute a structured pre-sales engineering methodology²⁰:



During technical discovery workshops, a pre-sales solution architect must systematically analyze customer process workflows²⁰. This involves evaluating physical shop-floor conditions (operating temperatures, lighting levels, metallic RF interference), auditing existing network infrastructure, assessing WMS/ERP application integration paths, and quantifying specific operational bottlenecks (e.g., pick latency, high error rates, worker turnover)²⁰. In the solution design phase, architects evaluate hardware and software trade-offs based on operational requirements²⁰:

- **Hardware Tiering**: Deploying compact, entry-level scanners (e.g., ProGlove LEO or MARK Basic) for short-range indoor sorting⁸ versus ruggedized multi-range scanners (e.g., ProGlove MARK 3) operating up to 600 cm for forklift material handling and high-rack picking⁵.

- **Software Integration Strategy:** Choosing between drop-in Broadcast Intents for rapid zero-code deployment on legacy terminal emulation platforms¹² versus native SDK integration for custom Android applications requiring dynamic wrist display updates³.

During Proof-of-Concept (PoC) execution, architects establish baseline key performance indicators (KPIs) prior to deployment²⁰. Solution architects run comparative trials, measuring cycle time reductions, tracking scan error reductions, capturing operator ergonomic feedback, and presenting verified financial ROI metrics to enterprise executive leadership²⁰.

10. Summary Outputs for Solution Architecture and Executive Strategy

Key Technical Insights for a Solution Architect

1. **Decoupled Android Intent Architectures Minimize Deployment Risk:** The primary software integration pathway for Android Enterprise environments relies on Broadcast Intents (`com.proglove.api.BARCODE`)¹². Decoupling the physical BLE wearable scanner from the WMS application layer allows enterprises to upgrade hardware without altering underlying application codebases¹².
2. **BLE 5.0 Bilateral Communication Enables Interactive Workflows:** Unlike legacy unidirectional Sub-1GHz links, BLE 5.0 supports continuous, bi-directional data exchange between host systems and wearable displays³. This enables architects to push dynamic pick instructions, bin locations, and visual validation alerts directly to wrist-mounted E-ink screens³.
3. **Sensor-Fusion Telemetry Unlocks Predictive Process Analytics:** Modern industrial wearables capture non-scan motion dynamics via embedded 3-axis IMUs³. By processing acceleration curves alongside scan timestamps, architects can help clients identify process bottlenecks, optimize facility layouts, and reduce worker physical strain².

Top Operational and IT Concerns from Warehouse and Plant Executives

EXECUTIVE & IT CONCERNS MATRIX	
OPERATIONAL / PLANT LEADERSHIP	
IT INFRASTRUCTURE & SECURITY	
* Total Cost of Ownership (TCO)	* Fleet Management & Zero-Touch Provisioning
* Labor Ergonomics & Safety	* Network Security & Data Encryption (BLE/Wi-Fi)
* Peak Season Scalability	* WMS/ERP System Integration & API Stability

- **Total Cost of Ownership (TCO) and Rapid ROI:** Plant managers require clear proof that capital expenditures for wearable hardware deliver rapid financial paybacks through documented cycle time savings (4–6 seconds saved per scan)⁶, reduced pick error rates¹⁹, and lower seasonal onboarding costs²⁰.
- **Fleet Management and Zero-Touch Provisioning:** Enterprise IT teams require streamlined tools to manage thousands of wireless endpoints across global facilities³. Solutions must support remote configuration pushes, over-the-air firmware management, and simple Scan2Pair pairing workflows³.
- **Security and System Compatibility:** Enterprise IT security teams require strong encryption standards across all wireless link layers (BLE AES-128) and seamless integration capabilities with enterprise cloud platforms (AWS IoT, Azure IoT) and core WMS engines (SAP EWM, Manhattan Associates)¹.
- **Hardware Durability and Ergonomic Adoption:** Operations executives prioritize solutions that improve workplace safety, reduce OSHA injury recordables¹, withstand harsh industrial conditions (IP65 rating, -30°C cold storage resilience)⁵, and achieve high adoption among frontline workers⁵.

Technical Discussion Questions for Solution Architect Interviews

1. *Architecture & Integration:* "How would you design a low-latency data capture architecture for a 500,000 sq. ft. distribution center operating SAP EWM on Android terminals, considering BLE propagation, RF interference from metallic shelving, and the trade-offs between Android Broadcast Intents versus SDK integration?"¹
2. *Gateway & Protocol Topology:* "If a client facility operates static packing lines without mobile computers, how would you configure ProGlove Gateways over WebSockets or MQTT to stream scan data directly to their cloud WMS while enabling multi-pairing for up to five operators per gateway?"³
3. *Troubleshooting & Discovery:* "During a PoC deployment in a cold storage facility (-20°C), an enterprise customer reports intermittent data dropouts. What technical diagnostic steps would you execute across the BLE RF link, Android power management policies, gateway configuration files, and device firmware specs to identify and resolve the issue?"³
4. *Process Analytics & ROI:* "How would you leverage 3-axis IMU acceleration data and scan timestamp telemetry from the ProGlove INSIGHT platform to demonstrate clear operational value to an enterprise customer whose primary bottleneck is long item search time rather than optical scan latency?"³
5. *Pre-Sales Strategy:* "Walk us through your approach to leading a technical discovery workshop with an enterprise IT director who is hesitant to transition their legacy Windows-based pistol-grip scanner fleet to hands-free Android wearable solutions."⁹

Works cited

1. Automatic Identification Data Capture Market 2026 to 2032 - Intel Market Research,
<https://www.intelmarketresearch.com/automatic-identificationdata-capture-market-21910>
2. From Automation to Augmentation: A Framework for Designing Human-Centric Work Environments in Society 5.0 - arXiv, <https://arxiv.org/html/2604.01364v1>
3. FAQs - ProGlove documentation, <https://docs.proglove.com/en/faqs-48868.html>
4. Best Warehouse Management Systems (WMS) for Retail - Manhattan Associates, <https://www.manh.com/our-insights/comparisons/best-wms-brands>
5. ProGlove Mark 3 Barcode Scanner | Spezialist für Barcodesysteme - GLOBOS Logistik, <https://www.globos.de/en/produkt/proglove-mark3-barcodescanner/>
6. ProGlove Mark 3 - Wearable scanner with 6 m scanning range - Barcotec, <https://www.barcotec.at/en/auto-id/wearable-scanners/proglove-mark-3>
7. Proglove MARK 3 Multi-Range 2D Wearable Scanner M010 - The Barcode Warehouse, <https://www.thebarcodewarehouse.co.uk/shop/proglove/wearable-scanners/mark-3/>
8. ProGlove - LAUBNER ID Solutions, <https://laubner.com/en/products/hardware-and-devices/barcode-scanner/glove-scanners-ring-scanners/proglove>
9. Introduction - ProGlove documentation, <https://docs.proglove.com/en/introduction-44594.html>
10. Introduction - ProGlove documentation, <https://docs.proglove.com/en/introduction-48574.html>
11. Technical Specification - Strategic Mobility Group, <https://smg3.com/wp-content/uploads/2024/07/SMG3-Proglove-MARK-3-Basic-Data-Sheet.pdf>
12. Intent API - basic integration - ProGlove documentation, <https://docs.proglove.com/en/intent-api---basic-integration.html>
13. Automatic Identification & Data Capture Market Report, 2025-2030 - Grand View Research, <https://www.grandviewresearch.com/industry-analysis/automatic-identification-data-capture-market-report>
14. Wearable Barcode Scanners Market Research Report 2034 - Dataintel, <https://dataintel.com/report/wearable-barcode-scanners-market>
15. Automatic Identification and Data Capture Market Analysis Report, Industry Overview, Market Size and Revenue, Share, Forecast 2024-2030, <https://www.strategicmarketresearch.com/market-report/automatic-identification-data-capture-market>
16. Automatic Identification and Data Capture Market Size 2034 - IMARC Group, <https://www.imarcgroup.com/automatic-identification-data-capture-market>
17. Proglove MARK 3 Barcode Scanner - Barcodesinc.com,

<https://www.barcodesinc.com/proglove/mark3.htm>

18. GitHub - workaroundgmbh/proglove_connect_samples: Sample project for ProGlove Connect App,
https://github.com/workaroundgmbh/proglove_connect_samples
19. AIDC Market Growth, Size & Trend | CAGR of 12.85% - 360 Research Reports,
<https://www.360researchreports.com/market-reports/aidc-market-209919>
20. Job Descriptions.md
21. FAQs - ProGlove documentation, <https://docs.proglove.com/en/faqs-36062.html>
22. INSIGHT Mobile (Android) - ProGlove documentation,
<https://docs.proglove.com/en/insight-mobile--android-.html>