


A Simplified GA

A Simple Example


- Let's walk through a **simple example!**
- Let's say you were asked to solve the following problem:
 - **Maximize:**
 - $f(x,y) = 0.5 + (\sin(\sqrt{x^2+y^2}))^2 - 0.5)/(1.0 + 0.001(x^2+y^2))^2$
 - Where x and y are take from [-100.0,100.0]
 - You must find a solution that is greater than **0.99754**, and you can only evaluate a total of 4000 candidate solutions (CSs)
- This seems like a difficult problem.
 - It would be nice if we could see what it looks like!
 - This may help us determine a good algorithm for solving it.

A 3D view of $f(x,y)$

$$0.5 + (\sin(\sqrt{x^2+y^2}))^2 \cdot 0.5 / (1.0 + 0.001 \cdot (x^2+y^2))^2$$





Looking at only one dimension $f(x, 1.0)$



基因演算法流程圖

Max $f(x,y)$

$$= 0.5 + (\sin(\sqrt{x^2+y^2}))^2 - 0.5 / (1.0 + 0.001(x^2+y^2))^2$$



1. 編碼 : (x_i, y_i)

初始化 : (x_i, y_i) 隨機

從 $[-100, 100] \times [-100, 100]$ 中取一點

2. 適應度 : $fit_i = f(x_i, y_i)$

3. 選擇 : 隨機從目前的 population 中選出一對父母 (x_{mom}, y_{mom}) 和 (x_{dad}, y_{dad})

4. 繁衍 :

$$x_{kid} = \text{rnd}(x_{mom}, x_{dad}) + N_x(0, \sigma)$$
$$y_{kid} = \text{rnd}(y_{mom}, y_{dad}) + N_y(0, \sigma)$$

5. 取代 :

$$\text{Pop}(t+1) = \{\text{Pop}(t) - \{\text{worst}\}\} \cup \{\text{kid}\}$$

A Simple Example

```
t = 0;
Initialize Pop(t); /* of P individuals */
Evaluate Pop(t);
while (t <= 4000) {
    Select_Parent(< $\mathbf{x}_{\text{mom}}$ ,  $y_{\text{mom}}$ >); /* Randomly */
    Select_Parent(< $\mathbf{x}_{\text{dad}}$ ,  $y_{\text{dad}}$ >); /* Randomly */
    Create_Offspring(< $\mathbf{x}_{\text{kid}}$ ,  $y_{\text{kid}}$ >):
     $\mathbf{x}_{\text{kid}} = \text{rnd}(\mathbf{x}_{\text{mom}}, \mathbf{x}_{\text{dad}}) + N_{\mathbf{x}}(0, \sigma);$ 
     $y_{\text{kid}} = \text{rnd}(y_{\text{mom}}, y_{\text{dad}}) + N_y(0, \sigma);$ 
     $\text{fit}_{\text{kid}} = \text{Evaluate}(\langle \mathbf{x}_{\text{kid}}, y_{\text{kid}} \rangle);$ 
    Pop(t+1) = Replace(worst, kid); {Pop(t) - {worst}}  $\cup$  {kid}
    t = t + 1;
}
```

```
6 NUM_ITERATION = 100
```

```
7
```


```
8 NUM_CHROME = 20
```

```
9 NUM_BIT = 2
```

世代數(迴圈數)

染色體個數

染色體長度



```
48 # ==== 主程式 ====
```

```
49 pop = initPop()
```

```
50 pop_fit = evaluatePop(pop)
```

```
51
```

```
52 for i in range(NUM_ITERATION) :
```

```
53     parent = selection(pop)
```

```
54     kid = reproduction(parent)
```

```
55     kid_fit = fitFunc(kid)
```

```
56     pop, pop_fit = replace(pop, pop_fit, kid, kid_fit)
```

```
57
```

```
58     bestIndex = np.argmax(pop_fit)
```

```
59     print('iteration %d: x = %s, y = %f' % (i, pop[bestIndex], pop_fit[bestIndex]))
```

初始化 pop

算 pop 的 fit

②

③

④

②

取代

⑤

找此世代最佳解的索引值

7

```

6 NUM_ITERATION = 100          # 世代數(迴圈數)
7
8 NUM_CHROME = 20              # 染色體個數
9 NUM_BIT = 2                  # 染色體長度

```

1. 編碼 : (x_i, y_i)
 初始化 : (x_i, y_i) 隨機從 $[-100, 100] \times [-100, 100]$ 中取一點

```

15 def initPop():               # 初始化群體
16     # 產生 NUM_CHROME * NUM_BIT 個  $[-100, 100]$  之間的隨機數
17     return np.random.uniform(low=-100, high=100, size=(NUM_CHROME, NUM_BIT))

```

2. 適應度 : $\text{Max } f(x, y)$
 $= 0.5 + (\sin(\sqrt{x^2 + y^2}))^2 - 0.5 / (1.0 + 0.001(x^2 + y^2))^2$

```

19 def fitFunc(x):              # 適應度函數
20     return 0.5 + ((math.sin(math.hypot(x[0], x[1])))**2 - 0.5) \
21         / (1.0 + 0.001 * (x[0]**2 + x[1]**2))**2
23 def evaluatePop(p):          # 評估群體之適應度
24     return [fitFunc(p[i]) for i in range(len(p))]

```

```

48 # ==== 主程式 ====

```

```

49 pop = initPop()              # 初始化 pop
50 pop_fit = evaluatePop(pop)   # 算 pop 的 fit
51
52 for i in range(NUM_ITERATION):
53     parent = selection(pop)   # 挑父母
54     kid = reproduction(parent) # 生子
55     kid_fit = fitFunc(kid)    # 算子代的 fit
56     pop, pop_fit = replace(pop, pop_fit, kid, kid_fit) # 取代
57
58     bestIndex = np.argmax(pop_fit) # 找此世代最佳解的索引值
59     print('iteration %d: x = %s, y = %f' % (i, pop[bestIndex], pop_fit[bestIndex]))

```



```
10 SIGMA = 0.2
```

```
# 生成子代時用到的干擾
```

```
14 # ==== 基因演算法會用到的函式 ====
```

```
15 def fitFunc(x): ① # 適應度函數
```

```
16     return 0.5 + ((math.sin(math.hypot(x[0], x[1]))**2) / (1.0 + 0.001 * (x[0]**2 + x[1]**2)))**2
```

```
18  
19 def initPop(): ② # 初始化群體
```

```
20     # 產生 NUM_CHROME * NUM_BIT 個[-100, 100]
```

```
21     return np.random.uniform(low=-100, high=100, size=(NUM_CHROME, NUM_BIT))
```

```
22  
23 def evaluatePop(p): # 評估群體之適應度
```

```
24     return [fitFunc(p[i]) for i in range(len(p))]
```

```
25  
26 def selection(p): ③ # 隨機找兩個父母
```

```
27     [i, j] = np.random.choice(NUM_CHROME, 2, replace=False) # 任選兩個index
```

```
28     return [p[i], p[j]]
```

```
29
```

```
30 def reproduction(p): ④ # 繁衍子代
```

```
31     return [np.random.uniform(np.min([p[0][j], p[1][j]]), np.max([p[0][j], p[1][j]])) \
```

```
32         + np.random.uniform(low=-SIGMA, high=SIGMA) for j in range(NUM_BIT)]
```

```
41 def replace(p, p_fit, k, k_fit): ⑤ # 適者生存
```

```
42     worstIndex = np.argmin(p_fit)
```

```
43     p[worstIndex] = k
```

```
44     p_fit[worstIndex] = k_fit
```

```
45
```

```
46     return p, p_fit
```

1. 編碼 : (x_i, y_i)

初始化 : (x_i, y_i) 隨機從 $[-100, 100] \times [-100, 100]$ 中取一點

2. 適應度 : $\text{Max } f(x, y)$

$= 0.5 + (\sin(\sqrt{x^2 + y^2}))^2 - 0.5 / (1.0 + 0.001(x^2 + y^2))^2$

3. 選擇 : 隨機從目前的 population 中選出一對父母

4. 繁衍 : $x_{\text{kid}} = \text{rnd}(x_{\text{mom}}, x_{\text{dad}}) + N_x(0, \sigma)$
 $y_{\text{kid}} = \text{rnd}(y_{\text{mom}}, y_{\text{dad}}) + N_y(0, \sigma)$

5. 取代 : $\text{Pop}(t+1) = \{\text{Pop}(t) - \{\text{worst}\}\} \cup \{\text{kid}\}$

Exercise

- Benchmark functions:

Test functions	Feasible spaces	n	f_{\min}
$f_1(\mathbf{x}) = \sum_{i=1}^n \left(-x_i \sin \left(\sqrt{ x_i } \right) \right)$	$[-500, 500]^n$	30	$-418.983n$
$f_2(\mathbf{x}) = \sum_{i=1}^n (x_i^2 - 10 \cos(2\pi x_i) + 10)$	$[-5.12, 5.12]^n$	30	0
$f_3(\mathbf{x}) = -20 \exp \left(-0.2 \sqrt{\frac{1}{n} \sum_{i=1}^n x_i^2} \right) - \exp \left(\frac{1}{n} \sum_{i=1}^n \cos(2\pi x_i) \right) + 20 + \exp(1)$	$[-32, 32]^n$	30	0
$f_4(\mathbf{x}) = \frac{1}{4000} \sum_{i=1}^n x_i^2 - \prod_{i=1}^n \cos \left(\frac{x_i}{\sqrt{i}} \right) + 1$	$[-600, 600]^n$	30	0
$f_5(\mathbf{x}) = \frac{\pi}{n} \{ 10 \sin^2(\pi y_1) + \sum_{i=1}^{n-1} (y_i - 1)^2 [1 + 10 \sin^2(\pi y_{i+1})] + (y_n - 1)^2 \} + \sum_{i=1}^n u(x_i, 10, 100, 4),$ where $y_i = 1 + \frac{1}{4}(x_i + 1)$ and $u(x_i, a, k, m) = \begin{cases} k(x_i - a)^m, & x_i > a \\ 0, & -a \leq x_i \leq a \\ k(-x_i - a)^m, & x_i < -a \end{cases}$	$[-50, 50]^n$	30	0
$f_6 = \sum_{i=1}^n \left[\sum_{j=1}^n (\chi_{ij} \sin \omega_j + \psi_{ij} \cos \omega_j) - \sum_{j=1}^n (\chi_{ij} \sin x_j + \psi_{ij} \cos x_j) \right]^2,$ where χ_{ij} and ψ_{ij} are random intergers in $[-100, 100]$, and ω_j is a random number in $[-\pi, \pi]$	$[-\pi, \pi]^n$	100	0
$f_7(\mathbf{x}) = \sum_{i=1}^{n-1} \left[100 (x_i^2 - x_{i+1})^2 + (x_i - 1)^2 \right]$	$[-5, 10]^n$	30	0
$f_8(\mathbf{x}) = \sum_{i=1}^n x_i^2$	$[-100, 100]^n$	30	0
$f_9(\mathbf{x}) = \sum_{i=1}^n x_i^4 + \text{random}[0, 1)$	$[-1.28, 1.28]^n$	30	0
$f_{10}(\mathbf{x}) = \sum_{i=1}^n x_i + \prod_{i=1}^n x_i $	$[-10, 10]^n$	30	0
$f_{11}(\mathbf{x}) = \sum_{i=1}^n \left(\sum_{j=1}^i x_j \right)^2$	$[-100, 100]^n$	30	0
$f_{12}(\mathbf{x}) = \max \{ x_i , \quad i = 1, 2, \dots, n \}$	$[-100, 100]^n$	30	0

Exercise (cont.)

- Use the GA sample code “GA-simplified” to find the optimal solutions of the following three functions:

Test functions	Feasible spaces	n	f_{\min}
$f_1(\mathbf{x}) = \sum_{i=1}^n \left(-x_i \sin \left(\sqrt{ x_i } \right) \right)$	$[-500, 500]^n$	30	$-418.983n$
$f_2(\mathbf{x}) = \sum_{i=1}^n (x_i^2 - 10 \cos(2\pi x_i) + 10)$	$[-5.12, 5.12]^n$	30	0
$f_3(\mathbf{x}) = -20 \exp \left(-0.2 \sqrt{\frac{1}{n} \sum_{i=1}^n x_i^2} \right) - \exp \left(\frac{1}{n} \sum_{i=1}^n \cos(2\pi x_i) \right) + 20 + \exp(1)$	$[-32, 32]^n$	30	0

- Note that it is very hard to find the optimal solutions when $n = 30$. Hence, when testing your program, you can check whether it can find the optimal solution when $n = 1$.
- Hint
 - 1. (編碼) 改成30維度
 - 2. (編碼) 改初始化群組的範圍
 - 3. (解碼) 改適應度函數成 f_1, f_2, f_3
 - 4. (輸出) 不要輸出 \mathbf{x} ，只要看 $y = f(\mathbf{x})$