

CONDUIT FITTINGS: DRAIN FITTING

EDF SERIES

FLAMEPROOF / INCREASED SAFETY AND DUST PROTECTION BY ENCLOSURE



APPLICATION

In the context of electrical and mechanical engineering, particularly for Explosion-Proof systems or Hazardous Areas, the EDF Series Drain Fitting (often paired with a "Breather") plays a critical role in maintaining the integrity of enclosures.



Primary Function

- Condensation Management : In environments with fluctuating temperatures, moisture in the air inside an enclosure can condense into water droplets.
- Drainage : The **EDF Series** is installed at the lowest point of the enclosure or conduit system. It uses gravity to allow accumulated water to exit the system automatically.
- Breathing : Many EDF models function as a "Breather-Drain," allowing air to flow in and out of the enclosure to equalize internal and external pressure, which significantly reduces the initial cause of condensation.

TECHNICAL DATA

Hazardous Area	GAS	DUST
Zones	1 & 2	21 & 22
Equipment Group	II 2G	II 2D
Explosion protection	Ex II2G Exd IIC T6	Ex II2D Ex Td A21 IP66
Conformity to Standards	IEC 60079-0 , IEC 60079-1	
Ambeint Temperature	-20°c to +75°c	

Specification

- Body material : Stainless steel, SS304
- Thread size : 1/2" NPT or M20 x 1.5

Catalogue Number Logic

EDF	-	■ ■
Series		Entries
		M1 M20 x 1.5
		N1 1/2" NPT

Dimension

