



Python MySQL Insert Into Table

[< Previous](#)[Next >](#)

Insert Into Table

To fill a table in MySQL, use the "INSERT INTO" statement.

Example

Insert a record in the "customers" table:

```
import mysql.connector

mydb = mysql.connector.connect(
    host="localhost",
    user="yourusername",
    passwd="yourpassword",
    database="mydatabase"
)

mycursor = mydb.cursor()

sql = "INSERT INTO customers (name, address) VALUES (%s, %s)"
val = ("John", "Highway 21")
mycursor.execute(sql, val)

mydb.commit()

print(mycursor.rowcount, "record inserted.")
```

[Run example >>](#)

Important!: Notice the statement: `mydb.commit()`. It is required to make the changes, otherwise no changes are made to the table.

Insert Multiple Rows

To insert multiple rows into a table, use the `executemany()` method.

The second parameter of the `executemany()` method is a list of tuples, containing the data you want to insert:

Example

Fill the "customers" table with data:

```
import mysql.connector

mydb = mysql.connector.connect(
    host="localhost",
    user="yourusername",
    passwd="yourpassword",
    database="mydatabase"
)

mycursor = mydb.cursor()

sql = "INSERT INTO customers (name, address) VALUES (%s, %s)"
val = [
    ('Peter', 'Lowstreet 4'),
    ('Amy', 'Apple st 652'),
    ('Hannah', 'Mountain 21'),
    ('Michael', 'Valley 345'),
    ('Sandy', 'Ocean blvd 2'),
    ('Betty', 'Green Grass 1'),
    ('Richard', 'Sky st 331'),
    ('Susan', 'One way 98'),
    ('Vicky', 'Yellow Garden 2'),
    ('Ben', 'Park Lane 38'),
    ('William', 'Central st 954'),
    ('Chuck', 'Main Road 989'),
    ('Viola', 'Sideway 1633')
]
```

```
mycursor.executemany(sql, val)

mydb.commit()

print(mycursor.rowcount, "was inserted.")
```

[Run example »](#)

Get Inserted ID

You can get the id of the row you just inserted by asking the cursor object.

Note: If you insert more than one row, the id of the last inserted row is returned.

Example

Insert one row, and return the ID:

```
import mysql.connector

mydb = mysql.connector.connect(
    host="localhost",
    user="yourusername",
    passwd="yourpassword",
    database="mydatabase"
)

mycursor = mydb.cursor()


sql = "INSERT INTO customers (name, address) VALUES (%s, %s)"
val = ("Michelle", "Blue Village")
mycursor.execute(sql, val)

mydb.commit()

print("1 record inserted, ID:", mycursor.lastrowid)
```

[Run example »](#)[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

- Tabs
- Dropdowns
- Accordions
- Side Navigation
- Top Navigation
- Modal Boxes
- Progress Bars
- Parallax
- Login Form
- HTML Includes
- Google Maps
- Range Sliders
- Tooltips
- Slideshow
- Filter List
- Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
PHP
jQuery
Bootstrap
XML

[Read More »](#)

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

Top 10 Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
SQL Tutorial
PHP Tutorial
jQuery Tutorial
Python Tutorial

Top 10 References

HTML Reference
CSS Reference
JavaScript Reference
W3.CSS Reference
Bootstrap Reference
SQL Reference
PHP Reference
HTML Colors
jQuery Reference
Python Reference

Top 10 Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- jQuery Examples
- Angular Examples
- XML Examples

Web Certificates

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- jQuery Certificate
- PHP Certificate
- Bootstrap Certificate
- XML Certificate

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2019 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

