



Python String Methods

[< Previous](#)[Next >](#)

Python has a set of built-in methods that you can use on strings.

Note: All string methods returns new values. They do not change the original string.

Method	Description
<u>capitalize()</u>	Converts the first character to upper case
<u>casefold()</u>	Converts string into lower case
<u>center()</u>	Returns a centered string
<u>count()</u>	Returns the number of times a specified value occurs in a string
<u>encode()</u>	Returns an encoded version of the string
<u>endswith()</u>	Returns true if the string ends with the specified value
<u>expandtabs()</u>	Sets the tab size of the string
<u>find()</u>	Searches the string for a specified value and returns the position of where it was found
<u>format()</u>	Formats specified values in a string
<u>format_map()</u>	Formats specified values in a string
<u>index()</u>	Searches the string for a specified value and returns the position of where it was found
<u>isalnum()</u>	Returns True if all characters in the string are alphanumeric
<u>isalpha()</u>	Returns True if all characters in the string are in the alphabet

<u>isdecimal()</u>	Returns True if all characters in the string are decimals
<u>isdigit()</u>	Returns True if all characters in the string are digits
<u>isidentifier()</u>	Returns True if the string is an identifier
<u>islower()</u>	Returns True if all characters in the string are lower case
<u>isnumeric()</u>	Returns True if all characters in the string are numeric
<u>isprintable()</u>	Returns True if all characters in the string are printable
<u>isspace()</u>	Returns True if all characters in the string are whitespaces
<u>istitle()</u>	Returns True if the string follows the rules of a title
<u>isupper()</u>	Returns True if all characters in the string are upper case
<u>join()</u>	Joins the elements of an iterable to the end of the string
<u>ljust()</u>	Returns a left justified version of the string
<u>lower()</u>	Converts a string into lower case
<u>lstrip()</u>	Returns a left trim version of the string
<u>maketrans()</u>	Returns a translation table to be used in translations
<u>partition()</u>	Returns a tuple where the string is parted into three parts
<u>replace()</u>	Returns a string where a specified value is replaced with a specified value
<u>rfind()</u>	Searches the string for a specified value and returns the last position of where it was found
<u>rindex()</u>	Searches the string for a specified value and returns the last position of where it was found
<u>rpartition()</u>	Returns a tuple where the string is parted into three parts
<u>rsplit()</u>	Splits the string at the specified separator, and returns a list
<u>rstrip()</u>	Returns a right trim version of the string
<u>split()</u>	Splits the string at the specified separator, and returns a list
<u>splitlines()</u>	Splits the string at line breaks and returns a list
<u>startswith()</u>	Returns true if the string starts with the specified value
<u>swapcase()</u>	Swaps cases, lower case becomes upper case and vice versa

<u>title()</u>	Converts the first character of each word to upper case
<u>translate()</u>	Returns a translated string
<u>upper()</u>	Converts a string into upper case
<u>zfill()</u>	Fills the string with a specified number of 0 values at the beginning


Note: All string methods returns new values. They do not change the original string.

Learn more about strings in our [Python Strings Tutorial](#).

◀ Previous

Next ▶

COLOR PICKER



HOW TO

- Tabs
- Dropdowns
- Accordions
- Side Navigation
- Top Navigation
- Modal Boxes
- Progress Bars
- Parallax
- Login Form
- HTML Includes
- Google Maps
- Range Sliders
- Tooltips
- Slideshow

Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
PHP
jQuery
Bootstrap
XML

[Read More »](#)

REPORT ERROR

PRINT PAGE

FORUM

ABOUT

Top 10 Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
SQL Tutorial
PHP Tutorial
jQuery Tutorial
Python Tutorial

Top 10 References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [SQL Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [jQuery Reference](#)
- [Python Reference](#)

Top 10 Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [jQuery Examples](#)
- [Angular Examples](#)
- [XML Examples](#)

Web Certificates

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [jQuery Certificate](#)
- [PHP Certificate](#)
- [Bootstrap Certificate](#)
- [XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2019 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

