



Python Classes and Objects

[< Previous](#)[Next >](#)

Python Classes/Objects

Python is an object oriented programming language.

Almost everything in Python is an object, with its properties and methods.

A Class is like an object constructor, or a "blueprint" for creating objects.

Create a Class

To create a class, use the keyword `class`:

Example

Create a class named MyClass, with a property named x:

```
class MyClass:  
    x = 5
```

[Run example »](#)

Create Object

Now we can use the class named myClass to create objects:

Example

Create an object named p1, and print the value of x:

```
p1 = MyClass()
print(p1.x)
```

[Run example »](#)

The __init__() Function

The examples above are classes and objects in their simplest form, and are not really useful in real life applications.

To understand the meaning of classes we have to understand the built-in __init__() function.

All classes have a function called __init__(), which is always executed when the class is being initiated.

Use the __init__() function to assign values to object properties, or other operations that are necessary to do when the object is being created:

Example

Create a class named Person, use the __init__() function to assign values for name and age:

```
class Person:
    def __init__(self, name, age):
        self.name = name
        self.age = age

p1 = Person("John", 36)

print(p1.name)
print(p1.age)
```

[Run example »](#)

Note: The `__init__()` function is called automatically every time the class is being used to create a new object.

Object Methods

Objects can also contain methods. Methods in objects are functions that belongs to the object.

Let us create a method in the Person class:

Example

Insert a function that prints a greeting, and execute it on the p1 object:

```
class Person:
    def __init__(self, name, age):
        self.name = name
        self.age = age

    def myfunc(self):
        print("Hello my name is " + self.name)

p1 = Person("John", 36)
p1.myfunc()
```

Run example »

Note: The `self` parameter is a reference to the class instance itself, and is used to access variables that belongs to the class.

The self Parameter

The `self` parameter is a reference to the class itself, and is used to access variables that belongs to the class.

It does not have to be named `self`, you can call it whatever you like, but it has to be the first parameter of any function in the class:

Example

Use the words *mysillyobject* and *abc* instead of *self*:

```
class Person:
    def __init__(mysillyobject, name, age):
        mysillyobject.name = name
        mysillyobject.age = age

    def myfunc(abc):
        print("Hello my name is " + abc.name)

p1 = Person("John", 36)
p1.myfunc()
```

Run example »

Modify Object Properties

You can modify properties on objects like this:

Example

Set the age of p1 to 40:

```
p1.age = 40
```

Run example »

Delete Object Properties

You can delete properties on objects by using the `del` keyword:

Example

Delete the age property from the p1 object:

```
del p1.age
```

[Run example »](#)

Delete Objects

You can delete objects by using the `del` keyword:


Example

Delete the p1 object:

```
del p1
```

[Run example »](#)[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

- Tabs
- Dropdowns
- Accordions
- Side Navigation
- Top Navigation
- Modal Boxes
- Progress Bars
- Parallax
- Login Form
- HTML Includes

Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
PHP
jQuery
Bootstrap
XML

[Read More »](#)

[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

Top 10 Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
W3.CSS Tutorial
Bootstrap Tutorial

[SQL Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Python Tutorial](#)

Top 10 References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[SQL Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Python Reference](#)

Top 10 Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Angular Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2019 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

