

```

import bpy

# Ensure an object is selected
obj = bpy.context.active_object
if not obj or obj.type != 'MESH':
    raise Exception("Please select a mesh object with a Boolean modifier.")

# Store cutter objects to delete later
cutters = []

# Apply Boolean modifiers and collect cutter objects
for mod in obj.modifiers:
    if mod.type == 'BOOLEAN':
        cutters.append(mod.object)
        bpy.context.view_layer.objects.active = obj
        bpy.ops.object.modifier_apply(modifier=mod.name)

# Delete cutter objects
bpy.ops.object.select_all(action='DESELECT')
for cutter in cutters:
    if cutter:
        cutter.select_set(True)
bpy.ops.object.delete()

# Clean up geometry
bpy.context.view_layer.objects.active = obj
bpy.ops.object.mode_set(mode='EDIT')
bpy.ops.mesh.select_all(action='SELECT')
bpy.ops.mesh.remove_doubles() # Merge by distance
bpy.ops.mesh.normals_make_consistent(inside=False)
bpy.ops.object.mode_set(mode='OBJECT')

# Add collision physics
if "Collision" not in obj.modifiers:
    bpy.ops.object.modifier_add(type='COLLISION')
    obj.collision.use_colider = True
    obj.collision.use_deform = True
    obj.collision.thickness_outer = 0.0
    obj.collision.thickness_inner = 0.0

```