

Início do login com Google — cabeçalhos saneados

Projeto: segundaav **URL:** https://segundaav.pages.dev

Pedido: GET https://segundaav.pages.dev/oauth/login/google

Saneamento: valores do cookie, client_id, state, code_challenge e nonce substituídos por [REMOVIDO].

Resposta

```
HTTP/1.1 302 Found
Date: Thu, 24 Sep 2026 23:00:46 GMT
Content-Length: 0
Location: https://accounts.google.com/o/oauth2/v2/auth?
  client_id=[REMOVIDO]
  &redirect_uri=https%3A%2F%2Fsegundaav.pages.dev%2Foauth%2Fcallback%2Fgoogle
  &response_type=code
  &state=[REMOVIDO]
  &code_challenge=[REMOVIDO]
  &code_challenge_method=S256
  &scope=openid+email+profile
  &nonce=[REMOVIDO]
Cache-Control: no-store
Set-Cookie: __Host-oauth-tx=[REMOVIDO]; Path=/; HttpOnly; Secure; SameSite=Lax; Max-Age=600
```

Conferência (item 15.2 do roteiro)

✓	Estado HTTP 302
✓	A resposta cria __Host-oauth-tx (Path=/; HttpOnly; Secure; SameSite=Lax; Max-Age=600)
✓	Location aponta para accounts.google.com
✓	response_type=code presente
✓	code_challenge_method=S256 presente
✓	redirect_uri é exatamente https://segundaav.pages.dev/oauth/callback/google
✓	scope=openid email profile e nonce presentes
✓	Client Secret e code_verifier ausentes