
Amazon CloudWatch Application Insights for .NET and SQL Server

Welcome

API Version 2018-11-25



Amazon CloudWatch Application Insights for .NET and SQL Server: Welcome

Copyright © 2019 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateApplication	3
Request Syntax	3
Request Parameters	3
Response Syntax	4
Response Elements	4
Errors	4
See Also	5
CreateComponent	6
Request Syntax	6
Request Parameters	6
Response Elements	6
Errors	6
See Also	7
CreateLogPattern	8
Request Syntax	8
Request Parameters	8
Response Syntax	9
Response Elements	9
Errors	9
See Also	10
DeleteApplication	11
Request Syntax	11
Request Parameters	11
Response Elements	11
Errors	11
See Also	12
DeleteComponent	13
Request Syntax	13
Request Parameters	13
Response Elements	13
Errors	13
See Also	14
DeleteLogPattern	15
Request Syntax	15
Request Parameters	15
Response Elements	15
Errors	16
See Also	16
DescribeApplication	17
Request Syntax	17
Request Parameters	17
Response Syntax	17
Response Elements	17
Errors	18
See Also	18
DescribeComponent	19
Request Syntax	19
Request Parameters	19
Response Syntax	19
Response Elements	19
Errors	20
See Also	20

DescribeComponentConfiguration	21
Request Syntax	21
Request Parameters	21
Response Syntax	21
Response Elements	21
Errors	22
See Also	22
DescribeComponentConfigurationRecommendation	24
Request Syntax	24
Request Parameters	24
Response Syntax	24
Response Elements	25
Errors	25
See Also	25
DescribeLogPattern	26
Request Syntax	26
Request Parameters	26
Response Syntax	26
Response Elements	27
Errors	27
See Also	27
DescribeObservation	29
Request Syntax	29
Request Parameters	29
Response Syntax	29
Response Elements	29
Errors	30
See Also	30
DescribeProblem	31
Request Syntax	31
Request Parameters	31
Response Syntax	31
Response Elements	31
Errors	32
See Also	32
DescribeProblemObservations	33
Request Syntax	33
Request Parameters	33
Response Syntax	33
Response Elements	33
Errors	34
See Also	34
ListApplications	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	35
Errors	36
See Also	36
ListComponents	37
Request Syntax	37
Request Parameters	37
Response Syntax	37
Response Elements	38
Errors	38
See Also	38
ListLogPatterns	40

Request Syntax	40
Request Parameters	40
Response Syntax	41
Response Elements	41
Errors	41
See Also	42
ListLogPatternSets	43
Request Syntax	43
Request Parameters	43
Response Syntax	43
Response Elements	44
Errors	44
See Also	44
ListProblems	46
Request Syntax	46
Request Parameters	46
Response Syntax	47
Response Elements	47
Errors	47
See Also	48
ListTagsForResource	49
Request Syntax	49
Request Parameters	49
Response Syntax	49
Response Elements	49
Errors	50
See Also	50
TagResource	51
Request Syntax	51
Request Parameters	51
Response Elements	51
Errors	51
See Also	52
UntagResource	53
Request Syntax	53
Request Parameters	53
Response Elements	53
Errors	53
See Also	54
UpdateApplication	55
Request Syntax	55
Request Parameters	55
Response Syntax	56
Response Elements	56
Errors	56
See Also	56
UpdateComponent	58
Request Syntax	58
Request Parameters	58
Response Elements	59
Errors	59
See Also	59
UpdateComponentConfiguration	60
Request Syntax	60
Request Parameters	60
Response Elements	61
Errors	61

See Also	61
UpdateLogPattern	63
Request Syntax	63
Request Parameters	63
Response Syntax	64
Response Elements	64
Errors	64
See Also	65
Data Types	66
ApplicationComponent	67
Contents	67
See Also	67
ApplicationInfo	68
Contents	68
See Also	68
LogPattern	70
Contents	70
See Also	70
Observation	72
Contents	72
See Also	73
Problem	74
Contents	74
See Also	75
RelatedObservations	76
Contents	76
See Also	76
Tag	77
Contents	77
See Also	77
Common Parameters	78
Common Errors	80

Welcome

Amazon CloudWatch Application Insights for .NET and SQL Server is a service that helps you detect common problems with your .NET and SQL Server-based applications. It enables you to pinpoint the source of issues in your applications (built with technologies such as Microsoft IIS, .NET, and Microsoft SQL Server), by providing key insights into detected problems.

After you onboard your application, CloudWatch Application Insights for .NET and SQL Server identifies, recommends, and sets up metrics and logs. It continuously analyzes and correlates your metrics and logs for unusual behavior to surface actionable problems with your application. For example, if your application is slow and unresponsive and leading to HTTP 500 errors in your Application Load Balancer (ALB), Application Insights informs you that a memory pressure problem with your SQL Server database is occurring. It bases this analysis on impactful metrics and log errors.

This document was last published on December 23, 2019.

Actions

The following actions are supported:

- [CreateApplication](#) (p. 3)
- [CreateComponent](#) (p. 6)
- [CreateLogPattern](#) (p. 8)
- [DeleteApplication](#) (p. 11)
- [DeleteComponent](#) (p. 13)
- [DeleteLogPattern](#) (p. 15)
- [DescribeApplication](#) (p. 17)
- [DescribeComponent](#) (p. 19)
- [DescribeComponentConfiguration](#) (p. 21)
- [DescribeComponentConfigurationRecommendation](#) (p. 24)
- [DescribeLogPattern](#) (p. 26)
- [DescribeObservation](#) (p. 29)
- [DescribeProblem](#) (p. 31)
- [DescribeProblemObservations](#) (p. 33)
- [ListApplications](#) (p. 35)
- [ListComponents](#) (p. 37)
- [ListLogPatterns](#) (p. 40)
- [ListLogPatternSets](#) (p. 43)
- [ListProblems](#) (p. 46)
- [ListTagsForResource](#) (p. 49)
- [TagResource](#) (p. 51)
- [UntagResource](#) (p. 53)
- [UpdateApplication](#) (p. 55)
- [UpdateComponent](#) (p. 58)
- [UpdateComponentConfiguration](#) (p. 60)
- [UpdateLogPattern](#) (p. 63)

CreateApplication

Adds an application that is created from a resource group.

Request Syntax

```
{
  "OpsCenterEnabled": boolean,
  "OpsItemSNSTopicArn": "string",
  "ResourceGroupName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

OpsCenterEnabled (p. 3)

When set to `true`, creates opsItems for any problems detected on an application.

Type: Boolean

Required: No

OpsItemSNSTopicArn (p. 3)

The SNS topic provided to Application Insights that is associated to the created opsItem. Allows you to receive notifications for updates to the opsItem.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 300.

Required: No

ResourceGroupName (p. 3)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\._\-]*`

Required: Yes

Tags (p. 3)

List of tags to add to the application. tag key (`Key`) and an associated tag value (`Value`). The maximum length of a tag key is 128 characters. The maximum length of a tag value is 256 characters.

Type: Array of [Tag \(p. 77\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
{
  "ApplicationInfo": {
    "Lifecycle": "string",
    "OpsCenterEnabled": boolean,
    "OpsItemSNSTopicArn": "string",
    "Remarks": "string",
    "ResourceGroupName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ApplicationInfo \(p. 4\)](#)

Information about the application.

Type: [ApplicationInfo \(p. 68\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceInUseException

The resource is already created or in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

TagsAlreadyExistException

Tags are already registered for the specified application ARN.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

CreateComponent

Creates a custom component by grouping similar standalone instances to monitor.

Request Syntax

```
{  
  "ComponentName": "string",  
  "ResourceGroupName": "string",  
  "ResourceList": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ComponentName (p. 6)

The name of the component.

Type: String

Required: Yes

ResourceGroupName (p. 6)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

ResourceList (p. 6)

The list of resource ARNs that belong to the component.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceInUseException

The resource is already created or in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

CreateLogPattern

Adds an log pattern to a LogPatternSet.

Request Syntax

```
{  
  "Pattern": "string",  
  "PatternName": "string",  
  "PatternSetName": "string",  
  "Rank": number,  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

Pattern (p. 8)

The log pattern.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

PatternName (p. 8)

The name of the log pattern.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

PatternSetName (p. 8)

The name of the log pattern set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Rank (p. 8)

Rank of the log pattern.

Type: Integer

Required: Yes

ResourceGroupName (p. 8)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Syntax

```
{
  "LogPattern": {
    "Pattern": "string",
    "PatternName": "string",
    "PatternSetName": "string",
    "Rank": number
  },
  "ResourceGroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LogPattern (p. 9)

The successfully created log pattern.

Type: [LogPattern \(p. 70\)](#) object

ResourceGroupName (p. 9)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceInUseException

The resource is already created or in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteApplication

Removes the specified application from monitoring. Does not delete the application.

Request Syntax

```
{  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ResourceGroupName (p. 11)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

BadRequestException

The request is not understood by the server.

HTTP Status Code: 400

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteComponent

Ungroups a custom component. When you ungroup custom components, all applicable monitors that are set up for the component are removed and the instances revert to their standalone status.

Request Syntax

```
{  
  "ComponentName": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ComponentName (p. 13)

The name of the component.

Type: String

Required: Yes

ResourceGroupName (p. 13)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 80).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteLogPattern

Removes the specified log pattern from a `LogPatternSet`.

Request Syntax

```
{  
  "PatternName": "string",  
  "PatternSetName": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

PatternName (p. 15)

The name of the log pattern.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: Yes

PatternSetName (p. 15)

The name of the log pattern set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: Yes

ResourceGroupName (p. 15)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

BadRequestException

The request is not understood by the server.

HTTP Status Code: 400

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeApplication

Describes the application.

Request Syntax

```
{  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ResourceGroupName (p. 17)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Syntax

```
{  
  "ApplicationInfo": {  
    "Lifecycle": "string",  
    "OpsCenterEnabled": boolean,  
    "OpsItemSNSTopicArn": "string",  
    "Remarks": "string",  
    "ResourceGroupName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationInfo (p. 17)

Information about the application.

Type: [ApplicationInfo \(p. 68\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeComponent

Describes a component and lists the resources that are grouped together in a component.

Request Syntax

```
{  
  "ComponentName": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ComponentName (p. 19)

The name of the component.

Type: String

Required: Yes

ResourceGroupName (p. 19)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Syntax

```
{  
  "ApplicationComponent": {  
    "ComponentName": "string",  
    "Monitor": boolean,  
    "ResourceType": "string",  
    "Tier": "string"  
  },  
  "ResourceList": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationComponent (p. 19)

Describes a standalone resource or similarly grouped resources that the application is made up of.

Type: [ApplicationComponent \(p. 67\)](#) object

ResourceList (p. 19)

The list of resource ARNs that belong to the component.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1011.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeComponentConfiguration

Describes the monitoring configuration of the component.

Request Syntax

```
{  
  "ComponentName": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ComponentName (p. 21)

The name of the component.

Type: String

Required: Yes

ResourceGroupName (p. 21)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Syntax

```
{  
  "ComponentConfiguration": "string",  
  "Monitor": boolean,  
  "Tier": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ComponentConfiguration (p. 21)

The configuration settings of the component. The value is the escaped JSON of the configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Monitor (p. 21)

Indicates whether the application component is monitored.

Type: Boolean

Tier (p. 21)

The tier of the application component. Supported tiers include DOT_NET_CORE, DOT_NET_WORKER, DOT_NET_WEB, SQL_SERVER, and DEFAULT

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Valid Values: DEFAULT | DOT_NET_CORE | DOT_NET_WORKER | DOT_NET_WEB | SQL_SERVER

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeComponentConfigurationRecommendation

Describes the recommended monitoring configuration of the component.

Request Syntax

```
{  
  "ComponentName": "string",  
  "ResourceGroupName": "string",  
  "Tier": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ComponentName (p. 24)

The name of the component.

Type: String

Required: Yes

ResourceGroupName (p. 24)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Tier (p. 24)

The tier of the application component. Supported tiers include DOT_NET_CORE, DOT_NET_WORKER, DOT_NET_WEB, SQL_SERVER, and DEFAULT.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Valid Values: DEFAULT | DOT_NET_CORE | DOT_NET_WORKER | DOT_NET_WEB | SQL_SERVER

Required: Yes

Response Syntax

```
{  
  "ComponentConfiguration": "string"  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ComponentConfiguration (p. 24)

The recommended configuration settings of the component. The value is the escaped JSON of the configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 80).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeLogPattern

Describe a specific log pattern from a LogPatternSet.

Request Syntax

```
{  
  "PatternName": "string",  
  "PatternSetName": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

PatternName (p. 26)

The name of the log pattern.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

PatternSetName (p. 26)

The name of the log pattern set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

ResourceGroupName (p. 26)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Syntax

```
{
```



```
"LogPattern": {  
  "Pattern": "string",  
  "PatternName": "string",  
  "PatternSetName": "string",  
  "Rank": number  
},  
"ResourceGroupName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LogPattern (p. 26)

The successfully created log pattern.

Type: [LogPattern \(p. 70\)](#) object

ResourceGroupName (p. 26)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeObservation

Describes an anomaly or error with the application.

Request Syntax

```
{  
  "ObservationId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ObservationId (p. 29)

The ID of the observation.

Type: String

Length Constraints: Fixed length of 38.

Pattern: o-[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}

Required: Yes

Response Syntax

```
{  
  "Observation": {  
    "EndTime": number,  
    "Id": "string",  
    "LineTime": number,  
    "LogFilter": "string",  
    "LogGroup": "string",  
    "LogText": "string",  
    "MetricName": "string",  
    "MetricNamespace": "string",  
    "SourceARN": "string",  
    "SourceType": "string",  
    "StartTime": number,  
    "Unit": "string",  
    "Value": number  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Observation (p. 29)

Information about the observation.

Type: [Observation \(p. 72\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeProblem

Describes an application problem.

Request Syntax

```
{  
  "ProblemId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ProblemId (p. 31)

The ID of the problem.

Type: String

Length Constraints: Fixed length of 38.

Pattern: p-[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}

Required: Yes

Response Syntax

```
{  
  "Problem": {  
    "AffectedResource": "string",  
    "EndTime": number,  
    "Feedback": {  
      "string": "string"  
    },  
    "Id": "string",  
    "Insights": "string",  
    "ResourceGroupName": "string",  
    "SeverityLevel": "string",  
    "StartTime": number,  
    "Status": "string",  
    "Title": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Problem (p. 31)

Information about the problem.

Type: [Problem \(p. 74\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeProblemObservations

Describes the anomalies or errors associated with the problem.

Request Syntax

```
{  
  "ProblemId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ProblemId (p. 33)

The ID of the problem.

Type: String

Length Constraints: Fixed length of 38.

Pattern: p-[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}

Required: Yes

Response Syntax

```
{  
  "RelatedObservations": {  
    "ObservationList": [  
      {  
        "EndTime": number,  
        "Id": "string",  
        "LineTime": number,  
        "LogFilter": "string",  
        "LogGroup": "string",  
        "LogText": "string",  
        "MetricName": "string",  
        "MetricNamespace": "string",  
        "SourceARN": "string",  
        "SourceType": "string",  
        "StartTime": number,  
        "Unit": "string",  
        "Value": number  
      }  
    ]  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

RelatedObservations (p. 33)

Observations related to the problem.

Type: [RelatedObservations \(p. 76\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListApplications

Lists the IDs of the applications that you are monitoring.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

MaxResults (p. 35)

The maximum number of results to return in a single call. To retrieve the remaining results, make another call with the returned `NextToken` value.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 40.

Required: No

NextToken (p. 35)

The token to request the next page of results.

Type: String

Required: No

Response Syntax

```
{  
  "ApplicationInfoList": [  
    {  
      "Lifecycle": "string",  
      "OpsCenterEnabled": boolean,  
      "OpsItemSNSTopicArn": "string",  
      "Remarks": "string",  
      "ResourceGroupName": "string"  
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationInfoList (p. 35)

The list of applications.

Type: Array of [ApplicationInfo \(p. 68\)](#) objects

NextToken (p. 35)

The token used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListComponents

Lists the auto-grouped, standalone, and custom components of the application.

Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ResourceGroupName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 37)

The maximum number of results to return in a single call. To retrieve the remaining results, make another call with the returned `NextToken` value.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 40.

Required: No

NextToken (p. 37)

The token to request the next page of results.

Type: String

Required: No

ResourceGroupName (p. 37)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: Yes

Response Syntax

```
{
  "ApplicationComponentList": [
    {
      "ComponentName": "string",
      "Monitor": boolean,

```

```
    "ResourceType": "string",  
    "Tier": "string"  
  },  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationComponentList (p. 37)

The list of application components.

Type: Array of [ApplicationComponent \(p. 67\)](#) objects

NextToken (p. 37)

The token to request the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListLogPatterns

Lists the log patterns in the specific log `LogPatternSet`.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string",  
  "PatternSetName": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

MaxResults (p. 40)

The maximum number of results to return in a single call. To retrieve the remaining results, make another call with the returned `NextToken` value.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 40.

Required: No

NextToken (p. 40)

The token to request the next page of results.

Type: String

Required: No

PatternSetName (p. 40)

The name of the log pattern set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: No

ResourceGroupName (p. 40)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: Yes

Response Syntax

```
{
  "LogPatterns": [
    {
      "Pattern": "string",
      "PatternName": "string",
      "PatternSetName": "string",
      "Rank": number
    }
  ],
  "NextToken": "string",
  "ResourceGroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LogPatterns (p. 41)

The list of log patterns.

Type: Array of [LogPattern \(p. 70\)](#) objects

NextToken (p. 41)

The token used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

ResourceGroupName (p. 41)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_\-]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListLogPatternSets

Lists the log pattern sets in the specific application.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string",  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

MaxResults (p. 43)

The maximum number of results to return in a single call. To retrieve the remaining results, make another call with the returned `NextToken` value.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 40.

Required: No

NextToken (p. 43)

The token to request the next page of results.

Type: String

Required: No

ResourceGroupName (p. 43)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_\]*`

Required: Yes

Response Syntax

```
{  
  "LogPatternSets": [ "string" ],  
  "NextToken": "string",  
  "ResourceGroupName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LogPatternSets (p. 43)

The list of log pattern sets.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: [a-zA-Z0-9\.\-_]*

NextToken (p. 43)

The token used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

ResourceGroupName (p. 43)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 80).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListProblems

Lists the problems with your application.

Request Syntax

```
{  
  "EndTime": number,  
  "MaxResults": number,  
  "NextToken": "string",  
  "ResourceGroupName": "string",  
  "StartTime": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

EndTime (p. 46)

The time when the problem ended, in epoch seconds. If not specified, problems within the past seven days are returned.

Type: Timestamp

Required: No

MaxResults (p. 46)

The maximum number of results to return in a single call. To retrieve the remaining results, make another call with the returned `NextToken` value.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 40.

Required: No

NextToken (p. 46)

The token to request the next page of results.

Type: String

Required: No

ResourceGroupName (p. 46)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: No

StartTime (p. 46)

The time when the problem was detected, in epoch seconds. If you don't specify a time frame for the request, problems within the past seven days are returned.

Type: Timestamp

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "ProblemList": [
    {
      "AffectedResource": "string",
      "EndTime": number,
      "Feedback": {
        "string": "string"
      },
      "Id": "string",
      "Insights": "string",
      "ResourceGroupName": "string",
      "SeverityLevel": "string",
      "StartTime": number,
      "Status": "string",
      "Title": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 47)

The token used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

ProblemList (p. 47)

The list of problems.

Type: Array of [Problem \(p. 74\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListTagsForResource

Retrieve a list of the tags (keys and values) that are associated with a specified application. A *tag* is a label that you optionally define and associate with an application. Each tag consists of a required *tag key* and an optional associated *tag value*. A tag key is a general label that acts as a category for more specific tag values. A tag value acts as a descriptor within a tag key.

Request Syntax

```
{  
  "ResourceARN": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ResourceARN (p. 49)

The Amazon Resource Name (ARN) of the application that you want to retrieve tag information for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags (p. 49)

An array that lists all the tags that are associated with the application. Each tag consists of a required tag key (*Key*) and an associated tag value (*Value*).

Type: Array of [Tag](#) (p. 77) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

TagResource

Add one or more tags (keys and values) to a specified application. A *tag* is a label that you optionally define and associate with an application. Tags can help you categorize and manage application in different ways, such as by purpose, owner, environment, or other criteria.

Each tag consists of a required *tag key* and an associated *tag value*, both of which you define. A tag key is a general label that acts as a category for more specific tag values. A tag value acts as a descriptor within a tag key.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ResourceARN (p. 51)

The Amazon Resource Name (ARN) of the application that you want to add one or more tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Tags (p. 51)

A list of tags that to add to the application. A tag consists of a required tag key (*key*) and an associated tag value (*value*). The maximum length of a tag key is 128 characters. The maximum length of a tag value is 256 characters.

Type: Array of [Tag \(p. 77\)](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

TooManyTagsException

The number of the provided tags is beyond the limit, or the number of total tags you are trying to attach to the specified resource exceeds the limit.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UntagResource

Remove one or more tags (keys and values) from a specified application.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

ResourceARN (p. 53)

The Amazon Resource Name (ARN) of the application that you want to remove one or more tags from.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

TagKeys (p. 53)

The tags (tag keys) that you want to remove from the resource. When you specify a tag key, the action removes both that key and its associated tag value.

To remove more than one tag from the application, append the `TagKeys` parameter and argument for each additional tag to remove, separated by an ampersand.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UpdateApplication

Updates the application.

Request Syntax

```
{  
  "OpsCenterEnabled": boolean,  
  "OpsItemSNSTopicArn": "string",  
  "RemoveSNSTopic": boolean,  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

[OpsCenterEnabled](#) (p. 55)

When set to `true`, creates opsItems for any problems detected on an application.

Type: Boolean

Required: No

[OpsItemSNSTopicArn](#) (p. 55)

The SNS topic provided to Application Insights that is associated to the created opsItem. Allows you to receive notifications for updates to the opsItem.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 300.

Required: No

[RemoveSNSTopic](#) (p. 55)

Disassociates the SNS topic from the opsItem created for detected problems.

Type: Boolean

Required: No

[ResourceGroupName](#) (p. 55)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: Yes

Response Syntax

```
{
  "ApplicationInfo": {
    "Lifecycle": "string",
    "OpsCenterEnabled": boolean,
    "OpsItemSNSTopicArn": "string",
    "Remarks": "string",
    "ResourceGroupName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationInfo (p. 56)

Information about the application.

Type: [ApplicationInfo \(p. 68\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UpdateComponent

Updates the custom component name and/or the list of resources that make up the component.

Request Syntax

```
{  
  "ComponentName": "string",  
  "NewComponentName": "string",  
  "ResourceGroupName": "string",  
  "ResourceList": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ComponentName (p. 58)

The name of the component.

Type: String

Required: Yes

NewComponentName (p. 58)

The new name of the component.

Type: String

Required: No

ResourceGroupName (p. 58)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

ResourceList (p. 58)

The list of resource ARNs that belong to the component.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceInUseException

The resource is already created or in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UpdateComponentConfiguration

Updates the monitoring configurations for the component. The configuration input parameter is an escaped JSON of the configuration and should match the schema of what is returned by `DescribeComponentConfigurationRecommendation`.

Request Syntax

```
{  
  "ComponentConfiguration": "string",  
  "ComponentName": "string",  
  "Monitor": boolean,  
  "ResourceGroupName": "string",  
  "Tier": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 78).

The request accepts the following data in JSON format.

ComponentConfiguration (p. 60)

The configuration settings of the component. The value is the escaped JSON of the configuration. For more information about the JSON format, see [Working with JSON](#). You can send a request to `DescribeComponentConfigurationRecommendation` to see the recommended configuration for a component. For the complete format of the component configuration file, see [Component Configuration](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Required: No

ComponentName (p. 60)

The name of the component.

Type: String

Required: Yes

Monitor (p. 60)

Indicates whether the application component is monitored.

Type: Boolean

Required: No

ResourceGroupName (p. 60)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Tier (p. 60)

The tier of the application component. Supported tiers include `DOT_NET_WORKER`, `DOT_NET_WEB`, `DOT_NET_CORE`, `SQL_SERVER`, and `DEFAULT`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Valid Values: `DEFAULT` | `DOT_NET_CORE` | `DOT_NET_WORKER` | `DOT_NET_WEB` | `SQL_SERVER`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerErrorException

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V2](#)

UpdateLogPattern

Adds a log pattern to a LogPatternSet.

Request Syntax

```
{  
  "Pattern": "string",  
  "PatternName": "string",  
  "PatternSetName": "string",  
  "Rank": number,  
  "ResourceGroupName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 78\)](#).

The request accepts the following data in JSON format.

Pattern (p. 63)

The log pattern.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

PatternName (p. 63)

The name of the log pattern.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

PatternSetName (p. 63)

The name of the log pattern set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Rank (p. 63)

Rank of the log pattern.

Type: Integer

Required: No

ResourceGroupName (p. 63)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Required: Yes

Response Syntax

```
{
  "LogPattern": {
    "Pattern": "string",
    "PatternName": "string",
    "PatternSetName": "string",
    "Rank": number
  },
  "ResourceGroupName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

LogPattern (p. 64)

The successfully created log pattern.

Type: [LogPattern \(p. 70\)](#) object

ResourceGroupName (p. 64)

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\.\-_]*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 80\)](#).

InternalServerError

The server encountered an internal error and is unable to complete the request.

HTTP Status Code: 400

ResourceInUseException

The resource is already created or in use.

HTTP Status Code: 400

ResourceNotFoundException

The resource does not exist in the customer account.

HTTP Status Code: 400

ValidationException

The parameter is not valid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

Data Types

The Amazon CloudWatch Application Insights API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [ApplicationComponent](#) (p. 67)
- [ApplicationInfo](#) (p. 68)
- [LogPattern](#) (p. 70)
- [Observation](#) (p. 72)
- [Problem](#) (p. 74)
- [RelatedObservations](#) (p. 76)
- [Tag](#) (p. 77)

ApplicationComponent

Describes a standalone resource or similarly grouped resources that the application is made up of.

Contents

ComponentName

The name of the component.

Type: String

Required: No

Monitor

Indicates whether the application component is monitored.

Type: Boolean

Required: No

ResourceType

The resource type. Supported resource types include EC2 instances, Auto Scaling group, Classic ELB, Application ELB, and SQS Queue.

Type: String

Required: No

Tier

The stack tier of the application component.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Valid Values: `DEFAULT` | `DOT_NET_CORE` | `DOT_NET_WORKER` | `DOT_NET_WEB` | `SQL_SERVER`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ApplicationInfo

Describes the status of the application.

Contents

LifeCycle

The lifecycle of the application.

Type: String

Required: No

OpsCenterEnabled

Indicates whether Application Insights will create opsItems for any problem detected by Application Insights for an application.

Type: Boolean

Required: No

OpsItemSNSTopicArn

The SNS topic provided to Application Insights that is associated to the created opsItems to receive SNS notifications for opsItem updates.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 300.

Required: No

Remarks

The issues on the user side that block Application Insights from successfully monitoring an application.

Type: String

Required: No

ResourceGroupName

The name of the resource group used for the application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9\._\-]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

LogPattern

An object that defines the log patterns that belongs to a `LogPatternSet`.

Contents

Pattern

A regular expression that defines the log pattern. A log pattern can contains at many as 50 characters, and it cannot be empty.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

PatternName

The name of the log pattern. A log pattern name can contains at many as 50 characters, and it cannot be empty. The characters can be Unicode letters, digits or one of the following symbols: period, dash, underscore.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: No

PatternSetName

The name of the log pattern. A log pattern name can contains at many as 30 characters, and it cannot be empty. The characters can be Unicode letters, digits or one of the following symbols: period, dash, underscore.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 30.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: No

Rank

Rank of the log pattern.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Observation

Describes an anomaly or error with the application.

Contents

EndTime

The time when the observation ended, in epoch seconds.

Type: Timestamp

Required: No

Id

The ID of the observation type.

Type: String

Length Constraints: Fixed length of 38.

Pattern: o-[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}

Required: No

LineTime

The timestamp in the CloudWatch Logs that specifies when the matched line occurred.

Type: Timestamp

Required: No

LogFilter

The log filter of the observation.

Type: String

Valid Values: `ERROR` | `WARN` | `INFO`

Required: No

LogGroup

The log group name.

Type: String

Required: No

LogText

The log text of the observation.

Type: String

Required: No

MetricName

The name of the observation metric.

Type: String

Required: No

MetricNamespace

The namespace of the observation metric.

Type: String

Required: No

SourceARN

The source resource ARN of the observation.

Type: String

Required: No

SourceType

The source type of the observation.

Type: String

Required: No

StartTime

The time when the observation was first detected, in epoch seconds.

Type: Timestamp

Required: No

Unit

The unit of the source observation metric.

Type: String

Required: No

Value

The value of the source observation metric.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Problem

Describes a problem that is detected by correlating observations.

Contents

AffectedResource

The resource affected by the problem.

Type: String

Required: No

EndTime

The time when the problem ended, in epoch seconds.

Type: Timestamp

Required: No

Feedback

Feedback provided by the user about the problem.

Type: String to string map

Valid Keys: `INSIGHTS_FEEDBACK`

Valid Values: `NOT_SPECIFIED` | `USEFUL` | `NOT_USEFUL`

Required: No

Id

The ID of the problem.

Type: String

Length Constraints: Fixed length of 38.

Pattern: `p-[0-9a-fA-F]{8}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{4}\-[0-9a-fA-F]{12}`

Required: No

Insights

A detailed analysis of the problem using machine learning.

Type: String

Required: No

ResourceGroupName

The name of the resource group affected by the problem.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9\.\-_]*`

Required: No

SeverityLevel

A measure of the level of impact of the problem.

Type: String

Valid Values: Low | Medium | High

Required: No

StartTime

The time when the problem started, in epoch seconds.

Type: Timestamp

Required: No

Status

The status of the problem.

Type: String

Valid Values: IGNORE | RESOLVED | PENDING

Required: No

Title

The name of the problem.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

RelatedObservations

Describes observations related to the problem.

Contents

ObservationList

The list of observations related to the problem.

Type: Array of [Observation \(p. 72\)](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Tag

An object that defines the tags associated with an application. A *tag* is a label that you optionally define and associate with an application. Tags can help you categorize and manage resources in different ways, such as by purpose, owner, environment, or other criteria.

Each tag consists of a required *tag key* and an associated *tag value*, both of which you define. A tag key is a general label that acts as a category for a more specific tag value. A tag value acts as a descriptor within a tag key. A tag key can contain as many as 128 characters. A tag value can contain as many as 256 characters. The characters can be Unicode letters, digits, white space, or one of the following symbols: `_` `:` `/` `=` `+` `-`. The following additional restrictions apply to tags:

- Tag keys and values are case sensitive.
- For each associated resource, each tag key must be unique and it can have only one value.
- The `aws:` prefix is reserved for use by AWS; you can't use it in any tag keys or values that you define. In addition, you can't edit or remove tag keys or values that use this prefix.

Contents

Key

One part of a key-value pair that defines a tag. The maximum length of a tag key is 128 characters. The minimum length is 1 character.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The optional part of a key-value pair that defines a tag. The maximum length of a tag value is 256 characters. The minimum length is 0 characters. If you don't want an application to have a specific tag value, don't specify a value for this parameter.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400