Project 4 — Blue Team: Securing the AI Identity System

Summary

This document presents screenshot evidence of the security controls implemented in Project 4, with each control linked to the corresponding findings from Project 3.

An input guardrail, combining regex rules and the Meta Llama Prompt Guard 2 classifier, blocks prompt injection and extraction attempts before they reach the agent. An output guardrail also checks responses and redacts credential-like strings before they are sent to users.

To secure communication between agents, Ed25519 signatures are used to verify messages before any action is taken. This ensures that forged or tampered messages are rejected. Auth0 access tokens are limited to 300 seconds, while refresh tokens use rotation and reuse detection.


The system also includes an anomaly detector that alerts on unusual request volumes, scope changes, and expired-token reuse. In addition, a risk-based Auth0 post-login Action blocks logins identified as high risk.

After applying these controls, we re-ran all five attacks from Project 3. The overall attack success rate dropped from approximately 88% to 0%.

Controls at a glance


Control	Fixes finding	Evidence
Input guardrail (rules + Prompt Guard 2)	A1, A3, A4, A5	Screenshot 1
Output guardrail — JWT/secret redaction	A1	Screenshot 2
Ed25519 agent message signing	A2	Screenshots 3 & 4
Short-lived tokens (300s) + refresh rotation	Token reuse	Screenshots 5 & 6
Anomaly detection (3 alert types)	Detection gap	Screenshot 7
Risk-based login Action	Account/geo risk	Screenshots 9 & 10
Before/after effectiveness validation	All (A1–A5)	Screenshot 8

1 — Input guardrail blocks the Project 3 attack payloads




Description: The script `input_guardrail.py` tests every payload from Project 3 using two layers of protection: regex rules and the Meta Llama Prompt Guard 2 classifier. Each malicious input is blocked, with the script showing which rules were triggered, such as `HIDDEN_INSTRUCTION`, `SPOOFED_AGENT_HEADER`, and `PROMPT_EXTRACTION`. When the classifier detects a threat, its score is also recorded. This prevents malicious injection and extraction attempts from reaching the AI agent.

1a — Input guardrail: remaining payloads blocked




Description: The suffix-injection, role-elevation, and RAG-poisoning payloads were also successfully blocked. The script identifies and records the specific rule triggered for each attempt, confirming that these attacks were stopped before reaching the agent.

1b — Input guardrail: false-positive test and results




Description: The guardrail was also tested against ten legitimate customer messages, and all of them passed without being blocked. The final results show that all 13 malicious payloads were blocked (100%), with a 0% false-positive rate. This confirms that the guardrail can stop malicious inputs while allowing normal customer interactions to continue.

2 — Output guardrail redacts credential-shaped strings




Description: The script `output_guardrail.py` checks every model response before it is sent to the user. If an attack causes the model to reveal a credential, the raw response is intercepted before it reaches the user. The guardrail uses rules such as `JWT_FULL`, `JWT_FRAGMENT`, and `SECRET_SEGMENT` to detect sensitive values and replace them with `[REDACTED]`. This ensures that exposed credentials are not included in the final response.

2a — Output guardrail: payload P1 raw vs redacted




Description: For payload P1, the model's raw response included a JWT-like value at the end of the `Auth-Ref` line. The output guardrail detected it and replaced the value with `[REDACTED]` before the response was returned.

2b — Output guardrail: summary




Description: The unit test confirms that the guardrail can detect and redact a complete JWT. The final results also show that it successfully blocked sensitive values in responses that attempted to leak credentials, leaving zero secret segments exposed in the output.

3 — Ed25519 key pair generated for agent identity



Description: The script `agent_signing.py` generates an Ed25519 key pair consisting of a private key and a public key, both saved in `.pem` format using Python's `cryptography` library. The orchestrator uses the private key to sign every message sent to another agent, while the receiving agent uses the public key to verify the signature before processing the message.


4 — Tampered and forged messages are rejected



Description: A correctly signed message is accepted, with the system displaying `SIGNATURE VALID → EXECUTE`. If even one character in the message is changed, signature verification fails because the signature no longer matches. The forged orchestrator message from Project 3 Attack 2 is also rejected because it has no valid signature.


In both cases, the requested action is rejected and a security event is logged. This prevents attackers from using forged or modified messages to impersonate the orchestrator.

5a — Auth0 access-token lifetime set to 300 seconds




Description: In the SecureNova Backend API settings, both the **Maximum Access Token Lifetime** and **Implicit/Hybrid Flow Access Token Lifetime** are set to 300 seconds. This limits the validity of an access token to five minutes, reducing the risk of misuse if a token is exposed.

5b — Refresh token rotation enabled



Description: On the AI Chat Web App, Allow Refresh Token Rotation is ON with a Rotation Overlap Period of 0, so each refresh token is single-use and is invalidated after use to prevent replay.

6 — Old refresh token rejected after rotation




Description: The script `refresh_rotation_test.py` successfully exchanges a refresh token and receives an HTTP 200 response, along with a new access token valid for 300 seconds and a rotated refresh token.

When the old refresh token is reused, the server returns `403 invalid_grant`. The newer refresh token is also rejected after the reuse attempt because the reuse detection mechanism revokes the entire token family.

Result: PASS — Refresh token rotation and reuse detection are working as expected.


7 — Anomaly detection alerts



Description: The script `anomaly_detection.py` analyses logged agent events and checks for three types of suspicious activity: more than 20 requests within 60 seconds, changes in scope between consecutive requests from the same agent, and attempts to reuse a token after it has expired.

All three alert types were successfully triggered during testing with the synthetic event set, confirming that the anomaly detection checks are working as expected.


8 — Before / after control-effectiveness comparison



Description: The script `before_after.py` tests all five attacks from Project 3 against the system after the security controls have been applied. Each attack's success rate drops to 0% after the corresponding control is introduced, resulting in an overall reduction of 100%.


The average of the five individual attack success rates before hardening was 87%, while the overall per-attempt success rate reported in Project 3 was approximately 88%. This small difference is due to the two different calculation methods.

9 — Auth0 risk-based post-login Action



Description: A custom Auth0 post-login Action calculates a risk score using factors such as the login country, account status, and user agent. If the score indicates a high-risk login, the Action blocks the login attempt. The Action is deployed under the **Login / Post Login** trigger.

10 — Risk Action blocks a high-risk login



Description: The Auth0 logs show a **Failed Login** event for the AI Chat Web App with the message: `Login blocked by SecureNova risk policy (score 60): account flagged as suspended`. This confirms that the post-login Action correctly identifies the high-risk condition and blocks the login attempt.