

```
CREATE TABLE users (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    username VARCHAR(50) UNIQUE NOT NULL,  
    PASSWORD VARCHAR(100) NOT NULL,  
    email VARCHAR(100) UNIQUE NOT NULL,  
    first_name VARCHAR(50) NOT NULL,  
    last_name VARCHAR(50) NOT NULL,  
    phone VARCHAR(20) NOT NULL,  
    is_driver BOOLEAN DEFAULT FALSE  
);  
  
CREATE TABLE rides (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    driver_id INT NOT NULL,  
    start_location VARCHAR(100) NOT NULL,  
    destination VARCHAR(100) NOT NULL,  
    departure_time DATETIME NOT NULL,  
    arrival_time DATETIME NOT NULL,  
    available_seats INT CHECK (available_seats BETWEEN 0 AND 4),  
    price DECIMAL(6,2) NOT NULL,  
    FOREIGN KEY (driver_id) REFERENCES users(id)  
);  
  
CREATE TABLE bookings (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    ride_id INT NOT NULL,  
    passenger_id INT NOT NULL,  
    seats INT NOT NULL DEFAULT 0, -- Added seats column  
    STATUS ENUM('pending', 'confirmed', 'cancelled') DEFAULT 'pending',  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (ride_id) REFERENCES rides(id),  
    FOREIGN KEY (passenger_id) REFERENCES users(id)  
);
```