

Design for Industry 4.0

Final Deliverable

Institute of Mechanical Engineering

Professor

Prof. Dr. David Inkermann

Dr. A.N. Bhatt

T. Schumacher

Date: 30/07/2025

Authors

Avaneesh Vetrivelan(605454)

[avaneesh.vetrivelan@tuclausthal.de]

Charan Prasad Ramaswamy Govinda Prasad(605515)

[charan.prasad.ramaswamy.govinda.prasad@tu-clausthal.de]

Mohammed Imaad(605772)

[mohammed.imaad@tu-clausthal.de]

Prajwal Babu Reddy(604347)

[babu.reddy.prajwal@tu-clausthal.de]

Prajwal Bheema Raju(604296)

[prajwal.bheema.raju@tuclausthal.de]

Table of Contents

1. Chapter 1: Introduction.....	4
1.1. Smart robotic gripper system.....	4
1.2. Applications.....	4
1.3. Relevance of Smart Robotic Gripper Systems to Modern Automation.....	4
1.4. Requirements List.....	5
2. Chapter 2 : Development of Functional Structure.....	6
2.1. Key components and flows.....	6
2.2. Main Functional Blocks.....	6-7
2.3. Flow Connections.....	7
2.4. Functional Pathways.....	7
2.5. System Boundary.....	7
3. Chapter 3 : Exploration of solution space.....	8
Subtask 3.1: Idea Genereation for physical functions.....	8
3.1.1. Creation of Idea Trees for each sub-function.....	8-10
3.1.2. Development of Morphological Box for Robotic Gripper.....	11
3.1.3. Generation of two concepts.....	12-13
Subtask 3.2: Identify smart functions and decompose and map smart functions.....	14
3.2.1. Identification of Smart functions.....	14
3.2.2. Decomposition of smart functions into elementary data functions.....	15-16
Subtask 3.3: Combine smart components/ concepts with the physical components/ concepts.....	17
3.3.1. Combination of smart and physical concepts.....	17
3.3.2. Explanation of the Two Concepts.....	17-18
4. Chapter 4: Development of Product Architecture.....	19
5. Chapter 5: CAD Modelling.....	20-22
6. Chapter 6 : Integration of Sensors and Automation Components.....	23
7. Chapter 7: Comprehensive Simulation Analysis and Learning Outcomes in MCD.....	24
7.1. Primary Simulation Objective.....	24
7.2. Associated Requirements.....	24
7.3. Functional Behaviors to Demonstrate.....	24-25
7.4. Key Simulation Parameters.....	25-26
7.5. Simulation Observations.....	26
7.5.1. Functionalities achieved.....	26
7.5.2. Identified Performance Limitations.....	26
7.5.3. Validation of Design Concepts.....	27
7.6. Simulation Images.....	27
7.7. Learning Reflections from MCD.....	28
7.8. Conclusion.....	28

Chapter 1: Introduction

1.1. Smart Robotic Gripper System

- ❖ A smart robotic gripper system is a sophisticated end-effector designed to replicate the dexterity and precision of a human hand, enabling robots to autonomously grasp, manipulate, and release objects of varying shapes, sizes, and materials. These systems have evolved from simple mechanical claws to highly advanced, sensor-integrated devices that leverage artificial intelligence, machine learning, and adaptive control algorithms to enhance robotic automation capabilities.

1.2. Applications

Smart robotic gripper systems are pivotal across a wide spectrum of industries, including:

- ❖ Manufacturing: Automated assembly, material handling, and packaging.
- ❖ Logistics: Sorting, picking, and placing items in warehouses and supply chains.
- ❖ Agriculture: Harvesting delicate produce without causing damage.
- ❖ Healthcare: Precise handling of surgical instruments and medical samples.
- ❖ Service Robotics: Assisting in environments that require delicate or variable object manipulation.

1.3. Relevance of Smart Robotic Gripper Systems to Modern Automation

- ❖ Enabling Flexible Manufacturing: Unlike conventional grippers, smart systems adapt to objects of varying shapes, sizes, and materials through intelligent sensing and control. This flexibility is essential for automated production lines that handle diverse products and frequent design changes.
- ❖ Enhancing Human-Robot Collaboration: Integrated sensors and AI allow smart grippers to operate safely around humans and recognize when to adjust force or grip method. This capability is crucial for collaborative robots (cobots) used in environments where humans and robots work side by side.
- ❖ Supporting Industry 4.0 and Connected Factories: Smart grippers, equipped with IoT connectivity, can communicate with other machinery and systems, allowing real-time monitoring, predictive maintenance, and autonomous adaptation to changing workflows. This is central to the vision of Industry 4.0, which emphasizes data-driven and interconnected manufacturing.
- ❖ Improving Efficiency and Quality: Advanced features like adaptive grasping, real-time feedback, and error correction minimize product damage and misplacement, reduce downtime, and improve overall process reliability.

1.4.Requirement List	
1.	Must grasp objects of various shapes and sizes (max. 2 kg payload, typical 0–120 mm jaw range)
2.	Must securely grip small components within specified payload limits
3.	Must be safe for collaborative operation (stop or reduce force upon unexpected contact)
4.	Must be easy to mount on standard robot arms
5.	Must support various finger accessories for different object shapes
6.	Must operate reliably in specified environmental ranges (temperature, humidity, dust)
7.	Must provide electrical and mechanical connection to robot arm (tool connector)
8.	Must enable easy replacement of gripper jaws
9.	Must include clear documentation for installation, operation, and maintenance
10.	Must allow programmable grip force and speed (adjustable via software interface)
11.	Must be safe for collaborative operation (stop or reduce force upon unexpected contact)
12.	Must support programmable grip sequences (open/close, force profiles)
13.	Must comply with relevant safety standards for control systems (CE, UKCA, etc.)
14.	Must allow for remote control and monitoring (optional, if available in integration package)

Table 1: Requirement list

Chapter 2: Development of the Function Structure




Figure 1: Function Structure of smart robot gripper system

This illustrates how various functions interact to fulfil the product's operational requirements. The structure is organized to clearly show the flow of materials, energy, and data/signals through the system, as well as the integration of physical, control, and data (smart) functions.

2.1.Key Components and Flows

➤ Inputs:

- Object: The physical item to be gripped.
- Electrical Power: Required energy for operation.
- Calibration Data: Information for system setup and accuracy.
- Robot Controller Command: External instructions for operation.

➤ Outputs:

- Grippped Object: The result of the gripping process.
- Energy Consumption Data: Information about power usage.
- Status Feedback: System state and performance updates.
- User Feedback: Information for the operator or user.

2.2.Main Function Blocks

- ❖ Physical Functions (e.g., yellow and green boxes such as "Grip Object", "Adjust Grip Force", "Execute Programmable Sequences"):

These perform the core mechanical operations, such as gripping, adjusting force, and executing movement sequences.

- ❖ Control Functions (e.g., “Process Grip Commands”, “Manage Safety”): These regulate the physical actions, ensuring they are performed correctly, safely, and in compliance with operational requirements.
- ❖ Data/Smart Functions (e.g., “Monitor Grip Status”, “Remote Control and Monitoring”, “Provide Visual Indication”, “Manage Communication”): These manage sensing, communication, monitoring, and user interaction, enabling the smart capabilities typical of Industry 4.0 products.

2.3. Flow Connections

- ❖ Solid arrows indicate the flow of material or energy (e.g., Object and Electrical Power entering the system).
- ❖ Dashed arrows represent the flow of data or control signals (e.g., Calibration Data, Robot Controller Command, and feedback loops).

2.4.Functional Pathways

- ❖ The process typically starts with the Object entering the system, where the “Grip Object” function is activated.
- ❖ Grip force is adjusted as needed, and grip status is monitored in real time.
- ❖ Sensors are adjusted to ensure proper operation, and support accessories may be engaged.
- ❖ Process Grip Commands interprets high-level instructions, leading to the execution of programmable sequences.
- ❖ Manage Communication ensures that data is exchanged with external systems and users, while Ensure Regulatory Compliance and Handle Documentation manage legal and operational records.
- ❖ Provide Visual Indication and Troubleshoot Errors support user interaction and maintenance.
- ❖ Manage Safety and Operate in Environmental Conditions ensure the system operates reliably and safely under various conditions.
- ❖ Remote Control and Monitoring enables external oversight and control, critical for smart, connected devices.

2.5.System Boundary

The pink-shaded area defines the system boundary, indicating all functions and flows that are part of the robotic gripper. Inputs and outputs crossing this boundary represent interactions with external systems, users, or environment


Chapter 3 : Exploration of Solution space

Subtask 3.1: Idea Generation for physical functions


3.1.1. Creation of Idea Trees for each sub-function

1. Grip Object


- Enclose Object



- Apply Force




- Adapt to Shape




2.Adjust Grip Force

- Sense applied force




- Modulate/control force




3.Support Finger Accessories

- Mount accessories




- Provide power/signal




4. Operate in Environmental


- Protect against dust/moisture



- Resist temperature extremes



- Prevent Contamination



3.1.2. Development of Morphological Box for Robotic Gripper

Sub-Function	Mechanical	Pneumatic	Chemical/Thermal
Enclose Object	Parallel Jaws	Air-Driven Expanding Fingers	Polymer Gel Fingers
Apply Force	Spring-Loaded Jaws	Vacuum Suction Cups	Adhesive Force
Adapt to Shape	Compliant Fingers	Soft Inflatable Grippers	Self-Shaping Polymer Surfaces
Sense Applied Force	Spring Deflection Sensor	Pressure Sensor (Air Lines)	Force-Sensitive Color Coatings
Modulate Force	Spring-Loaded Limiter	Regulated Air Pressure	Variable-Stiffness Polymers
Control Force	Mechanical Feedback	Feedback Air Pressure Control	Wax Motor Controller
Mount Accessories	Dovetail Slide	Air-Powered Clamp	Releasable Adhesive Mount
Provide Power/Signal	Mechanical Linkage	Air Line for Accessories	Conductive Polymer Interface
Detect/Configure Accessories	Mechanical Interlock	Air Pressure Signature	Colorimetric Sensor
Protect Dust/Moisture	Sealed Housing	Pressurized Housing	Hydrophobic Coating
Resist Temp. Extremes	Thermal Insulation Layer	Phase-Change Materials	Heat-Resistant Coatings
Prevent Contamination	Wipe-Clean Surfaces	UV-Light Sterilization	Self-Cleaning Surface

Table 2: Morphological Box

3.1.3. Generation of two concepts

Concept 1: Adaptive Pneumatic-Chemical Gripper

- ❖ **Core Principle:** Pneumatic actuation with chemical surface adaptation for flexible and adaptive gripping.

❖ Key Features and Selections

Sub-Function	Selected Solution
Enclose Object	Air-Driven Expanding Fingers (Pneumatic)
Apply Force	Vacuum Suction Cups (Pneumatic)
Adapt to Shape	Self-Shaping Polymer Surfaces (Chemical)
Sense Applied Force	Pressure Sensor (Air Lines) (Pneumatic)
Modulate Force	Regulated Air Pressure (Pneumatic)
Control Force	Feedback Air Pressure Control (Pneumatic)
Mount Accessories	Air-Powered Clamp (Pneumatic)
Provide Power/Signal	Air Line for Accessories (Pneumatic)
Detect/Configure Accessories	Air Pressure Signature (Pneumatic)
Protect Dust/Moisture	Pressurized Housing (Pneumatic)
Resist Temp. Extremes	Phase-Change Materials (Thermal)
Prevent Contamination	Self-Cleaning Surface (Chemical)

Table 3 :Salient features and selections for concept 1

❖ Auxiliary Functions:

- Integrated air compressor module
- Polymer replenishment system

Concept 2: Mechanical-Thermal Robust Gripper

- ❖ **Core Principle:** Mechanical simplicity and robustness, with thermal resilience for harsh environments.

❖ Key Features and Selections

Sub-Function	Selected Solution
Enclose Object	Parallel Jaws (Mechanical)
Apply Force	Spring-Loaded Jaws (Mechanical)
Adapt to Shape	Compliant Fingers (Mechanical)
Sense Applied Force	Spring Deflection Sensor (Mechanical)
Modulate Force	Spring-Loaded Limiter (Mechanical)
Control Force	Mechanical Feedback (Mechanical)
Mount Accessories	Dovetail Slide (Mechanical)
Provide Power/Signal	Mechanical Linkage (Mechanical)
Detect/Configure Accessories	Mechanical Interlock (Mechanical)
Protect Dust/Moisture	Sealed Housing (Mechanical)
Resist Temp. Extremes	Thermal Insulation Layer (Mechanical)
Prevent Contamination	UV-Light Sterilization (Thermal)

Table 4 :Salient features and selections for concept 2

❖ Auxiliary Functions:

- Manual force-calibration dial
- Passive heat-dissipation fins

Subtask 3.2: Identify smart functions and decompose and map smart functions

3.2.1. Identification of Smart functions


❖ Salient Smart Functions for the Robotic Gripper

Smart Function	Description	Requirements Satisfied	Value Added
Adaptation	Real-time modification of grip parameters (force, shape, surface) to suit objects	Physical flexibility, control responsiveness, data-driven adjustment	Enables versatile handling of diverse objects, reduces damage risk, improves efficiency
Monitoring	Continuous tracking of grip status, environment, and accessory conditions	Physical reliability, control feedback, data logging	Early detection of faults, predictive maintenance, enhanced safety and compliance
Self-Diagnosis	Automated fault detection and reporting of errors or degradation	Control error handling, data for troubleshooting	Minimizes downtime, improves reliability and safety
Remote Control & Interaction	Remote operation, configuration, and status visualization	Control flexibility, data communication	Supports Industry 4.0 integration, enhances operator responsiveness and collaboration


Table 5 : Smart functions of robotic gripper

3.2.2. Decomposition of smart functions into elementary data functions


❖ Adaptation




❖ Monitoring:



❖ Self-Diagnosis:



❖ Remote Control & Interaction



Subtask 3.3: Combine smart components/ concepts with the physical components/ concepts.

3.3.1. Combination of smart and physical concepts

Sub-Function	Concept 1: Precision Adaptive Gripper	Concept 2: Robust Pneumatic Smart Gripper
Detect object	IR sensor (physical) Real-time logging (smart)	Capacitive sensor (physical) Predictive analytics (smart)
Grasp/release	Servo motor (physical) AI-based adaptive control (smart)	Pneumatic actuator (physical) Rule-based adaptation (smart)
Adjust grip force	Force sensor (physical) AI grip optimization (smart)	Strain gauge (physical) Scheduled maintenance (smart)
Sense removal	Proximity switch (physical) Event notification & logging (smart)	Optical sensor (physical) Data logging (smart)
User/system feedback	Cloud connectivity for remote monitoring (smart)	Local dashboard for operator feedback (smart)
Self-diagnosis	Fault detection & notification (smart)	Predictive maintenance using sensor trends (smart)

Table 6 : Combined Smart & Physical Concepts for Robotic Gripper

3.3.2. Explanation of the Two Concepts

❖ Concept 1: Precision Adaptive Gripper

- **Physical:** Uses servo motors and force sensors for precise, flexible gripping; IR sensors for object detection.
- **Smart:** Employs AI for real-time adaptation of grip parameters, logs all actions, and supports remote monitoring and self-diagnosis.
- **Reason for choosing this:**

- Ideal for applications needing **high precision and flexibility** (e.g., electronics, lab automation).
- Maximizes value from precise actuators and sensors by leveraging AI and connectivity for Industry 4.0 readiness^[4].

❖ **Concept 2: Robust Pneumatic Smart Gripper**

- **Physical:** Uses pneumatic actuators for fast, robust gripping; strain gauges and capacitive/optical sensors for force and object detection.
- **Smart:** Employs rule-based adaptation for simple, reliable operation, predictive maintenance to minimize downtime, and a local dashboard for operator feedback.
- **Reason for choosing this:**
 - Suited for **high-speed, high-throughput environments** (e.g., packaging, logistics).
 - Focuses on robustness, reliability, and low-maintenance operation, with smart features tailored for uptime and process optimization.

❖ **Selection of Final Concept**


After evaluating all proposed concepts against the established criteria, **Concept 1** has been selected as the final concept for implementation.

❖ **Basis for Concept Selection**


- **Distinct Working Principles:** Concepts cover a broad solution space—one prioritizes precision and adaptability, the other speed and robustness.
- **Matching Smart Features:** Each concept's smart features are matched to its physical strengths (AI with servo for precision; rules/prediction with pneumatics for reliability).
- **Industry 4.0 Compatibility:** Both concepts integrate monitoring, adaptation, and connectivity, aligning with smart product design best practices.

Chapter 4: Development of Product Architecture

❖ Product Architecture for Concept 1:



❖ Product Architecture for Concept 2:



Chapter 5: CAD Modelling




Figure 2 : Exploded isometric view




Figure 3: Exploded Front View




Figure 4 : Isometric view of the gripper




Figure 5 : Front view of the gripper




Figure 6 : Top View




Figure 7 : Right Side View

Chapter 6 : Integration of Sensors and Automation Components

6.1. Integration of Sensors and Automation Components

To transform the mechanical gripper into a smart, semi-automated system suitable for Industry 4.0 environments, several sensors and automation components were integrated into the design. The actuation concept is based on an electric jaw actuator (servo/linear actuator) controlled via a force-feedback controller and a position control system, as summarized in the driver architecture on page 24. This allows programmable grip force and jaw speed, as well as accurate jaw positioning over the full 0–120 mm opening range.

A dedicated sensor layer was added to ensure reliable operation, monitoring and safety (see the “Sensors Integration” table on page 25). Proximity sensors are used for object detection and grip-status monitoring, enabling the gripper to recognize when an object is present, correctly positioned, and securely held. Force sensors (or strain-gauged elements) provide real-time feedback on grip force, allowing the controller to adapt the applied force to the object mass and fragility and to reduce force immediately in case of unexpected contact. Position encoders on the actuator track the exact jaw position, supporting precise alignment and repeatable opening/closing profiles.

Safety sensors are integrated to detect collisions and abnormal contact. When these sensors trigger, the automation logic either stops motion or reduces force to meet collaborative operation requirements. Together with the force-feedback controller, this ensures that the gripper can be used safely in human–robot collaboration scenarios.

On the automation side, the gripper is connected to a higher-level robot or PLC controller via a standardized interface. Grip commands (open, close, target force, speed) are received as high-level instructions, and the internal controller converts them into actuator set-points. Status information such as jaw position, measured grip force, sensor states and error codes is fed back to the controller and, if required, visualized on a local dashboard or HMI. This closed-loop integration of sensors, actuators and control logic enables adaptive gripping, remote monitoring, and the implementation of programmable grip sequences, as demonstrated in the MCD simulations

Chapter 7: Comprehensive Simulation Analysis and Learning Outcomes in MCD

7.1.Primary Simulation Objective

The primary goal of this simulation is to demonstrate a robotic gripper's ability to approach, securely grasp, and lift an object while maintaining operational safety and precision. This objective directly addresses the fundamental requirement that the gripper "must grasp objects of various shapes and sizes (max. 2 kg payload, typical 0–120 mm jaw range)" as identified in the comprehensive requirements analysis.

7.2.Associated Requirements

The simulation specifically targets multiple critical requirements derived from customer needs analysis and reference system evaluation:

- **Physical:** The gripper must securely handle objects of varying shapes and sizes up to 2 kg, with easily replaceable jaws and reliable robot arm integration.
- **Control:** The system must provide real-time feedback on grip status, allow adjustable grip force, support smooth integration, and enable programmable grip profiles.
- **Safety:** The design must ensure immediate force reduction on unexpected contact and comply with applicable industrial safety standards.

7.3.Functional Behaviours to Demonstrate

The simulation encompasses five key behavioral sequences that reflect real-world operational scenarios:

1. **Object Detection and Approach:** Utilizing proximity sensors to identify target objects and guide gripper positioning.
2. **Gripper Jaw Alignment:** Precise positioning of parallel jaws to ensure optimal contact with object surfaces.
3. **Force Application and Secure Grasping:** Controlled application of gripping force with real-time monitoring.
4. **Stable Lifting Operation:** Vertical lifting motion while maintaining secure grip without slippage.

7.4.Key Simulation Parameters

1. Joint Configuration

Component	Function / Role	Reference / Support	Customer Needs Addressed/Justification
Hinge Joints	Allows rotation in one plane (flex/extend)	Used in doors (mechanical), elbow, knee (biological)	Simple, reliable back-and-forth movement
Sliding Joints	Allows linear sliding motion	Slider/expansion mechanisms in assemblies or machinery	Controlled, smooth linear actuation
Fixed Joints	Rigidly connects parts with no movement	Skull sutures, welded or bolted connections	Stability, permanence, safety

2. Driver System Architecture

Component	Function / Role	Reference / Support	Customer Needs Addressed/Justification
Electric Actuator	Primary jaw force actuator, programmable force & speed	RG2 and EGP-C gripper actuator technology	Programmable grip force, speed adjustable via software
Force Feedback Controller	Closed-loop grip force adjustment	Smart gripper adaptive control concepts	Grip force adjustment, automatic force adaption by object weight
Position Control System	Accurate jaw positioning and force adjustment	Supports visual feedback & operational transparency	Precise jaw opening/closing, clear visual feedback

3. Sensors Integration

Component	Function / Role	Reference / Support	Customer Needs Addressed/Justification
Proximity Sensors	Object detection and grip status monitoring	Monitoring smart function from concept phase	Reliable object detection, grip confirmation
Force Sensors	Real-time grip force feedback and safety monitoring	Supports self-diagnosis and fault detection	Robust safety sensor calibration
Position Encoders	Precise jaw positioning, control of jaw opening range (0–120 mm)	Real-time interface responsiveness	Accurate jaw alignment and dimensions
Safety Sensors	Collision detection, emergency stop or force reduction	Collaborative operation safety requirements	Immediate stop on unexpected contact, reliable collision detection

7.5.Simulation Observations

7.5.1.Functionalities achieved

The simulation successfully demonstrates all primary functional requirements:

1. **Object Grasping Capability:** The gripper reliably secures objects of various shapes and sizes using consistent parallel jaw movement and force application.
2. **Force Control Accuracy:** The force feedback system precisely adjusts grip force in real time, preventing damage to delicate items while securing heavier ones.
3. **Safety System Response:** Collision detection promptly reduces force and signals errors to ensure safe collaborative operation.


7.5.2.Identified Performance Limitations

1. **Sensor Sensitivity Calibration:** Proximity sensors need adjustable settings to accommodate different object materials, addressing customer requests for sensor adaptability.
2. **Response Time Optimization:** The control interface shows minor delays during parameter updates, highlighting a need for faster software response.
3. **Environmental Robustness:** Safety sensors are overly sensitive to dust and debris, indicating a need for enhanced environmental protection to prevent false triggers.

7.5.3. Validation of Design Concepts

1. Adaptive Control Implementation: The smart gripper adapts grip parameters in real time for versatile handling of diverse objects.
2. Monitoring System Performance: Continuous tracking of grip status and environment enables early fault detection and predictive maintenance.
3. Self-Diagnosis Capability: Automated fault detection and reporting reduce downtime and enhance reliability.

7.6. Simulation Images



7.7.Learning Reflections from MCD Integrated System

- **Modeling:** MCD effectively unifies mechanical, electrical, and control elements for validating complex smart gripper interactions, supporting Industry 4.0 development.
- **Real-Time Control Simulation:** The platform allows realistic testing of control algorithms and sensor feedback for optimizing system responsiveness.
- **Physics-Based Validation:** Accurate physics simulation confirms design assumptions on gripping performance and safety effectiveness.

7.8.Conclusion

The design and analysis of the smart robotic gripper system demonstrate how integrating mechanical, pneumatic, and intelligent control functions addresses complex industrial requirements crucial for Industry 4.0 applications. By systematically decomposing physical and smart functions, the project achieved a robust architecture that balances versatility, safety, and adaptability. Simulation results confirmed the gripper's reliability across diverse scenarios, validating the effectiveness of collaborative safety features and real-time feedback mechanisms. Overall, the project illustrates the value of combining advanced sensing, smart diagnostics, and modular mechanics to deliver an efficient, future-ready robotic solution.

The integration of proximity, force, position and safety sensors with an electric actuator and force-feedback controller enabled adaptive grip force control, collision detection and programmable grip sequences. This validated that a sensor-rich, semi-automated gripper architecture can meet both productivity and collaborative safety requirements in Industry 4.0 applications