Working with Styles & Layout

Bala Krishna Ragala

The plan

- Exploring Styles and using styles
 - Inline Styles, Style Objects, Stylesheet
- Exploring layout
 - Understanding Box model
 - Understanding FlexBox model
- Styling Text
- Styling Images
- Debugging Styles

Exploring Styles

- Use style prop on the UI element to apply styles
- React Native you can apply styles in following ways
 - Inline right on the component
 - Object as JS object with styling properties
 - Stylesheet Stylesheet.create function

Stylesheet

- An abstraction similar to CSS StyleSheets
- Define

```
const styles = StyleSheet.create({
   container: {
     borderRadius: 4,
     borderWidth: 0.5,
     borderColor: '#d6d7da',
   },
   title: {
     fontSize: 19,
     fontWeight: 'bold',
   },
   activeTitle: {
     color: 'red',
   },
});
```

• Use

```
<View style={styles.container}>
  <Text style={[styles.title, this.props.isActive && styles.activeTitle]} />
</View>
```

What Stylesheet

Code quality:

- By moving styles away from the render function, you're making the code easier to understand.
- Naming the styles is a good way to add meaning to the low level components in the render function.

Performance:

- Making a stylesheet from a style object makes it possible to refer to it by ID instead of creating a new style object every time.
- It also allows to send the style only once through the bridge. All subsequent uses are going to refer an id (not implemented yet).

Inline Styles

```
<Text style={{fontSize:18, fontWeight:'bold'}}>
Welcome to RN, STYLING!
</Text>
```

Styles as Objects

```
const textStyles = {
   color: '#fff',
   fontSize: 22,
   fontWeight: '900',
   paddingLeft: 20,
   paddingRight: 20,
   paddingTop: 5,
   paddingBottom: 5
<Text style={textStyles}>This is header</Text>
```

Hairline Width


- A constant
- will always be a round number of pixels (so a line defined by it can look crisp) and will try to match the standard width of a thin line on the underlying platform.
- However, you should not rely on it being a constant size, because on different platforms and screen densities its value may be calculated differently

```
SignIn Normal

hairlineBorder: {
borderWidth: StyleSheet.hairlineWidth
}

SignIn Hairline
```

Exploring Layout - Box Model



Flexbox – your box


- Used to layout the elements in React Native
- Influenced by web but a downsized to suit mobile dev
- All components on RN and flex containers and are positioned relatively
- In RN display style property take value as flex ONLY and this is implicit
- A relationship between the container and its immediate children
- Items in container are either horizontally or vertically stacked
- flexDirection property should be used to alter the direction if needed
- Default direction is set to Column in React Native


Dive into axis


- X and Y axis influence the alignment of elements in flex
- Referred as mainaxis and crossaxis
- Mainaxis is set by flexDirection
- Alignment of items on mainaxis are influenced by justifyContent
- Otheraxis referred to crossaxis
- Alignment of items on crossaxis are influenced by alignItems


flexDirection	Main Axis	Cross Axis
column	Υ	X
row	X	Υ

flexDirection











flex


```
<View style={[{flex: 1}, styles.elementsContainer]}>
    <View style={{flex: 1, backgroundColor: '#EE2C38'}} />
    <View style={{flex: 2, backgroundColor: '#FAA030'}} />
    <View style={{flex: 3, backgroundColor: '#32B76C'}} />
</View>
The red view got flex:1,
the Vellow view got flex:2
and the green view got flex:3.
1+2+3=6 which means that
red view will get 1/6 of the space,
the Yellow 2/6 of the space and
the green 3/6 of the space
```



justifyContent

- Aligns content over main axis
- Possible values
 - flex-start
 - center
 - flex-end
 - space-between
 - Space-around






alignItems

- Aligns content over cross axis
- Possible values
 - flex-start
 - center
 - flex-end
 - Stretch (makes flex item to take available width if no width specified)











alignSelf

- Align an item along the cross axis overwriting his parent alignItems property
- Possible values
 - flex-start
 - center
 - flex-end
 - Stretch (makes flex item to take available width if no width specified)











flexWrap


- Controls whether flex items are forced on a single line or can be wrapped on multiple lines.
- Possible values
 - wrap
 - nowrap






alignContent


- So if you went with flexWrap: 'wrap' you have multiple lines of items, this property will help you align the lines on the cross-axis.
- Possible values
 - flex-start
 - center
 - flex-end
 - stretch
 - space-between
 - Space-around



position

- The position property specifies how an element is positioned in a view
- Possible Values
 - relative
 - absolute





Shrink and grow flexbox (advanced)

- 3 properties flexGrow, flexShrink, flexBasis
- flexBasis used to set basis for size calculation for flexGrow and flexShrink
 - Flex-basis affects an element's size across the main axis.
 - Possible values column / row based on the flexDirection
- flexGrow Grow in size as per flexBasis
- flexShrink Shrink in size as per flexBasis

flowGrow


All squares to the same width, 120px

width: 120px;



flowGrow

- when it comes to the property called **flexGrow**, the default is **0**. That means the squares are not allowed to grow to take up the space in the container
- Incrementing flex-grow to 1 for every square, result is below
- **flexGrow** value overrides the width
- Flex-grow is all about proportions.






flowGrow - live

```
.square { flex-grow: 1; }
```


.square#three { flex-grow: 1; }



flexShrink

- flexShrink is the opposite of flexGrow, determining how much a square is allowed to shrink
- Its main use is to specify which items you want to shrink, and which items you don't. By default, every square has a flex-shrink of 1 which means it will shrink as the box contracts.

.square { flex-shrink: 1; }



flexShrink

• Now let's set the flex-shrink of Square #3 to 0. It's forbidden to shrink, so it while it grows to fit the container, it refuses to dip below its set 120px width.

.square { flex-shrink: 1; }

.square#three { flex-shrink: 0; }

1 2 3 4 5 6 8 9

Text (Native Component)

- A React component for displaying text.
- Supports nesting, styling, and touch handling

```
<Text style={styles.baseText}>
    <Text style={styles.titleText} onPress={this.onPressTitle}>
        {this.state.titleText}{'\n'}{'\n'}
        </Text>
        <Text numberOfLines={5}>
        {this.state.bodyText}
        </Text>
</Text>
```

Styling Text

- Most of the rules around React Native styling are equally applicable to text
- Some of the props
 - fontSize
 - fontWeight
 - fontStyle
 - textAlign
 - fontFamily
 - lineHeight
 - fontVariant
 - letterSpacing
 - writingDirection

Image (Native Component)


 A React component for displaying different types of images, including network images, static resources, temporary local images, and images from local disk, such as the camera roll.

```
<View>
  <Image
    source={require('/react-native/img/favicon.png')}
  <Image
    style={{width: 50, height: 50}}
    source={{uri: 'https://facebook.github.io/react-native/docs/assets
  <Image
    style={{width: 66, height: 58}}
    source={{uri: 'data:image/png;base64,iVBORw0KGgoAAAANSUhEUgAAADMAA
  />
</View>
```

Styling Images

- Use Image component to render images
- Use width and height props to manage imageview size
- Without width and height images take default 0 X 0 view size
- Use resizeMode to control the view of the images
- resizeMode
 - contain
 - stretch
 - center
 - cover
 - repeat

Debugging Styles



Platform Specific Code

- Platform module
 - import {Platform} from 'react-native';

```
const styles = StyleSheet.create({
  height: Platform.OS === 'ios' ? 200 : 100,
});
```

```
const Component = Platform.select({
  ios: () => require('ComponentIOS'),
  android: () => require('ComponentAndroid'),
})();

<Component />;
```

```
const styles = StyleSheet.create({
  container: {
   flex: 1,
    ...Platform.select({
     ios: {
        backgroundColor: 'red',
      android: {
        backgroundColor: 'blue',
     },
   }),
```

Platform-specific extensions

- When your platform-specific code is more complex, you should consider splitting the code out into separate files.
- React Native will detect when a file has a .ios. or .android. extension and load the relevant platform file when required from other components
- For example
 - BigButton.ios.js
 - BigButton.android.js
- Import {BigButton} from "./BigButton"
 - React Native will automatically pick up the right file based on the running platform.

Question Time

- When flexDirection is row what is main axis?
- Which property aligns content on main axis?
- Name 3 different styles of styling react native UI?
- Name resize modes of images?
- What is hairline width?
- Normal, italic, bold which style property accepts these values?
- What is default width and height of image if not specified?
- Name 2 axis of flexbox
- In box model padding vs margin?
- Name the module which helps to read info about current running platform?