

# Rajalakshmi Engineering College

Name: CHARISHMA PRIYADARSHINI B R

Email: 240701088@rajalakshmi.edu.in

Roll no: 2116240701088

Phone: 7032692975

Branch: REC

Department: I CSE AG

Batch: 2028

Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 4\_COD\_Question 1

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Imagine a bustling coffee shop, where customers are placing their orders for their favorite coffee drinks. The cafe owner Sheeren wants to efficiently manage the queue of coffee orders using a digital system. She needs a program to handle this queue of orders.

You are tasked with creating a program that implements a queue for coffee orders. Each character in the queue represents a customer's coffee order, with 'L' indicating a latte, 'E' indicating an espresso, 'M' indicating a macchiato, 'O' indicating an iced coffee, and 'N' indicating a nabob.

Customers can place orders and enjoy their delicious coffee drinks.

#### ***Input Format***

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Enqueue the coffee order into the queue. If the choice is 1, the following input is a space-separated character ('L', 'E', 'M', 'O', 'N').

Choice 2: Dequeue a coffee order from the queue.

Choice 3: Display the orders in the queue.

Choice 4: Exit the program.

### ***Output Format***

The output displays messages according to the choice and the status of the queue:

If the choice is 1:

1. Insert the given order into the queue and display "Order for [order] is enqueued." where [order] is the coffee order that is inserted.
2. If the queue is full, print "Queue is full. Cannot enqueue more orders."

If the choice is 2:

1. Dequeue a character from the queue and display "Dequeued Order: " followed by the corresponding order that is dequeued.
2. If the queue is empty without any orders, print "No orders in the queue."

If the choice is 3:

1. The output prints "Orders in the queue are: " followed by the space-separated orders present in the queue.
2. If there are no orders in the queue, print "Queue is empty. No orders available."

If the choice is 4:

1. Exit the program and print "Exiting program"

If any other choice is entered, the output prints "Invalid option."

Refer to the sample output for the exact text and format.

### **Sample Test Case**

Input: 1 L

1 E

1 M

1 O

1 N

1 O

3

2

3

4

Output: Order for L is enqueued.

Order for E is enqueued.

Order for M is enqueued.

Order for O is enqueued.

Order for N is enqueued.

Queue is full. Cannot enqueue more orders.

Orders in the queue are: L E M O N

Dequeued Order: L

Orders in the queue are: E M O N

Exiting program

### **Answer**

```
#include <stdio.h>
```

```
#define MAX_SIZE 5
```

```
char orders[MAX_SIZE];
```

```
int front = -1;
```

```
int rear = -1;
```

```
void initializeQueue() {
```

```
    front = -1;
```

```
    rear = -1;
```

```
}
```

```
int isEmpty()
```

```
{
    if(front==-1)
    {
        return 1;
    }
    else
    {
        return 0;
    }
}
```

```
int isFull()
{
    if(rear==MAX_SIZE-1)
    {
        return 1;
    }
    else
    {
        return 0;
    }
}
```

```
int enqueue(char order)
{
    if(isFull())
    {
        printf("Queue is full. Cannot enqueue more orders.\n");
    }
    else
    {
        if(front==-1)
        {
            front=0;
        }
        rear++;
        orders[rear]=order;
        printf("Order for %c is enqueued.\n",orders[rear]);
    }
    return 0;
}
```

```
int dequeue()
{
    if(isEmpty())
    {
        printf("No orders in the queue.\n");
    }
    else
    {
        printf("Dequeued Order: %c\n",orders[front]);
        if(front==rear)
        {
            front=rear=-1;
        }
        else
        {
            front=front+1;
        }
    }
    return 1;
}
```

```
void display()
{
    if(!isEmpty())
    {
        printf("Orders in the queue are: ");
        for(int i=front;i<=rear;i++)
        {
            printf("%c ",orders[i]);
        }
        printf("\n");
    }
    else
    {
        printf("Queue is empty. No orders available.\n");
    }
}
```

```
int main() {
    char order;
    int option;
    initializeQueue();
    while (1) {
```

```
    if (scanf("%d", &option) != 1) {  
        break;  
    }  
    switch (option) {  
        case 1:  
            if (scanf(" %c", &order) != 1) {  
                break;  
            }  
            if (enqueue(order)) {  
            }  
            break;  
        case 2:  
            dequeue();  
            break;  
        case 3:  
            display();  
            break;  
        case 4:  
            printf("Exiting program");  
            return 0;  
        default:  
            printf("Invalid option.\n");  
            break;  
    }  
}  
return 0;  
}
```

**Status :** Correct

**Marks : 10/10**