

Read Mapping

Burrows Wheeler Transform and Reference Based Assembly

Peter N. Robinson

Institut für Medizinische Genetik und Humangenetik
Charité Universitätsmedizin Berlin

Genomics: Lecture #5 WS 2014/2015

Today

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Burrows Wheeler Transform
- FM index
- Burrows Wheeler Aligner (bwa)

Outline

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

1 Burrows Wheeler Transform

2 FM Index

3 Burrows Wheeler Aligner – bwa

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

The BWT applies a reversible transformation to a block of input text. The transformation does not itself compress the data, but reorders it to make it easy to compress with simple algorithms such as move-to-front coding.

Burrows M, Wheeler DJ (1994) A block-sorting lossless data compression algorithm. Technical report 124. Palo Alto, CA: *Digital Equipment Corporation*.

- Basis for the bzip2 compression algorithm
- Basis for many of the read mapping algorithms in common use today

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- The significance of the BWT for most of the rest of the world is as a data compression technique
- However, the BWT leads to a block-sorted data structure that is well suited to searching short strings in a larger text.
- The FM index uses the BWT to enable search with time linear in the length of the search string.

Ferragina P, Manzini P (2000) Opportunistic Data Structures with Applications.

Proceedings of the 41st IEEE Symposium on Foundations of Computer Science

- Today, we will explain the BWT and then the FM index and show how they are used in bwa for read alignment.

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

First step: form all **rotations** of the input text, which we will call T. Note that as with the suffix array and suffix tree, we append a **termination character** \$ to the end of the text

T="abracadabra\$"

```
0: abracadabra$
1: bracadabra$a
2: racadabra$ab
3: acadabra$abr
4: cadabra$abra
5: adabra$abrac
6: dabra$abrac
7: abra$abracad
8: bra$abracada
9: ra$abracadab
10: a$abracadabr
11: $abracadabra
```

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Second step: Sort the rotated strings lexicographically

0: abracadabra\$		0: \$abracadabra
1: bracadabra\$a		1: a\$abracadabr
2: racadabra\$ab		2: abra\$abracad
3: acadabra\$abr		3: abracadabra\$
4: cadabra\$abra		4: acadabra\$abr
5: adabra\$abrac	sort	5: adabra\$abrac
6: dabra\$abrac	→	6: bra\$abracada
7: abra\$abracad		7: bracadabra\$a
8: bra\$abracada		8: cadabra\$abra
9: ra\$abracadab		9: dabra\$abrac
10: a\$abracadabr		10: ra\$abracadab
11: \$abracadabra		11: racadabra\$ab

recall that the termination character \$ comes before every other character lexicographically.

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Third step: The **Burrows Wheeler Transform** is simply the last column of the **Burrows Wheeler matrix**.

\$	a	b	r	a	c	a	d	a	b	r	a
a	\$	a	b	r	a	c	a	d	a	b	r
a	b	r	a	\$	a	b	r	a	c	a	d
a	b	r	a	c	a	d	a	b	r	a	\$
a	c	a	d	a	b	r	a	\$	a	b	r
a	d	a	b	r	a	\$	a	b	r	a	c
b	r	a	\$	a	b	r	a	c	a	d	a
b	r	a	c	a	d	a	b	r	a	\$	a
c	a	d	a	b	r	a	\$	a	b	r	a
d	a	b	r	a	\$	a	b	r	a	c	a
r	a	\$	a	b	r	a	c	a	d	a	b
r	a	c	a	d	a	b	r	a	\$	a	b

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

We will denote the Burrows Wheeler transform of an input string T as

$$\text{BWT}(T)$$

- Thus, $\text{BWT}(T) = \text{"ard\$rcaaaabb"}$
- It is relatively easy to implement a naive version of the BWT
 - 1 Create all rotations of T
 - 2 Sort the rotations lexicographically
 - 3 Concatenate the last character of each rotation to form $\text{BWT}(T)$

Burrows Wheeler Transform (BWT)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

The BWT tends to contain lots of “runs” of identical characters, which is a good feature to have for compression algorithms such as **run-length encoding**.

- This is slightly difficult to appreciate with the short strings we are using for the slides, but consider the following excerpt of BWT(*Macbeth*, Act 1, Scene 1):

```
...uoaoiiiiiiiiiiiiiiiiiaaaaaauiiiiiiiiiiiiiiiiiiaAAiiiiiiiioieei...
```

A simple run-length encoding might be

```
...uoaoi{15}a{5}i{5}ui{17}aA{2}i{7}oie{2}i...
```

BWT and Suffix array

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

BW matrix

\$abracadabra
a\$abracadabr
abra\$abracad
abracadabra\$
acadabra\$abr
adabra\$abrac
bra\$abracada
bracadabra\$a
cadabra\$abra
dabra\$abraca
ra\$abracadab
racadabra\$ab

Suffix array with corresponding suffixes

[11] \$
[10] a\$
[7] abra\$
[0] abracadabra\$
[3] acadabra\$
[5] adabra\$
[8] bra\$
[1] bracadabra\$
[4] cadabra\$
[6] dabra\$
[9] ra\$
[2] racadabra\$

- The Burrows Wheeler matrix is (nearly) the same as the suffixes referred to by the suffix array of the same string

BWT and Suffix array

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

We can now write an algorithm to create $BWT(T)$ from the suffix array of T . $SA(T)$, by noting that position i of the BWT corresponds to the character that is just to the left of the i th suffix in the original string.

This character is “rotated” around to the back of the BW matrix

BW matrix

**Suffix array with
corresponding suffixes**

Consider the fourth sorted rotation in the BWM and the fourth suffix in the suffix array for $T=abracadabra\$$

abra\$**abracad**

[7] abra\$

The character just to the left of the suffix is the i^{th} character of $BWT(T)$

$T=abracad$ **a** $abra\$$

BWT and Suffix array

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

BW matrix

Suffix array with corresponding suffixes

Consider the fourth sorted rotation in the BWM and
the fourth suffix in the suffix array for $T=\text{abracadabra}\$$

$\text{abra}\$$ abracad [7] $\text{abra}\$$

The character just to the left of the
suffix is the i^{th} character of $\text{BWT}(T)$

$T=\text{abracad}\textcolor{blue}{a}\text{bra}\$$

- We can now construct the BWT as follows

$$\text{BWT}(T) = \begin{cases} T[\text{SA}[i] - 1] & \text{if } \text{SA}[i] > 0 \\ \$ & \text{if } \text{SA}[i] = 0 \end{cases} \quad (1)$$

To see the reason for the second case, consider that the first suffix of the suffix array is always $\$$

BWT and Suffix array

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

T=abracadabra\$

012345678901

$$\text{BWT}(T) = \begin{cases} T[\text{SA}[i] - 1] & \text{if } \text{SA}[i] > 0 \\ \$ & \text{if } \text{SA}[i] = 0 \end{cases} \quad (2)$$

BW matrix

\$abracadabra
a\$abracadabr
abra\$abracad
abracadabra\$
acadabra\$abr
adabra\$abrac
bra\$abracada
bracadabra\$a
cadabra\$abra
dabra\$abraca
ra\$abracadab
racadabra\$ab

Suffix array with corresponding suffixes

[11] \$
[10] a\$
[7] abra\$
[0] abracadabra\$
[3] acadabra\$
[5] adabra\$
[8] bra\$
[1] bracadabra\$
[4] cadabra\$
[6] dabra\$
[9] ra\$
[2] racadabra\$

(Work through example)

Constructing a BWT from a Suffix Array

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

The naive algorithm is pretty simple to implement

Algorithm 1 `bwtFromSuffixArray(T)`

```
1:  $sa = \text{constructSuffixArray}(T\$)$ 
2:  $L = \text{length}(sa)$ 
3:  $bwt = \text{new string}[L]$ 
4: for  $i=0$  to  $i=L-1$  do
5:   if  $sa[i] = 0$  then
6:      $bwt[i] = \$$ 
7:   else
8:      $bwt[i] = T[sa[i] - 1]$ 
9:   end if
10: end for
11: return  $bwt$ 
```

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

If we have used the BWT to compress a string, and now want to get the original string back, we need to

- 1 Reverse the compression procedure (e.g., run-length encoding)
- 2 Get the original string back from the BWT

So, how *do* we reverse the Burrows Wheeler transformation?

The reversibility of the BWT depends on the

LF Mapping property

For any character, the T-ranking of characters in the first column (**F**) is the same as order of characters in the last column (**L**)

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

So, what is the T-ranking?

a₀b₀r₀a₁c₀a₂d₀a₃b₁r₁a₄\$

- The T-ranking of the character at any given position is the number of times that an identical character has preceeded it in T
- The T-ranking of \$ is always zero and is omitted here
- The ranks shown just to help understand the LF mapping property, they are not stored explicitly

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

```
$ a b r a c a d a b r a  
 0 0 0 0 1 0 2 0 3 1 1 4  
a $ a b r a c a d a b r  
 4 0 0 0 1 0 2 0 3 1 1  
a b r a $ a b r a c a d  
 3 1 1 4 0 0 0 0 1 0 2 0  
a b r a c a d a b r a $  
 0 0 0 1 0 2 0 3 1 1 4 0  
a c a d a b r a $ a b r  
 1 0 2 0 3 1 1 4 0 0 0 0  
a d a b r a $ a b r a c  
 2 0 3 1 1 4 0 0 0 0 1 0  
b 1 1 4 $ a b r a c a d  
 1 1 4 0 0 0 1 0 2 0 3  
b r a c a d a b r a $ a  
 0 0 1 0 2 0 3 1 1 4 0 0  
c a d a b r a $ a b r a  
 0 2 0 3 1 1 4 0 0 0 1  
d a b r a $ a b r a c a  
 0 3 1 1 4 0 0 0 1 0 2  
r a $ a b r a c a d a b  
 1 4 0 0 0 0 1 0 2 0 3  
r a c a d a b r a $ a b  
 0 1 0 2 0 3 1 1 4 0 0 0
```

- Here is the Burrows Wheeler matrix with the T-ranks of all the characters.

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

```
$0a0b0r0a1c0a2d0a3b1r1a4
a4$0a0b0r0a1c0a2d0a3b1r1
a3b1r1a4$0a0b0r0a1c0a2d0
a0b0r0a1c0a2d0a3b1r1a4$0
a1c0a2d0a3b1r1a4$0a0b0r0
a2d0a3b1r1a4$0a0b0r0a1c0
b1r1a4$0a0b0r0a1c0a2d0a3
b0r0a1c0a2d0a3b1r1a4$0a0
c0a2d0a3b1r1a4$0a0b0r0a1
d0a3b1r1a4$0a0b0r0a1c0a2
r1a4$0a0b0r0a1c0a2d0a3b1
r0a1c0a2d0a3b1r1a4$0a0b0
```

- What do you notice about the T-ranks of the a characters?

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- The a's have the same relative order in the F and the L columns
- A similar observation pertains to the other characters

```
$0a0b0r0a1c0a2d0a3b1r1a4  
a4$0a0b0r0a1c0a2d0a3b1r1  
a3b1r1a4$0a0b0r0a1c0a2d0  
a0b0r0a1c0a2d0a3b1r1a4$0  
a1c0a2d0a3b1r1a4$0a0b0r0  
a2d0a3b1r1a4$0a0b0r0a1c0  
b1r1a4$0a0b0r0a1c0a2d0a3  
b0r0a1c0a2d0a3b1r1a4$0a0  
c0a2d0a3b1r1a4$0a0b0r0a1  
d0a3b1r1a4$0a0b0r0a1c0a2  
r1a4$0a0b0r0a1c0a2d0a3b1  
r0a1c0a2d0a3b1r1a4$0a0b0
```

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

\$	0	a	0	b	0	r	0	a	1	c	0	a	2	d	0	a	3	b	1	r	1	a	4
a	4	\$	0	a	0	b	0	r	0	a	1	c	0	a	2	d	0	a	3	b	1	r	1
a	3	b	1	r	1	a	4	\$	0	a	0	b	0	r	0	a	1	c	0	a	2	d	0
a	0	b	0	r	0	a	1	c	0	a	2	d	0	a	3	b	1	r	1	a	4	\$	0
a	1	c	0	a	2	d	0	a	3	b	1	r	1	a	4	\$	0	a	0	b	0	r	0
a	2	d	0	a	3	b	1	r	1	a	4	\$	0	a	0	b	0	r	0	a	1	c	0
b	1	r	1	a	4	\$	0	a	0	b	0	r	0	a	1	c	0	a	2	d	0	a	3
b	0	r	0	a	1	c	0	a	2	d	0	a	3	b	1	r	1	a	4	\$	0	a	0
c	0	a	2	d	0	a	3	b	1	r	1	a	4	\$	0	a	0	b	0	r	0	a	1
d	0	a	3	b	1	r	1	a	4	\$	0	a	0	b	0	r	0	a	1	c	0	a	2
r	1	a	4	\$	0	a	0	b	0	r	0	a	1	c	0	a	2	d	0	a	3	b	1
r	0	a	1	c	0	a	2	d	0	a	3	b	1	r	1	a	4	\$	0	a	0	b	0

- The relative T-ranks of the a characters in column **F** are determined by the lexicographic ranks of the strings **to the right** of the characters

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

\$	a	b	r	a	c	a	d	a	b	r	a	
0	0	0	0	1	0	2	0	3	1	1		4
a	\$	a	b	r	a	c	a	d	a	b	r	
4	0	0	0	0	1	0	2	0	3	1	1	
a	b	r	a	\$	a	b	r	a	c	a	d	
3	1	1	4	0	0	0	1	0	2			0
a	b	r	a	c	a	d	a	b	r	a	\$	
0	0	0	1	0	2	0	3	1	1	4	0	
a	c	a	d	a	b	r	a	\$	a	b	r	
1	0	2	0	3	1	1	4	0	0			0
a	d	a	b	r	a	\$	a	b	r	a	c	
2	0	3	1	1	4	0	0	0	1	0		0
b	r	a	\$	a	b	r	a	c	a	d		
1	1	4	0	0	0	1	0	2				3
b	r	a	c	a	d	a	b	r	a	\$		
0	0	1	0	2	0	3	1	1	4	0		0
c	a	d	a	b	r	a	\$	a	b	r		
0	2	0	3	1	1	4	0	0				1
d	a	b	r	a	\$	a	b	r	a	c		
0	3	1	1	4	0	0						2
r	a	\$	a	b	r	a	c	a	d	a	b	
1	4	0	0	0	1	0	2	0	3			1
r	a	c	a	d	a	b	r	a	\$	a	b	
0	1	0	2	0	3	1	1	4	0			0

- The relative T-ranks of the a characters in column L must reflect the lexicographic ranks of the strings to the “rotated” right of the characters

Reversing the BWT


Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa



- These are the same strings (consequence of the rotation!)

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- We introduce another “vertical” ranking
- The B-ranking of a character at a specific position is the number of that times the same character has occurred in the F column “above” the current position
- The B-ranking is thus like a cumulative count of the characters

```
$0abracadabra0  
a0$abracadabr0  
a1bra$abracad0  
a2bracadabra$0  
a3cadabra$abr1  
a4dabra$abrac0  
b0ra$abracada1  
b1racadabra$a2  
c0adabra$abra3  
d0abra$abraca4  
r0a$abracadab0  
r1acadabra$ab1
```

Just the F and L columns are shown for better

legibility

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Column **F** has a simple structure: Chunks of identical characters with ascending B-ranks
- Column **L** does not generally have this kind of strict chunk structure, but the B-ranks of any given character also are arranged in ascending order

F **L**

\$₀abracadabra₀
a₀\$abracadabr₀
a₁bra\$abracad₀
a₂bracadabra\$₀
a₃cadabra\$abr₁
a₄dabra\$abrac₀
b₀ra\$abracada₁
b₁racadabra\$a₂
c₀adabra\$abra₃
d₀abra\$abraca₄
r₀a\$abracadab₀
r₁acadabra\$ab₁

Ascending B-ranks

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Can we now use these observations to reconstruct the original string?
- We will first try to reconstruct the first column of the BWM

Ascending B-ranks

F		L
?	a ₀	
?	r ₀	
?	d ₀	
?	\$ ₀	
?	r ₁	
?	c ₀	
?	a ₁	
?	a ₂	
?	a ₃	
?	a ₄	
?	b ₀	
?	b ₁	

Reversing the BWT

Read
Mapping (4)


Peter N.
Robinson

BW
Transform

FM Index

bwa

- Consider c_0 .
- We know that the \$, all the a's, all the b's, but not any of the d's must precede c_0 in the first column



Reversing the BWT

Read
Mapping (4)


Peter N.
Robinson

BW
Transform

FM Index

bwa

- The index of c_0 in column **F** must equal $1+5+2=8$
- We will refer to this as the **cumulative index property**



Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- We will reconstruct the string from **right to left**
- We know the last character is \$, so we initialize our reconstructed string accordingly

F

$\$ _0$
 $a _0$
 $a _1$
 $a _2$
 $a _3$
 $a _4$
 $b _0$
 $b _1$
 $c _1$
 $d _0$
 $r _0$
 $r _1$

L

$a _0$
 $r _0$
 $d _0$
 $\$ _0$
 $r _1$
 $c _0$
 $a _1$
 $a _2$
 $a _3$
 $a _4$
 $b _0$
 $b _1$

Reconstruction to date

T=... \$

Reversing the BWT

Read Mapping (4)



Peter N.
Robinson

BW
Transform

FM Index

bwa

- Because of the **cumulative index property** and because a come right after \$, we go to the second row of the BWM and find a_0 .
- The character that precedes it in T is now in the last column (L)

F		L
\$ ₀		a_0
a_0		r_0
a_1		d_0
a_2		$\$0$
a_3		r_1
a_4		c_0
b_0		a_1
b_1		a_2
c_1		a_3
d_0		a_4
r_0		b_0
r_1		b_1

Reconstruction to date

T = ... $r_0 a_0 \$$

Reversing the BWT

Read Mapping (4)


Peter N.
Robinson

BW
Transform

FM Index

bwa

- To find the position of r_0 in the first column, we note that its index must be $1+5+2+1+1=10$ because of the **cumulative index property**
- We go to column **L** to get the next preceding character



Reconstruction to date

$T = \dots b_0 r_0 a_0 \$$

Reversing the BWT

Read Mapping (4)


Peter N.
Robinson

BW
Transform

FM Index

bwa

- The game continues...
- To find the position of b_0 in the first column, we note that its index must be $1+5=6$ because of the **cumulative index property**
- We go to column **L** to get the next preceding character



Reconstruction to date

$T = \dots a_1 b_0 r_0 a_0 \$$

Reversing the BWT

Read Mapping (4)


Peter N.
Robinson

BW
Transform

FM Index

bwa

- Note that to find the position of a_4 with the **cumulative index property** we take into account of the indexes of the preceding characters (i.e., \$), as well as that of a_0, a_1, a_2, a_3 , so that our index is $1+4=5$
- and so on...



Reconstruction to date

$T = \dots a_4 d_0 a_1 b_0 r_0 a_0 \$$

Reversing the BWT

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

But what information exactly did we need to do this reversal?

- We can do everything starting **only** from the BWT(T)
- If we count the number of each character in BWT(T)¹, we can easily reconstruct the “chunks” of characters in the first column of the BWM

¹ Or we can store it in an array of size $\mathcal{O}(|\Sigma|)$ for characters in some alphabet Σ .

Outline

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

1 Burrows Wheeler Transform

2 FM Index

3 Burrows Wheeler Aligner – bwa

FM Index

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

The FM index uses the BWT and some other auxiliary data structures to generate a fast and efficient index for search for patterns within a larger string T

Paolo Ferragina and Giovanni Manzini (2000) Opportunistic Data Structures with Applications. *Proceedings of the 41st Annual Symposium on Foundations of Computer Science*. p.390.

FM Index

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- The main data structures of the FM index are **F** and **L** from the BWM
- Note that **F** can be represented as an array of ints (one per character of our alphabet)
- In our example, and using the order $\$ < a < b < c < d < r$ we have

1	5	2	1	1	2
---	---	---	---	---	---
- As mentioned, **L** is also easily compressible

F **L**

$\$$ ₀abracadabraa₀
a₀\$abracadabr₀
a₁bra\$abracad₀
a₂bracadabra\$₀
a₃cadabra\$abr₁
a₄dabra\$abrac₀
b₀ra\$abracada₁
b₁racadabra\$a₂
c₀adabra\$abra₃
d₀abra\$abraca₄
r₀a\$abracadab₀
r₁acadabra\$ab₁

FM Index

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- But how can we search?
- As mentioned, the BWM is very similar to a suffix array, but a binary search over just **F** and **L** is obviously not possible (the “middle” of the matrix is missing)
- We will again make use of the B-ranks

F		L
\$	₀	abracadabra
a	₀	\$abracadabr
a	₁	bra\$abracad
a	₂	bracadabra\$
a	₃	cadabra\$abr
a	₄	dabra\$abrac
b	₀	ra\$abracada
b	₁	racadabra\$a
c	₀	adabra\$abra
d	₀	abra\$abraca
r	₀	a\$abracadab
r	₁	acadabra\$ab

FM Index

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- For example, let us search for the string $P=abra$ in our “genome” $T=abracadabra$
- Our strategy is to look for all rows of $BWM(T)$ that have P as a prefix
- We successively look for the longer P suffixes, starting with the last character of P
- But it is easy to find the chunk of the $BWM(T)$ that starts with a given character using the **cumulative index property**

Search string **abra**

F **L**

\$ ₀	a	b	r	a	c	a	d	a	b	r	a	\$ ₀
a ₀	\$	a	b	r	a	c	a	d	a	b	r	\$ ₀
a ₁	b	r	a	\$	a	b	r	a	c	a	d	\$ ₀
a ₂	b	r	a	c	a	d	a	b	r	a	\$	\$ ₀
a ₃	c	a	d	a	b	r	a	\$	a	b	r	\$ ₁
a ₄	d	a	b	r	a	\$	a	b	r	a	c	\$ ₀
b ₀	r	a	\$	a	b	r	a	c	a	d	a	\$ ₁
b ₁	r	a	c	a	d	a	b	r	a	\$	a	\$ ₂
c ₀	a	d	a	b	r	a	\$	a	b	r	a	\$ ₃
d ₀	a	b	r	a	\$	a	b	r	a	c	a	\$ ₄
r ₀	a	\$	a	b	r	a	c	a	d	a	b	\$ ₀
r ₁	a	c	a	d	a	b	r	a	\$	a	b	\$ ₁

FM Index

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Once we have found all rows that begin with the last letter of P, we can look in **L** to identify those rows whose next to last letter also corresponds to P
- We can also read off the B-ranks of these characters and use the LF mapping to find the rows in **F** that begin with these characters

Search string **abra**

F **L**

\$ ₀	abracadabra	a ₀
a ₀	\$abracadabr	r ₀
a ₁	bra\$abracad	d ₀
a ₂	bracadabra\$	\$ ₀
a ₃	cadabra\$abr	r ₁
a ₄	dabra\$abrac	c ₀
b ₀	ra\$abracada	a ₁
b ₁	racadabra\$a	a ₂
c ₀	adabra\$abra	a ₃
d ₀	abra\$abraca	a ₄
r ₀	a\$abracadab	b ₀
r ₁	acadabra\$ab	b ₁

FM Index

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Using the LF mapping we find the rows in **F** that begin with ra (r_0 and r_1)
- The character that precedes “r” in our query string P is “b”, so we can continue
- We have now matched the last 3 characters of $P=abra$ and continue one more step using the LF mapping

Search string **abra**

F **L**

\$ ₀	abracadabra	a ₀
a ₀	\$abracadabr	r ₀
a ₁	bra\$abracad	d ₀
a ₂	bracadabra\$	o ₀
a ₃	cadabra\$abr	r ₁
a ₄	dabra\$abrac	c ₀
b ₀	ra\$abracada	a ₁
b ₁	racadabra\$a	a ₂
c ₀	adabra\$abra	a ₃
d ₀	abra\$abraca	a ₄
r ₀	a\$abracadab	b ₀
r ₁	acadabra\$ab	b ₁

FM Index

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- We find the rows that begin with bra (b_0 and b_1) and look at the corresponding characters in **L** to see if we have a match for P

Search string **abra**

F **L**

\$ ₀	abracadabra	a ₀
a ₀	\$abracadabr	r ₀
a ₁	bra\$abracad	d ₀
a ₂	bracadabra\$	\$ ₀
a ₃	cadabra\$abr	r ₁
a ₄	dabra\$abrac	c ₀
b ₀	ra\$abracada	a ₁
b ₁	racadabra\$a	a ₂
c ₀	adabra\$abra	a ₃
d ₀	abra\$abraca	a ₄
r ₀	a\$abracadab	b ₀
r ₁	acadabra\$ab	b ₁

FM Index

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Finally, we find the rows of the BWM that begin with our query string: [2, 4)
- These are equivalent to the rows we would have identified with a binary search over the suffix array (which is of course an array of start positions of suffixes)
- However, it is not immediately clear how to identify the positions in T that correspond to P using the FM index.

Search string **abra**

F **L**

\$ ₀	abracadabra	₀
a ₀	\$abracadabr	₀
a ₁	bra\$abracad	₀
a ₂	bracadabra\$	₀
a ₃	cadabra\$abr	₁
a ₄	dabra\$abrac	₀
b ₀	ra\$abracada	₁
b ₁	racadabra\$a	₂
c ₀	adabra\$abra	₃
d ₀	abra\$abraca	₄
r ₀	a\$abracadab	₀
r ₁	acadabra\$ab	₁

FM Index

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- What about the search pattern $P=adaa$?
- We match the last character as previously
- But: when we now look at the corresponding rows of **L**, there is no “a”
- Ergo, the search pattern does not occur in T.

Search string **adaa**

F **L**

\$ ₀	abracadabra ₀
a ₀	\$abracadabr ₀
a ₁	bra\$abracad ₀
a ₂	bracadabra\$ ₀
a ₃	cadabra\$abr ₁
a ₄	dabra\$abrac ₀
b ₀	ra\$abracada ₁
b ₁	racadabra\$a ₂
c ₀	adabra\$abra ₃
d ₀	abra\$abraca ₄
r ₀	a\$abracadab ₀
r ₁	acadabra\$ab ₁

FM Index- Interim Report

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

We have presented a somewhat naive version of the FM index search. However, we have glossed over three issues that need to be solved to produce an efficient and practical algorithm

FM Index- Interim Report

Read
Mapping (4)

Peter N.
Robinson


BW
Transform

FM Index

bwa

Issue #1

- How do we efficiently find the preceding character (i.e., starting from a chunk of prefixes in or starting in **F**, how do we find the correct characters in **L** to continue leftwards)?
- In the worst case, we may have to scan down as far as the length of the entire input string, $\mathcal{O}(|T|)$



FM Index- Interim Report

Read Mapping (4)

**Peter N.
Robinson**

BW
Transform

FM Index

bwa

Issue #2

- Recall that we did not want to **explicitly** store the B-ranks of the characters – this would be at least 4 bytes per input character, and whatever advantage we had with respect to the suffix array would disappear
- So, we still need a way of getting the B-rank of the characters in **L**

F **L**

\$₀abracadabra₀
a₀\$abracadabr₀
a₁bra\$abracad₀
a₂bracadabra\$₀
a₃cadabra\$abr₁
a₄dabra\$abrac₀
b₀ra\$abracada₁
b₁racadabra\$a₂
c₀adabra\$abra₃
d₀abra\$abraca₄
r₀a\$abracadab₀
r₁acadabra\$ab₁

FM Index- Interim Report

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Issue #3

- Recall that with the suffix array, we explicitly stored the start position of each suffix of T
- We do not have this information with the BWM
- So, we still need a way of figuring out where matches occur in T

0: MISSISSIPPI\$		11: \$
1: ISSISSIPPI\$		10: I\$
2: SSISSIPPI\$		7: IPPI\$
3: SSISSIPPI\$		4: ISS IPPI\$
4: ISSIPPI\$		1: ISS ISSIPPI\$
5: SSIPPI\$	sort →	0: MISSISSIPPI\$
6: SIPPI\$		9: PI\$
7: IPPI\$		8: PPI\$
8: PPI\$		6: SIPPI\$
9: PI\$		3: SSISSIPPI\$
10: I\$		5: SSIPPI\$
11: \$		2: SSISSIPPI\$

FM Index- Tally Table

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Issue #1: efficiently find
the preceding character

- Keep a tally table
- Precalculate the number of each specific character in L up to every row

FL

$\$_0 a_0$

$a_0 r_0$

$a_1 d_0$

$a_2 \$_0$

$a_3 r_1$

$a_4 c_0$

$b_0 a_1$

$b_1 a_2$

$c_0 a_3$

$d_0 a_4$

$r_0 b_0$

$r_1 b_1$

a	b	c	d	r
1	0	0	0	0
1	0	0	0	1
1	0	0	1	1
1	0	0	1	1
1	0	0	1	2
1	0	1	1	2
2	0	1	1	2
3	0	1	1	2
4	0	1	1	2
5	0	1	1	2
5	1	1	1	2
5	2	1	1	2

Tally table

FM Index- Tally Table

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Say we are search for $P=abra$
- After we have found all rows beginning with a in the first step, we need to find rows with r in the last column
- Say the range of rows is $[i, j]$
- We look in the tally table in row $i - 1$. No occurrences of r to date!
- Now look in the tally table row j . Two occurrences of r to date!
- Therefore, we know that (only) r_0 and r_1 occur in L in the range $[i, j]$

FL

$\$_0 a_0$

$a_0 r_0$

$a_1 d_0$

$a_2 \$_0$

$a_3 r_1$

$a_4 c_0$

$b_0 a_1$

$b_1 a_2$

$c_0 a_3$

$d_0 a_4$

$r_0 b_0$

$r_1 b_1$

a	b	c	d	r
1	0	0	0	0
1	0	0	0	1
1	0	0	1	1
1	0	0	1	2
1	0	1	1	2
2	0	1	1	2
3	0	1	1	2
4	0	1	1	2
5	0	1	1	2
5	1	1	1	2
5	2	1	1	2

← 0 r's

← 2 r's

Tally table

FM Index- Tally Table

Read Mapping (4)

Peter N. Robinson

BW
Transform

FM Index

bwa

- A problem with this idea is that we need to store $\mathcal{O}(|T| \cdot |\Sigma|)$ integers
- What if we store only every k^{th} row?
- We reduce the size of the tally table by a factor of k , but at the price of not having all of the information we need immediately available

FL

$\$ _0 a _0$

$a _0 r _0$

$a _1 d _0$

$a _2 \$ _0$

$a _3 r _1$

$a _4 c _0$

$b _0 a _1$

$b _1 a _2$

$c _0 a _3$

$d _0 a _4$

$r _0 b _0$

$r _1 b _1$

a	b	c	d	r
1	0	0	0	0
1	0	0	1	1
2	0	1	1	2
5	0	1	1	2

← 0r's

← ???

Tally table

FM Index- Tally Table

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- For instance, to calculate the rank of the a near the $\leftarrow ???$
- We can go to the previous checkpoint and count the number of a's that we encounter from there to the position we are interested in: $113 + 1 = 114$
- Or: We can go to the next checkpoint and subtract the number of a's that we encounter along the way: $115 - 1 = 114$
- In general, we will subtract one from the tally to obtain the zero-based B-rank

L	A	C	
	113	42	→ 113 a's
			→ ???
	115	47	→ 115 a's

Tally table

FM Index- Tally Table

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Assuming we space the check point rows a constant number of rows away from one another: $\mathcal{O}(1)$, for instance, 50 rows, then lookups are still $\mathcal{O}(1)$ rather than $\mathcal{O}(|T|)$
- We now also have a way of getting the B-ranks we need for issue # 2 (Still $\mathcal{O}(|T|)$ space, but with a smaller constant).

L

	A	C	
A	113	42	→ 113 a's
C			
C			
G			
A			
C			
C			→ ???
T			
A			
C	115	47	→ 115 a's
T			
T			
A			
A			
T			
T			
A			

Tally table

FM Index- Finding indices in T

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

F	L	
\$ ₀	abracadabra ₀	[11] \$
a ₀	\$abracadabr ₀	[10] a\$
a ₁	bra\$abracad ₀	[7] abra\$
a ₂	bracadabra\$ ₀	[0] abracadabra\$
a ₃	cadabra\$abr ₁	[3] acadabra\$
a ₄	dabra\$abrac ₀	[5] adabra\$
b ₀	ra\$abracada ₁	[8] bra\$
b ₁	racadabra\$a ₂	[1] bracadabra\$
c ₀	adabra\$abra ₃	[4] cadabra\$
d ₀	abra\$abraca ₄	[6] dabra\$
r ₀	a\$abracadab ₀	[9] ra\$
r ₁	acadabra\$ab ₁	[2] racadabra\$

- Issue #3 referred to the desire to have information as in the suffix array that would allow us to find the position of matches in the original string
- Recall the suffix array stores the indices of suffixes that are equivalent to the strings of the BWM

FM Index- Finding indices in T

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

F	L	
\$ ₀ abracadabra ₀	[11]	\$
a ₀ \$abracadabr ₀	[10]	a\$
a ₁ bra\$abracad ₀	[7]	abra\$
a ₂ bra\$acadabra\$ ₀	[0]	abracadabra\$
a ₃ cadabra\$abr ₁	[3]	acadabra\$
a ₄ dabra\$abrac ₀	[5]	adabra\$
b ₀ ra\$abracada ₁	[8]	bra\$
b ₁ racadabra\$a ₂	[1]	bracadabra\$
c ₀ adabra\$abra ₃	[4]	cadabra\$
d ₀ abra\$abraca ₄	[6]	dabra\$
r ₀ a\$abracadab ₀	[9]	ra\$
r ₁ acadabra\$ab ₁	[2]	racadabra\$

abracadabra\$

abra Pos. 0

abra Pos. 7

- For instance, if we had just used the algorithm described above to find two occurrences of the pattern abra then we could look up the start positions 0 and 7 if we also had the suffix array

FM Index- Finding indices in T

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

F	L	
\$ ₀	abracadabra ₀	[11] \$
a ₀	\$abracadabr ₀	[10] a\$
a ₁	bra\$abracad ₀	[7] abra\$
a ₂	bracadabra\$ ₀	[0] abracadabra\$
a ₃	cadabra\$abr ₁	[3] acadabra\$
a ₄	dabra\$abrac ₀	[5] adabra\$
b ₀	ra\$abracada ₁	[8] bra\$
b ₁	racadabra\$a ₂	[1] bracadabra\$
c ₀	adabra\$abra ₃	[4] cadabra\$
d ₀	abra\$abraca ₄	[6] dabra\$
r ₀	a\$abracadab ₀	[9] ra\$
r ₁	acadabra\$ab ₁	[2] racadabra\$

- But, if we stored the entire suffix array, this would incur roughly an additional $4 \times |T|$ bytes of storage
- We can use the same checkpoint idea
- Don't store all of the values of the suffix array, just store every k^{th} value
- Importantly, we store every k^{th} value for the original string T, not every k^{th} value in the original suffix array – this ensures constant time.

FM Index- Finding indices in T

Read

Mapping (4)

Peter N.
Robinson

BW

Transform

FM Index

bwa

F	L		
\$ ₀	abracadabra ₀	[11]	\$
a ₀	\$abracadabr ₀	[10]	a\$
a ₁	bra\$abracad ₀	? [7]	abra\$
a ₂	bra\$acadabra\$ ₀	[0]	abracadabra\$
a ₃	cadabra\$abr ₁	[3]	acadabra\$
a ₄	dabra\$abrac ₀	[5]	adabra\$
b ₀	ra\$abracada ₁	[8]	bra\$
b ₁	racadabra\$a ₂	[1]	bracadabra\$
c ₀	adabra\$abra ₃	[4]	cadabra\$
d ₀	abra\$abraca ₄	[6]	dabra\$
r ₀	a\$abracadab ₀	[9]	ra\$
r ₁	acadabra\$ab ₁	[2]	racadabra\$

- So, let's again search for the pattern P=abra
- We find one hit and our "selective suffix array" indicates the index to be at position 0
- What do we do about the other hit?

FM Index- Finding indices in T

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

F	L	
\$ ₀	abracadabra ₀	[11] \$
a ₀	\$abracadabr ₀	[10] a\$
a ₁	bra\$abracad ₀	? [7] abra\$
a ₂	\$bracadabra\$ ₀	[0] abracadabra\$
a ₃	cadabra\$abr ₁	[3] acadabra\$
a ₄	dabra\$abrac ₀	[5] adabra\$
b ₀	ra\$abracada ₁	[8] bra\$
b ₁	racadabra\$a ₂	[1] bracadabra\$
c ₀	adabra\$abra ₃	[4] cadabra\$
d ₀	bra\$abraca ₄	[6] dabra\$
r ₀	a\$abracadab ₀	[9] ra\$
r ₁	acadabra\$ab ₁	[2] racadabra\$

- Let us take advantage of the LF mapping
- This tells us where to find the d_0 in the first column **F**
- We can look this up in our selective suffix array – but note that we have moved one position to the left – the position of dabra is 6, but the position of abra is 7!

FM Index- Finding indices in T

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

F	L	
\$ ₀	abracadabra ₀	[11] \$
a ₀	\$abracadabr ₀	[10] a\$
a ₁	bra\$abracad ₀	? [7] abra\$
a ₂	bracadabra\$ ₀	[0] abracadabra\$
a ₃	cadabra\$abr ₁	[3] acadabra\$
a ₄	dabra\$abrac ₀	[5] adabra\$
b ₀	ra\$abracada ₁	[8] bra\$
b ₁	racadabra\$a ₂	[1] bracadabra\$
c ₀	cadabra\$abra ₃	[4] cadabra\$
d ₀	bra\$abraca ₄	[6] dabra\$
r ₀	a\$abracadab ₀	[9] ra\$
r ₁	acadabra\$ab ₁	[2] racadabra\$

- Note that the fact that we are storing every k^{th} value for the original string T, ensures that we need to perform at most $k - 1$ “hops” to retrieve the index we are looking for
- However, we are still keeping $\mathcal{O}(|T|)$ elements in the selective suffix array

FM Index- Memory footprint

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

The FM index has a substantially smaller memory footprint than does the suffix tree (at least 60 GB) or the suffix array (at least 12 GB)

Component	Complexity	Size (Human Genome)
F	$\mathcal{O}(\Sigma)$	16 bytes (4 ints)
L	$ T $ chars	2 bits $\times 3 \times 10^9 \approx 750$ MB
selective SA	$\sim \frac{1}{k} T $ integers	400 MB with $k = 32$
checkpoints	$\sim \frac{1}{x} T \cdot \Sigma $ integers	100 MB with $x = 128$

- Total size for FM index of human genome thus about 1.5 GB

Notes: (i) We store the 4 nucleotides with 2 bits each, i.e., 4 nucleotides per byte. (ii) k and x are the lengths of the skips

Outline

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

1 Burrows Wheeler Transform

2 FM Index

3 Burrows Wheeler Aligner – bwa

BWT/FM Index algorithms for read mapping

Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

There are lots of published aligners for genomic resequencing. Perhaps the best known amongst them use the BWT/FM Index plus lots of **Bells and Whistles**.

- **bwa**: Li H, Durbin R (2009) Fast and accurate short read alignment with Burrows-Wheeler transform. *Bioinformatics* **25**:1754-60.
- **bowtie**: Langmead B, Trapnell C, Pop M, Salzberg SL (2009) Ultrafast and memory-efficient alignment of short DNA sequences to the human genome. *Genome Biol* **10**:R25.
- **SOAP2**: Li R et al (2009) SOAP2: an improved ultrafast tool for short read alignment. *Bioinformatics*. **25**:1966-7.
- ...

The nomenclature and descriptions used in the bwa paper are different in a few ways to those used in this lecture.

- Here I will present some of the aspects of the paper
- Exact matching is performed roughly as described
- A major issue that needs to be solved by any practical read mapper is **inexact matching**
- We will introduce the topic of inexact matching with the brute force approach that is mentioned (and rejected) in the introduction to the bwa paper

bwa: GOOGOL


Read Mapping (4)

Peter N.
Robinson

BW
Transform
FM Index
bwa

The prefix trie for string X is a tree where each edge is labeled with a symbol and the string concatenation of the edge symbols on the path from a leaf to the root gives a unique prefix of X.


On the prefix trie, the string concatenation of the edge symbols from a node to the root gives a unique substring of X, called the string represented by the node.



bwa: GOOGOL

Note that the prefix trie of T is **identical to the suffix trie of the reverse of T**

With the prefix trie, testing whether a query W is an exact substring of T is equivalent to finding the node that represents W , which can be done in $\mathcal{O}(|W|)$ time by matching each symbol in W to an edge, starting from the root.



bwa: GOOGOL

Read
Mapping (4)

Peter N.
Robinson

BW
Transform


FM Index

bwa

Consider the suffix array and the prefix trie of GOOGOL

0	6	\$googo l
1	3	gol\$go o
2	0	googol \$
3	5	l\$goog o
4	2	ogol\$g o
5	4	ol\$goo g
6	1	oogol\$ g

Symbol \wedge marks the start of the string. The two numbers in a node give the SA interval of the string represented by the node



bwa: GOOGOL

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

bwa uses the following notation for “**suffix array interval**”

- All occurrences of substrings with a common suffix W appear next to each other in the suffix array, defining the SA interval

$$[\underline{R}(W), \overline{R}(W)]$$

- For instance, the SA interval of “go” is $[1, 2]$ and the suffix array interval of “o” is $[4, 6]$

0	6	\$googo l
1	3	gol\$go o
2	0	googol \$
3	5	l\$goog o
4	2	ogol\$g o
5	4	ol\$goo g
6	1	oogol\$ g

Read Mapping (4)

BW Transform

bwa

The dashed line shows the route of the brute-force search for a query string **LOL**, allowing at most one mismatch. Edge labels in squares mark the mismatches to the query in searching. The only hit is the bold node **[1, 1]** which represents string **GOL**.



bwa: GOOGOL

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

bwa uses the following notation for “**suffix array interval**”

The bwa paper presents our method of calculating the SA interval of the query W using a slightly different notation

- Can be done iteratively from the end of W

$$\begin{aligned}\underline{R}(aW) &= C(a) + \text{Occ}(a, \underline{R}(W) - 1) + 1 \\ \overline{R}(aW) &= C(a) + \text{Occ}(a, \underline{R}(W))\end{aligned}$$

where

- $C(a)$ = Number of symbols in $X[0, n - 2]$ that are lexicographically smaller than a
- $\text{Occ}(a, i)$ = Number of occurrences of a in $BWT[0, i]$

0	6	\$googo l
1	3	gol\$go o
2	0	googol \$
3	5	l\$goog o
4	2	ogol\$g o
5	4	ol\$goo g
6	1	oogol\$ g

bwa: Inexact matching, precalculations (1)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Let us follow along the example in the bwa paper (Figure 1 and Figure 3). We have

- Reference string $X = \text{'GOOGOL\$'}$
- Query string $W = \text{'LOL'}$
- The precalculations require us to calculate the $\text{BWT}(X)$. For convenience, we show the sorted BWM
 - 0: \$GOOGOL
 - 1: GOL\$G00
 - 2: GOOGOL\$
 - 3: L\$GOOGO
 - 4: OGOL\$GO
 - 5: OL\$GOOG
 - 6: OOGOL\$G
- The $\text{BWT}(X) = \text{'LO$OOGG'}$

bwa: Inexact matching, precalculations (2)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- We now calculate $C(a)$ for $X = \text{'GOOGOL\$'}$, defined in the paper as the number of symbols in $X[0, n2]$ that are lexicographically smaller than $a \in \Sigma$
- Let us assume $\Sigma = \{G, L, O\}$
- The vector \mathbf{C} is then

a	$C(a)$
G	0
L	2
O	5

bwa: Inexact matching, precalculations (3)

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- We now calculate $O(a, i)$ the number of occurrences of a in $B[0, i]$, where B is the BWT of X

i	a	$O(G, i)$	$O(L, i)$	$O(O, i)$
0	G	1	0	0
1	O	1	0	1
2	O	1	0	2
3	G	2	0	2
4	O	2	0	3
5	L	2	1	3

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

The overall algorithm looks like this

Algorithm 2 InexactSearch(W, z)

- 1: CalculateD(W)
 - 2: **return** InexRecur($W, |W| - 1, z, 1, |X| - 1$)
-

- InexRecur(W, i, z, k, l) returns the SA intervals of substrings in X that match W with no more than z differences
 - W : query
 - i : Search for matches to $W[0..i]$
 - z max number of mismatches
 - k, l : On the condition that the suffix W_{i+1} matches interval $[k..l]$

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Let us examine the `CalculateD(W)` algorithm

Algorithm 3 `CalculateD(W)`

```
1:  $z \leftarrow 0$ 
2:  $j \leftarrow 0$ 
3: for  $i = 0$  to  $|W| - 1$  do
4:   if  $W[j..i]$  is not a substring of  $X$  then
5:      $z \leftarrow z + 1$ 
6:      $j \leftarrow i + 1$ 
7:   end if
8:    $D(i) \leftarrow z$ 
9: end for
10: return  $D$ 
```

$D(i)$ is the **lower bound** of the number of differences in $W[0..i]$ to the best match in X

bwa: Inexact matching


Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa



- Consider that we can implement a search for inexact matches as a depth-first search (as shown here) or as a breadth first search (which is actually what bwa does)
- We can bound the DFS if we know that it does not make any sense to continue the search. $\text{CalculatedD}(W)$ is a heuristic that allows us to **stop** the DFS **early**

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform
FM Index
bwa

Algorithm 4 CalculateD(W)

```
1:  $z \leftarrow 0$ 
2:  $j \leftarrow 0$ 
3: for  $i = 0$  to  $|W| - 1$  do
4:   if  $W[j..i]$  is not a substring of  $X$  then
5:      $z \leftarrow z + 1$ 
6:      $j \leftarrow i + 1$ 
7:   end if
8:    $D(i) \leftarrow z$ 
9: end for
10: return  $D$ 
```

- For $X = \text{'GOOGOL\$'}$ and $W = \text{'LOL'}$, the for loop goes from 0..2
- we obtain $D(0)=0$, $D(1)=1$, $D(2)=1$

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Algorithm 5 InexRecur(W, i, z, k, ℓ)

```
1: if  $z < D(i)$  then
2:   return  $\emptyset$ 
3: end if
4: if  $i < 0$  then
5:   return  $\{k, \ell\}$  //i.e., an SA interval
6: end if
7:  $I \leftarrow \emptyset$ 
8: for each  $b \in \{a, c, g, t\}$  do
9:    $k \leftarrow C(b) + O(b, k - 1) + 1$ 
10:   $\ell \leftarrow C(b) + O(b, \ell) + 1$ 
11:  if  $k \leq \ell$  then
12:    if  $b = W[i]$  then
13:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z, k, \ell)$  //match
14:    else
15:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z - 1, k, \ell)$  //mismatch, decrement z
16:    end if
17:  end if
18: end for
19: return  $D$ 
```

Lines 1-3

- If the lower bound on the number of differences in $W[0..i]$ is already more than the maximum number of mismatches z , give up
- return null

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Algorithm 6 InexRecur(W, i, z, k, ℓ)

```
1: if  $z < D(i)$  then
2:   return  $\emptyset$ 
3: end if
4: if  $i < 0$  then
5:   return  $\{k, \ell\}$  //i.e., an SA interval
6: end if
7:  $I \leftarrow \emptyset$ 
8: for each  $b \in \{a, c, g, t\}$  do
9:    $k \leftarrow C(b) + O(b, k - 1) + 1$ 
10:   $\ell \leftarrow C(b) + O(b, \ell) + 1$ 
11:  if  $k \leq \ell$  then
12:    if  $b = W[i]$  then
13:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z, k, \ell)$  //match
14:    else
15:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z - 1, k, \ell)$  //mismatch, decrement z
16:    end if
17:  end if
18: end for
19: return  $D$ 
```

Lines 4-5

- If $i < 0$ then we are arriving from a recursive call where we have finished matching W (potentially including up to z mismatches)
- We return the SA interval $\{k, \ell\}$ representing the hits

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Algorithm 7 InexRecur(W, i, z, k, ℓ)

```
1: if  $z < D(i)$  then
2:   return  $\emptyset$ 
3: end if
4: if  $i < 0$  then
5:   return  $\{k, \ell\}$  //i.e., an SA interval
6: end if
7:  $I \leftarrow \emptyset$ 
8: for each  $b \in \{a, c, g, t\}$  do
9:    $k \leftarrow C(b) + O(b, k - 1) + 1$ 
10:   $\ell \leftarrow C(b) + O(b, \ell) + 1$ 
11:  if  $k \leq \ell$  then
12:    if  $b = W[i]$  then
13:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z, k, \ell)$  //match
14:    else
15:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z - 1, k, \ell)$  //mismatch, decrement z
16:    end if
17:  end if
18: end for
19: return  $I$ 
```

Line 7

- Initialize the **current interval** to the empty set for this recursion

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Algorithm 8 InexRecur(W, i, z, k, ℓ)

```
1: if  $z < D(i)$  then
2:   return  $\emptyset$ 
3: end if
4: if  $i < 0$  then
5:   return  $\{k, \ell\}$  //i.e., an SA interval
6: end if
7:  $I \leftarrow \emptyset$ 
8: for each  $b \in \{a, c, g, t\}$  do
9:    $k \leftarrow C(b) + O(b, k - 1) + 1$ 
10:   $\ell \leftarrow C(b) + O(b, \ell) + 1$ 
11:  if  $k \leq \ell$  then
12:    if  $b = W[i]$  then
13:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z, k, \ell)$  //match
14:    else
15:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z - 1, k, \ell)$  //mismatch, decrement z
16:    end if
17:  end if
18: end for
19: return  $D$ 
```

Line 8

- loop over all nucleotides, looking for a match...

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Algorithm 9 InexRecur(W, i, z, k, ℓ)

```
1: if  $z < D(i)$  then
2:   return  $\emptyset$ 
3: end if
4: if  $i < 0$  then
5:   return  $\{k, \ell\}$     //i.e., an SA interval
6: end if
7:  $I \leftarrow \emptyset$ 
8: for each  $b \in \{a, c, g, t\}$  do
9:    $k \leftarrow C(b) + O(b, k - 1) + 1$ 
10:   $\ell \leftarrow C(b) + O(b, \ell) + 1$ 
11:  if  $k \leq \ell$  then
12:    if  $b = W[i]$  then
13:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z, k, \ell)$     //match
14:    else
15:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z - 1, k, \ell)$     //mismatch, decrement z
16:    end if
17:  end if
18: end for
19: return  $I$ 
```

Lines 9–11

- Figure out the interval in **F** where the current character **b** would be
- check whether this interval is empty

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Algorithm 10 InexRecur(W, i, z, k, ℓ)

```
1: if  $z < D(i)$  then
2:   return  $\emptyset$ 
3: end if
4: if  $i < 0$  then
5:   return  $\{k, \ell\}$     //i.e., an SA interval
6: end if
7:  $I \leftarrow \emptyset$ 
8: for each  $b \in \{a, c, g, t\}$  do
9:    $k \leftarrow C(b) + O(b, k - 1) + 1$ 
10:   $\ell \leftarrow C(b) + O(b, \ell) + 1$ 
11:  if  $k \leq \ell$  then
12:    if  $b = W[i]$  then
13:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z, k, \ell)$     //match
14:    else
15:       $I \leftarrow I \cup \text{InexRecur}(W, i - 1, z - 1, k, \ell)$     //mismatch, decrement z
16:    end if
17:  end if
18: end for
19: return  $I$ 
```

Lines 12–15

- If we have a match, keep going and decrement i
- If we have a mismatch, then also decrement z and keep going

bwa: Inexact matching

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

Consider now the role of the D matrix in the DFS shown in the figure

- The initial call to $\text{InexRecur}(W, i - 1, z - 1, k, \ell)$ (with $W=\text{LOL}$ and $X=\text{GOOGOL\$}$ and maximally one mismatch allowed) is
- $\text{InexRecur}(W, |W| - 1, z, 1, |X| - 1)$ i.e., $\text{InexRecur}(W, 2, 1, 1, 6)$
- The DFS first passes by lines 1–7 from the root node and chooses the character 'G'
- G does not match the first character of 'LOL', so there is a mismatch, and we recursively call InexRecur
- The recursive call looks like this $\text{InexRecur}(W, 1, 0, 1, 6)$
- When we get to line 1, $i = 1$ and $z = 0$. Recalling that we calculated $D(1) = 1$, we have that $z < D(i)$, and we return without having examined the subtree emanating from 'G'
- similarly, we avoid descending into the 'O' subtree

bwa: Inexact matching


Read Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa



- Therefore, our use of the D matrix allowed use to avoid continuing the DFS in two subtrees of this prefix trie

Finally

Read
Mapping (4)

Peter N.
Robinson

BW
Transform

FM Index

bwa

- Email: peter.robinson@charite.de
- Office hours by appointment

Further reading

- Parts of these slides were adapted from the brilliant Youtube lectures of Ben Langmead on the BWT/FM index (any infelicities are only my fault)
- Langmead B, Trapnell C, Pop M, Salzberg SL (2009) Ultrafast and memory-efficient alignment of short DNA sequences to the human genome. *Genome Biol* 10:R25.
- Li H, Durbin R (2009) Fast and accurate short read alignment with Burrows-Wheeler transform. *Bioinformatics* 25:1754-60.
- Li H, Homer N (2010) A survey of sequence alignment algorithms for next-generation sequencing. *Brief Bioinform.* 11:473-83.