

MCAL22 Artificial Intelligence and Machine Learning Lab**INDEX**

Sr. No	Artificial Intelligence Section	Date	CO	Sign
1.	Implementation of Logic programming using PROLOG DFS for water jug problem		CO1	
2.	Implementation of Logic programming using PROLOG BFS for tic-tac-toe problem		CO1	
3.	Implementation of Logic programming using PROLOG Hill-climbing to solve 8- Puzzle Problem.		CO1	
4.	Introduction to Python Programming: Learn the different libraries - NumPy, Pandas, SciPy, Matplotlib, Scikit Learn.		CO2	
5.	Implement Perceptron algorithm for OR operation		CO2	
6.	Improve the prediction accuracy by estimating the weight values for the training data using stochastic gradient descent. (Perceptron)		CO2	
7.	Implement Adaline algorithm for AND operation		CO2	

Sr. No	Machine Learning Section	Date	CO	Sign
1.	Implementation of Features Extraction and Selection, Normalization, Transformation, Principal Components Analysis.		CO3	
2.	Implementation of Logistic regression		CO4	
3.	Implementation of Classifying data using Support Vector Machine (SVM)- Linear and Non-Linear SVM Classification		CO4	
4.	Implement Elbow method for K means Clustering		CO4	
5.	Implementation of Bagging Algorithm: Random Forest		CO4	
6.	Implementation of Boosting Algorithms: AdaBoost, Stochastic Gradient Boosting, Voting Ensemble		CO4	

Artificial Intelligence Section

Practical 1: Implementation of Logic programming using PROLOG DFS for water jug problem

CODE:

```
start(2,0):-write(' 4lit Jug: 2 | 3lit Jug: 0|\n'),
write('~~~~~\n'),
write('Goal Reached! Congrats!!\n'),
write('~~~~~\n').
start(X,Y):-write(' Water Jug Game \n'),
write('Intial State: 4lit Jug- 0lit\n'),
write(' 3lit Jug- 0lit\n'),
write('Final State: 4lit Jug- 2lit\n'),
write(' 3lit Jug- 0lit\n'),
write('Follow the Rules: \n'),
write('Rule 1: Fill 4lit Jug\n'),
write('Rule 2: Fill 3lit Jug\n'),
write('Rule 3: Empty 4lit Jug\n'),
write('Rule 4: Empty 3lit Jug\n'),
write('Rule 5: Pour water from 3lit Jug to fill 4lit Jug\n'),
write('Rule 6: Pour water from 4lit Jug to fill 3lit Jug\n'),
write('Rule 7: Pour all of water from 3lit Jug to 4lit Jug\n'),
write('Rule 8: Pour all of water from 4lit Jug to 3lit Jug\n'),
write(' 4lit Jug: 0 | 3lit Jug: 0'),nl,
write(' Current Quantity :'),
write(' 4lit Jug: '),write(X),write(' | 3lit Jug: '),
write(Y),write(' |\n'),
write(' Enter the move::'),
read(N),
contains(X,Y,N).
contains(_,Y,1):-start(4,Y).
contains(X,_,2):-start(X,3).
contains(_,Y,3):-start(0,Y).
contains(X,_,4):-start(X,0).
contains(X,Y,5):-N is Y-4+X, start(4,N).
contains(X,Y,6):-N is X-3+Y, start(N,3).
contains(X,Y,7):-N is X+Y, start(N,0).
contains(X,Y,8):-N is X+Y, start(0,N).
```

OUTPUT:

```
?- start(0,0).
Water Jug Game
Initial State: 4lit Jug- 0lit
3lit Jug- 0lit
Final State: 4lit Jug- 2lit
3lit Jug- 0lit
Follow the Rules:
Rule 1: Fill 4lit Jug
Rule 2: Fill 3lit Jug
Rule 3: Empty 4lit Jug
Rule 4: Empty 3lit Jug
Rule 5: Pour water from 3lit Jug to fill 4lit Jug
Rule 6: Pour water from 4lit Jug to fill 3lit Jug
Rule 7: Pour all of water from 3lit Jug to 4lit Jug
Rule 8: Pour all of water from 4lit Jug to 3lit Jug
4lit Jug: 0 | 3lit Jug: 0
Current Quantity : 4lit Jug: 0| 3lit Jug: 0|
```

```
Enter the move::1.
Water Jug Game
Initial State: 4lit Jug- 0lit
3lit Jug- 0lit
Final State: 4lit Jug- 2lit
3lit Jug- 0lit
Follow the Rules:
Rule 1: Fill 4lit Jug
Rule 2: Fill 3lit Jug
Rule 3: Empty 4lit Jug
Rule 4: Empty 3lit Jug
Rule 5: Pour water from 3lit Jug to fill 4lit Jug
Rule 6: Pour water from 4lit Jug to fill 3lit Jug
Rule 7: Pour all of water from 3lit Jug to 4lit Jug
Rule 8: Pour all of water from 4lit Jug to 3lit Jug
4lit Jug: 0 | 3lit Jug: 0
Current Quantity : 4lit Jug: 4| 3lit Jug: 0|
```

```
Enter the move::|: 6.
Water Jug Game
Initial State: 4lit Jug- 0lit
3lit Jug- 0lit
Final State: 4lit Jug- 2lit
3lit Jug- 0lit
Follow the Rules:
Rule 1: Fill 4lit Jug
Rule 2: Fill 3lit Jug
Rule 3: Empty 4lit Jug
Rule 4: Empty 3lit Jug
Rule 5: Pour water from 3lit Jug to fill 4lit Jug
Rule 6: Pour water from 4lit Jug to fill 3lit Jug
Rule 7: Pour all of water from 3lit Jug to 4lit Jug
Rule 8: Pour all of water from 4lit Jug to 3lit Jug
4lit Jug: 0 | 3lit Jug: 0
Current Quantity : 4lit Jug: 1| 3lit Jug: 3|
```

```
Enter the move::|: 4.  
Water Jug Game  
Intial State: 4lit Jug- 0lit  
3lit Jug- 0lit  
Final State: 4lit Jug- 2lit  
3lit Jug- 0lit  
Follow the Rules:  
Rule 1: Fill 4lit Jug  
Rule 2: Fill 3lit Jug  
Rule 3: Empty 4lit Jug  
Rule 4: Empty 3lit Jug  
Rule 5: Pour water from 3lit Jug to fill 4lit Jug  
Rule 6: Pour water from 4lit Jug to fill 3lit Jug  
Rule 7: Pour all of water from 3lit Jug to 4lit Jug  
Rule 8: Pour all of water from 4lit Jug to 3lit Jug  
4lit Jug: 0 | 3lit Jug: 0  
Current Quantity : 4lit Jug: 1| 3lit Jug: 0|
```

```
Enter the move::|: 8.  
Water Jug Game  
Intial State: 4lit Jug- 0lit  
3lit Jug- 0lit  
Final State: 4lit Jug- 2lit  
3lit Jug- 0lit  
Follow the Rules:  
Rule 1: Fill 4lit Jug  
Rule 2: Fill 3lit Jug  
Rule 3: Empty 4lit Jug  
Rule 4: Empty 3lit Jug  
Rule 5: Pour water from 3lit Jug to fill 4lit Jug  
Rule 6: Pour water from 4lit Jug to fill 3lit Jug  
Rule 7: Pour all of water from 3lit Jug to 4lit Jug  
Rule 8: Pour all of water from 4lit Jug to 3lit Jug  
4lit Jug: 0 | 3lit Jug: 0  
Current Quantity : 4lit Jug: 0| 3lit Jug: 1|
```

```
Enter the move::|: 1.  
Water Jug Game  
Intial State: 4lit Jug- 0lit  
3lit Jug- 0lit  
Final State: 4lit Jug- 2lit  
3lit Jug- 0lit  
Follow the Rules:  
Rule 1: Fill 4lit Jug  
Rule 2: Fill 3lit Jug  
Rule 3: Empty 4lit Jug  
Rule 4: Empty 3lit Jug  
Rule 5: Pour water from 3lit Jug to fill 4lit Jug  
Rule 6: Pour water from 4lit Jug to fill 3lit Jug  
Rule 7: Pour all of water from 3lit Jug to 4lit Jug  
Rule 8: Pour all of water from 4lit Jug to 3lit Jug  
4lit Jug: 0 | 3lit Jug: 0  
Current Quantity : 4lit Jug: 4| 3lit Jug: 1|
```

```
Enter the move::|: 6.
Water Jug Game
Initial State: 4lit Jug- 0lit
3lit Jug- 0lit
Final State: 4lit Jug- 2lit
3lit Jug- 0lit
Follow the Rules:
Rule 1: Fill 4lit Jug
Rule 2: Fill 3lit Jug
Rule 3: Empty 4lit Jug
Rule 4: Empty 3lit Jug
Rule 5: Pour water from 3lit Jug to fill 4lit Jug
Rule 6: Pour water from 4lit Jug to fill 3lit Jug
Rule 7: Pour all of water from 3lit Jug to 4lit Jug
Rule 8: Pour all of water from 4lit Jug to 3lit Jug
4lit Jug: 0 | 3lit Jug: 0
Current Quantity : 4lit Jug: 2| 3lit Jug: 3|
Enter the move::|: 4.
4lit Jug: 2 | 3lit Jug: 0|
~~~~~
Goal Reached! Congrats!!
~~~~~
true .
```

Practical 2: Implementation of Logic programming using PROLOG BFS for tic-tac-toe problem

CODE:

```
% To play a game with the computer, type
% play.
% Predicates that define the winning conditions:
win(Board, Player) :- rowwin(Board, Player).
win(Board, Player) :- colwin(Board, Player).
win(Board, Player) :- diagwin(Board, Player).

rowwin(Board, Player) :- Board = [Player,Player,Player,_,_,_,_,_].
rowwin(Board, Player) :- Board = [_,_,Player,Player,Player,_,_,_].
rowwin(Board, Player) :- Board = [_,_,_,_,Player,Player,Player].

colwin(Board, Player) :- Board = [Player,_,_,Player,_,_,Player,_,_].
colwin(Board, Player) :- Board = [_,Player,_,_,Player,_,_,Player,_,_].
colwin(Board, Player) :- Board = [_,_,Player,_,_,Player,_,_,Player].

diagwin(Board, Player) :- Board = [Player,_,_,_,Player,_,_,_,Player].
diagwin(Board, Player) :- Board = [_,_,Player,_,_,_,Player,_,_].
move([b,B,C,D,E,F,G,H,I], Player, [Player,B,C,D,E,F,G,H,I]).
move([A,b,C,D,E,F,G,H,I], Player, [A,Player,C,D,E,F,G,H,I]).
move([A,B,b,D,E,F,G,H,I], Player, [A,B,Player,D,E,F,G,H,I]).
move([A,B,C,b,E,F,G,H,I], Player, [A,B,C,Player,E,F,G,H,I]).
move([A,B,C,D,b,F,G,H,I], Player, [A,B,C,D,Player,F,G,H,I]).
move([A,B,C,D,E,b,G,H,I], Player, [A,B,C,D,E,Player,G,H,I]).
move([A,B,C,D,E,F,b,H,I], Player, [A,B,C,D,E,F,Player,H,I]).
move([A,B,C,D,E,F,G,b,I], Player, [A,B,C,D,E,F,G,Player,I]).
move([A,B,C,D,E,F,G,H,b], Player, [A,B,C,D,E,F,G,H,Player]).

display([A,B,C,D,E,F,G,H,I]) :- write([A,B,C]),nl,write([D,E,F]),nl,
write([G,H,I]),nl,nl.

% Predicates to support playing a game with the user:
x_can_win_in_one(Board) :- move(Board, x, Newboard), win(Newboard, x).

% The predicate validate generates the computer's (playing o) reponse
% from the current Board.
validate(Board,Newboard) :-
move(Board, o, Newboard),
win(Newboard, o),
!.
validate(Board,Newboard) :-
move(Board, o, Newboard),
not(x_can_win_in_one(Newboard)).
validate(Board,Newboard) :-
move(Board, o, Newboard).

% The following translates from an integer description
```

% of x's move to a board transformation.

```
xmove([b,B,C,D,E,F,G,H,I], 1, [x,B,C,D,E,F,G,H,I]).  
xmove([A,b,C,D,E,F,G,H,I], 2, [A,x,C,D,E,F,G,H,I]).  
xmove([A,B,b,D,E,F,G,H,I], 3, [A,B,x,D,E,F,G,H,I]).  
xmove([A,B,C,b,E,F,G,H,I], 4, [A,B,C,x,E,F,G,H,I]).  
xmove([A,B,C,D,b,F,G,H,I], 5, [A,B,C,D,x,F,G,H,I]).  
xmove([A,B,C,D,E,b,G,H,I], 6, [A,B,C,D,E,x,G,H,I]).  
xmove([A,B,C,D,E,F,b,H,I], 7, [A,B,C,D,E,F,x,H,I]).  
xmove([A,B,C,D,E,F,G,b,I], 8, [A,B,C,D,E,F,G,x,I]).  
xmove([A,B,C,D,E,F,G,H,b], 9, [A,B,C,D,E,F,G,H,x]).  
xmove(Board, _, Board) :- write('Illegal move. '), nl.
```

% The 0-place predicate playo starts a game with the user.

```
play :- explain, playfrom([b,b,b,b,b,b,b,b]).
```

```
explain :-  
    write('You play X by entering integer positions followed by a period. '),  
    nl,  
    display([1,2,3,4,5,6,7,8,9]).
```

```
playfrom(Board) :- win(Board, x), write('You win!').  
playfrom(Board) :- win(Board, o), write('I win!').  
playfrom(Board) :- read(N),  
    xmove(Board, N, Newboard),  
    display(Newboard),  
    validate(Newboard, Newnewboard),  
    display(Newnewboard),  
    playfrom(Newnewboard).
```

OUTPUT:

```
?- play.  
You play X by entering integer positions followed by a period.  
[1,2,3]  
[4,5,6]  
[7,8,9]  
  
|: 1.  
[x,b,b]  
[b,b,b]  
[b,b,b]  
  
[x,o,b]  
[b,b,b]  
[b,b,b]  
  
|: 7.  
[x,o,b]  
[b,b,b]  
[x,b,b]  
  
[x,o,b]  
[o,b,b]  
[x,b,b]  
  
|: 5.  
[x,o,b]  
[o,x,b]  
[x,b,b]  
  
[x,o,o]  
[o,x,b]  
[x,b,b]  
  
|: 9.  
[x,o,o]  
[o,x,b]  
[x,b,x]  
  
[x,o,o]  
[o,x,o]  
[x,b,x]  
  
You win!  
true .
```


Practical 3: Implementation of Logic programming using PROLOG Hill-climbing to solve 8- Puzzle Problem.

CODE:

```

ids :-
    start(State),
    length(Moves, N),
    hill([State], Moves, Path), !,
    show([start | Moves], Path),
    format('~nmoves = ~w~n', [N]).

hill([State | States], [], Path) :-
    goal(State), !,
    reverse([State | States], Path).

hill([State | States], [Move | Moves], Path) :-
    move(State, Next, Move),
    not(memberchk(Next, [State | States])),
    hill([Next, State | States], Moves, Path).

show([], _).
show([Move | Moves], [State | States]) :-
    State = state(A,B,C,D,E,F,G,H,J),
    format('~n~w~n~n', [Move]),
    format('~w ~w ~w~n', [A,B,C]),
    format('~w ~w ~w~n', [D,E,F]),
    format('~w ~w ~w~n', [G,H,J]),
    show(Moves, States).

% Empty position is marked with '*'
start( state(0,1,*,2,3,4,5,6,7) ).

goal( state(*,0,1,2,3,4,5,6,7) ).

move( state(A,*,C,D,E,F,G,H,J), state(*,A,C,D,E,F,G,H,J), left ).
move( state(A,B,*,D,E,F,G,H,J), state(A,*,B,D,E,F,G,H,J), left ).
move( state(A,B,C,D,*,F,G,H,J), state(A,B,C,*,D,F,G,H,J), left ).
move( state(A,B,C,D,E,*,G,H,J), state(A,B,C,D,*,E,G,H,J), left ).
move( state(A,B,C,D,E,F,*,G,H,J), state(A,B,C,D,E,F,*,G,H,J), left ).
move( state(A,B,C,D,E,F,G,H,*), state(A,B,C,D,E,F,G,*,H), left ).

move( state(*,B,C,D,E,F,G,H,J), state(B,*,C,D,E,F,G,H,J), right).
move( state(A,*,C,D,E,F,G,H,J), state(A,C,*,D,E,F,G,H,J), right).
move( state(A,B,C,*,E,F,G,H,J), state(A,B,C,E,*,F,G,H,J), right).
move( state(A,B,C,D,*,F,G,H,J), state(A,B,C,D,F,*,G,H,J), right).
move( state(A,B,C,D,E,F,*,H,J), state(A,B,C,D,E,F,H,*,J), right).
move( state(A,B,C,D,E,F,G,*,J), state(A,B,C,D,E,F,G,J,*,), right).

move( state(A,B,C,*,E,F,G,H,J), state(*,B,C,A,E,F,G,H,J), up).
move( state(A,B,C,D,*,F,G,H,J), state(A,*,C,D,B,F,G,H,J), up).

```

```
move( state(A,B,C,D,E,*G,H,J), state(A,B,*D,E,C,G,H,J), up).  
move( state(A,B,C,D,E,F,*H,J), state(A,B,C,*E,F,D,H,J), up).  
move( state(A,B,C,D,E,F,G,*J), state(A,B,C,D,*F,G,E,J), up).  
move( state(A,B,C,D,E,F,G,H,*), state(A,B,C,D,E,*G,H,F), up).
```

```
move( state(*,B,C,D,E,F,G,H,J), state(D,B,C,*E,F,G,H,J), down ).  
move( state(A,*C,D,E,F,G,H,J), state(A,E,C,D,*F,G,H,J), down ).  
move( state(A,B,*D,E,F,G,H,J), state(A,B,F,D,E,*G,H,J), down ).  
move( state(A,B,C,*E,F,G,H,J), state(A,B,C,G,E,F,*H,J), down ).  
move( state(A,B,C,D,*F,G,H,J), state(A,B,C,D,H,F,G,*J), down ).  
move( state(A,B,C,D,E,*G,H,J), state(A,B,C,D,E,J,G,H,*), down ).
```

OUTPUT:

```
?- ids.  
  
start  
  
0 1 *  
2 3 4  
5 6 7  
  
left  
  
0 * 1  
2 3 4  
5 6 7  
  
left  
  
* 0 1  
2 3 4  
5 6 7  
  
moves = 2  
true.
```

Practical 4: Introduction to Python Programming: Learn the different libraries

- NumPy, Pandas, SciPy, Matplotlib, Scikit Learn.

➤ NumPy

```
[1]: !pip install numpy
Requirement already satisfied: numpy in c:\users\kapil\anaconda3\lib\site-packages (1.26.4)

[5]: import numpy as np

[9]: #creating an array
digits=np.array([[2,4,6],
                 [1,3,5],
                 [7,8,9]
                 ])

[11]: digits

[11]: array([[2, 4, 6],
           [1, 3, 5],
           [7, 8, 9]])

[13]: #Addition
a=15
b=25
c=a+b
c

[13]: 40
```

```
[15]: #Addition of two arrays
arr1=np.array([2,3,4])
arr2=np.array([1,5,2])
arr3=np.add(arr1,arr2)
arr3

[15]: array([3, 8, 6])

[17]: #Transpose
digits.transpose()

[17]: array([[2, 1, 7],
           [4, 3, 8],
           [6, 5, 9]])

[21]: #Sort Array
sortArray=np.array([
    [1,4,2],
    [3,8,5],
    [6,9,7]
])
np.sort(sortArray,axis=None)

[21]: array([1, 2, 3, 4, 5, 6, 7, 8, 9])
```

```
[21]: #Sort Array
sortArray=np.array([
    [1,4,2],
    [3,8,5],
    [6,9,7]
])
np.sort(sortArray,axis=None)

[21]: array([1, 2, 3, 4, 5, 6, 7, 8, 9])

[23]: #Array type
arr=np.array([1,4,6,8], dtype='S')
print(arr)
print(arr.dtype)

[b'1' b'4' b'6' b'8']
|S1
```

➤ Pandas

```
[26]: import pandas as pd

[28]: #Creating Dataframe
      data={
          'India':[7,4,9],
          'Austria':[1,5,8]
      }
      num=pd.DataFrame(data)
      num

[28]:
```

	India	Austria
0	7	1
1	4	5
2	9	8

```


[30]: num=pd.DataFrame(data,index=['Food','Education','People'])
      num

[30]:
```

	India	Austria
Food	7	1
Education	4	5
People	9	8

➤ SciPy

```
import numpy as np

[35]:

A=np.array([[3,2],[6,3]])

#To find determinant
from scipy import linalg
linalg.det(A)

[35]:


-3.0
```

➤ Matplotlib

```
[38]: #Matplotlib  
from matplotlib import pyplot as plt
```


```
[40]: #x-axis values  
x=[4,1,2,7,9]  
#y-axis values  
y=[1,6,3,2,9]  
  
plt.plot(x,y)
```

```
[40]: [ <matplotlib.lines.Line2D at 0x22114a42030> ]
```



```
[42]: #Histogram
```

```
h=[5,10,2,7,1]  
plt.hist(h)  
plt.show()
```




```
[48]: #Scatter Plot
x=[3,6,1,2,9]
y=[1,6,3,10,5]

plt.scatter(x,y)
plt.title("Scatter Diagram")

#Labels
plt.xlabel("Time(hr)")
plt.ylabel("Distance(km)")
```

```
[48]: Text(0, 0.5, 'Distance(km)')
```



➤ Scikit

```
[53]: import pandas as pd
from sklearn.datasets import load_wine

wine_data=load_wine()

#Conversion to pandas DataFrame
wine_df=pd.DataFrame(wine_data.data,columns=wine_data.feature_names)

#Add target Label
wine_df["target"]=wine_data.target

#Preview
wine_df.head()
```

```
[53]:
```

	alcohol	malic_acid	ash	alkalinity_of_ash	magnesium	total_phenols	flavanoids	nonflavanoid_phenols	proanthocyanins	color_intensity	hue	od280/od315_of_dilute
0	14.23	1.71	2.43	15.6	127.0	2.80	3.06	0.28	2.29	5.64	1.04	
1	13.20	1.78	2.14	11.2	100.0	2.65	2.76	0.26	1.28	4.38	1.05	
2	13.16	2.36	2.67	18.6	101.0	2.80	3.24	0.30	2.81	5.68	1.03	
3	14.37	1.95	2.50	16.8	113.0	3.85	3.49	0.24	2.18	7.80	0.86	
4	13.24	2.59	2.87	21.0	118.0	2.80	2.69	0.39	1.82	4.32	1.04	

Practical 5: Implement Perceptron algorithm for OR operation

```
[4]: import numpy as np

class Perceptron:
    def __init__(self, learning_rate=0.01, n_iterations=1):
        self.learning_rate = learning_rate
        self.n_iterations = n_iterations
        self.weights = None
        self.bias = None

    def fit(self, X, y):
        n_samples, n_features = X.shape
        self.weights = np.zeros(n_features)
        self.bias = 0

        y_ = np.array([1 if i > 0 else 0 for i in y])

        for _ in range(self.n_iterations):
            for idx, x_i in enumerate(X):
                linear_output = np.dot(x_i, self.weights) + self.bias
                y_predicted = self.activation_function(linear_output)

                update = self.learning_rate * (y_[idx] - y_predicted)
                self.weights += update * x_i
                self.bias += update

    def activation_function(self, x):
        return np.where(x >= 0, 1, 0)

    def predict(self, X):
        linear_output = np.dot(X, self.weights) + self.bias
        y_predicted = self.activation_function(linear_output)
        return y_predicted

# OR gate inputs and outputs
X = np.array([[0, 0], [0, 1], [1, 0], [1, 1]])
y = np.array([0, 1, 1, 1])

# Initialize and train the perceptron
perceptron = Perceptron(learning_rate=0.1, n_iterations=6)
perceptron.fit(X, y)

# Test the perceptron
predictions = perceptron.predict(X)
print(predictions)

[0 1 1 1]
```

Practical 6: Improve the prediction accuracy by estimating the weight values for the training data using stochastic gradient descent. (Perceptron)

```
[1]: import numpy as np
import matplotlib.pyplot as plt

# Generate synthetic data
np.random.seed(42)
X = 2 * np.random.rand(100, 1)
y = 4 + 3 * X + np.random.randn(100, 1)

def sgd(X, y, learning_rate=0.1, epochs=1000, batch_size=1):
    m = len(X)
    theta = np.random.randn(2, 1) # Initialize parameters randomly

    # Add a bias term to X (X_0 = 1)
    X_bias = np.c_[np.ones((m, 1)), X]
    cost_history = []

    for epoch in range(epochs):
        # Shuffle the data at the beginning of each epoch
        indices = np.random.permutation(m)
        X_shuffled = X_bias[indices]
        y_shuffled = y[indices]

        for i in range(0, m, batch_size):
            # Select a mini-batch or a single sample
            X_batch = X_shuffled[i:i+batch_size]
            y_batch = y_shuffled[i:i+batch_size]

            # Compute the gradient
            gradients = 2 / batch_size * X_batch.T.dot(X_batch.dot(theta) - y_batch)

            # Update the parameters (theta)
            theta -= learning_rate * gradients

        # Calculate and record the cost (Mean Squared Error) after each epoch
        predictions = X_bias.dot(theta)
        cost = np.mean((predictions - y) ** 2)
        cost_history.append(cost)

        # Print progress every 100 epochs
        if epoch % 100 == 0:
            print(f"Epoch {epoch}, Cost: {cost:.4f}")

    return theta, cost_history


# Train the model using SGD
theta_final, cost_history = sgd(X, y, learning_rate=0.1, epochs=1000, batch_size=1)

# Plot the cost history
plt.plot(cost_history)
plt.xlabel('Epochs')
plt.ylabel('Cost (MSE)')
plt.title('Cost Function during Training')
plt.grid(True)
plt.show()
```



```
# Plot the data and the regression line
plt.scatter(X, y, color='blue', label='Data points')
X_plot = np.c_[np.ones((X.shape[0], 1)), X]
plt.plot(X, X_plot.dot(theta_final), color='red', label='SGD fit line')
plt.xlabel('X')
plt.ylabel('y')
plt.title('Linear Regression using Stochastic Gradient Descent')
plt.legend()
plt.grid(True)
plt.show()
```

Epoch 0, Cost: 1.5818
Epoch 100, Cost: 1.5665
Epoch 200, Cost: 1.4445
Epoch 300, Cost: 1.7038
Epoch 400, Cost: 0.9102
Epoch 500, Cost: 0.8184
Epoch 600, Cost: 0.8352
Epoch 700, Cost: 0.8543
Epoch 800, Cost: 1.0508
Epoch 900, Cost: 0.8262



Practical 7: Implement Adaline algorithm for AND operation

```
[1]: import numpy as np

class Adaline:
    def __init__(self, input_size, learning_rate=0.1, epochs=100):
        self.weights = np.zeros(input_size)
        self.bias = 0
        self.learning_rate = learning_rate
        self.epochs = epochs

    def activation(self, X): # X is input
        return X

    def predict(self, X):
        return self.activation(np.dot(X, self.weights) + self.bias)

    def train(self, X, y):
        for epoch in range(self.epochs):
            for i in range(len(X)):
                prediction = self.predict(X[i])
                error = y[i] - prediction
                self.weights += self.learning_rate * error * X[i]
                self.bias += self.learning_rate * error

    def evaluate(self, X):
        return np.where(self.predict(X) >= 0.5, 1, 0)

# Training data for AND gate
X = np.array([[0, 0], [0, 1], [1, 0], [1, 1]])
y = np.array([0, 0, 0, 1])

adaline = Adaline(input_size=2, learning_rate=0.1, epochs=100)
adaline.train(X, y)
predictions = adaline.evaluate(X)

for i, prediction in enumerate(predictions):
    print(f"Input: {X[i]} => Predicted: {prediction} => Actual: {y[i]}")

Input: [0 0] => Predicted: 0 => Actual: 0
Input: [0 1] => Predicted: 0 => Actual: 0
Input: [1 0] => Predicted: 0 => Actual: 0
Input: [1 1] => Predicted: 1 => Actual: 1
```

Machine Learning Section

Practical 1: Implementation of Features Extraction and Selection, Normalization, Transformation, Principal Components Analysis.

1. Feature Extraction

```
[1]: from sklearn.feature_extraction.text import TfidfVectorizer

documents = ["machine learning is amazing", "deep learning is a part of machine learning"]
vectorizer = TfidfVectorizer()
X_tfidf = vectorizer.fit_transform(documents)

print("TF-IDF shape:", X_tfidf.shape)

TF-IDF shape: (2, 7)
```

2. Feature Selection

```
[2]: from sklearn.datasets import load_iris
from sklearn.feature_selection import SelectKBest, chi2

data = load_iris()
X, y = data.data, data.target

# Select top 2 features based on chi-square test
X_selected = SelectKBest(chi2, k=2).fit_transform(X, y)

print("Selected Features shape:", X_selected.shape)

Selected Features shape: (150, 2)
```

3. Normalization

```
[3]: from sklearn.preprocessing import Normalizer

normalizer = Normalizer()
X_normalized = normalizer.fit_transform(X)

print("Normalized data (first sample):", X_normalized[0])

Normalized data (first sample): [0.80377277 0.55160877 0.22064351 0.0315205 ]
```

4. Transformation

```
[4]: from sklearn.preprocessing import StandardScaler

scaler = StandardScaler()
X_scaled = scaler.fit_transform(X)

print("Standardized data (first sample):", X_scaled[0])

Standardized data (first sample): [-0.90068117  1.01900435 -1.34022653 -1.3154443 ]
```

5. Principal Component Analysis

```
[5]: from sklearn.decomposition import PCA

# Reduce to 2 principal components
pca = PCA(n_components=2)
X_pca = pca.fit_transform(X_scaled)

print("PCA transformed shape:", X_pca.shape)

PCA transformed shape: (150, 2)
```

Practical 2: Implementation of Logistic regression

```
[21]: #Problem Statement 1: Build and train a Logistic Regression Model to do binary classification of iris flowers using the iris dataset.

import numpy as np
from sklearn import datasets

iris = datasets.load_iris()
print(type(iris))
print(list(iris.keys()))
X = iris["data"][:,3:] # petal width
y = (iris["target"] == 2).astype(np.int64) # 1 if Iris-Virginica, else 0


<class 'sklearn.utils._bunch.Bunch'>
['data', 'target', 'frame', 'target_names', 'DESCR', 'feature_names', 'filename', 'data_module']

[5]: from sklearn.linear_model import LogisticRegression

log_reg = LogisticRegression(solver="lbfgs", random_state=42)
log_reg.fit(X,y)

[5]: LogisticRegression
LogisticRegression(random_state=42)

[17]: import matplotlib.pyplot as plt
X_new = np.linspace(0,3,1000).reshape(-1,1)
y_proba = log_reg.predict_proba(X_new)
plt.plot(X_new, y_proba[:,1], "g-")
plt.plot(X_new, y_proba[:,0], "b--")
plt.xlabel('Petal width (cm)')
plt.ylabel('Probability')
plt.legend(['Iris-Virginica', 'Not Iris-Virginica'])
```



```
[19]: #Problem Statement 2: Logistic Regression for predicting class using two features: Petal Length and width.

from sklearn.linear_model import LogisticRegression

X = iris["data"][:, (2, 3)] # petal length, petal width
y = (iris["target"] == 2).astype(np.int64)


log_reg2 = LogisticRegression(solver="lbfgs", C=10**10, random_state=42)
log_reg2.fit(X, y)

x0, x1 = np.meshgrid(
    np.linspace(2.9, 7, 500).reshape(-1, 1),
    np.linspace(0.8, 2.7, 200).reshape(-1, 1),
)
X_new = np.c_[x0.ravel(), x1.ravel()]
print(X_new.shape)

y_proba = log_reg2.predict_proba(X_new)

plt.figure(figsize=(10, 4))
plt.plot(X[y==0, 0], X[y==0, 1], "cs")
plt.plot(X[y==1, 0], X[y==1, 1], "r^")
zz = y_proba[:, 1].reshape(x0.shape)
contour = plt.contour(x0, x1, zz, cmap=plt.cm.brg)
left_right = np.array([2.9, 7])
boundary = -(log_reg2.coef_[0][0] * left_right + log_reg2.intercept_[0]) / log_reg2.coef_[0][1]
plt.clabel(contour, inline=1, fontsize=12)
plt.plot(left_right, boundary, "k--", linewidth=3)
plt.text(3.5, 1.5, "Not Iris virginica", fontsize=14, color="b", ha="center")
plt.text(6.5, 2.3, "Iris virginica", fontsize=14, color="g", ha="center")
plt.xlabel("Petal length", fontsize=14)
plt.ylabel("Petal width", fontsize=14)
plt.axis([2.9, 7, 0.8, 2.7])

(100000, 2)
[19]: (2.9, 7.0, 0.8, 2.7)
```



Practical 3: Implementation of Classifying data using Support Vector Machine (SVM)- Linear and Non-Linear SVM Classification

➤ Linear SVM

```
[1]: %matplotlib inline
import matplotlib
import matplotlib.pyplot as plt

def plot_svc_decision_boundary(svm_clf, xmin, xmax):
    w = svm_clf.coef_[0]
    b = svm_clf.intercept_[0]

    # At the decision boundary, w0*x0 + w1*x1 + b = 0
    # => x1 = -w0/w1 * x0 - b/w1
    x0 = np.linspace(xmin, xmax, 200)
    decision_boundary = -w[0]/w[1] * x0 - b/w[1]

    margin = 1/w[1]
    gutter_up = decision_boundary + margin
    gutter_down = decision_boundary - margin

    svcs = svm_clf.support_vectors_
    plt.scatter(svcs[:, 0], svcs[:, 1], s=180, facecolors='FFAAAA')
    plt.plot(x0, decision_boundary, "k-", linewidth=2)
    plt.plot(x0, gutter_up, "k--", linewidth=2)
    plt.plot(x0, gutter_down, "k--", linewidth=2)
```

```
[2]: from sklearn.svm import SVC
from sklearn import datasets
import numpy as np

# Load Iris dataset
iris = datasets.load_iris()
X = iris["data"][:, (2, 3)] # Select petal length and petal width
y = iris["target"]

# Select only Setosa and Versicolor classes
setosa_or_versicolor = (y == 0) | (y == 1)
X = X[setosa_or_versicolor]
y = y[setosa_or_versicolor]

# SVM Classifier model with a Large but finite C value
svm_clf = SVC(kernel="linear", C=1e10) # Large C approximates a hard margin
svm_clf.fit(X, y)

# Make a prediction
prediction = svm_clf.predict([[2.4, 3.1]])
print("Predicted class:", prediction[0])

Predicted class: 1
```


```
[3]: #plot the decision boundaries
import numpy as np

plt.figure(figsize=(12,3.2))

from sklearn.preprocessing import StandardScaler
scaler = StandardScaler()
X_scaled = scaler.fit_transform(X)
svm_clf.fit(X_scaled, y)

plt.plot(X_scaled[:, 0][y==1], X_scaled[:, 1][y==1], "bo")
plt.plot(X_scaled[:, 0][y==0], X_scaled[:, 1][y==0], "ms")
plot_svc_decision_boundary(svm_clf, -2, 2)
plt.xlabel("Petal Width normalized", fontsize=12)
plt.ylabel("Petal Length normalized", fontsize=12)
plt.title("Scaled", fontsize=16)
plt.axis([-2, 2, -2, 2])

[3]: (-2.0, 2.0, -2.0, 2.0)
```





➤ Non-Linear SVM

```
[1]: from sklearn.datasets import make_moons
      from sklearn.pipeline import Pipeline
      from sklearn.preprocessing import PolynomialFeatures
      from sklearn.preprocessing import StandardScaler
      from sklearn.svm import SVC

[2]: import numpy as np
      %matplotlib inline
      import matplotlib
      import matplotlib.pyplot as plt

[4]: from sklearn.datasets import make_moons
      X, y = make_moons(n_samples=100, noise=0.15, random_state=42)
      #define a function to plot the dataset
      def plot_dataset(X, y, axes):
          plt.plot(X[:, 0][y==0], X[:, 1][y==0], "cs")
          plt.plot(X[:, 0][y==1], X[:, 1][y==1], "m^")
          plt.axis(axes)
          plt.grid(True, which='both')
          plt.xlabel(r"$x_1$", fontsize=20)
          plt.ylabel(r"$x_2$", fontsize=20, rotation=0)
      #Let's have a look at the data we have generated
      plot_dataset(X, y, [-1.5, 2.5, -1, 1.5])
      plt.show()
```




```
[7]: #define a function plot the decision boundaries
def plot_predictions(clf, axes):
    #create data in continuous linear space
    x0s = np.linspace(axes[0], axes[1], 100)
    x1s = np.linspace(axes[2], axes[3], 100)
    x0, x1 = np.meshgrid(x0s, x1s)
    X = np.c_[x0.ravel(), x1.ravel()]
    y_pred = clf.predict(X).reshape(x0.shape)
    y_decision = clf.decision_function(X).reshape(x0.shape)
    plt.contourf(x0, x1, y_pred, cmap=plt.cm.brg, alpha=0.2)
    plt.contourf(x0, x1, y_decision, cmap=plt.cm.brg, alpha=0.1)

[9]: #C controls the width of the street
#Degree of data
#create a pipeline to create features, scale data and fit the model
polynomial_svm_clf = Pipeline((
    ("poly_features", PolynomialFeatures(degree=3)),
    ("scalar", StandardScaler()),
    ("svm_clf", SVC(kernel="poly", degree=10, coef0=1, C=5))
))
#call the pipeline
polynomial_svm_clf.fit(X,y)
```


```
[9]: Pipeline
├── PolynomialFeatures
│   └── StandardScaler
│       └── SVC
```

```
[11]: #plot the decision boundaries
plt.figure(figsize=(11, 4))

#plot the decision boundaries
plot_predictions(polynomial_svm_clf, [-1.5, 2.5, -1, 1.5])

#plot the dataset
plot_dataset(X, y, [-1.5, 2.5, -1, 1.5])

plt.title(r"$d=3, \text{coef0}=1, C=5$", fontsize=18)
plt.show()
```



Practical 4: Implement Elbow method for K means Clustering

```
[1]: !pip install --user threadpoolctl==3.1.0

Collecting threadpoolctl==3.1.0
  Downloading threadpoolctl-3.1.0-py3-none-any.whl.metadata (9.2 kB)
  Downloading threadpoolctl-3.1.0-py3-none-any.whl (14 kB)
Installing collected packages: threadpoolctl
Successfully installed threadpoolctl-3.1.0
```

```
[3]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from sklearn.cluster import KMeans

# Load the dataset
df = pd.read_csv("clustering.csv")

# Display first few rows of the dataset
print(df.head())

# Drop missing values
df_cleaned = df.dropna()

# Selecting numerical columns for clustering
numerical_cols = df_cleaned.select_dtypes(include=[np.number]).columns
print("Numerical columns used for clustering:", numerical_cols.tolist())

# Feature selection for clustering (Modify as needed)
X = df_cleaned[numerical_cols]
```

```
# Apply the Elbow Method
wcss = [] # Within-cluster sum of squares
for i in range(1, 11): # Trying different cluster numbers from 1 to 10
    kmeans = KMeans(n_clusters=i, random_state=42, n_init=10)
    kmeans.fit(X)
    wcss.append(kmeans.inertia_)

# Plot the Elbow Method

plt.plot(range(1, 11), wcss, marker='o', linestyle='--')
plt.xlabel('Number of Clusters')
plt.ylabel('WCSS')
plt.title('Elbow Method for Optimal k')
plt.show()

# Choose optimal k (Modify based on the elbow plot observation)
k_optimal = 3 # Example choice, change based on your dataset

# Apply K-Means with the optimal number of clusters
kmeans = KMeans(n_clusters=k_optimal, random_state=42, n_init=10)
df_cleaned['Cluster'] = kmeans.fit_predict(X)

# Display clustered data
print(df_cleaned.head())


# Plot the clusters (for 2D visualization, choose two relevant features)
plt.scatter(df_cleaned[numerical_cols[0]], df_cleaned[numerical_cols[1]], c=df_cleaned['Cluster'], cmap='viridis')
plt.xlabel(numerical_cols[0])
plt.ylabel(numerical_cols[1])
plt.title(f'K-Means Clustering (k={k_optimal})')
plt.colorbar(label='Cluster')
plt.show()
```

	Loan_ID	Gender	Married	Dependents	Education	Self_Employed	\
0	LP001003	Male	Yes	1	Graduate	No	
1	LP001005	Male	Yes	0	Graduate	Yes	
2	LP001006	Male	Yes	0	Not Graduate	No	
3	LP001008	Male	No	0	Graduate	No	
4	LP001013	Male	Yes	0	Not Graduate	No	

	ApplicantIncome	CoapplicantIncome	LoanAmount	Loan_Amount_Term	\
0	4583	1508.0	128.0	360.0	
1	3000	0.0	66.0	360.0	
2	2583	2358.0	120.0	360.0	
3	6000	0.0	141.0	360.0	
4	2333	1516.0	95.0	360.0	

	Credit_History	Property_Area	Loan_Status
0	1.0	Rural	N
1	1.0	Urban	Y
2	1.0	Urban	Y
3	1.0	Urban	Y
4	1.0	Urban	Y

Numerical columns used for clustering: ['ApplicantIncome', 'CoapplicantIncome', 'LoanAmount', 'Loan_Amount_Term', 'Credit_History']




Number of Clusters

	Loan_ID	Gender	Married	Dependents	Education	Self_Employed	\
0	LP001003	Male	Yes	1	Graduate	No	
1	LP001005	Male	Yes	0	Graduate	Yes	
2	LP001006	Male	Yes	0	Not Graduate	No	
3	LP001008	Male	No	0	Graduate	No	
4	LP001013	Male	Yes	0	Not Graduate	No	

	ApplicantIncome	CoapplicantIncome	LoanAmount	Loan_Amount_Term	\
0	4583	1508.0	128.0	360.0	
1	3000	0.0	66.0	360.0	
2	2583	2358.0	120.0	360.0	
3	6000	0.0	141.0	360.0	
4	2333	1516.0	95.0	360.0	

	Credit_History	Property_Area	Loan_Status	Cluster
0	1.0	Rural	N	2
1	1.0	Urban	Y	2
2	1.0	Urban	Y	0
3	1.0	Urban	Y	2
4	1.0	Urban	Y	0



Practical 5: Implementation of Bagging Algorithm: Random Forest

```
[1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import accuracy_score
from sklearn.decomposition import PCA

# Load dataset
iris = load_iris()
X = iris.data
y = iris.target

# Split data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

# Initialize and train the Random Forest Classifier
rf_classifier = RandomForestClassifier(n_estimators=100, random_state=42)
rf_classifier.fit(X_train, y_train)

# Make predictions
y_pred = rf_classifier.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f'Accuracy of Random Forest Classifier: {accuracy * 100:.2f}%')

Accuracy of Random Forest Classifier: 100.00%
```

Practical 6: Implementation of Boosting Algorithms: AdaBoost, Stochastic Gradient Boosting, Voting Ensemble

```
[1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier, AdaBoostClassifier, GradientBoostingClassifier, VotingClassifier
from sklearn.tree import DecisionTreeClassifier
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score
from sklearn.decomposition import PCA

# Load dataset
iris = load_iris()
X = iris.data
y = iris.target

# Split data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

# Random Forest Classifier
rf_classifier = RandomForestClassifier(n_estimators=100, random_state=42)
rf_classifier.fit(X_train, y_train)
y_pred_rf = rf_classifier.predict(X_test)
accuracy_rf = accuracy_score(y_test, y_pred_rf)
print(f'Accuracy of Random Forest Classifier: {accuracy_rf * 100:.2f}%')
```

```
# AdaBoost Classifier
adaboost = AdaBoostClassifier(base_estimator=DecisionTreeClassifier(max_depth=1), n_estimators=50, random_state=42)
adaboost.fit(X_train, y_train)
y_pred_adaboost = adaboost.predict(X_test)
accuracy_adaboost = accuracy_score(y_test, y_pred_adaboost)
print(f'Accuracy of AdaBoost Classifier: {accuracy_adaboost * 100:.2f}%')
```

```
# Gradient Boosting Classifier
gb_classifier = GradientBoostingClassifier(n_estimators=100, learning_rate=0.1, random_state=42)
gb_classifier.fit(X_train, y_train)
y_pred_gb = gb_classifier.predict(X_test)
accuracy_gb = accuracy_score(y_test, y_pred_gb)
print(f'Accuracy of Gradient Boosting Classifier: {accuracy_gb * 100:.2f}%')
```

```
# Voting Classifier (Ensemble of Logistic Regression, Decision Tree, and Random Forest)
voting_classifier = VotingClassifier(estimators=[
    ('lr', LogisticRegression()),
    ('dt', DecisionTreeClassifier()),
    ('rf', RandomForestClassifier(n_estimators=100))
], voting='hard')
voting_classifier.fit(X_train, y_train)
y_pred_voting = voting_classifier.predict(X_test)
accuracy_voting = accuracy_score(y_test, y_pred_voting)
print(f'Accuracy of Voting Classifier: {accuracy_voting * 100:.2f}%')
```

```
# Reduce dimensions for visualization
pca = PCA(n_components=2)
X_reduced = pca.fit_transform(X)

# Scatter plot of the dataset
plt.figure(figsize=(8, 6))
plt.scatter(X_reduced[:, 0], X_reduced[:, 1], c=y, cmap='viridis', edgecolor='k', alpha=0.7)
plt.xlabel('Principal Component 1')
plt.ylabel('Principal Component 2')
plt.title('Iris Dataset Visualization with PCA')
plt.colorbar(label='Class Labels')
plt.show()
```

Accuracy of Random Forest Classifier: 100.00%
Accuracy of AdaBoost Classifier: 100.00%
Accuracy of Gradient Boosting Classifier: 100.00%

