

Package ‘rNOMADS’

March 4, 2019

Type Package

Title An R Interface to the NOAA Operational Model Archive and Distribution System

Version 2.4.1

Date 2019-3-2

Depends R (>= 3.4.0), rvest (>= 0.3.2)

Imports stringr (>= 1.2.0), fields (>= 9.0), GEOMap (>= 2.3-5), MBA, RCurl (>= 1.95-4.7), XML (>= 3.98.1.9), uuid (>= 0.1-2)

Description An interface to the National Oceanic and Atmospheric Administration's Operational Model Archive and Distribution System (NO-MADS, see <<http://nomads.ncep.noaa.gov/>> for more information) that allows R users to quickly and efficiently download global and regional weather model data for processing. rNOMADS currently supports a variety of models ranging from global weather data to an altitude of over 40 km, to high resolution regional weather models, to wave and sea ice models. It can also retrieve archived NOMADS models. rNOMADS can retrieve binary data in grib format as well as import ascii data directly into R by interfacing with the GrADS-DODS system.

License GPL (>= 3)

Maintainer Daniel C. Bowman <danny.c.bowman@gmail.com>

MailingList <rnomsads-user@lists.r-forge.r-project.org>

URL <<https://bovineaerospace.wordpress.com/category/r/>>, <<https://r-forge.r-project.org/projects/rnomads/>>, <<https://www.r-project.org>>

NeedsCompilation no

Author Daniel C. Bowman [aut, cre]

Repository CRAN

Date/Publication 2019-03-04 08:00:03 UTC

R topics documented:

rNOMADS-package 2

ArchiveGribGrab	4
BuildProfile	6
CheckNOMADSArchive	8
CrawlModels	9
DODSGrab	10
GetClosestForecasts	12
GetDODSDates	14
GetDODSModelRunInfo	15
GetDODSModelRuns	17
GribGrab	18
GribInfo	20
LinkExtractor	21
MagnitudeAzimuth	23
ModelGrid	24
NOMADSArchiveList	26
NOMADSRealTimeList	27
ParseModelPage	28
PlotWindProfile	29
ReadGrib	31
SubsetNOMADS	34
WebCrawler	36
Index	38

rNOMADS-package	<i>An interface to the NOAA Operational Model Archive and Distribution System</i>
-----------------	---

Description

Automatically download forecast data from the National Oceanic and Atmospheric Administration’s Operational Model Archive and Distribution System (NOMADS) and read it into R. This can be done in two ways: reading ascii data directly from the server using the DODS-GrADS system or downloading binary files in GRIB1 or GRIB2 format. The grib capability of rNOMADS uses an external series of routines called wgrib2 to read operational model data; get wgrib2 at <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/>. The package will also attempt to call another external routine called wgrib if the user wishes to read GRIB1 files; get wgrib at <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib.html>.

Details

Package: rNOMADS
Type: Package
Version: 2.2.0
Date: 2016-03-21
License: GPL v3

Author(s)

Daniel C. Bowman <danny.c.bowman@gmail.com>

References

Bowman, D. C. and Lees, J. M. (2015). Near real time weather and ocean model data access with rNOMADS. *Computers & Geosciences* 78, pp. 88-95.

NOMADS website:

<http://nomads.ncep.noaa.gov/>

wgrib2 download page:

<http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/>

wgrib2 reference:

Ebisuzaki, W, Bokhorst, R., Hyvatti, J., Jovic, D., Nilssen, K, Pfeiffer, K., Romero, P., Schwarb, M., da Silva, A., Sondell, N., and Varlamov, S. (2011). wgrib2: read and write GRIB2 files. *National Weather Service Climate Prediction Center*,

<http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/>

wgrib download page:

<http://www.cpc.ncep.noaa.gov/products/wesley/wgrib.html>

Examples

```
#Getting temperature for North Carolina, USA,
#6-12 hours ago depending on when the latest model run was.
#Get values at the ground surface and at the 800 mb level
#Then make a contour plot of the surface temperature.
#We use GrADS-DODS here for compatibility.

#Using the Global Forecast System 0.5x0.5 model
## Not run:

urls.out <- GetDODSDates(abbrev = "gfs_0p50")
model.url <- tail(urls.out$url, 1) #Get most recent model date

#Get most recent model run

model.runs <- GetDODSModelRuns(model.url)
model.run <- tail(model.runs$model.run, 1)

#Get ground temperature for the 6 hour prediction
variable <- "tmp2m" #temp at 2 m
time <- c(2,2) #6 hour prediction
lon.dom <- seq(0, 360, by = 0.5) #domain of longitudes in model
lat.dom <- seq(-90, 90, by = 0.5) #domain of latitudes in model
lon <- which((lon.dom >= 360 - 84) & (lon.dom <= 360 - 74)) - 1 #NOMADS indexes start at 0
lat <- which((lat.dom <= 37) & (lat.dom >= 32)) - 1 #NOMADS indexes start at 0
model.data.surface <- DODSGrab(model.url, model.run, variable, time, c(min(lon), max(lon)),
```

```

    c(min(lat), max(lat)))

lev <- c(8, 8) #800 mb level
variable <- "tmpprs"
model.data.800mb <- DODSGrab(model.url, model.run, variable, time, c(min(lon), max(lon)),
    c(min(lat), max(lat)), level = lev)

#Make results into arrays
model.array.surface <- ModelGrid(model.data.surface, c(0.5, 0.5))
model.array.800mb <- ModelGrid(model.data.800mb, c(0.5, 0.5))

#Make a contour plot of the temperature around North Carolina, USA:
contour(x = model.array.surface$x - 360, y = model.array.surface$y,
    model.array.surface$z[1,1,,] - 273.15, xlab = "Longitude", ylab = "Latitude",
    main = paste("North Carolina Surface Temperatures for",
    model.array.surface$fcst.date, "UTC in Celsius"))

dev.new()
contour(x = model.array.800mb$x - 360, y = model.array.800mb$y,
    model.array.800mb$z[1,1,,] - 273.15, xlab = "Longitude", ylab = "Latitude",
    main = paste("North Carolina Temperatures at 800 mb for",
    model.array.surface$fcst.date, "UTC in Celsius"))

## End(Not run)

```

ArchiveGribGrab

Download archived model data from the NOMADS server.

Description

This function interfaces with the programming API at <http://nomads.ncdc.noaa.gov/> to download archived NOMADS model data. The available models can be viewed by calling [NOMADSArchiveList](#) without arguments. The data arrives in grib (gridded binary) format that can be read with [ReadGrib](#). Some of these files are in GRIB format, others are in GRIB2 format; select the appropriate file type when calling [ReadGrib](#).

Usage

```

ArchiveGribGrab(abbrev, model.date, model.run, preds,
    local.dir = NULL, file.names = NULL, tidy = FALSE,
    verbose = TRUE, download.method = NULL, file.type = "grib2")

```

Arguments

abbrev	Model abbreviation per NOMADSArchiveList .
model.date	The year, month, and day of the model run, in YYYYMMDD format
model.run	Which hour the model was run (i.e. 00, 06, 12, 18 for GFS)
preds	A scalar or vector of prediction to get (analysis is 00)

<code>local.dir</code>	Where to save the grib file, defaults to the current directory.
<code>file.names</code>	A list of length <code>length(preds)</code> of file names to which the downloaded GRIB files are directed to. Default NULL, meaning files will be named per their model date and time.
<code>tidy</code>	If TRUE, remove all files with the suffix ".grb" from <code>local.dir</code> prior to downloading a new grib file.
<code>verbose</code>	If TRUE, give information on connection status. Default TRUE
<code>download.method</code>	Allows the user to set the download method used by <code>download.file</code> : "internal", "wget" "curl", "lynx". If NULL (the default), let R decide.
<code>file.type</code>	Determine whether to get GRIB1 ("grib1") or GRIB2 ("grib2") file formats. Sometimes both are available, sometimes only one.

Value

`grib.info$file.name`
The path and file name of the grib file that was downloaded.

`grib.info$url` The URL that the grib file was downloaded from

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

References

<http://nomads.ncdc.noaa.gov/>

See Also

[CheckNOMADSArchive](#), [NOMADSArchiveList](#), [ReadGrib](#)

Examples

```
#An example for the Global Forecast System
#Get data for January 1 2014
#Temperature at 2 m above ground
#3 hour prediction
# using GRIB

abbrev <- "gfsan1"
model.date <- 20140101
model.run <- 06
preds <- 3

## Not run:
model.info <- ArchiveGribGrab(abbrev, model.date,
  model.run, preds, file.type = "grib2")
model.data <- ReadGrib(model.info[[1]]$file.name, c("2 m above ground"), c("TMP"))
```

```
#Get surface temperature in Chapel Hill, NC
lat <- 35.907605
lon <- -79.052147

profile <- BuildProfile(model.data, lon, lat, TRUE)
print(paste0("The temperature prediction in Chapel Hill was ",
  sprintf("%.0f", profile[[1]]$profile.data[1,1,1] - 272.15), " degrees Celsius."))

## End(Not run)
```

BuildProfile

Get model data at a specific point.

Description

Takes the output of [ReadGrib](#) or [DODSGrab](#) and extracts data at a specific point, performing interpolation if required.

Usage

```
BuildProfile(model.data, lon, lat, spatial.average, points = 4)
```

Arguments

<code>model.data</code>	Data structure returned by ReadGrib or DODSGrab .
<code>lon</code>	Longitudes of points of interest.
<code>lat</code>	Latitudes of points of interest.
<code>spatial.average</code>	Whether to interpolate data using b-splines to obtain value at the requested point (<code>spatial.average = TRUE</code>) or use the nearest model node (<code>spatial.average = FALSE</code>).
<code>points</code>	How many points to include in the interpolation, will be ignored if <code>spatial.average = FALSE</code> .

Details

It is much more efficient to download a large chunk of data and extract profile points from that as opposed to downloading individual small model chunks in the vicinity of each point of interest.

Value

<code>profile</code>	A list with as many elements as profile points, with fields:
<code>profile\$profile.data</code>	A levels x variables x time matrix with data at a specific point
<code>profile\$location</code>	The location for which the profile is generated
<code>profile\$forecast.date</code>	What dates and times the profile contains

```
profile$variables
```

The variables the profile contains

```
profile$levels
```

 The levels the profile contains

Note

The “outside of model domain” warning may occur if the profile point is very close to the prime meridian (in the case of a 0-360 longitude definition) or the antipode of the prime meridian (+/- 180 degrees longitude in the case of -180 to 180 degrees definition). For a full download of a global model (e. g. the GFS), this does not mean the point is actually outside of the model domain. For example, the 0.5 degree GFS has nodes from 0 to 359.5 degrees longitude; a profile point requested at 359.9 degrees longitude will cause this warning even though it is within the global GFS model domain.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[ReadGrib](#), [DODSGrab](#)

Examples

```
#Get temperature profile in Chapel Hill, NC.

#First, define each location
lon <- -79.052094
lat <- 35.907562

#Get second to latest GFS 0.5 model, use analysis forecast
#(this ensures the data's fully up on NOMADS)

## Not run:
model.url <- CrawlModels(abbrev = "gfs_0p50", depth = 2)[2]
pred <- ParseModelPage(model.url)$pred[1]

## End(Not run)

#Get levels
pressure <- c(1, 2, 3, 5, 7,
10, 20, 30, 50, 70,
seq(100, 1000, by = 25))
levels <- paste(pressure, " mb", sep = "")

#Variables - temperature and height only
variables <- c("TMP", "HGT")

## Not run:
grib.info <- GribGrab(model.url, pred, levels, variables,
  model.domain = c(-85, -75, 37, 32))
```

```

grib.data <- ReadGrib(grib.info[[1]]$file.name, levels, variables)

profile <- BuildProfile(grib.data, lon, lat, TRUE, points = 8)
plot(profile[[1]]$profile.data[,2, 1] - 272.15,
      profile[[1]]$profile.data[,1, 1], xlab = "Temperature (C)",
      ylab = "Height (m)", main = "Temperature Profile above Chapel Hill, NC")

## End(Not run)

```

CheckNOMADSArchive *Check to see if archived data exists.*

Description

This function checks to see if data exists for a given date and model. It checks for both GRIB1 or GRIB2 files.

Usage

```
CheckNOMADSArchive(abbrev, model.date = NULL)
```

Arguments

abbrev	Model abbreviation per NOMADSArchiveList .
model.date	The year, month, and day to check for data, in YYYYMMDD format. If NULL, check all available dates in NOMADS archive.

Value

available.models\$date	What date the file is for, in YYYYMMDD format.
available.models\$model.run	At what hour (GMT) the model was run.
available.models\$pred	What predictions are available
available.models\$file.name	List of file names for available model dates, runs, and predictions

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

References

<http://nomads.ncdc.noaa.gov/>

See Also

[NOMADSArchiveList](#), [ArchiveGribGrab](#)

Examples

```
#See what is available for January 1 of this year

abbrev <- "gfs4"
model.date <- paste0(format(Sys.time(), "%Y"), "0101")
## Not run:
gfs.available.models <- CheckNOMADSArchive(abbrev, model.date)

## End(Not run)
```

CrawlModels

Get Available Model Runs

Description

This function determine which instances of a given model are available for download.

Usage

```
CrawlModels(abbrev = NULL, model.url = NULL, depth = NULL, verbose = TRUE)
```

Arguments

abbrev	The model abbreviation, see NOMADSRealTimeList . Defaults to NULL.
model.url	A URL to use instead of using the abbreviations in NOMADSRealTimeList . Defaults to NULL.
depth	How many model instances to return. This avoids having to download the entire model list (sometimes several hundred) if only the first few instances are required. Defaults to NULL, which returns everything.
verbose	Print out each link as it is discovered. Defaults to TRUE.

Details

This function calls [WebCrawler](#), a recursive algorithm that discovers each link available in the URL provided. It then searches each link in turn, and follows those links until it reaches a dead end. At that point, it returns the URL. For the model pages on the NOMADS web site, each dead end is a model instance that can be examined using [ParseModelPage](#) or have data retrieved from it using [GribGrab](#).

Value

urls.out	A list of web page addresses, each of which corresponds to a model instance.
----------	--

Note

It is a good idea to set depth to a small number rather than leave it at the default value. Some models (such as the Global Forecast System) have a large number of instances, and crawling each one can take a lot of time. I recommend depth = 2, since the first URL may not have an active model on it yet if the model is still being uploaded to the server. In that case, the first URL will contain no data, and the second URL can be used instead.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[WebCrawler](#), [ParseModelPage](#), [NOMADSRealTimeList](#), [GribGrab](#)

Examples

```
#Get the latest 5 instances
#for the Global Forecast System 0.5 degree model

## Not run: urls.out <- CrawlModels(abbrev = "gfs_0p50", depth = 5)
```

DODSGrab

Download model data from the NOMADS server using the GrADS-DODS system.

Description

This function interfaces with the NOMADS server to download weather, ocean, and sea ice data. The available models can be viewed by calling [NOMADSRealTimeList](#) and [NOMADSArchiveList](#). The data arrives in ascii format, so this function can be used to retrieve data on any operating system.

Usage

```
DODSGrab(model.url, model.run, variables, time, lon, lat,
         levels = NULL, ensembles = NULL, display.url = TRUE,
         verbose = FALSE, request.sleep = 1)
```

Arguments

model.url	A model URL for a specific date, probably from GetDODSDates .
model.run	A specific model run to get, probably from GetDODSModelRuns .
variables	A list of the data types to get.
time	A two component vector denoting which time indices to get.

lon	A two component vector denoting which longitude indices to get.
lat	A two component vector denoting which latitude indices to get.
levels	A two component vector denoting which levels to get, if applicable.
ensembles	A two component vector denoting which ensemble runs to get, if applicable.
display.url	If TRUE, print out the URL for the data request.
verbose	If TRUE, give a very detailed description of the download. Default FALSE.
request.sleep	If multiple requests are to be sent to the server, pause by this many seconds between them. This is courteous and also helps prevent timeouts.

Value

model.data	A structure with a series of elements containing data extracted from GrADS-DODS system.
------------	---

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

References

<http://nomads.ncep.noaa.gov/>

See Also

[GetDODSDates](#), [GetDODSModelRuns](#), [GetDODSModelRunInfo](#)

Examples

```
#An example for the Global Forecast System 0.5 degree model
#Make a world temperature map for the latest model run

## Not run:
#Figure out which model is most recent
model.urls <- GetDODSDates("gfs_0p50")
latest.model <- tail(model.urls$url, 1)
model.runs <- GetDODSModelRuns(latest.model)
latest.model.run <- tail(model.runs$model.run, 1)

#Download worldwide temperature data at 2 m
variable <- "tmp2m"
time <- c(0, 0) #Analysis run, index starts at 0
lon <- c(0, 719) #All 720 longitude points
lat <- c(0, 360) #All 361 latitude points
model.data <- DODSGrab(latest.model, latest.model.run,
  variable, time, lon, lat)

#Make it into a nice array and plot it
model.grid <- ModelGrid(model.data, c(0.5, 0.5))
image(model.grid$z[1,1,,])
```

```
## End(Not run)
```

GetClosestForecasts *Get the forecast time closest to a given date for a given model*

Description

This function returns which forecast precedes the date and which forecast follows the date for a given model product. Thus a user can average the two forecasts together to provide a precise forecast for a given date. It is optimized for grib file retrieval.

Usage

```
GetClosestForecasts(abbrev, forecast.date, model.date = "latest",
  depth = NULL, verbose = TRUE)
```

Arguments

abbrev	The requested model product
forecast.date	What date you want a forecast for, as a date/time object. It must be in the UTC time zone.
model.date	Which model run to use, in YYYYMMDDHH, where HH is 00, 06, 12, 18. Defaults to "latest", which gets the most recent model uploaded to the server.
depth	How many model instances to return. This avoids having to download the entire model list (sometimes several hundred) if only the first few instances are required. Defaults to NULL, which returns everything. This input only makes sense when model.date != "latest".
verbose	Gives a detailed account of progress. Defaults to TRUE.

Value

forecasts\$model.url	URL to send to GribGrab for downloading data.
forecasts\$model.run.date	When the model was run.
forecasts\$back.forecast	Nearest forecast behind requested date.
forecasts\$fore.forecast	Nearest forecast after requested date.
forecasts\$back.hr	How many hours the back forecast is behind the requested date.
forecasts\$fore.hr	How many hours the fore forecast is in front of the requested date.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[BuildProfile](#), [GribGrab](#)

Examples

```
#Get the exact temperature profile of Chapel Hill, NC
#by performing a weighted average of GFS model forecasts.

#Figure out which forecasts to use
forecast.date <- as.POSIXlt(Sys.time(), tz = "UTC")
abbrev <- "gfs_0p50"

## Not run:
forecasts <- GetClosestForecasts(abbrev = abbrev, forecast.date)

## End(Not run)

#Get levels
pressure <- c(1, 2, 3, 5, 7,
10, 20, 30, 50, 70,
seq(100, 1000, by = 25))
levels <- paste(pressure, " mb", sep = "")

#Variables - temperature and height only
variables <- c("TMP", "HGT")

#Location
lon <- c(-79.052083)
lat <- c(35.907492)
model.domain <- c(lon - 1, lon + 1, lat + 1, lat - 1)

## Not run:
#Get the data for each
grb.info <- GribGrab(forecasts$model.url,
  c(forecasts$fore.forecast, forecasts$back.forecast), levels, variables,
  model.domain = model.domain)

fore.data <- ReadGrib(grb.info[[1]]$file.name, levels, variables)
back.data <- ReadGrib(grb.info[[2]]$file.name, levels, variables)

back.profile <- BuildProfile(back.data, lon, lat,
  spatial.average = TRUE, points = 8)

fore.profile <- BuildProfile(fore.data, lon, lat,
  spatial.average = TRUE, points = 8)

temps <- cbind(back.profile[[1]]$profile.data[, which(back.profile[[1]]$variables == "TMP"),,
```

```

fore.profile[[1]]$profile.data[, which(fore.profile[[1]]$variables == "TMP"),])

heights <- cbind(back.profile[[1]]$profile.data[, which(back.profile[[1]]$variables == "HGT"),],
  fore.profile[[1]]$profile.data[, which(fore.profile[[1]]$variables == "HGT"),])

time.gap <- forecasts$fore.hr - forecasts$back.hr
exact.temp <- (temps[,1] * abs(forecasts$fore.hr) + temps[,2] * abs(forecasts$back.hr))/time.gap
exact.hgt <- (heights[,1] * abs(forecasts$fore.hr) + heights[,2] * abs(forecasts$back.hr))/time.gap

#Plot results
plot(c(min(temps), max(temps)), c(min(heights), max(heights)), type = "n",
  xlab = "Temperature (C)", ylab = "Height (m)")
points(temps[,1], heights[,1], pch = 1, col = 1)
points(temps[,2], heights[,2], pch = 2, col = 2)
points(exact.temp, exact.hgt, col = 3, lty = 2, pch = 3)
legend("topleft", pch = c(1, 2, 3), col = c(1, 2, 3),
  legend = c(forecasts$back.forecast, forecasts$fore.forecast, as.character(Sys.time()))))

## End(Not run)

```

GetDODSDates

Find available model run dates for data on the GrADS - DODS system.

Description

This function checks the GrADS data server to see what dates and model subsets are available for model specified by ABBREV

Usage

```
GetDODSDates(abbrev, archive=FALSE, request.sleep=1)
```

Arguments

abbrev	A model abbreviation as specified in NOMADSRealTimeList or NOMADSArchiveList .
archive	Whether the model is on the NCEP real time server (FALSE) or on the NCDC model archive server (TRUE).
request.sleep	Seconds to pause between HTTP requests when scanning model pages - this prevents timeouts. Default 1.

Details

This function determines which dates are available for download for a particular model through the GrADS - DODS system. Once the user determines which dates are available, the output of this function can be passed to [GetDODSModelRuns](#) to determine which model runs can be downloaded.

Value

model	The model that was requested.
date	A list of model run dates available for download.
url	A list of URLs corresponding to the model run dates.

Note

Sometimes, sending lots of HTTP requests in rapid succession can cause errors. If messages resembling "Error: failed to load HTTP resource" appear, try increasing `request.sleep`. The code will take longer to execute but it will be more likely to finish successfully.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[GetDODSModelRuns](#), [DODSGrab](#)

Examples

```
#An example for the Global Forecast System 0.5 degree model

#Get the latest model url and date
abbrev <- "gfs_0p50"
## Not run:
urls.out <- GetDODSDates(abbrev)
print(paste("Most recent model run:", tail(urls.out$date, 1)))

#Get model dates from the GFS archive
abbrev <- "gfs-avn-hi"
urls.out <- GetDODSDates(abbrev, archive = TRUE, request.sleep = 1)

## End(Not run)
```

GetDODSModelRunInfo	<i>Get model coverage and data information for models on GrADS-DODS system.</i>
---------------------	---

Description

Given a URL from [GetDODSDates](#) and a model run from [GetDODSModelRuns](#), get information on the model domain, levels, and variables.

Usage

```
GetDODSModelRunInfo(model.url, model.run, download.file=TRUE)
```

Arguments

model.url	A URL for a model on the GrADS - DODS system, probably returned by GetDODSDates .
model.run	A specific model run, probably returned by GetDODSModelRuns
download.file	If TRUE, download the DODS .info file and read it in. If FALSE, try and read the .info file directly from the Internet.

Details

This routine grabs information about the latitude, longitude, and time coverage of a specific model instance. It also finds data about levels (if present) and lists all the available variables (though they may not have data in them). The user can refer to this information to construct calls to the DODS system via [DODSGrab](#). Note that the XML package has trouble interpreting https from time to time; this can be circumvented by keeping download.file=TRUE.

Value

model.info	Information provided by the GrADS - DODS system about the given model instance.
------------	---

Note

This function is very helpful in figuring out what's inside poorly documented models.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[GetDODSDates](#), [GetDODSModelRuns](#), [DODSGrab](#)

Examples

```
#An example for the Global Forecast System 0.5 degree model

#Get some information about the latest model url and date, real time server
abbrev <- "gfs_0p50"
## Not run:
urls.out <- GetDODSDates(abbrev)
model.url <- tail(urls.out$url, 1)
model.runs <- GetDODSModelRuns(model.url)
model.info <- GetDODSModelRunInfo(model.url, tail(model.runs$model.run, 1))
print(model.info)
```



```
## End(Not run)
```

`GetDODSModelRuns`*Find available model runs on the GrADS - DODS system.*

Description

Given a URL from [GetDODSDates](#), find which model runs are available for download on the GrADS - DODS system.

Usage

```
GetDODSModelRuns(model.url)
```

Arguments

<code>model.url</code>	A URL for a model on the GrADS - DODS system, probably returned by GetDODSDates .
------------------------	---

Details

This function determines which dates are available for download for a particular model through the GrADS - DODS system. Once the user determines which dates are available, the output of this function can be passed to [GetDODSModelRuns](#) to determine which model runs can be downloaded.

Value

<code>model.run</code>	A list of model runs available for the requested date.
<code>model.run.info</code>	Information provided by the GrADS - DODS system about each model run.

Note

To get model run information for archived analysis models, pass URLs directly from [NOMADSArchiveList](#) directly to `GetDODSModelRuns`.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[GetDODSDates](#), [DODSGrab](#), [GetDODSModelRunInfo](#)

Examples

```
#An example for the Global Forecast System 0.5 degree model

#Get the latest model url and date, real time server
abbrev <- "gfs_0p50"
## Not run:
urls.out <- GetDODSDates(abbrev)
model.url <- tail(urls.out$url, 1)
model.runs <- GetDODSModelRuns(model.url)
print(paste("Latest model run", tail(model.runs$model.run.info, 1)))

## End(Not run)
#Get model dates from the GFS analysis archive
abbrev <- "gfsanl"
model.url <- NOMADSArchiveList("dods", abbrev = abbrev)$url
## Not run:
model.runs <- GetDODSModelRuns(model.url)
print(model.runs$model.run.info)

## End(Not run)
```

GribGrab

Download grib file from the NOMADS server.

Description

This function interfaces with the programming API at <http://nomads.ncep.noaa.gov/> to download NOMADS model data. The available models can be viewed by calling [NOMADSRealTimeList](#). The data arrives in grib (gridded binary) format that can be read with [ReadGrib](#).

Usage

```
GribGrab(model.url, preds, levels, variables,
         local.dir = NULL, file.names = NULL,
         model.domain = NULL, tidy = FALSE, verbose = TRUE,
         check.url = TRUE, download.method = NULL)
```

Arguments

<code>model.url</code>	The address of a model download page, probably from CrawlModels .
<code>preds</code>	A vector of predictions (or model times) determined by the specific model from <code>model.url</code>
<code>levels</code>	A list of model levels to download.
<code>variables</code>	A list of model variables to download.
<code>local.dir</code>	Where to save the grib file, defaults to the current directory.
<code>file.names</code>	What to name the grib file, defaults to "fcst.grb".

<code>model.domain</code>	A vector of latitudes and longitudes that specify the area to return a forecast for. This is a rectangle with elements: west longitude, east longitude, north latitude, south latitude.
<code>tidy</code>	If TRUE, remove all files with the suffix ".grb" from <code>local.dir</code> prior to downloading a new grib file.
<code>verbose</code>	If TRUE, give information on connection status. Default TRUE
<code>check.url</code>	If TRUE, verify that the model URL is real and contains data. Default TRUE
<code>download.method</code>	Allows the user to set the download method used by <code>download.file</code> : "internal", "wget" "curl", "lynx". If NULL (the default), let R decide.

Value

<code>grib.info\$file.name</code>	The path and file name of the grib file that was downloaded.
<code>grib.info\$url</code>	The URL that the grib file was downloaded from

Note

This requires the external programs `wgrib2` and/or `wgrib` to be installed (depending on whether the files are in GRIB2 or GRIB format).

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

References

<http://nomads.ncep.noaa.gov/>

See Also

[CrawlModels](#), [ParseModelPage](#), [ReadGrib](#)

Examples

```
#An example for the Global Forecast System 0.5 degree model

#Get the latest model url
## Not run:
urls.out <- CrawlModels(abbrev = "gfs_0p50", depth = 1)

#Get a list of forecasts, variables and levels
model.parameters <- ParseModelPage(urls.out[1])

#Figure out which one is the 6 hour forecast
#provided by the latest model run
#(will be the forecast from 6-12 hours from the current date)
```

```

my.pred <- model.parameters$pred[grepl("06$", model.parameters$pred)]

#What region of the atmosphere to get data for
levels <- c("2 m above ground", "800 mb")

#What data to return
variables <- c("TMP", "RH") #Temperature and relative humidity

#Get the data
grib.info <- GribGrab(urls.out[1], my.pred, levels, variables)

#Extract the data
model.data <- ReadGrib(grib.info[[1]]$file.name, levels, variables)

#Reformat it
model.grid <- ModelGrid(model.data, c(0.5, 0.5))

#Show an image of world temperature at ground level
image(model.grid$z[2, 1,,])

## End(Not run)

```

GribInfo

Get grib file inventory.

Description

Find out what model, date, levels, and variables are contained in a grib file.

Usage

```
GribInfo(grib.file, file.type = "grib2")
```

Arguments

<code>grib.file</code>	Full path to a grib file.
<code>file.type</code>	Whether the file is in grib2 format ("grib2") or grib format ("grib").

Details

This function allows you to find out what is inside an unknown grib file. It does this by performing a system call to `wgrib2` or `wgrib`.

Value

<code>grib.info</code>	Inventory of the grib file. If the input is in grib2 format, you also get the grid definition.
------------------------	--

Note

In order to use this function, you need to have installed `wgrib2` (for grib2 files) or `wgrib` (for grib files). You can find these here: <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/> and <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib.html>.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[ReadGrib](#), [GetDODSModelRunInfo](#), [GribGrab](#)

Examples

```
## Not run:
#An example for the Global Forecast System 0.5 degree model

#Get the second latest model url, for stability
urls.out <- CrawlModels(abbrev = "gfs_0p50", depth = 2)

#Get a list of forecasts, variables and levels
model.parameters <- ParseModelPage(urls.out[2])

#Figure out which one is the 6 hour forecast
#provided by the latest model run
#(will be the forecast from 6-12 hours from the current date)

my.pred <- model.parameters$pred[grep("06$", model.parameters$pred)]

#What region of the atmosphere to get data for
levels <- c("2 m above ground", "800 mb")

#What data to return
variables <- c("TMP", "RH") #Temperature and relative humidity

#Get the data
grib.info <- GribGrab(urls.out[2], my.pred, levels, variables)

#Print out the inventory - it should match the requested data
grib.inv <- GribInfo(grib.info[[1]]$file.name, "grib2")

## End(Not run)
```

Description

Parse a web page, capturing and returning any links found.

Usage

```
LinkExtractor(url)
```

Arguments

url	A URL to scan for links.
-----	--------------------------

Details

This is an internal routine used by several functions in the package.

Value

links	A vector of link URLs
-------	-----------------------

Note

While it might be fun to try `LinkExtractor` on a large website such as Google, the results will be unpredictable and perhaps disastrous if depth is not set. This is because there is no protection against infinite recursion.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[WebCrawler](#)

Examples

```
#Find model runs for the
#GFS 0.5x0.5 model

## Not run:
urls.out <- LinkExtractor(
  "http://nomads.ncep.noaa.gov/cgi-bin/filter_gfs_0p50.pl")

## End(Not run)
```

MagnitudeAzimuth	<i>Convert zonal-meridional wind speeds to magnitude/azimuth.</i>
------------------	---

Description

Given zonal (East-West) and meridional (North-South) wind speeds, calculate magnitude of wind vector and azimuth from north, in degrees.

Usage

```
MagnitudeAzimuth(zonal.wind, meridional.wind)
```

Arguments

zonal.wind	A vector of zonal (East-West) winds, west negative.
meridional.wind	A vector of meridional (North-South) winds, south negative.

Value

winds\$magnitude	Magnitude of wind vector.
winds\$azimuth	Azimuth of wind vector in degrees from North

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

Examples

```
zonal.wind <- c(35.5, -2)
meridional.wind <- c(-5, 15)
winds <- MagnitudeAzimuth(zonal.wind, meridional.wind)
print(winds$magnitude)
print(winds$azimuth)
```

ModelGrid

Transform model data into an array

Description

This function takes output from [ReadGrib](#) or [DODSGrab](#) and produces an array with dimensions: levels x variables x longitudes x latitudes. This greatly reduces the size of the data set as well as makes it easier to manipulate. The data must be in a regular latitude/longitude grid (like the GFS model, for example).

Usage

```
ModelGrid(model.data, resolution,
          levels = NULL, variables = NULL,
          model.domain = NULL)
```

Arguments

<code>model.data</code>	Output from ReadGrib .
<code>resolution</code>	Resolution of grid, in degrees if <code>grid.type = "latlon"</code> , in kilometers if <code>grid.type = "cartesian"</code> , as a 2 element vector <code>c(East-West, North-South)</code> .
<code>levels</code>	The model levels to include in the grid, if <code>NULL</code> , include all of them.
<code>variables</code>	The model variables to include in grid, if <code>NULL</code> , include all of them.
<code>model.domain</code>	A vector <code>c(LEFT LON, RIGHT LON, TOP LAT, BOTTOM LAT)</code> of the region to include in output. If <code>NULL</code> , include everything.

Details

If you set the spacing of `lon.grid` and/or `lat.grid` coarser than the downloaded model grid, you can reduce the resolution of your model, possibly making it easier to handle.

Value

<code>z</code>	An array of dimensions levels x variables x lon x lat; each level x variable contains the model grid of data from that variable and level
<code>x</code>	Vector of longitudes
<code>y</code>	Vector of latitudes
<code>variables</code>	The variables contained in the grid
<code>levels</code>	The levels contained in the grid
<code>model.run.date</code>	When the forecast model was run
<code>fcst.date</code>	The date of the forecast

Note

Only use this function when the model grid is regular. For example, the GFS high resolution model is 0.5 x 0.5 degree across its domain. I have provided this function as a convenience since I only use it for manipulating GFS model data. I am not sure how well it works for other models. Consider yourself warned!

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[ReadGrib](#), [DODSGrab](#)

Examples

```
## Not run:
#Get some example data
urls.out <- CrawlModels(abbrev = "gfs_0p50", depth = 1)
model.parameters <- ParseModelPage(urls.out[1])
levels <- c("2 m above ground", "100 mb")
variables <- c("TMP", "RH") #Temperature and relative humidity
grib.info <- GribGrab(urls.out[1], model.parameters$pred[1], levels, variables)
#Extract the data
model.data <- ReadGrib(grib.info[[1]]$file.name, levels, variables)

#Make it into an array
gfs.array <- ModelGrid(model.data, c(0.5, 0.5))

#What variables and levels we have
print(gfs.array$levels)
print(gfs.array$variables)

#Find minimum temperature at the ground surface, and where it is
min.temp <- min(gfs.array$z[2, 1,,] - 273.15)
sprintf("%.1f", min.temp) #in Celsius

ti <- which(gfs.array$z[2, 1,,] == min.temp + 273.15, arr.ind = TRUE)

lat <- gfs.array$y[ti[1,2]] #Lat of minimum temp
lon <- gfs.array$x[ti[1,1]] #Lon of minimum temp

#Find maximum temperature at 100 mb atmospheric pressure
max.temp <- max(gfs.array$z[1, 1,,] - 273.15)
sprintf("%.1f", max.temp) #Brrr!

## End(Not run)
```

NOMADSArchiveList	<i>Archived models available for download through rNOMADS</i>
-------------------	---

Description

A list of abbreviations, names and URLs for the NOMADS models archived on the NCDC web site.. Users can refer to this list to find out more information about the available models, and rNOMADS uses the abbreviations to determine how to access the archives.

Usage

```
NOMADSArchiveList(url.type, abbrev = NULL)
```

Arguments

url.type	Determine whether to return a URL for extracting GRIB files ("grib") or for getting ascii format data directly from the server ("dods").
abbrev	Return information about the model that this abbreviation refers to. Defaults to NULL, in which case information about all the models available through rNOMADS.

Value

abbrevs	An abbreviation for each model
names	A full name for each model
urls	The web address of the download page for each model

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[NOMADSRealTimeList](#)

Examples

```
#The archived model list in rNOMADS  
archived.model.list <- NOMADSArchiveList("grib")
```

NOMADSRealTimeList	<i>Models available for download through rNOMADS</i>
--------------------	--

Description

Scans the NOMADS Real Time web site to generate a list of available model products. Users can refer to this list to find out more information about the available models, and rNOMADS uses the abbreviations to determine which URLs to scan and download.

Usage

```
NOMADSRealTimeList(url.type, abbrev = NULL)
```

Arguments

url.type	Determine whether to return a URL for extracting GRIB files ("grib") or for getting ascii format data directly from the server ("dods").
abbrev	Return information about the model that this abbreviation refers to. Defaults to NULL, in which case information about all the models available through rNOMADS.

Value

abbrevs	An abbreviation for each model
names	A full name for each model
urls	The web address of the download page for each model

Note

A big thanks to user hrbrmstr at Stack Overflow for helping with the NCEP web site parsing code.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[WebCrawler](#), [ParseModelPage](#), [NOMADSArchiveList](#), [GribGrab](#), [DODSGrab](#)

Examples

```
## Not run:
#Grib filter
model.list <- NOMADSRealTimeList("grib")

#DODS interface
model.list <- NOMADSRealTimeList("dods")

## End(Not run)
```

ParseModelPage	<i>Extract predictions, levels, and variables</i>
----------------	---

Description

This function parses the model download pages on NOMADS, and extracts information on predictions, levels, and variables available for each.

Usage

```
ParseModelPage(model.url)
```

Arguments

<code>model.url</code>	The URL of the model to extract information from, probably returned by NOMADSRealTimeList .
------------------------	---

Details

This function scrapes the web page for a given model and determines which predictions, levels, and variables are present for each. Predictions are instances returned by each model (for example, the GFS model produces 3 hour predictions up to 192 hours from the model run). Levels are regions of the atmosphere, surface of the Earth, or subsurface that the model produces output for (for example the GFS model has a “2 m above ground” level that has data for temperature, etc, at that height across the Earth). Variables are types of data (temperature, for example).

Value

<code>pred</code>	Model predictions
<code>levels</code>	Locations of data points
<code>variables</code>	Data types

Note

Many of the names for predictions, levels, and variables are somewhat cryptic.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[WebCrawler](#), [ParseModelPage](#), [GribGrab](#)

Examples

```
#An example for the Global Forecast System 0.5 degree model

#Get the latest model url
## Not run:
urls.out <- CrawlModels(abbrev = "gfs_0p50", depth = 1)

#Get a list of forecasts, variables and levels
model.parameters <- ParseModelPage(urls.out[1])

## End(Not run)
```

PlotWindProfile	<i>Plot wind speed and direction</i>
-----------------	--------------------------------------

Description

Creates a polar plot showing the azimuth, elevation, and magnitude of winds.

Usage

```
PlotWindProfile(zonal.wind, meridional.wind, height, magnitude = NULL,
  magnitude.range = c(0, 50), height.range = c(0, 50000), points = TRUE, lines = FALSE,
  radial.axis = TRUE, elev.circles = NULL, elev.labels = NULL, radial.lines = NULL,
  colorbar = TRUE, colorbar.label = NULL, north.label = TRUE, invert = FALSE, ...)
```

Arguments

zonal.wind	A vector or list of vectors of zonal (East-West) winds, west negative.
meridional.wind	A vector or list of vectors of meridional (North-South) winds, south negative.
height	A vector or list of vectors of height at which each wind measurement was taken.
magnitude	A vector or list of vectors of magnitudes to plot at each wind azimuth, instead of using the wind magnitudes. This allows plotting of other data (such as the speed of sound) along the wind vectors. Defaults to NULL.
magnitude.range	Ranges of wind speed to plot. Values greater or lesser than these will be saturated. Defaults to c(0, 50).
height.range	Ranges of heights to plot, values outside of this will not appear. Defaults to c(0, 50000).
points	Whether to plot measurements as points. Defaults to TRUE.
lines	Whether to connect measurements together with lines. Defaults to FALSE.

<code>radial.axis</code>	Whether to plot an axis at the outer edge of the diagram. Defaults to TRUE.
<code>elev.circles</code>	Plot a dashed circles as elevation scales. Defaults to NULL, which plots nothing.
<code>elev.labels</code>	What labels to put on the elevation scales. Defaults to NULL, which means no labels.
<code>radial.lines</code>	Plot lines radiating from the center of the plot showing azimuth directions. Defaults to NULL, which plots nothing.
<code>colorbar</code>	If TRUE, plot a color bar. Defaults to TRUE.
<code>colorbar.label</code>	What label to put on the colorbar. Defaults to NULL, which means no label.
<code>north.label</code>	If TRUE, put a label denoting the north direction. Defaults to TRUE.
<code>invert</code>	Reverses the edge and the center of the plot, making elevations decrease towards the center. Defaults to FALSE.
<code>...</code>	This function supports some optional parameters as well: <ul style="list-style-type: none"> • <code>r.axis</code> - radius of plot axis • <code>tick.len</code> - length of azimuth ticks • <code>r.axis.ticks</code> - Whether or not to put tick marks on the outer axis • <code>max.az</code> - If plotting lines and the difference between two segments is greater than this value, interpolate between them to make things smooth • <code>color.map</code> - A list of colors to use, defaults to <code>rainbow(n.cols, start=0, end=5/6)</code> • <code>n.cols</code> - Number of color bins in color map • <code>sub.col</code> - Color of internal (elevation and azimuth) axes as a vector of length 2 • <code>sub.lty</code> - Type of internal axes, as a vector of length 2 • <code>sub.lwd</code> - Width of internal axes, as a vector of length 2 • <code>elev.labels.az</code> - Which azimuth to plot elevation labels on • <code>point.cex</code> - size of points, if plotted • <code>pch</code> - Plot character of points, if plotted • <code>lty</code> - Line style, if lines are selected • <code>lwd</code> - Line thickness, if lines are selected • <code>colorbar.tick</code> - Where to put labels on colorbar

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

Examples

```
## Not run:
download.file("http://www.unc.edu/~haksaeng/rNOMADS/myTA.RDATA",
  destfile = "myTA.RDATA")
load("myTA.RDATA")
#Find the latest Global Forecast System model run
model.urls <- GetDODSDates("gfs_0p50")
latest.model <- tail(model.urls$url, 1)
model.runs <- GetDODSModelRuns(latest.model)
```

```

latest.model.run <- tail(model.runs$model.run, 1)

#Get model nodes

lons <- seq(0, 359.5, by = 0.5)
lats <- seq(-90, 90, by = 0.5)
lon.ind <- which(lons <= (max(myTA$lons + 360) + 1) & lons >= (min(myTA$lons + 360) - 1))
lat.ind <- which(lats <= (max(myTA$lat) + 1) & lats >= (min(myTA$lat) - 1))
levels <- c(0, 46)
time <- c(0, 0)

#Get data
variables <- c("hgtprs", "ugrdprs", "vgrdprs")
model.data <- DODSGrab(latest.model, latest.model.run,
  variables, time, c(min(lon.ind), max(lon.ind)),
  c(min(lat.ind), max(lat.ind)), levels)

#Build profiles
profile <- BuildProfile(model.data, myTA$lons + 360, myTA$lat,
  spatial.average = FALSE)

#Build profiles
zonal.wind <- NULL
meridional.wind <- NULL
height <- NULL

for(k in 1:length(profile)) {
  hgt <- profile[[k]]$profile.data[, which(profile[[k]]$variables == "hgtprs"),]
  ugrd <- profile[[k]]$profile.data[, which(profile[[k]]$variables == "ugrdprs"),]
  vgrd <- profile[[k]]$profile.data[, which(profile[[k]]$variables == "vgrdprs"),]

  synth.hgt <- seq(min(hgt),
    max(hgt), length.out = 1000)
  ugrd.spline <- splinefun(hgt, ugrd, method = "natural")
  vgrd.spline <- splinefun(hgt, vgrd, method = "natural")
  zonal.wind[[k]] <- ugrd.spline(synth.hgt)
  meridional.wind[[k]] <- vgrd.spline(synth.hgt)
  height[[k]] <- synth.hgt
}

#Plot them all
PlotWindProfile(zonal.wind, meridional.wind, height, lines = TRUE,
  points = FALSE, elev.circles = c(0, 25000, 50000), elev.labels = c(0, 25, 50),
  radial.lines = seq(45, 360, by = 45), colorbar = TRUE, invert = FALSE,
  point.cex = 2, pch = 19, lty = 1, lwd = 1,
  height.range = c(0, 50000), colorbar.label = "Wind Speed (m/s)")

## End(Not run)

```

Description

This function wraps `wgrib2` and `wgrib`, external grib file readers provided by the National Weather Service Climate Prediction Center (see <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/> and <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib.html>). `ReadGrib` extracts forecast data into R. It does this by building an argument string, executing a system call to the appropriate external grib file reader, and extracting the result. Note that `wgrib2` must be installed for `ReadGrib` to work for current grib files, and `wgrib` may need to be installed when looking at archived data.

Usage

```
ReadGrib(file.names, levels, variables,
         forecasts = NULL, domain = NULL, domain.type = "latlon",
         file.type = "grib2", missing.data = NULL)
```

Arguments

<code>file.names</code>	The path and file name of the grib files to read.
<code>levels</code>	The levels to extract.
<code>variables</code>	The variables to extract.
<code>forecasts</code>	Names of forecasts to extract. If <code>NULL</code> , include everything.
<code>domain</code>	Include model nodes in the specified region: <code>c(LEFT LON, RIGHT LON, NORTH LAT, SOUTH LAT)</code> . If <code>NULL</code> , include everything. This argument works for GRIB2 only.
<code>domain.type</code>	Either <code>"latlon"</code> (the domain argument is a latitude/longitude quadruplet) or <code>"index"</code> (the domain argument is a model node index quadruplet; much faster but requires you to know the model setup)
<code>file.type</code>	Whether the file is in GRIB (<code>"grib1"</code>) or GRIB2 (<code>"grib2"</code>) format. Default is <code>"grib2"</code> .
<code>missing.data</code>	Replace missing data in grib archive with this value. If <code>NULL</code> , leave the data out. Only works with <code>wgrib2</code> . Default <code>NULL</code> .

Details

This function constructs system calls to `wgrib` and `wgrib2`. Therefore, you must have installed these programs and made it available on the system path. Unless you are interested in accessing archive data that's more than a few years old, you can install `wgrib2` only. A description of `wgrib2` and installation links are available at <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/> and <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib.html>. Also, `rNOMADS` is focused towards GRIB2 files; I have included GRIB1 format support as a convenience.

Value

<code>model.data</code>	A structure with a series of elements containing data extracted from the grib files.
-------------------------	--

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

References

Ebisuzaki, W, Bokhorst, R., Hyvatti, J., Jovic, D., Nilssen, K, Pfeiffer, K., Romero, P., Schwarb, M., da Silva, A., Sondell, N., and Varlamov, S. (2011). wgrib2: read and write GRIB2 files. *National Weather Service Climate Prediction Center*, <http://www.cpc.ncep.noaa.gov/products/wesley/wgrib2/>

See Also

[GribGrab](#), [ArchiveGribGrab](#), [ModelGrid](#)

Examples

```
#Operational Forecast Data Extraction
#NCEP output is always in GRIB2 format - this makes things easy for us
#An example for the Global Forecast System 0.5 degree model

#Get the latest model url
## Not run:
urls.out <- CrawlModels(abbrev = "gfs_0p50", depth = 1)

#Get a list of forecasts, variables and levels
model.parameters <- ParseModelPage(urls.out[1])

#Figure out which one is the 6 hour forecast
#provided by the latest model run
#(will be the forecast from 6-12 hours from the current date)

my.pred <- model.parameters$pred[grep("06$", model.parameters$pred)]

#What region of the atmosphere to get data for
levels <- c("2 m above ground", "800 mb")

#What data to return
variables <- c("TMP", "RH") #Temperature and relative humidity

#Get the data
model.info <- GribGrab(urls.out[1], my.pred, levels, variables)

#Extract the data
model.data <- ReadGrib(model.info[[1]]$file.name, levels, variables)

#Reformat it
model.grid <- ModelGrid(model.data, c(0.5, 0.5))

#Show an image of world temperature at ground level
image(model.grid$z[2, 1,,])

## End(Not run)
```

`SubsetNOMADS`*Subset model data output*

Description

Subset data structure returned by [ReadGrib](#) or [DODSGrab](#) by variables, levels, etc.

Usage

```
SubsetNOMADS(model.data, levels = NULL, variables = NULL, lon = NULL,  
lat = NULL, ensembles = NULL, forecast.date = NULL, model.run.date = NULL)
```

Arguments

<code>model.data</code>	Data structure from ReadGrib or DODSGrab
<code>levels</code>	Vector of levels to keep
<code>variables</code>	Vector of variables to keep
<code>lon</code>	Vector of longitudes of model nodes to keep
<code>lat</code>	Vector of latitudes of model nodes to keep
<code>ensembles</code>	Vector of ensemble runs to keep
<code>forecast.date</code>	Vector of forecast dates to keep
<code>model.run.date</code>	Vector of model run dates to keep

Value

`model.data.sub` A subset of `model.data`.

Note

Multiple elements in each argument vector are obviously OR (i.e. variables are “tmpprs” OR “hgtprs”) but multiple subset vectors are AND. Thus it is simple to construct a `model.data.sub` with variables: tmpprs and hgtptrs only from ensemble runs 3 and 4, for example.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[ReadGrib](#), [DODSGrab](#), [ModelGrid](#), [BuildProfile](#)

Examples

```
## Not run:
#Plot winds from 20 GENS model runs

#Get the latest ensemble model run
model.urls <- GetDODSDates("gens")
latest.model <- tail(model.urls$url, 1)
model.runs <- GetDODSModelRuns(latest.model)
model.run <- tail(model.runs$model.run[grepl("all",
  model.runs$model.run)], 1)

#Define region of interest: Chapel Hill, NC
lon <- -79.052104
lat <- 35.907553

lons <- seq(0, 359, by = 1)
lats <- seq(-90, 90, by = 1)

lon.diff <- abs(lon + 360 - lons)
lat.diff <- abs(lat - lats)

model.lon.ind <- which(lon.diff == min(lon.diff)) - 1
model.lat.ind <- which(lat.diff == min(lat.diff)) - 1

#Set up call to NOMADS
time <- c(0, 0)      #Analysis(?) model only
node.lon <- c(model.lon.ind - 2, model.lon.ind + 2) #Longitude grid
node.lat <- c(model.lat.ind - 2, model.lat.ind + 2) #Latitude grid
variables <- c("ugrdprs", "vgrdprs", "hgtprs") #Wind speeds, and geopotential height
levels <- c(0, 25) #All available levels
ensembles <- c(0, 20) #All available ensembles

model.data <- DODSGrab(latest.model, model.run, variables, time,
  node.lon, node.lat, levels = levels, ensembles = ensembles)

#Plot winds
zonal.wind <- NULL
merid.wind <- NULL
height <- NULL

for(k in ((ensembles[1]:ensembles[2] + 1))) {
  model.data.sub <- SubsetNOMADS(model.data, ensembles = c(k),
    variables = c("hgtprs", "ugrdprs", "vgrdprs"))
  profile <- BuildProfile(model.data.sub, lon + 360, lat)
  hgt <- profile[[1]]$profile.data[, which(profile[[1]]$variables == "hgtprs"),]
  ugrd <- profile[[1]]$profile.data[, which(profile[[1]]$variables == "ugrdprs"),]
  vgrd <- profile[[1]]$profile.data[, which(profile[[1]]$variables == "vgrdprs"),]

  synth.hgt <- seq(min(hgt),
    max(hgt), length.out = 1000)
  ugrd.spline <- splinefun(hgt, ugrd, method = "natural")
}
```

```

vgrd.spline <- splinefun(hgt, vgrd, method = "natural")
zonal.wind[[k]] <- ugrd.spline(synth.hgt)
merid.wind[[k]] <- vgrd.spline(synth.hgt)
height[[k]] <- synth.hgt
}

PlotWindProfile(zonal.wind, merid.wind, height, lines = TRUE,
  points = FALSE, elev.circles = c(0, 15000, 30000), elev.labels = c(0, 15, 30),
  radial.lines = seq(45, 360, by = 45), colorbar = TRUE, invert = FALSE,
  point.cex = 2, pch = 19, lty = 1, lwd = 1,
  height.range = c(0, 30000), colorbar.label = "Wind Speed (m/s)")

## End(Not run)

```

WebCrawler

Get web pages

Description

Discover all links on a given web page, follow each one, and recursively scan every link found. Return a list of web addresses whose pages contain no links.

Usage

```
WebCrawler(url, depth = NULL, verbose = TRUE)
```

Arguments

url	A URL to scan for links.
depth	How many links to return. This avoids having to recursively scan hundreds of links. Defaults to NULL, which returns everything.
verbose	Print out each link as it is discovered. Defaults to TRUE.

Details

[CrawlModels](#) uses this function to get all links present on a model page.

Value

urls.out	A list of web page addresses, each of which corresponds to a model instance.
----------	--

Note

While it might be fun to try WebCrawler on a large website such as Google, the results will be unpredictable and perhaps disastrous if depth is not set. This is because there is no protection against infinite recursion.

Author(s)

Daniel C. Bowman <daniel.bowman@unc.edu>

See Also

[CrawlModels](#), [ParseModelPage](#)

Examples

```
#Find the first 10 model runs for the
#GFS 0.5x0.5 model

## Not run: urls.out <- WebCrawler(
  "http://nomads.ncep.noaa.gov/cgi-bin/filter_gfs_0p50.pl", depth = 10)
## End(Not run)
```

Index

- *Topic **chron**
 - GetClosestForecasts, [12](#)
 - *Topic **connection**
 - ArchiveGribGrab, [4](#)
 - CrawlModels, [9](#)
 - DODSGrab, [10](#)
 - GribGrab, [18](#)
 - LinkExtractor, [21](#)
 - WebCrawler, [36](#)
 - *Topic **documentation**
 - NOMADSArchiveList, [26](#)
 - NOMADSRealTimeList, [27](#)
 - *Topic **file**
 - ReadGrib, [31](#)
 - *Topic **hplot**
 - PlotWindProfile, [29](#)
 - *Topic **manip**
 - BuildProfile, [6](#)
 - MagnitudeAzimuth, [23](#)
 - ModelGrid, [24](#)
 - SubsetNOMADS, [34](#)
 - *Topic **package**
 - rNOMADS-package, [2](#)
 - *Topic **utilities**
 - CheckNOMADSArchive, [8](#)
 - GetDODSDates, [14](#)
 - GetDODSModelRunInfo, [15](#)
 - GetDODSModelRuns, [17](#)
 - GribInfo, [20](#)
 - ParseModelPage, [28](#)
- ArchiveGribGrab, [4](#), [8](#), [33](#)
- BuildProfile, [6](#), [13](#), [34](#)
- CheckNOMADSArchive, [5](#), [8](#)
- CrawlModels, [9](#), [18](#), [19](#), [36](#), [37](#)
- DODSGrab, [6](#), [7](#), [10](#), [15–17](#), [24](#), [25](#), [27](#), [34](#)
- GetClosestForecasts, [12](#)
- GetDODSDates, [10](#), [11](#), [14](#), [15–17](#)
- GetDODSModelRunInfo, [11](#), [15](#), [17](#), [21](#)
- GetDODSModelRuns, [10](#), [11](#), [14–17](#), [17](#)
- GribGrab, [9](#), [10](#), [13](#), [18](#), [21](#), [27](#), [28](#), [33](#)
- GribInfo, [20](#)
- LinkExtractor, [21](#)
- MagnitudeAzimuth, [23](#)
- ModelGrid, [24](#), [33](#), [34](#)
- NOMADSArchiveList, [4](#), [5](#), [8](#), [10](#), [14](#), [17](#), [26](#), [27](#)
- NOMADSRealTimeList, [9](#), [10](#), [14](#), [18](#), [26](#), [27](#), [28](#)
- ParseModelPage, [9](#), [10](#), [19](#), [27](#), [28](#), [28](#), [37](#)
- PlotWindProfile, [29](#)
- ReadGrib, [4–7](#), [18](#), [19](#), [21](#), [24](#), [25](#), [31](#), [34](#)
- rNOMADS (rNOMADS-package), [2](#)
- rNOMADS-package, [2](#)
- SubsetNOMADS, [34](#)
- WebCrawler, [9](#), [10](#), [22](#), [27](#), [28](#), [36](#)