Molecule identification from MS/MS for CASMI 2026: one change per submission, from 0.115 to 0.479

Charlene Leong

2 November 2026

Abstract

We rank candidate structures for 400 molecules from their tandem mass spectra in the CASMI 2026 Kaggle competition, scored by MRR@25 on the InChIKey connectivity block. The first submission scored 0.115 against a local estimate of 0.664; the estimate came from labels drawn from the same data as the candidates, and was retracted. Since then every number reported is a public leaderboard score, and each of the 18 submissions changed one thing (a nineteenth re-ran v19 unchanged). A PubChem-scale pool with a popularity prior, a learned spectrum-to-fingerprint model, and two forward models that predict each candidate's spectrum take the score to 0.349; a second PubChem pass that avoids structures similar to the copied train rows takes it to 0.356, against 0.421 for the public notebook these components come from. Running that notebook unchanged as our own kernel scored 0.415, +0.059 over the best of our own pipeline. Running a later public notebook, E006 with PubChem promotion at $rel > 150$ (public 0.446), unchanged as our kernel reproduced its public score exactly: 0.446, +0.031 over the first fork and +0.090 over our own best. It was the base every later change was measured against: raising its engine-2 fusion weight from 0.6 to 0.8 scored 0.437, and a third public notebook (0.451 upstream at its version 52) forked unchanged at its current version 53 scored 0.445. A fourth public notebook of the same lineage, which adds PubChemLite structures to the second engine's library (public 0.456), reproduced its score exactly as our kernel: 0.456, +0.010 over the E006 fork. A fifth, dmitriigluzdov's version 26, which adds joint ICEBERG+GLACIER reordering, fold-safe FPNets in the PubChem channel and a candidate-aware rank-1 promotion, scored 0.465 as our kernel, +0.009 over the 0.456 fork and the current best. A de novo route was closed offline before any submission: FRIGID, given the true formula, placed the answer in its top 10 for 0 of 50 held-out molecules against a pre-registered bar of 5. A sixth fork, a neural spectrum-model re-rank of the final 25 at twice its upstream weight, scored 0.444 and was discarded. A seventh, Busya PRIME's public 0.477 notebook, which keeps the same re-rank off rank 1 (weight 0.25 there, 0.75 for ranks 2–25) and adds a fragment check that may replace rank 1, scored 0.477 as our kernel, +0.012 over the 0.465 fork, the last measured gain. Analogue propagation across test molecules on top of it scored the same 0.477 and was discarded. A ninth, alex chilton's public 0.479 notebook, which adds a documentation prior and InChIKey14 deduplication on ranks 2–25, scored 0.479: our highest public score, but +0.002 is inside the run-to-run noise, so it is kept as the base, not counted as a gain. Two offline probes, a newer MIST encoder and an external spectral library, were closed without a submission. Blending the public neural scorer with three seed retrains of it scored 0.463 and was discarded. 31 submissions were made and all were scored. No calibrated local estimate of the score exists.

1 Task

Each test molecule has one or more LC-MS/MS spectra (400 molecules, 1213 spectra). A submission lists up to 25 SMILES per molecule; the score is the mean reciprocal rank of the answer, matched on the first 14 characters of the InChIKey. The competition runs notebooks offline, so every database and model is attached as a dataset. Only the public split of the leaderboard is visible.

2 Method

Current best: a fork of the public 0.479 notebook (dedup-fork, 0.479, inside the noise of 0.477). The submission is alex chilton's public notebook *CASMI26 LB 0.479 | MIDX Exact Dedup Fill* (itself Baidalin Adilzhan's *midx exact dedup fill*, unchanged), run byte-identical (md5 `a6871ca3...`) as the private kernel `charyeezy/casmi-fork479`, version 1, vendored at `casmi/notebooks/fork479/`. It is the merged-fork pipeline described next with a final layer on ranks 2–25: a documentation prior read from `pool_popularity.csv` (PubChem popularity 0.10, a spectral-library bonus 0.05 only where the best library match reaches 0.87, a natural-product bonus 0.02); the old leader pinned at rank 2 after a fragment-check move; and deduplication by the metric's InChIKey14 key, with freed slots filled by scored outside candidates.

Base before it: a fork of the public 0.477 notebook (merged-fork, 0.477). The submission was Busya PRIME's public notebook *LB 0.477 · Two 0.472 Fixes, Merged the Right Way*, run byte-identical (md5 `74efef20...`) as the private kernel `charyeezy/casmi-merged-fork`, version 1, vendored at `casmi/notebooks/fork477/`. It runs the pinned 0.465 pipeline described next once, then stacks two public changes that each showed 0.472. The first is alex chilton's leader-safe neural re-rank: each molecule's final 25 are re-ordered by reciprocal-rank fusion with sanpier's spectrum model (`sanpier/casmi-spectrum-model-v1`) at weight 0.25 for rank 1 and 0.75 for ranks 2–25. The second is Roman Tamrazov's Spectral Parallax, an untrained MetFrag-style fragment check that may replace rank 1; its leader moves are taken from the 0.50 (V2) order it was built on and merged as $[P_0, V_0]$ + the rest of the custom order. Candidate sets never change.

Previous best: a fork of the public version-26 notebook (data-fork, 0.465). The submission was dmitriigluzdov's public notebook *CASMI 26: The Data Behind Spectra to Structures*, version 26, run unchanged as the private kernel `charyeezy/casmi-data-fork`, vendored at `casmi/notebooks/fork464/`. It is the 0.456 recipe described next with four changes: GLACIER proxies kept where ICEBERG scores exist, joint ICEBERG+GLACIER re-ordering of proxy-covered lists, five fold-safe FPNets in the PubChem channel plus a sixth PubChem slot at rank 24, and a candidate-aware rank-1 PubChem promotion (Saner Turhaner, 0.465 upstream).

Before it: a fork of the public 0.456 notebook (pubchemlite-fork). The submission was Hongbin Gu's public notebook *casmi26-v465-v15-pop015*, run byte-identical (md5 `9d1ab164...`) as the private kernel `charyeezy/casmi-pubchemlite-fork`, version 1, on the same GPU image as the other forks, with 15 public datasets attached. It is the E006 pipeline described next, through the 0.451 recipe (promotion at $rel > 150$, the rank-2 hedge, standardised ChEBI/LIPID MAPS candidates), with three changes: PubChemLite structures added to engine 2's library (0.455 upstream), GLACIER proxy scores from other adducts for molecules without an $[M+H]^+$ spectrum (N1A), and the PubChem popularity weight at 0.15 instead of 0.25 (0.456).

Before that: a fork of the public E006 notebook (e006-fork, 0.446). The submission was the public notebook *CASMI26 | E006 + PubChem Promo rel>150 | LB 0.446*, run byte-identical (md5 `9829a966...`) as the private kernel `charyeezy/casmi-e006-fork`, version 2, on a T4. Its lineage is flexonafft's v80 recipe (public 0.436), then E006 (0.442), then the PubChem promotion's structure-evidence clause at $rel > 150$ instead of 250 (0.446). Three candidate sources run side by side: engine 1 is the v4n pipeline of the previous fork (below, top 60); engine 2 is a separate two-ranker engine over COCONUT, ChEBI/LIPID MAPS and train structures, with simulated ranker rows (top 40); and a PubChem-only channel ranks up to 25 non-pool structures by $z(f \cdot z) + 0.25\times$ popularity. ICEBERG and GLACIER (GLACIER on $[M+H]^+$ only) score the same-formula groups of all three lists. PubChem structures are merged into the engine-1 list when the library's maximum similarity is below 0.9, and the first is promoted to rank 1 when $(S > 6 \wedge pop \geq 5) \vee rel > 150$, where rel is how far the best PubChem $f \cdot z$ exceeds the best pool candidate's. The merged list is fused with engine 2 by weighted reciprocal rank, $1/(3 + r_1) + 0.6/(3 + r_2)$, re-ranked by GLACIER within formula groups, deduplicated

by the official metric identity with one vote per identity per engine, re-ranked by ICEBERG where GLACIER has no scores, and finally engine 2's top structure is inserted at rank 2 when it differs from rank 1 (`rank2`).

First fork: the 0.421 notebook (fork-v1, 0.415). From the first fork on 17 October the submission was the public notebook *CASMI26 | v4n Fusion + PubChem on public 0.421*, run unchanged as the private kernel `charyeezy/casmi-v4n-fork` on a T4. It searches every test spectrum against all of train and propagates matches to analogs; ranks a pool of train ∪ COCONUT ∪ generated derivatives with a public LightGBM ranker (`ranker_v4b.pkl`, 160 features, 4 boosters); joins PubChem candidates only when the library's maximum similarity is below 0.7; and re-scores with ICEBERG and GLACIER (off for library hits), falling back to fragment rescoring where they cannot run. Where our pipeline excluded the train structure behind each copied spectrum, the fork uses train matches as evidence.

Our own pipeline (best 0.356, v19), described below, is the record of what we built before the forks.

1. **Candidates.** Within a 5 ppm window of the molecule's neutral mass, the 1000 best-documented PubChem connectivities (by $\log(1+\text{substances})+\log(1+\text{PubMed})$) from a 106-million-structure tier, plus train structures in the window.

2. **Copied spectra.** 1189 of 1213 test spectra are bit-identical to a train row; every molecule has at least one. The train structure behind it is removed from the candidates.

3. **Ranking.** An ensemble of two public FPNet checkpoints predicts fingerprint logits z per spectrum and per polarity-merged spectrum; a candidate with fingerprint f scores $f \cdot z$, z-scored within the molecule, plus $0.25\times$ popularity.

4. **Forward models.** For the top 60, ICEBERG and GLACIER predict every candidate's spectrum. Within each same-formula group reaching the top 25 the order becomes $z(\text{score}) + \lambda\, z(\text{ICEBERG}) + \lambda\, z(\text{GLACIER})$, with $\lambda = 1$.

3 The funnel

stage	surviving
test molecules	400
candidates per molecule (median, max)	1038, 1445
copied train structures removed	400 (one per molecule)
molecules with $[M+H]^+$ / $[M+Na]^+$ spectra (forward-model coverage)	371
candidates scored by each forward model	21,865 of 23,552 sent
molecules whose top-1 the forward models change ($\lambda = 1$)	208

4 Results

Every score is the public leaderboard's. Thirty submissions were made, including one identical re-run; all were scored; none is omitted. One further run, the E006 fork's kernel version 1, failed its own GPU preflight and was not submitted (below).

v	change from the previous kept version	public MRR@25
1	fragment explainability over train's 275,798 structures	0.115
4	+ PubChem tier, 4000 nearest-mass per molecule	0.049
5	popularity shortlist of 300, +0.25× popularity	0.135
6	FPNet in place of fragment explainability	0.250
7	FPNet ensemble (two checkpoints)	0.258
8	popularity weight 0.15 (not kept)	0.254
9	shortlist 1000	0.261
11	copied train structures removed	0.262
12	ICEBERG, CPU, 269 of 371 molecules scored	0.286
13	ICEBERG on a T4, all 371	0.292
14	+ GLACIER, $\lambda = 0.5$	0.320
15	$\lambda = 1.0$	0.349
16	GLACIER on $[M+H]^+$ only (not kept)	0.345
17	$\lambda = 1.5$ (not kept)	0.346
18	+ spectrum-driven second PubChem pass (not kept)	0.353
19	second pass skips Tanimoto ≥ 0.5 to the copied structure	0.356
19	identical re-run	0.353
20	threshold 0.4 (not kept)	0.354
21	ICEBERG weight 0.5, GLACIER 1.0 (not kept)	0.333
fork-v1	the public 0.421 notebook, unchanged, as our kernel	0.415
fork-v2	PubChem channel over 10,000 rows, not 5000 (not kept)	0.415
e006-fork	the public 0.446 E006 notebook, unchanged, as our kernel	0.446
e006-v3	engine-2 fusion weight 0.8, not 0.6 (not kept)	0.437
spectra-fork	the public 0.451 notebook at version 53, unchanged (not kept)	0.445
pubchemlite-fork	the public 0.456 notebook (+ PubChemLite in engine 2), unchanged	0.456
data-fork	the public 0.464 notebook (v26), unchanged	0.465
neural-fork	the public 0.466 neural re-rank, weight 0.50 (not kept)	0.444
merged-fork	the public 0.477 notebook, unchanged	0.477
analogue-fork	+ analogue propagation on ranks 2–25 (not kept)	0.477
dedup-fork	the public 0.479 notebook, unchanged (inside the noise)	**0.479**
seed-blend	+ three seed retrains in the ranks 2–25 neural score (not kept)	0.463

Two levers account for almost all of the gain: the learned spectrum model (+0.115, v5 to v6) and the forward models (+0.087, v11 to v15). Tuning the shortlist and the prior's weight (v8, v9) moved the score by under 0.01, as did removing the copied structures, although that changed 267 top-1 picks: FPNet, trained on the copied rows, had returned their structures, and what replaced them was as rarely right. Identical runs differ by about ±0.005; v16, v17 and v18 fall inside it and were reverted. v18 is the instructive one: on 280 held-out train molecules, scored by an FPNet that never saw them, a second PubChem pass chosen by the spectrum lifted the answer's presence among the candidates from 126 to 236 and MRR@25 from 0.241 to 0.405. On the test set it moved the score by +0.004. The production FPNet was trained on the train rows the test spectra copy, and the pass's top-1 picks moved toward those copied structures (median Tanimoto 0.26 to 0.42 over the 192 molecules whose top-1 changed). v19 skips second-pass candidates with Tanimoto ≥ 0.5 to the copied structure (894 dropped over 400 molecules) and scored 0.356, +0.007 over v15. Against v18, which differs only by the filter, the gain is +0.003, inside the noise, so v19 is kept but does not clear G1; its threshold was also chosen after seeing v18. An identical re-run of v19 scored 0.353, and the 0.4 threshold (v20) 0.354: the filter's effect is not

distinguishable from noise.

The fork (fork-v1) scored 0.415, +0.059 over v19 and the largest single gain after FPNet. Its commit run took 1286 s, loaded the ranker, built every base list without error, injected 600 PubChem rows in its 12 smoke molecules with no failures, and GLACIER scored 11 of the 12. Widening its PubChem channel to the top 10,000 pass-1 rows (fork-v2), chosen from our recall probe (255 against 236 of 280 held-out answers), scored 0.415 again and was discarded.

The E006 fork scored 0.446 (submission 57298936), its public score exactly, +0.031 over fork-v1 and +0.090 over v19. Its first kernel version used the source's metadata, which names Kaggle's CPU image; the notebook's T4 preflight failed (`nvidia-smi` exit 12) and it was not submitted. Version 2 runs on the GPU image fork-v1 uses. Its commit run took 1183 s: engine ready, ranker 160 features and 4 boosters, 0 base errors, ICEBERG 11 of 12 and GLACIER 11 of 11 smoke molecules scored, the engine-2 cell applied on 400 rows, and 400 output rows. Scoring the hidden test took about 4 h. Because this fork reproduced its public score on the same account and day, fork-v1's 0.006 shortfall is not a general account or scoring-day effect.

Two later submissions changed or replaced the E006 fork and neither was kept. e006-v3 changed one byte (cell 35): the engine-2 weight in the final rank fusion, 0.8 instead of 0.6. Its gate passed (ranker 160 features and 4 boosters, 0 errors, ICEBERG and GLACIER 11 smoke molecules each) and it scored 0.437 (submission 57310111), −0.009, outside the noise. dmitriigluzdov's public notebook *CASMI 26: From Spectra to Structures* reports 0.451 at its version 52 (E006 with depth-7 engine-2 rankers and standardised ChEBI/LIPID MAPS candidates); Kaggle serves only version 53, which adds ranker seeds. Forked unchanged as the private kernel `charyeezy/casmi-spectra-fork` (md5 `951a34f8...`, the author's 4 datasets, GPU image), it scored 0.445 (submission 57311145), inside the noise of 0.446.

The fourth fork (pubchemlite-fork) scored 0.456 (submission 57435777, 20 October), its public score exactly, +0.010 over the E006 fork and outside the noise. Its gate passed: ranker 160 features and 4 boosters, 0 errors, ICEBERG and GLACIER 11 smoke molecules each, and 400 output rows; the commit run took about 1190 s. Its upstream steps from the 0.451 base (PubChemLite +0.004, then N1A and popularity 0.15 +0.001) are its author's public scores; we reproduced only the endpoint.

The fifth fork (data-fork) scored 0.465 (submission 57588653, 24 October), +0.009 over pubchemlite-fork and above the ±0.005 noise, so it clears G1 and is the new best. Its gate (`gate_fork451.py`) passed: 400 output rows, 12 smoke molecules full, ICEBERG and GLACIER 11 each.

The sixth fork (neural-fork) was not kept. Saner Turhaner's public notebook *PubChem + Neural025 — LB 0.466* runs a frozen 0.465 baseline, then re-orders each molecule's final 25 by reciprocal-rank fusion, $1/(3 + r_{\text{base}}) + w/(3 + r_{\text{neural}})$, with a separately trained spectrum model (`sanpier/casmi-spectrum-model-v1`); candidate sets never change. Upstream $w = 0.25$ scored 0.466. Our one change, $w = 0.50$, run as the private kernel `charyeezy/casmi-neural-fork` (vendored at `casmi/notebooks/fork466/`), scored 0.444 (submission 57615727, 25 October): −0.022 against $w = 0.25$ upstream and −0.021 against data-fork, which stays the best. Its gate (`gate_neural.py`) passed: 400 output rows, 12 smoke molecules full, ICEBERG and GLACIER 11 each, and the neural stage at weight 0.5 re-ordered all 12 smoke molecules and changed top-1 on 2, so the drop is the setting, not a broken run. At a flat weight the re-rank adds at most +0.001 to the 0.465 base; more weight hurts.

The seventh fork (merged-fork) scored 0.477 (submission 57822991, 31 October), reproducing its public score: +0.012 over data-fork, above the ±0.005 noise, so it clears G1 and is the new best. It keeps the neural re-rank from moving rank 1 (weight 0.25 there, 0.75 below) and lets the fragment check do so instead. Its gate (`gate_fork477.py`) passed: the 0.465 pipeline's checks from its stage logs, both layer reports written, the fragment check not skipped, and 400 output rows with the 12 smoke molecules full.

The eighth fork (analogue-fork, fork477 v3, kernel version 2, submission 57826104) was not kept. It adds one cell after the merge. The host allowed automated similarity between test molecules on

26 October. Test molecules whose leader has a library match ≥ 0.87 are anchors; for every other molecule whose spectra reach cosine ≥ 0.70 with an anchor, candidates below rank 1 gain $0.10 \times \cos \times$ Tanimoto(candidate, anchor leader), and the tail is re-sorted by $1/(3 + \text{position})$ + bonus. Rank 1 and the candidate sets never change. At most 113 of 400 visible-test molecules have such a neighbour; on labelled natural products such neighbours share structure 46% of the time. It scored 0.477 (31 October), identical to the base: not enough to move the leaderboard at $\lambda = 0.10$, and discarded.

The ninth fork (dedup-fork, submission 57867559, 1 November 20:37 AEDT) scored 0.479, reproducing its public score: +0.002 over merged-fork, below G1's +0.005 and inside the source's own run-to-run spread of about 0.002 (two notebooks reported at 0.478 on their pages rescored 0.468 and 0.476). It is numerically our highest score but not a measured gain; it is kept (KEEP) as the base because it is the current public line. Its gate (`gate_fork479.py`) passed: the merged-fork checks, plus the final layer's log lines; the prior loaded 710,701 pool records and reordered 12 of 12 smoke lists, with 0 dedup swaps, 0 outsider fills and no neutral-prior fallback.

Seed ensemble of the neural scorer (seed-blend, 6 November). We retrained sanpier's public spectrum model three times with its own recipe (16×500 steps, then a 16-epoch refit), changing only the seed, on the shared A100: about 1 h 26 min each, holdout scores 0.481, 0.487 and 0.465 against the public model's 0.484. Kernel version 2 of the dedup fork replaced the ranks 2–25 neural score with the mean per-molecule z-score of the public model and the three seeds, at equal weight. The gate passed (all three seeds ran on all 400 molecules; 300 had every member scoring; Spearman to the public scorer 0.913, 0.933, 0.928). It scored 0.463 (submission 58046573), -0.016, beyond the noise: discarded. The seeds rank much like the public model and two of three validate lower, so equal weights likely dilute it; that explanation is untested.

Two offline checks, 1 November, no submission. The MIST `msg_aug` encoder (Zenodo 23303289), run on an A100, reached mean fingerprint Tanimoto 0.385 on the 50 FRIGID molecules below (median 0.336, SE 0.022) against a gate of 0.40 fixed before the run; the old `mist_msg.pt` gave 0.261. Its `noaug` control is unusable (0.19 even on its own training spectra), so the source of the gain is not measured; the MIST/FRIGID line stays closed. An external GNPS + MassSpecGym library (Zenodo 20042904) holds 41,210 structures, of which 3,096 (13,814 spectra) are not already in train; they match 0 of 400 test molecules at cosine ≥ 0.5 within 20 ppm in the same ion mode. Every visible test spectrum matches train at ≥ 0.87, so the visible test looks like train stand-ins rather than the hidden test; for novel Enveda-180-like structures exact reach is about 0 by construction. Dropped without a submission.

Two offline checks, 18 October, no submission. Both ran on an Apple M5 on 18 October. FRIGID, the host-approved de novo model (MIST-MSG encoder, FRIGID-base decoder), was run on 50 Enveda-180 $[M+H]^+$ molecules that have no spectra in any public library, given the true formula. The bar, fixed before the run, was the answer in the top 10 for at least 5 of 50. It found 0 of 50 (top 1, 5 and 10 alike); the best of each top 10 reached mean Tanimoto 0.230 to the answer, 3588 of 3819 generations were valid (94%, a lower bound), at 35 s per spectrum. Diagnostics run after the result locate the failure in the encoder: MIST's predicted fingerprints reach Tanimoto 0.26 to the truth on these spectra against 0.63 on MassBank, while the decoder fed the true fingerprint recovers 49 of 50 at rank 1, an upper bound inflated because its 230-million-structure pretraining probably includes these compounds. The follow-up asked whether the fold-safe FPNet could replace MIST. On 50 Enveda-180 molecules held out of its training (re-drawn, since only 10 of the first 50 were held out), its fingerprints reach Tanimoto 0.245 in its own 10,226-bit space and 0.180 mapped to FRIGID's 4096-bit Morgan space, against 0.268 for MIST on the same molecules; it keeps only 1,464 of the 4,096 ECFP4 bits, and was trained to rank candidates rather than reconstruct bits. Retraining a 4096-bit head would take an estimated 10–15 T4 hours, not justified on this evidence.

Closed, with the reason.

- FRIGID de novo with MIST's fingerprints: 0 of 50 in the top 10 with the true formula, against

a pre-registered bar of 5 of 50; the encoder (Tanimoto 0.26 on Enveda spectra) is the bottleneck.

- FRIGID driven by the fold-safe FPNet: Tanimoto 0.180 in FRIGID's bit space (0.245 in its own) against MIST's 0.268 on the same 50 held-out molecules; a 4096-bit retrain (10–15 T4 hours) not justified.
- Engine-2 fusion weight 0.8 (e006-v3): -0.009 against 0.446.
- The 0.451 notebook at version 53 (spectra-fork): 0.445, no gain over 0.446.
- A neural spectrum-model re-rank of the final 25 at a flat weight 0.50 (neural-fork): 0.444, -0.022 against the same notebook's 0.466 at weight 0.25; more weight on rank 1 hurts. Kept off rank 1, the re-rank is part of merged-fork's +0.012.
- PubChem promotion at $rel > 100$ on E006: not run. Decided before any submission on a reach check from public evidence: its public sibling already scored 0.444 against 0.446.
- A different GLACIER checkpoint: ours is ms-pred's public MassSpecGym-trained GLACIER; the paper's contrastive fine-tune gives 69.95 against 69.69 MassSpecGym top-1, and its NIST gain needs NIST-licensed weights, so there is nothing to swap.
- Analogue propagation across test molecules on ranks 2–25 (analogue-fork): 0.477, no change from the 0.477 base at $\lambda = 0.10$ (at most 113 of 400 molecules reachable).
- MIST `msg_aug` as FRIGID's encoder: Tanimoto 0.385 on the 50 FRIGID molecules against a pre-registered gate of 0.40.
- External GNPS + MassSpecGym library (Zenodo 20042904): 3,096 structures new to train reach 0 of 400 test molecules.
- PubChem channel over 10,000 rows (fork-v2), forward-model weight 1.5 (v17), GLACIER on $[M+H]^+$ only (v16), popularity weight 0.15 (v8): inside the noise or below it.

Next. The base is still the 0.479 dedup fork (inside the noise of 0.477). No leader has published a method; public notebooks claim up to 0.482 (7 November), inside the noise of 0.479, and the seed blend closed the same-model ensemble route. The ICEBERG PubChem atlas, allowed by the host on 28 October, was reviewed on 3 November and skipped. A daily watch of public notebooks runs until 10 November and flags any claim of 0.485 or more. Analogue propagation on the 0.477 base scored 0.477 (no change). Before it, single settings of the E006 family look tuned (promotion threshold swept upstream, engine-2 weight 0.8 lost 0.009, forward models already at 1.0, a neural re-rank at weight 0.50 lost 0.021) and the de novo route failed offline, while the public lineage gained +0.044 in a week (0.421 to 0.465), then +0.012 more to 0.477. The cheapest lever left is a daily check of new public notebooks, forking any credible improvement that reproduces; it gave the 0.479 rebase. The leaderboard top is 0.521 (1 November).

5 What is not established

- **Why fork-v1 scores 0.415, not 0.421.** Both our runs of the unchanged notebook score 0.006 below its public score. The E006 fork reproduced its public 0.446 exactly on the same account and day, so a general account or day effect is ruled out; the cause is not established.
- **Why the 0.451 notebook scores 0.445 for us.** Its 0.451 is reported for version 52; we could fork only version 53, which adds ranker seeds. Whether the seeds or non-reproduction explain the gap is not established.

- **Whether a de novo route could help with a better encoder.** FRIGID found nothing with MIST's fingerprints; an encoder fine-tuned on Enveda's spectra is untested. The 39–52% of the test outside PubChem and COCONUT is the SOTA sweep's estimate, not a measurement on the hidden test.
- **Whether the 0.479 layer helps at all.** Its +0.002 over 0.477 is inside the source's own run-to-run spread; the effect of the documentation prior, leader pin and deduplication on their own is not measured by us.
- **What `msg_aug` would do to ranking.** At Tanimoto 0.26 FRIGID found 0 of 50; whether 0.385 gives any hits, or helps as an FPNet replacement or a re-ranking feature, was not run.
- **What in the 0.477 notebook earns its gain.** We ran it unchanged; how its +0.012 over the 0.465 fork divides between the leader-safe re-rank and the fragment check is not measured by us (each showed 0.472 upstream alone).
- **Why analogue propagation changed nothing.** The hidden rerun's logs are not visible, so whether few lists moved or the moves did not matter is not established; whether a larger λ than 0.10 would help is untested.
- **What in the version-26 notebook earns its gain.** We ran it unchanged; how its +0.009 over the 0.456 fork divides between the proxy re-ordering, the fold-safe FPNets, the sixth PubChem slot and the candidate-aware promotion is not measured by us.
- **What in the 0.456 notebook earns its gain.** We ran it unchanged; how its +0.010 over the E006 fork divides between PubChemLite, N1A and the popularity weight is its author's public scores, not our measurement.
- **What in E006 earns its gain.** We ran the 0.446 notebook unchanged, so how its +0.031 over fork-v1 divides between engine-2 fusion, the ChEBI/LIPID MAPS candidates, the simulated ranker rows, the metric-identity overlays, the rank-2 hedge and the promotion threshold is not measured by us.
- **A per-molecule breakdown of the forks' gains.** The hidden test is not visible, so which molecules it gains on, and how many have a library match, is unknown.
- **A local estimate of the score.** Train-derived labels rated our first submission at 0.664 against 0.115 on the leaderboard. Public notebooks cannot supply labels: their downloadable outputs score only about 12 smoke-test molecules and write a placeholder (`CCO`) for the rest, since full predictions run only inside Kaggle's scoring rerun; an earlier reading of "three lineages agreeing on 12 of 400" was those placeholders, as was a local 0.030 for the 0.421 notebook. Nor can train supply a test-like held-out set: only 41 isomer pairs in 2.54 million rows share a spectrum with at least 3 peaks, and 7 of them split across the fold-safe FPNet's training as test answers and copied structures do. A public labelled panel does not calibrate either: sanpier's 120-molecule panel ranks the 0.477 recipe below the 0.465 baseline (-0.004 ± 0.003), where the leaderboard gave +0.012. Each submission is the only measurement.
- **The private score.** Three choices — the shortlist size, λ, and GLACIER's input — were selected on the public split, as was v19's similarity threshold, so 0.356 is optimistic. The forks' settings were fixed by their authors before we saw any result, but tuned on the public leaderboard (the E006 notebook reports its threshold sweep there; the 0.456 notebook chose its popularity weight there), so 0.446, 0.456, 0.465, 0.477 and 0.479 may be optimistic too.

- **Candidate recall.** Whether the answer is among the candidates cannot be separated from ranking with one MRR; a wider PubChem channel added held-out answers but no score (fork-v2).
- **Why the data is shaped as it is.** The copied train structures are the answer for at most ∼46 of 400 molecules.
- **The environment switch alone.** The move to a pinned Python 3.12 image and RDKit 2026.3 (v12) was not measured separately.
- **Forward-model coverage on the hidden test.** Our pipeline left 29 visible-test molecules without forward-model evidence; the forks' coverage of the hidden test is unknown.

Sources

Code and history: `https://github.com/charleneleong-ai/ai4science/pull/80`. Forked notebooks: CASMI26 LB 0.479 | MIDX Exact Dedup Fill (current best), LB 0.477 · Two 0.472 Fixes, Merged the Right Way, casmi26-v465-v15-pop015, CASMI26 | E006 + PubChem Promo rel>150 | LB 0.446, CASMI 26: From Spectra to Structures and CASMI26 | v4n Fusion + PubChem on public 0.421. Every input and checkpoint with its version: `casmi/docs/experiment-card.md`. Competition: `https://www.kaggle.com/competitions/enveda-CASMI26-molecule-id-mass-spectra`.