

Matrix Inversion

Group 23

UM-SJTU Joint Institute

October 17, 2018

1 Introduction

2 Algorithm

- Cholesky Decomposition
- Levinson-Durbin Recursion

3 Implementation

4 References

Matrix Inversion

Matrix Inversion

Group 23

Introduction

Algorithm

- Cholesky
- Decomposition
- Levinson-Durbin
- Recursion

Implementation

References

Definition

The **inverse** of a $n \times n$ matrix \mathbf{A} , denoted as \mathbf{A}^{-1} , is a matrix that satisfies the expression

$$\mathbf{A}\mathbf{A}^{-1} = \mathbf{A}^{-1}\mathbf{A} = \mathbf{I}_n$$

Where \mathbf{I}_n is a $n \times n$ matrix with 1 on its diagonal and 0 otherwise.

Naive Matrix Inversion Method

Matrix Inversion

Group 23

Introduction

Algorithm

- Cholesky
Decomposition
- Levinson-Durbin
Recursion

Implementation

References

The naive method to solve matrix inversion is to treat the expression $\mathbf{A}\mathbf{A}^{-1} = \mathbf{I}_n$ as a linear equation system whose unknowns are $1 \times n$ vectors (rows of \mathbf{A}^{-1})

Solving this equation is of $\mathcal{O}(n^4)$ complexity (Gaussian Elimination)

Two Matrix Inversion Algorithms

Matrix Inversion

Group 23

Introduction

Algorithm

Cholesky
Decomposition
Levinson-Durbin
Recursion

Implementation

References

- Cholesky Decomposition
 - Complexity: $\mathcal{O}(n^3)$
 - Application: Hermitian matrices
- Levinson-Durbin Recursion
 - Complexity: $\mathcal{O}(n^3)$
 - Application: Symmetric Toeplitz matrices

Cholesky Decomposition

Matrix
Inversion

Group 23

Introduction

Algorithm

Cholesky
Decomposition

Levinson-Durbin
Recursion

Implementation

References

A symmetric matrix \mathbf{A} can be represented as product of two transpose triangular matrix as the following

$$\mathbf{A} = \mathbf{U}^T \mathbf{U}$$

where \mathbf{U} is an $n \times n$ upper triangular matrix.

Note: The implementation of finding \mathbf{U} for a certain \mathbf{A} can be in-place, so that no extra space is needed.

Based on the Cholesky decomposition, the equation can be transformed as

$$\mathbf{U}^T \mathbf{U} \mathbf{A}^{-1} = \mathbf{I}_n \Rightarrow \begin{cases} \mathbf{U}^T \mathbf{B} &= \mathbf{I}_n \\ \mathbf{U} \mathbf{A}^{-1} &= \mathbf{B} \end{cases}$$

and solving these two equations is simple because back/forward substitution can be directly applied.

What's more, the symmetric property of \mathbf{A} will also cause a reduction in the calculation.

Levinson-Durbin Recursion

Matrix Inversion

Group 23

Introduction

Algorithm

Cholesky
Decomposition

Levinson-Durbin
Recursion

Implementation

References

The first step of Levinson Durbin is to partition the matrix into blocks

$$\mathbf{A} = \begin{bmatrix} \mathbf{B}_{(n-1) \times (n-1)} & \mathbf{C}_{(n-1) \times 1} \\ \mathbf{D}_{1 \times (n-1)} & \mathbf{E}_{1 \times 1} \end{bmatrix}$$

The algorithm will first find an inversion of \mathbf{B} , denoted as \mathbf{B}^{-1} using recursive call and also find a **backward vector** of \mathbf{A} , denoted as \mathbf{u} which satisfies

$$\mathbf{A}\mathbf{u} = \begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \\ 1 \end{bmatrix}$$

Append a row of zeros to the bottom of \mathbf{B}^{-1} , and it can be seen that

$$\begin{bmatrix} \mathbf{B}_{(n-1) \times (n-1)} & \mathbf{C}_{(n-1) \times 1} \\ \mathbf{D}_{1 \times (n-1)} & \mathbf{E}_{1 \times 1} \end{bmatrix} \begin{bmatrix} \mathbf{B}_{(n-1) \times (n-1)}^{-1} \\ \mathbf{0}_{1 \times (n-1)} \end{bmatrix} = \begin{bmatrix} \mathbf{I}_{(n-1)} \\ \text{error}_{1 \times (n-1)} \end{bmatrix}$$

Then what should we do is add scaled \mathbf{u} on the columns of the new matrix to eliminate the errors. At last append \mathbf{u} to the right, then \mathbf{A}^{-1} is calculated.

Python specifics included to improve coding efficiency

Matrix Inversion

Group 23

Introduction

Algorithm

Cholesky
Decomposition
Levinson-Durbin
Recursion

Implementation

References

The basic object used is **numpy.mat** to store the matrices.
There are several reasons

- It is more convenient for storing and generating test matrices using numpy commands
- Many loops and case statement in the implementation can be substituted by matrices operations (row operation, matrix partition, matrix multiplication, etc.), and numpy.mat has adequate implementations of these operations.

References

Matrix Inversion

Group 23

Introduction

Algorithm

Cholesky
Decomposition

Levinson-Durbin
Recursion

Implementation

References

- Aravindh Krishnamoorthy, Deepak Menon (2013), "Matrix Inversion Using Cholesky Decomposition"
- Trench, W. F. (1964). "An algorithm for the inversion of finite Toeplitz matrices." J. Soc. Indust. Appl. Math., v. 12, pp. 515-522.
- Musicus, B. R. (1988). "Levinson and Fast Choleski Algorithms for Toeplitz and Almost Toeplitz Matrices." RLE TR No. 538, MIT