

General Formatting (draw.dtx)

Charles Duan

September 6, 2026

After parsing a citation string, *Hereinafter* must produce formatted text for each of the citation items in the string. This section describes the overall process of joining together citations, choosing among several possible citation forms for a given reference, and setting up any other requisite information for proper citation display.

An important element of citation formatting is keeping track of “state,” namely information about references cited so far that is needed for proper formatting of later citations in the document. As a simple example, it is necessary to keep track of the previously cited reference so that if the next reference is the same, text such as *id.* can be written. This feature of legal citation is discussed in `state.dtx`.

To implement information capture from a citation data structure, recall that the data structure itself uses macros `\hi@pse@cite`, `\hi@pse@page`, and so on that delimit the components of citation items. We simply need to define macros for each of those delimiters, thereby setting up all the necessary information.

`\hi@draw@citation`

This macro is the general entry point for user citation commands: It sets up the overall citation environment, invokes the citation string parser to obtain a data structure of parsed citation information, and then iterates over that data structure to produce formatted text. #1 and #2 are hooks that user citation commands can use to set up the citation environment, and #3 is the data structure received from `\hi@pse@parse`.

```
\def\hi@draw@citation#1#2#3{%
%
% Set up the environment
\ifnum\hi@citelevel>\z@ \begingroup\fi
\advance\hi@citelevel\@ne
\hi@state@startstring
\@hi@dotfalse
\hi@signals@init
%
% The TOA sometimes needs to be in vertical mode.
\if\hi@in@toa\else \leavevmode \fi
%
% Allow pre-citation hooks from the caller.
#1%
%
% Execute the citation.
#3%
%
% Execute post-citation hooks.
#2%
%
% Clean up
\hi@state@endstring
\advance\hi@citelevel\m@ne
\ifnum\hi@citelevel>\z@
\if\hi@dot \aftergroup\@hi@dottrue \fi
\endgroup
\fi
}
```

Counter for citation nesting level. This allows for citations inside citations (e.g., in parentheses).

```
\newcount\hi@citelevel
```

1 Drawing a Citation Item

The following tasks must be performed when drawing¹ each citation item within a citation string. While this list of tasks is largely of importance only to software implementers, it may be of interest to some cite-checkers to see the full list of considerations that go into formatting a single citation item.

1. Citation state must be updated; see `state.dtx`.
2. Each citation item maintains a list of parentheticals, which come from either the reference definition or the user's citation string content.
3. The citation item's components must be collected. Some references are able to modify the components afterwards.
4. The punctuation that precedes the citation item must be determined, according to the previous and current signals.
5. The short, long, or *id.* form of the citation must be chosen. That choice must be accounted for in computations for future citations.
6. If the citation is in a footnote, then how the citation affects this and other footnotes must be considered. See the discussion in `state.dtx`.
7. The citation must be recorded for indexing in a Table of Authorities.
8. If the citation text ends with a period, then any period following the item must be suppressed. This is obvious to human editors but surprisingly difficult for computers.
9. For a sentence-style citation, the first letter of each sentence must be capitalized. That could be the signal or a part of the citation text itself.

This macro is run for every citation item inside a citation string. It performs the following tasks.

```
\def\hi@pse@cite#1{%
```

First, it initializes the citation state and parentheticals list for this citation.

```
\hi@state@startelt % Resets all the \this@[x] macros to \relax
\hi@parens@reset
```

Next, it runs all the `\hi@pse@⟨component⟩` macros to collect necessary citation information. Furthermore, if this citation has `\mc@⟨cite⟩` defined, then execute it at this point to allow the desired modifications to the state variables.

```
#1%
\@ifundefined{mc@\this@case}{}{\@nameuse{mc@\this@case}}%
```

¹The term “drawing” in this manual refers to generation of formatting codes and outputs at the time of typesetting a citation.

Next it chooses the citation form to use according to `\hi@draw@chooscite`, saving the desired form to a temporary macro.

```
\hi@draw@chooscite{\def\hi@draw@this@type}%
```

The citation's effect on footnotes is next considered. See the discussion on citation counts in footnotes. Also the citation must be added to the Table of Authorities.

```
@testcase
\ifx\hi@draw@this@type\hi@draw@idname\fi{\hi@note@advance@id}%
\if\hi@name\fi{\hi@note@advance}%
\default{\hi@note@advance@id}%
\hi@draw@addtooa
```

Finally, the preceding punctuation and the citation itself can be produced.

```
\hi@draw@this@punct
\@test\ifx\hi@draw@this@punct\empty\fi{\hi@deferred@note@enditem\space}%
\hi@dotfalse
\hi@draw@this@fmtsig
\hi@draw@cite
```

After the citation text is produced, we record the use of the reference. The recordation seems to need to come after producing the text because some citation macros (inline statutes) call `\hi@record@choose` to figure out which form to use. We also update the state variables as appropriate.

```
\hi@record@cite\@this@case
\hi@state@endelt
```

Next, the parentheticals are displayed. They must be displayed *after* state variables are updated, because nested citations within the parentheticals ought to take into account the main citation. For example, a citation of case at 100 (explaining: case at 150) should be typeset with an *id.* form inside the parenthetical.

```
\hi@parens@show
\hi@nocap
\hi@nametrue
}
```

Adds the citation to the Table of Authorities.

```
\def\hi@draw@addtooa{%
\ifx\@this@page\relax
\hi@addtooa{\@this@case}{}%
\else
\hi@addtooa{\@this@case}{\@this@orig@page}%
\fi
}
```

Executes the appropriate drawing citation macro. The type has been set already in the macro `\hi@draw@this@type`.

```
\def\hi@draw@cite{%
\@test\ifx\hi@draw@this@type\hi@draw@idname\fi{%
\ifundefined\hi@draw@this@type_@{\@this@case} {%
\hi@draw@id
}%
\@nameuse{\hi@draw@this@type_@{\@this@case}%
}%
}%
\@ifundefined\hi@draw@this@type_@{\@this@case} {%
\hi@draw@cite@undefined
}%
\@nameuse{\hi@draw@this@type_@{\@this@case}%
}%
}%
}
```

If there is no macro for the current reference and citation type, then this macro is run by default.

```
\def\hi@draw@cite@undefined{%
\expandafter\hi@missing@cite\expandafter{\@this@case}%
\textbf{\hi@usevol{\@this@case\hi@maybepage{ at }}\hi@nocap
}
```

Draws *id.* citations, which consist of a volume number, keyword (defined as `\hi@id`), and page number.

```
\def\hi@id{\hi@fn@latin{id.}\protect\@hi@dottrue}%
\def\hi@draw@idname{idc}
\def\hi@draw@id{%
  \hi@citeguts{%
    \@testcase
      \ifx\@this@vol\relax\fi}%
    \ifx\@this@vol\@last@vol\fi}%
    \default{\@this@vol\hi@nocap\space}%
  \hi@id
  \hi@ifsamepage{}{%
    \hi@pageordefault{%
      ~\hi@page@atorsect
    }{}%
  }%
}%
}
```

`\hi@ifsamepage` `{\if-true}{\if-false}` Determines if `\@this@page` is the same as `\@last@page`. Runs `\if-true` if so, or `\if-false` otherwise. The command is robust so it may be included in reference definitions.

```
\DeclareRobustCommand\hi@ifsamepage{%
  \@test\ifx\@this@page\@last@page\fi
}
```

1(a) Reading Citation Item Components These are macros corresponding to each of the components from the citation state machine.

Reads the optional argument, setting the appropriate state variable.

```
\def\hi@pse@opt#1{\def\@this@opt{#1}}
```

Reads the signal, volume number, and reference name, setting state variables as appropriate.

```
\def\hi@pse@svr#1{\hi@pse@sigvolref{#1}\hi@draw@sigvolref}
\def\hi@draw@sigvolref#1#2#3{%
  %
  % Set the next signal, and receive the punctuation and formatted signal to
  % draw in the two given macros.
  %
  \hi@signals@set{#1}{\@twodef\hi@draw@this@punct\hi@draw@this@fmtsig}%
  %
  % Set the remaining state variables.
  \ifstrempy{#2}{\def\@this@vol{#2}}%
  \def\@this@case{#3}%
}
```

Reads and formats the page number per `\@this@case` (which should already be set).

```
\def\hi@pse@page#1{%
  \def\@this@orig@page{#1}%
  \ifundefined{pc@\@this@case}{%
    \protected@edef\@this@page{\hi@fmt@pageno{#1}}%
  }{%
    \@nameuse{pc@\@this@case}{#1}%
  }%
}
```

Processes a parenthetical in a citation item. See the `parens.dtx`.

```
\def\hi@pse@paren#1{%
  \hi@paren@parse{#1}%
}
```

2 Citation Forms

When formatting a citation item, each reference can generate a variety of citation forms—full citations, short citations, inline texts, and so on. For each reference `\<ref-name>`, each of its citation forms is stored in a macro `\<prefix>@<ref-name>`, with `\<prefix>` being an identifier of the citation form. For example, `\fc@brown` would be the definition of the full citation for a reference named brown.

Each citation form is given and explained below, along with its $\langle prefix \rangle$.

Type	Prefix	Description
Full	fc	The full citation form.
Short	sc	The non- <i>id.</i> short form. Defaults to the full form.
List	lc	The form used in the Table of Authorities. Defaults to the full form.
Pin cite	pc	Some references have special ways of treating pin cite numbers. This citation form is used in the pin cite formatting routine (see <code>pages.dtx</code>).
<i>Id.</i>	idc	The form to be used for immediately successive citations, if not the standard <i>id.</i> form.
Inline full	ifc	The inline citation form to be used upon the first inline usage.
Inline short	isc	The inline citation form to be used on subsequent inline usages.

It may be helpful for debugging to see these macros. To do so, include the following in your document:

```
\expandafter\show\csname  $\langle prefix \rangle$ @ $\langle ref-name \rangle$ \endcsname
```

3 Choosing the Citation Form

When a reference is cited, *Hereinafter* must determine which citation form to use. The choice depends on the citation command issued (see `iface.dtx`) and the context within the document (primarily, what citations have come before). The following rules inform that choice.

- An *id.* citation is appropriate only when the reference being cited matches the last reference, recorded as described in `state.dtx`. In any event, it is never appropriate in an inline citation.
- The table of authorities form is chosen for non-nested citations inside a table of authorities. If no table of authorities form is present for a given reference, the full citation form is used instead. For nested citations inside a table of authorities, the full citation is always used.
- In other cases, a complex algorithm must be applied to choose between the short and full citation forms.² This algorithm is described in `short.dtx`.

²As described in `short.dtx`, the algorithm is complex because it depends on where previous citations were used: A full citation in a footnote, for example, does not justify a short form in main body text.

In any event, if no short citation form is defined for a reference, the full citation form is used.

- In an inline context, the same algorithm described in `short.dtx` is used, except the inline full/short citation forms are preferred if they are defined.

In addition to choosing a citation form, the package sometimes allows a “nameless” variant of a citation form. For example, a citation to a case may omit the name of the case if the name was previously used in the text. In general, a nameless citation to a reference is permitted if the previous inline citation was to the same reference. There are some nuances to what constitutes the “previous” citation, as described in `state.dtx`.

Chooses among the citation forms. #1 is a callback that is given the prefix of the chosen citation form. Also sets `\hi@noname` as appropriate.

```
\def\hi@draw@choossecite#1{%
  \@testcase
  \ifhi@inline\fi{\hi@draw@choossecite@inline{#1}}%
  \ifx\@last@case\@this@case\fi{#1{dc}}%
  \default{%
    \ifx\@last@inline\@this@case \hi@noname \fi
    \hi@draw@choossecite@{#1}%
  }%
}
```

Chooses the citation form when it is certain not to be *id*. This macro distinguishes the table of authorities, and otherwise defers to `\hi@record@choose`.

```
\def\hi@draw@choossecite@#1{%
  \@test\ifhi@in@toa\fi{%
    \ifnum\hi@citelevel=\@one\fi{%
      \hi@draw@which{lc,fc}{#1}%
    }%
  }%
  \hi@record@choose{\@this@case}{%
    #1{fc}%
  }%
  \hi@draw@which{sc,fc}{#1}%
}%
}
```

Chooses the citation form for inline citations.

```
\def\hi@draw@choossecite@inline#1{%
  \hi@record@choose{\@this@case}{%
    \hi@draw@which{ifc,fc}{#1}%
  }%
  \hi@draw@which{isc,ifc,sc,fc}{#1}%
}%
}
```

Selects the first prefix for which the current reference has a defined macro. #1 is a comma-separated list of prefixes, and #2 is a callback that is given an argument of the selected reference.

```
\def\hi@draw@which#1#2{%
  \find@in{,}{#1}{\hi@draw@which@{#2}}{#2{#1}}%
}
% |#1| is the callback, |#2| the first prefix, |#3| the rest of the prefixes.
\def\hi@draw@which@#1#2#3{%
  \ifundefined{#2@\@this@case}{\hi@draw@which{#3}{#1}}{#1{#2}}%
}
```

In previous versions, the nameless variant of citations was chosen by the pseudo-reference name `*`. The package now determines whether to use nameless variants automatically, but still accepts `*` as a synonym for the previous inline reference.

```
\@namedef{mc@*}{%
  \ifx\@last@inline\relax
    \PackageError{hi}{pkgnam}{Star citation must follow an inline

```

```

citation){Probably change the star citation out}%
\def\@this@case{???}%
\else
% \hi@noname -- See \hi@draw@choosecite
\let\@this@case\@last@inline
\fi
}

```

4 Missing References

Sometimes it is desirable to cite to a reference that has not yet been defined. This allows authors familiar with a reference to cite it without having to stop immediately to enter the reference definition and parameters. The package formats the undefined references in bold and also compiles a list of undefined references, which is displayed at the end of document compilation.

As a convenience, the package also keeps track of defined references that are missing page numbers. The user enters the unknown page number as a question mark, and the package displays a list of all unentered page numbers at the end of compilation.

```

\def\hi@missing@cites{}
\def\hi@missing@pages{}
%
\def\hi@missing@cite#1{%
\expandafter\hi@missing@cite@\expandafter{\the\inputlineno}{#1}%
}
\def\hi@missing@cite@#1#2{%
\ifundefined{hi@miss@cite@#2}{%
\g@addto@macro\hi@missing@cites{\hi@missing@display{#2}{\l. #1}}%
\expandafter\let\csname hi@miss@cite@#2\endcsname\@empty
}{}%
}
\def\hi@missing@page#1{%
\expandafter\hi@missing@page@\expandafter{\the\inputlineno}{#1}%
}
\def\hi@missing@page@#1#2{%
\g@addto@macro\hi@missing@pages{\hi@missing@display{#2}{\l. #1}}%
}
\def\hi@missing@display#1#2{%
\space\space\space\space\pad@string{#1}{iiiiiiiiiiiiiiiiiiii} #2%
\MessageBreak
}
\AtEndDocument{%
\ifx\hi@missing@cites\@empty\else
\PackageWarning\hi@pkgname{%
The following citations were undefined:\MessageBreak
\hi@missing@cites
}%
\fi
\ifx\hi@missing@pages\@empty\else
\PackageWarning\hi@pkgname{%
The following citations were missing page numbers:\MessageBreak
\hi@missing@pages
}%
\fi
}

```