

Endnotes (endnotes.dtx)

Charles Duan

September 6, 2026

The usual $\LaTeX$ endnote option stores the unexecuted text of notes and then executes them all at the end of the document. This does not work for legal citations because the content of the body text interacts with the content of the endnotes: An inline citation in body text can change the appearance of citations in the notes, for example. Instead, it is necessary to typeset endnotes as they are encountered and store them to a vertical box that can be displayed upon request.

To use endnotes, include the option `endnote` with this package. This will automatically convert all footnotes to endnotes, including citations using `\note`. (Specifically, all footnote texts will be executed with the macro `\HiEndNote` described below). The following macros may further be used to control the content of the endnotes.

If endnotes are not used, then define the user commands to do nothing.

```
\let\HiEndNote\@gobble
\let\HiEndDelay\@gobble
\let\HiEndSection\relax
\def\hi@useendnotes{%
```

The subsequent code is only run if endnotes are requested.

`\hi@endnotes` is the vertical box where endnotes will be stored until used.

```
\newbox\hi@endnotes
```

`\@footnotetext` is redefined to run `\HiEndNote`, adding the note text to the vertical box. Note that, as described in `state.dtx`, the `\@footnotetext` macro will be decorated for citation count tracking with `\AtBeginDocument`, so the tracking macros need not be added here.

```
\long\def\@footnotetext##1{%
  \HiEndNote{%
    \reset@font\normalsize
    \parskip\z@
    \HiEndFont
    \protected@edef\@currentlabel{%
      \csname p@footnote\endcsname\@thefnmark
    }%
    \color@begingroup
    \makefn@text{\ignorespaces##1}%
    \color@endgroup
  }%
}%
```

`\HiEndNote` $\{\langle text \rangle\}$

Adds arbitrary text to the endnote list. The text is set in vertical mode.

```
\long\def\HiEndNote##1{%
  \global\setbox\hi@endnotes\vbox{%
    \ifvoid\hi@endnotes\else
      \prevdepth\dp\hi@endnotes
    \unvbox\hi@endnotes
  }%
}
```

```

\fi
\ifx\hi@endnotes@delayed\relax\else
\hi@endnotes@delayed
\global\let\hi@endnotes@delayed\relax
\fi
##1%
}%
}

```

\HiENDelay $\{\langle text \rangle\}$

reserves a certain text for future adding to the endnote list. The text is actually added only if other endnote text is added before `\HiENDelay` is invoked a second time. This is useful for adding chapter or section heading markers to an endnote list conditionally. If the chapter contains no endnotes, then the chapter heading will never be inserted into the endnote list.

Again, the text is set in vertical mode.

```

\def\HiENDelay##1{%
\global\def\hi@endnotes@delayed{##1}%
}
\let\hi@endnotes@delayed\relax

```

\HiENSection Inserts text into the endnote list (using `\HiENDelay`) indicating where a section heading occurred. The section number is inserted automatically, preceded by “Section.”

```

\def\HiENSection{%
\HiENDelay{%
\vskip .7\baselineskip
{\noindent\large\textbf{Section \@currentlabel}\par}%
\penalty\@M
\vskip .3\baselineskip
}%
}

```

\HiENFont `\HiENFont` can be defined to set the font for endnotes. It must be defined before endnotes are added, since once they are added the notes have been typeset and cannot be changed.

```

\def\HiENFont{}%

```

\theendnotes `\theendnotes` emits the list of endnotes. If the macro is not called, it will be automatically executed at the end of the document with a warning.

```

\def\theendnotes{%
\setbox\hi@endnotes\vtop{\unvbox\hi@endnotes}%
\@tempskipa\baselineskip
\multiply\@tempskipa\m@ne
\advance\@tempskipa\prevdepth
\advance\@tempskipa\ht\hi@endnotes
\multiply\@tempskipa\m@ne
\ifdim\@tempskipa>\z@ \vskip\@tempskipa \fi
\unvbox\hi@endnotes
}
\AtEndDocument{%
\ifvoid\hi@endnotes\else
\PackageWarning\hi@pkgname{%
Endnotes not displayed;\MessageBreak inserting them%
}%
\vskip\baselineskip
\footnoterule
\theendnotes
\fi
}%
}% End of |\hi@useendnotes|

```