

Legacy Command Names (legacy.dtx)

Charles Duan

September 6, 2026

The following are legacy macro names that have been changed to conform to *Hereinafter*'s naming convention of starting user-level macros with the prefix `\Hi`. By default, they will be defined only if they are not previously defined by another package, but a warning will be issued if another package has defined them. The options `legacy` and `nolegacy` affect this behavior.

`\hi@legacy@cmd` $\{\langle legacy \rangle\}\{\langle canonical \rangle\}\{\langle xref \rangle\}$
Defines $\langle legacy \rangle$ to execute $\{\langle canonical \rangle\}$, after checking whether $\langle legacy \rangle$ exists. The $\langle xref \rangle$ is used only for manual display purposes.

```
\def\hi@legacy@cmd#1#2#3{%
  \hi@legacy@chk#1{%
    \def#1{#2}% Rather than \let, in case macro is redefined later
  }%
}
```

`\hi@legacy@chk` $\{\langle legacy \rangle\}\{\langle if-true \rangle\}$
Checks whether $\langle legacy \rangle$ ought to be defined. If so, then run $\langle if-true \rangle$. By default, the test is whether $\langle legacy \rangle$ is already defined, and a warning is issued. Package options change this.

```
\def\hi@legacy@chk#1#2{%
  \ifdefined#1%
    \ifx#1\relax
      #2
    \else
      \PackageWarning\hi@pkgname{%
        Legacy command \string#1\space already defined; not overwriting%
      }%
    \fi
  \else
    #2%
  \fi
}
```

Legacy name	New Name	See
\sic	\HiSic	iface.dtx
\PageNumber	\HiParsePin	pages.dtx
\AuthorityTag	\HiTOATag	toa.dtx
\enabletoa	\HiEnableTOA	toa.dtx
\disabletoa	\HiDisableTOA	toa.dtx
\NewTOACategory	\HiNewTOACat	toa.dtx
\SetTOACategory	\HiSetTOACat	toa.dtx
\DefaultTOACategory	\HiDefaultTOACat	toa.dtx
\addtooa	\HiAddToTOA	toa.dtx
\StarCount	\HiStarCount	toa.dtx
\StarText	\HiStarText	toa.dtx
\StarMark	\HiStarMark	toa.dtx
\toaheading	\HiTOAHeading	toa.dtx
\AuthorityTable	\HiTOATable	toa.dtx
\TOALeader	\HiTOALeader	toa.dtx
\toacite	\HiTOACite	toa.dtx
\toaskip	\HiTOASkip	toa.dtx
\PassimText	\HiTOAPassim	toa.dtx
\toahangindentlen	\HiTOAIndent	toa.dtx
\AbbreviateFor	\HiAbbrev	abbrevs.dtx
\ExplanatoryPhrase	\HiExplPhrase	abbrevs.dtx
\MakeFontPack	\HiFontPack	fonts.dtx
\UseFontPack	\HiUseFontPack	fonts.dtx
\UseFontFor	\HiFont	fonts.dtx
\noid	\HiNoId	state.dtx
\fullcite	\HiFullCite	state.dtx
\nofullcite	\HiNoFullCite	state.dtx
\fulltitle	\HiFullTitle	state.dtx
\resetcitationforms	\HiResetState	state.dtx
\ShowCitationState	\HiShowState	state.dtx
\EndnoteText	\HiEndNote	endnotes.dtx
\EndnoteTextDelayed	\HiENDelay	endnotes.dtx
\SectionNote	\HiENSection	endnotes.dtx
\EndnoteFont	\HiENFont	endnotes.dtx

0(a) Citation Command Shortcuts The following are not “legacy” commands but rather are shortcuts for the citation commands described in `iface.dtx`.

Shortcut name	Full Name	See
\Ct	\sentence	iface.dtx
\ct	\clause	iface.dtx
\Ci	\Inline	iface.dtx
\ci	\inline	iface.dtx
\cn	\note	iface.dtx
\cx	\HiAddToTOA	iface.dtx