last time

storing page tables in memory

as array of page table entries

page table entries encoded as integer

page table base register — OS tells CPU base address of array

each program memory access = two real ones

preview: multi-level page table lookup

lab this week

no lab

a subset of TAs will be in Rice 130 to give office-hour-type help

anonymous feedback (1)

got this last Tuesday, missed addressing last Thursday (sorry!)

"Can you make the quizzes have more number of questions and/or each MCQ be worth less points? The percentage scores decreases drastically by making just one mistake. The quiz is also worth a huge portion of the final grade and being able to do better on it would help get a good grade."


probably should be some more questions, but I think I'd get more complaints if I really embraced more questions would like to use comments to give more naunce in quiz grades

anonymous feedback (2)


"I was hoping to have a little lecture time dedicated to explaining the nuances to the homework assignment, especially a clarification for what ptbr points to, and the difference between VPN and Physical page numbers in the context of this homework assignment"

"Do you mind re-visiting and explaining page_allocate()'s behavior?"


page table lookup (and translate())




page table lookup (and translate())



page table lookup (and allocate)



page table lookup (and allocate)



ptbr in assignment

```
size_t ptbr; points to beginning of (primary) page table initially 0 = doesn't point to anything
```

filled in by first call to page_allocate or by testing code

typical timings

task	typical time (order of magnitude)
empty function	nanosecond
getppid (syscall)	microsecond
<pre>system(/bin/true) (run program)</pre>	milliseconds
start signal handler	microseconds
signal ping/pong (context switch?)	tens of microseconds

my desktop: 39-bit physical addresses; 48-bit virtual addresses

4096 byte pages

my desktop: 39-bit physical addresses; 48-bit virtual addresses

4096 byte pages

top 16 bits of 64-bit addresses not used for translation

my desktop: 39-bit physical addresses; 48-bit virtual addresses

4096 byte pages

exercise: how many page table entries? (assuming page table like shown before)

exercise: how large are physical page numbers?

my desktop: 39-bit physical addresses; 48-bit virtual addresses

4096 byte pages

exercise: how many page table entries? (assuming page table like shown before)

exercise: how large are physical page numbers?

my desktop: 39-bit physical addresses; 48-bit virtual addresses

4096 byte pages

exercise: how many page table entries? (assuming page table like shown before)

exercise: how large are physical page numbers?

page table entries are 8 bytes (room for expansion, metadata) trick: power of two size makes table lookup faster

would take up 2^{39} bytes?? (512GB??)


huge page tables

huge virtual address spaces!

impossible to store PTE for every page

how can we save space?

holes



most pages are invalid

saving space

basic idea: don't store (most) invalid page table entries
use a data structure other than a flat array
 want a map — lookup key (virtual page number), get value (PTE)
options?

saving space

```
basic idea: don't store (most) invalid page table entries
use a data structure other than a flat array
want a map — lookup key (virtual page number), get value (PTE)
options?
```

hashtable

actually used by some historical processors but never common

saving space

```
basic idea: don't store (most) invalid page table entries
use a data structure other than a flat array
    want a map — lookup key (virtual page number), get value (PTE)
options?
```

hashtable

actually used by some historical processors but never common

tree data structure

but not quite a search tree

search tree tradeoffs


lookup usually implemented in hardware


lookup should be simple solution: lookup splits up address bits (no complex calculations)


lookup should not involve many memory accesses

doing two memory accesses is already very slow solution: tree with many children from each node (far from binary tree's left/right child)

two-level page tables for 65536 pages (16-bit VPN; 256 entries/table)









TE for VPN 0x3FF

16




TE for VPN 0x3FF


16



TE for VPN 0x3FF

16





two-level page tables for 65536 pages (16-bit VPN; 256 entries/table) second-level page tables actual data for p for VPN 0x00 (if PTE valid) first-level page table for VPN $0 \times 0 - 0 \times FF$ tor VPN 0x100-0x1FFIPTE for VPN 0xFF VPN 0x200-0x2FF for VPN 0x300-0x3FF VPN 0x300 for VPN 0xFF00-0xFFFF VPN 0x302 TE for VPN 0x303


for VPN 0x3FF


virtual address


11 0101 01 00 1011 00 00 1101 1111


VPN — split into two parts (one per level)


this example: parts equal sized — common, but not required






























another view




9-bit virtual address

6-bit physical address



- 9-bit virtual address
- 6-bit physical address
- 8-byte pages \rightarrow 3-bit page offset (bottom) ⁶
- 9-bit VA: 6 bit VPN + 3 bit PO
- 6-bit PA: 3 bit PPN + 3 bit PO



physical addr

PPN page offset

9-bit virtual address

virtual addr page offset VPN

- 6-bit physical address
- PPN8-byte pages \rightarrow 3-bit page offset (bottom) ⁶
- 9-bit VA: 6 bit VPN + 3 bit PO

page table (either level)

page offset

physical addr

- 6-bit PA: 3 bit PPN + 3 bit PO
- 1 page page tables w/ 1 byte entry \rightarrow 8 entry PTs



9-bit virtual address

virtual addr page offset VPN pt 1 VPN pt 2

PPN

physical addr

- 6-bit physical address
- 8-byte pages \rightarrow 3-bit page offset (bottom) ⁶
- page offset page table (either level)

- 9-bit VA: 6 bit VPN + 3 bit PO
- 6-bit PA: 3 bit PPN + 3 bit PO
- 1 page page tables w/ 1 byte entry \rightarrow 8 entry PTs
- valid? PPN

- 8 entry page tables \rightarrow 3-bit VPN parts
- 9-bit VA: 3 bit VPN part 1; 3 bit VPN part 2

physical addresses	byte	es			phys addre	sical sses	byt	es		
0x00-3	00	11	22	33	0x26	9-3	00	91	72	13
0x04-7	44	55	66	77	0x24	1-7	F4	Α5	36	07
0x08-B	88	99	AA	ВВ	0x28	3-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x20	C-F	CD	DE	EF	F0
0x10-3	1A	2A	ЗА	4A	0x36	9-3	ВА	0A	ВА	0Α
0x14-7	1B	2B	3B	4B	0x34	1-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38	3-B	EC	0C	EC	оC
0x1C-F	1C	2C	3C	4C	0x30	C-F	AC	DC	DC	0C

physical addresses	byt	es		
0x00-3	00	11	22	33
0x04-7	44	55	66	77
0x08-B	88	99	AΑ	ВВ
0x0C-F	CC	DD	EE	FF
0x10-3	1A	2A	ЗА	4A
0x14-7	1В	2B	3B	4B
0x18-B	1C	2C	3C	4C
0x1C-F	1C	2C	3C	4C

physical addresses	byt	es		
0x20-3	00	91	72	13
0x24-7	F4	Α5	36	07
0x28-B	89	9A	AB	ВС
0x2C-F	CD	DE	EF	F0
0x30-3	ВА	0A	ВА	0Α
0x34-7	DΒ	0B	DB	0B
0x38-B	EC	0C	EC	0C
0x3C-F	AC	DC	DC	0C

	physical bytes addresses
33	0x20-300 91 72 13
77	0x24-7F4 A5 36 07
ВВ	0x28-B89 9A AB BC
FF	0x2C-FCD DE EF F0
4A	0x30-3BA 0A BA 0A
4B	0x34-7DB 0B DB 0B
4C	0x38-BEC 0C EC 0C
4C	0x3C-FAC DC DC 0C
	77 BB FF 4A 4B 4C

physical addresses	byt	es			physica addresses	byt	es		
0x00-3	00	11	22	33	0x20-3			72	13
0x04-7	44	55	66	77	0x24-7	F4	Α5	36	07
0x08-B	88	99	AΑ	ВВ	0x28-E	89	9A	ΑB	ВС
0x0C-F	CC	DD	ΕE	FF	0x2C-F	CD	DE	EF	F0
0x10-3	1A	2A	3A	4A	0x30-3	ВА	0A	ВА	0Α
0x14-7	1В	2B	3B	4B	0x34-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38-E	EC	0C	EC	9C
0x1C-F	1C	2C	3C	4C	0x3C-F	AC	DC	DC	0C

physical addresses	byte	es			physical addresses	byt	es		
0x00-3	00	11	22	33	0x20-3			72	13
0x04-7	44	55	66	77	0x24-7	F4	Α5	36	07
0x08-B	88	99	AΑ	ВВ	0x28-B	89	9A	AB	ВС
0x0C-F	CC	DD	EE	FF	0x2C-F	CD	DE	EF	F0
0x10-3	1A	2A	ЗА	4A	0x30-3	ВА	0A	ВА	0Α
0x14-7	1B	2B	3B	4B	0x34-7	DΒ	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38-B	EC	0C	EC	0C
0x1C-F	1C	2C	3C	4C	0x3C-F	AC	DC	DC	0C

physical addresses	byte	es			phy addr	ysical esses	byt	es		
0x00-3			22	33		20-3			D2	D3
0x04-7	44	55	66	77	0x2	24-7	D4	D5	D6	D7
0x08-B	88	99	AA	ВВ	0x2	28-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x2	2C-F	CD	DE	EF	F0
0x10-3	1A	2A	ЗА	4A	0x3	30-3	ВА	0A	ВА	0Α
0x14-7	1B	2B	3B	4B	0x3	34-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x3	88-B	EC	0C	EC	ОС
0x1C-F	1C	2C	3C	4C	0x3	3C-F	FC	0C	FC	0C

physical addresses	bytes			physical bytes addresses
0x00-3		22	33	0x20-3D0 D1 D2 D3
0x04-7	44 55	66	77	0x24-7D4 D5 D6 D7
0x08-B	88 99	AA	ВВ	0x28-B89 9A AB BC
0x0C-F	CC DD	EE	FF	0x2C-FCD DE EF F0
0x10-3	1A 2A	ЗА	4A	0x30-3BA 0A BA 0A
0x14-7	1B 2B	3B	4B	0x34-7DB 0B DB 0B
0x18-B	1C 2C	3C	4C	0x38-BEC 0C EC 0C
0x1C-F	1C 2C	3C	4C	0x3C-FFC 0C FC 0C

physical addresses	byte	es			physical addresses	byt	es		
0x00-3			22	33	0x20-3			D2	D3
0x04-7	44	55	66	77	0x24-7	D4	D5	D6	D7
0x08-B	88	99	AΑ	ВВ	0x28-B	89	9A	AB	ВС
0x0C-F	CC	DD	ΕE	FF	0x2C-F	CD	DE	EF	F0
0x10-3	1A	2A	3A	4A	0x30-3	ВА	0A	ВА	0Α
0x14-7	1В	2B	3B	4B	0x34-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38-B	EC	0C	EC	0C
0x1C-F	1C	2C	3C	4C	0x3C-F	FC	0C	FC	0C

physical bytes addresses	physical bytes addresses
addresses	addresses
0x00-3 00 11 22 33	0x20-3 D0 D1 D2 D3
0x04-744 55 66 77	0x24-7 D4 D5 D6 D7
0x08-B88 99 AA BB	0x28-B89 9A AB BC
0x0C-FCC DD EE FF	0x2C-FCD DE EF F0
0x10-3 1A 2A 3A 4A	0x30-3BA 0A BA 0A
0x14-7 1B 2B 3B 4B	0x34-7 DB 0B DB 0B
0x18-B1C 2C 3C 4C	0x38-BEC 0C EC 0C
0x1C-F1C 2C 3C 4C	0x3C-FFC 0C FC 0C

physical addresses	byte	es			phy addr	/sical esses	byt	es		
0x00-3			22	33		20-3			D2	D3
0x04-7	44	55	66	77	0x2	4-7	D4	D5	D6	D7
0x08-B	88	99	AA	ВВ	0x2	8-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x2	C-F	CD	DE	EF	F0
0x10-3	1A	2A	ЗА	4A	0x3	80-3	ВА	0A	ВА	0Α
0x14-7	1B	2B	3B	4B	0x3	4-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x3	8-B	EC	0C	EC	9C
0x1C-F	1C	2C	3C	4C	0x3	C-F	FC	0C	FC	0C

multi-level page tables

VPN split into pieces for each level of page table

top levels: page table entries point to next page table usually using physical page number of next page table

bottom level: page table entry points to destination page

validity checks at each level

note on VPN splitting

indexes used for lookup parts of the virtual page number (there are not multiple VPNs)

splitting addresses

if:

256-byte (2⁸ byte) pages 4-byte page table entries 3 levels of page tables page tables take up 1 page

Q1: page offset size (bits)

A. <=4 B. 5-7 C. 8-11 D. 12-15 E. >15

Q2: virtual page number size (bits)

A. <=4 B. 5-7 C. 8-11 D. 12-15 E. >15

Q3: split address 0x1234

x86-64 page table splitting

48-bit virtual address

12-bit page offset (4KB pages)

36-bit virtual page number, split into four 9-bit parts


page tables at each level: 2^9 entries, 8 bytes/entry page tables take up 4KB (1 page)

assignment part 2/3

supporting arbitrary numbers of LEVELS, POBITS

code review in lab after reading days limited allowed collaboration


pa = translate(va) [LEVELS=2]





first page_allocate(va) [LEVELS=2]

0x05898


PTBR







first page_allocate(va) [LEVELS=2]



later page allocates?

some of those allocations done earlier e.g. ptbr already set

should reuse existing allocation then

physical addresses	byte	es			physical addresses	byt	es		
0x00-3			22	33	0x20-3			D2	D3
0x04-7	44	55	66	77	0x24-7	D4	D5	D6	D7
0x08-B	88	99	AΑ	ВВ	0x28-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x2C-F	CD	DE	EF	F0
0x10-3	1A	2A	5A	4A	0x30-3	ВА	0A	ВА	0A
0x14-7	1B	2B	3B	4B	0x34-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38-B	EC	0C	EC	0C
0x1C-F	1C	2C	3C	4C	0x3C-F	FC	0C	FC	0C

physical addresses	byte	es			phys addre	sical sses	byt	es		
0x00-3			22	33	0x20				D2	D3
0x04-7	44	55	66	77	0x24	4-7	D4	D5	D6	D7
0x08-B	88	99	AΑ	ВВ	0x28	8-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x20	C-F	CD	DE	EF	F0
0x10-3	1A	2A	3A	4A	0x30	9-3	ВА	0Α	ВА	0Α
0x14-7	1B	2B	3B	4B	0x34	4-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38	8-B	EC	0C	EC	оC
0x1C-F	1C	2C	3C	4C	0x30	C-F	FC	0C	FC	0C

physical bytes addresses							
0x00-3	00	11	22	33			
0x04-7	44	55	66	77			
0x08-B	88	99	AΑ	ВВ			
0x0C-F	CC	DD	EE	FF			
0x10-3	1A	2A	3A	4A			
0x14-7	1B	2B	3B	4B			
0x18-B	1C	2C	3C	4C			
0x1C-F	1C	2C	3C	4C			

physical addresses	byt	es		
0x20-3	D0	D1	D2	D3
0x24-7	D4	D5	D6	D7
0x28-B	89	9A	AΒ	ВС
0x2C-F	CD	DE	EF	F0
0x30-3	ВА	0A	ВА	0A
0x34-7	DB	0B	DB	0B
0x38-B	EC	0C	EC	0C
0x3C-F	FC	00	FC	00

9-bit virtual addresses, 6-bit physical; 8 byte pages, 1 byte PTE page tables 1 page; PTE: 3 bit PPN (MSB), 1 valid bit, 4 unused page table base register 0x08; translate virtual address 0x00B

physical addresses	byte	es			phy addr	/sical esses	byt	es		
0x00-3			22	33		20-3			D2	D3
0x04-7	44	55	66	77	0x2	4-7	D4	D5	D6	D7
0x08-B	88	99	AA	ВВ	0x2	8-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x2	C-F	CD	DE	EF	F0
0x10-3	1A	2A	ЗА	4A	0x3	80-3	ВА	0A	ВА	0Α
0x14-7	1B	2B	3B	4B	0x3	4-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x3	8-B	EC	0C	EC	0C
0x1C-F	1C	2C	3C	4C	0x3	C-F	FC	0C	FC	0C

9-bit virtual addresses, 6-bit physical; 8 byte pages, 1 byte PTE page tables 1 page; PTE: 3 bit PPN (MSB), 1 valid bit, 4 unused page table base register 0x08; translate virtual address 0x1CB

physical addresses	byte	es			physical addresses	byt	es		
0x00-3			22	33	0x20-3			D2	D3
0x04-7	44	55	66	77	0x24-7	D4	D5	D6	D7
0x08-B	88	99	AΑ	ВВ	0x28-B	89	9A	ΑB	ВС
0x0C-F	CC	DD	EE	FF	0x2C-F	CD	DE	EF	F0
0x10-3	1A	2A	3A	4A	0x30-3	ВА	0Α	ВА	0Α
0x14-7	1B	2B	3B	4B	0x34-7	DB	0B	DB	0B
0x18-B	1C	2C	3C	4C	0x38-B	EC	0C	EC	0C
0x1C-F	1C	2C	3C	4C	0x3C-F	FC	0C	FC	0C

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical addresses	byt	es		
addresses	-, -			
0x00-3	00	11	22	33
0x04-7	44	55	66	77
0x08-B				
0x0C-F	CC	DD	EE	FF
0x10-3	1A	2A	3A	4A
0x14-7	1В	2B	3B	4B
0x18-B				
0x1C-F	ΑC	ВС	DC	EC

```
physical addresses

0x20-3 D0 E1 D2 D3

0x24-7 D4 E5 D6 E7

0x28-B 89 9A AB BC

0x2C-F CD DE EF F0

0x30-3 BA 0A BA 0A

0x34-7 DB 0B DB 0B

0x38-B EC 0C EC 0C

0x3C-F FC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical baddresses	ovt	es			
0x00-3	90	11	22	33	
0x04-7	14	55	66	77	
0x08-B	38	99	AΑ	ВВ	
0x0C-F					
0x10-3	LΑ	2A	3A	4A	
0x14-7	LΒ	2B	3B	4B	
0x18-B	LĊ	2C	3C	4C	
0x1C-F	١C	ВС	DC	EC	

```
physical bytes
addresses
0x20-3D0 E1 D2 D3
0x24-7D4 E5 D6 E7
0x28-Bl89 9A AB BC
0x2C-FCD DE EF F0
0x30-3|BA 0A BA 0A
0x34-7DB 0B DB 0B
0x38-B|EC 0C EC 0C
0x3C-FIFC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical baddresses	ovt	es			
0x00-3	90	11	22	33	
0x04-7	14	55	66	77	
0x08-B	38	99	AΑ	ВВ	
0x0C-F					
0x10-3	LΑ	2A	3A	4A	
0x14-7	LΒ	2B	3B	4B	
0x18-B	LĊ	2C	3C	4C	
0x1C-F	١C	ВС	DC	EC	

```
physical bytes
addresses
0x20-3D0 E1 D2 D3
0x24-7D4 E5 D6 E7
0x28-Bl89 9A AB BC
0x2C-FCD DE EF F0
0x30-3|BA 0A BA 0A
0x34-7DB 0B DB 0B
0x38-B|EC 0C EC 0C
0x3C-FIFC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical addresses	bvt	es		
addresses,	-) -			
0x00-3				
0x04-7	44	55	66	77
0x08-B	88	99	AΑ	ВВ
0x0C-F	CC	DD	EE	FF
0x10-3	1A	2A	ЗА	4A
0x14-7	1B	2B	3B	4B
0x18-B	1C	2C	3C	4C
0x1C-F	AC	ВС	DC	EC

```
physical bytes
addresses
0x20-3D0 E1 D2 D3
0x24-7D4 E5 D6 E7
0x28-Bl89 9A AB BC
0x2C-FCD DE EF F0
0x30-3|BA 0A BA 0A
0x34-7DB 0B DB 0B
0x38-B|EC 0C EC 0C
0x3C-FIFC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical baddresses	ovt	es			
0x00-3	90	11	22	33	
0x04-7	14	55	66	77	
0x08-B	38	99	AΑ	ВВ	
0x0C-F					
0x10-3	LΑ	2A	3A	4A	
0x14-7	LΒ	2B	3B	4B	
0x18-B	LĊ	2C	3C	4C	
0x1C-F	١C	ВС	DC	EC	

```
physical bytes
addresses
0x20-3D0 E1 D2 D3
0x24-7D4 E5 D6 E7
0x28-Bl89 9A AB BC
0x2C-FCD DE EF F0
0x30-3|BA 0A BA 0A
0x34-7DB 0B DB 0B
0x38-B|EC 0C EC 0C
0x3C-FIFC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical addresses	byt	es		
0x00-3			22	33
0x04-7	44	55	66	77
0x08-B				
0x0C-F				
0x10-3	1A	2A	3A	4A
0x14-7	1В	2B	3B	4B
0x18-B				
0x1C-F	AC	ВС	DC	EC

```
physical bytes
addresses
0x20-3D0 E1 D2 D3
0x24-7D4 E5 D6 E7
0x28-Bl89 9A AB BC
0x2C-FCD DE EF F0
0x30-3|BA 0A BA 0A
0x34-7DB 0B DB 0B
0x38-B|EC 0C EC 0C
0x3C-FIFC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical baddresses	ovt	es			
0x00-3	90	11	22	33	
0x04-7	14	55	66	77	
0x08-B	38	99	AΑ	ВВ	
0x0C-F					
0x10-3	LΑ	2A	3A	4A	
0x14-7	LΒ	2B	3B	4B	
0x18-B	LĊ	2C	3C	4C	
0x1C-F	١C	ВС	DC	EC	

```
physical bytes
addresses
0x20-3D0 E1 D2 D3
0x24-7D4 E5 D6 E7
0x28-Bl89 9A AB BC
0x2C-FCD DE EF F0
0x30-3|BA 0A BA 0A
0x34-7DB 0B DB 0B
0x38-B|EC 0C EC 0C
0x3C-FIFC 0C FC 0C
```

10-bit virtual addresses, 6-bit physical; 16 byte pages, 2 byte PTE

page tables 1 page; PTE 1st byte: (MSB) 2-bit PPN, valid bit; rest unused

physical addresses	hvt	es		
0x00-3	00	11	22	33
0x04-7	44	55	66	77
0x08-B	88	99	AΑ	ВВ
0x0C-F	CC	DD	EE	FF
0x10-3	1A	2A	3A	4A
0x14-7	1B	2B	3B	4B
0x18-B	1C	2C	3C	4C
0x1C-F	AC	ВС	DC	EC

```
physical bytes addresses 0x20-3 D0 E1 D2 D3 0x24-7 D4 E5 D6 E7 0x28-B 89 9A AB BC 0x2C-F CD DE EF F0 0x30-3 BA 0A BA 0A 0x34-7 DB 0B DB 0B 0x38-B EC 0C EC 0C 0x3C-F FC 0C FC 0C
```

running a program

Some program

	Used by OS
	Stack
 -	leap / other dynamic
	Writable data
	Code + Constants

running a program

Some program

Used by OS Stack Heap / other dynamic Writable data Code + Constants

OS's memory

part of context switch is changing the page table

extra privileged instructions

part of context switch is changing the page table

extra privileged instructions

where in memory is the code that does this switching?

part of context switch is changing the page table extra privileged instructions

where in memory is the code that does this switching? probably have a page table entry pointing to it hopefully marked kernel-mode-only

part of context switch is changing the page table extra privileged instructions

where in memory is the code that does this switching? probably have a page table entry pointing to it hopefully marked kernel-mode-only

code better not be modified by user program otherwise: uncontrolled way to "escape" user mode

vim (two copies)

Emacs (run by user mst3k)

U	sed by OS
	Stack
Heap /	other dynamic
Wı	ritable data
vim (Co	de + Constants)

Emacs (run by user xyz4w)

	Used by OS
	Stack
	Heap / other dynamic
	Writable data
vi	m (Code + Constants)

vim (two copies)

Emacs (run by user mst3k)	Emacs (run by user xyz4w)	
Used by OS	Used by OS	
Stack	Stack	
Heap / other dynamic	Heap / other dynamic	
Writable data	Writable data	
$vim\; (Code + Constants)$	$vim\; (Code + Constants)$	

same data?

two copies of program

would like to only have one copy of program

what if mst3k's vim tries to modify its code?

would break process abstraction:

"illusion of own memory"

permissions bits

```
page table entry will have more permissions bits can access in user mode? can read from? can write to? can execute from?
```


checked by MMU like valid bit

page table (logically)

virtual page #	valid?	user?	write?	exec?	physical page #
0000 0000	0	0	0	0	00 0000 0000
0000 0001	1	1	1	0	10 0010 0110
0000 0010	1	1	1	0	00 0000 1100
0000 0011	1	1	0	1	11 0000 0011
•••					
1111 1111[1	0	1	0	00 1110 1000


space on demand

Program Memory




space on demand

Program Memory



space on demand

Program Memory



%rsp = 0x7FFFC000

```
...
// requires more stack space
A: pushq %rbx

B: movq 8(%rcx), %rbx
C: addq %rbx, %rax
...
```

VPN	valid?	page
•••	•••	
0x7FFFB	0	
0x7FFFC	1	0x200DF
0x7FFFD	1	0x12340
0x7FFFE	1	0x12347
0x7FFFF	1	0x12345
•••	•••	•••

%rsp = 0x7FFFC000

```
// requires more stack space
A: pushq %rbx
page fault!
B: movq 8(%rcx), %rbx
C: addq %rbx, %rax
...
```

VPN	valid?	physical
VIIN	valiu:	page
•••	•••	•••
0x7FFFB	0	
0x7FFFC	1	0x200DF
0x7FFFD	1	0x12340
0x7FFFE	1	0x12347
0x7FFFF	1	0x12345
•••	•••	•••

pushq triggers exception hardware says "accessing address 0x7FFBFF8" OS looks up what's should be there — "stack"

%rsp = 0x7FFFC000

```
// requires more stack space
A: pushq %rbx restarted

B: movq 8(%rcx), %rbx
C: addq %rbx, %rax
...
```

VPN	valid?	physical page
VIIN	valiu:	page
•••	•••	•••
0x7FFFB	1	0x200D8
0x7FFFC	1	0x200DF
0x7FFFD	1	0x12340
0x7FFFE	1	0x12347
0x7FFFF	1	0x12345
•••	•••	•••

in exception handler, OS allocates more stack space OS updates the page table then returns to retry the instruction

note: the space doesn't have to be initially empty

only change: load from file, etc. instead of allocating empty page

loading program can be merely creating empty page table everything else can be handled in response to page faults no time/space spent loading/allocating unneeded space

mmap

```
Linux/Unix has a function to "map" a file to memory
int file = open("somefile.dat", O_RDWR);
    // data is region of memory that represents file
char *data = mmap(..., file, 0);
   // read byte 6 from somefile.dat
char seventh_char = data[6];
   // modifies byte 100 of somefile.dat
data[100] = 'x';
    // can continue to use 'data' like an array
```

Linux maps: list of maps

```
$ cat /proc/self/maps
00400000-0040b000 r-xp 00000000 08:01 48328831
                                                         /bin/cat
0060a000-0060b000 r-p 0000a000 08:01 48328831
                                                         /bin/cat
0060b000-0060c000 rw-p 0000b000 08:01 48328831
                                                         /bin/cat
01974000-01995000 rw-p 00000000 00:00 0
                                                         [heap]
7f60c718b000-7f60c7490000 r-p 00000000 08:01 77483660
                                                         /usr/lib/locale/locale—archive
7f60c7490000-7f60c764e000 r-xp 00000000 08:01 96659129
                                                         /lib/x86_64-linux-gnu/libc-2.1
7f60c764e000-7f60c784e000 ----p 001be000 08:01 96659129
                                                         /lib/x86_64-linux-gnu/libc-2.1
7f60c784e000-7f60c7852000 r-p 001be000 08:01 96659129
                                                         /lib/x86_64-linux-gnu/libc-2.1
7f60c7852000-7f60c7854000 rw-p 001c2000 08:01 96659129
                                                         /lib/x86 64-linux-gnu/libc-2.1
7f60c7854000-7f60c7859000 rw-p 00000000 00:00 0
7f60c7859000-7f60c787c000 r-xp 00000000 08:01 96659109
                                                         /lib/x86_64-linux-gnu/ld-2.19.
7f60c7a39000-7f60c7a3b000 rw-p 00000000 00:00 0
7f60c7a7a000-7f60c7a7b000 rw-p 00000000 00:00 0
7f60c7a7b000-7f60c7a7c000 r-p 00022000 08:01 96659109
                                                         /lib/x86_64-linux-gnu/ld-2.19.
7f60c7a7c000-7f60c7a7d000 rw-p 00023000 08:01 96659109
                                                         /lib/x86_64-linux-gnu/ld-2.19.s
7f60c7a7d000-7f60c7a7e000 rw-p 00000000 00:00 0
7ffc5d2b2000-7ffc5d2d3000 rw-p 00000000 00:00 0
                                                         [stack]
7ffc5d3b0000-7ffc5d3b3000 r—p 00000000 00:00 0
                                                         [vvar]
7ffc5d3b3000-7ffc5d3b5000 r-xp 00000000 00:00 0
                                                         vdsol
fffffffff600000-ffffffffff601000 r-xp 00000000 00:00 0
                                                         [vsyscall]
```

Linux maps: list of maps

```
$ cat /proc/self/maps
00400000-0040b000 r-xp 00000000 08:01 48328831
                                                        /bin/cat
0060a000-0060b000 r-p 0000a000 08:01 48328831
                                                         /bin/cat
0060b000-0060c000 rw-p 0000b000 08:01 48328831
                                                         /bin/cat
01974000 - 01995000 \text{ rw-p} 00000000 00:00 0
                                                         [heap]
7f60c718b000_7f60c7490000
                                                         <u>usr/lib/locale/lo</u>cale—archive
7f60c74900 OS tracks list of struct vm_area_struct with:
                                                                          gnu/libc-2.1
7f60c764e0
                                                                          gnu/libc-2.1
          (shown in this output):
7f60c784e0
                                                                          gnu/libc-2.1
7f60c78520
                                                                          gnu/libc-2.1
             virtual address start, end
7f60c78540
                                                                          gnu/ld-2.19.s
7f60c78590
             permissions
7f60c7a390
7f60c7a7a0
             offset in backing file (if any)
7f60c7a7b0
                                                                          gnu/ld-2.19.s
7f60c7a7c0
             pointer to backing file (if any)
                                                                          gnu/ld-2.19.s
7f60c7a7d0
7ffc5d2b20
7ffc5d3b00
           (not shown):
7ffc5d3b30
ffffffffff
             info about sharing of non-file data
```

page tricks generally

deliberately make program trigger page/protection fault

but don't assume page/protection fault is an error

have seperate data structures represent logically allocated memory e.g. "addresses 0x7FFF8000 to 0x7FFFFFFF are the stack"

page table is for the hardware and not the OS

hardware help for page table tricks

information about the address causing the fault
e.g. special register with memory address accessed
harder alternative: OS disassembles instruction, look at registers

(by default) rerun faulting instruction when returning from exception

precise exceptions: no side effects from faulting instruction or after e.g. pushq that caused did not change %rsp before fault e.g. can't notice if instructions were executed in parallel

swapping

early motivation for virtual memory: swapping

using disk (or SSD, ...) as the next level of the memory hierarchy how our textbook and many other sources presents virtual memory

OS allocates program space on disk own mapping of virtual addresses to location on disk

DRAM is a cache for disk

swapping

early motivation for virtual memory: swapping

using disk (or SSD, ...) as the next level of the memory hierarchy how our textbook and many other sources presents virtual memory

OS allocates program space on disk own mapping of virtual addresses to location on disk

DRAM is a cache for disk

swapping components

```
"swap in" a page — exactly like allocating on demand!
    OS gets page fault — invalid in page table
    check where page actually is (from virtual address)
    read from disk
    eventually restart process
"swap out" a page
    OS marks as invalid in the page table(s)
    copy to disk (if modified)
```

HDD/SDDs are slow

HDD reads and writes: milliseconds to tens of milliseconds minimum size: 512 bytes writing tens of kilobytes basically as fast as writing 512 bytes

SSD writes and writes: hundreds of microseconds designed for writes/reads of kilobytes (not much smaller)

HDD/SDDs are slow

HDD reads and writes: milliseconds to tens of milliseconds minimum size: 512 bytes writing tens of kilobytes basically as fast as writing 512 bytes

SSD writes and writes: hundreds of microseconds designed for writes/reads of kilobytes (not much smaller)

HDD/SDDs are slow


HDD reads and writes: milliseconds to tens of milliseconds minimum size: 512 bytes writing tens of kilobytes basically as fast as writing 512 bytes


SSD writes and writes: hundreds of microseconds designed for writes/reads of kilobytes (not much smaller)


HDD/SDDs are slow


HDD reads and writes: milliseconds to tens of milliseconds minimum size: 512 bytes writing tens of kilobytes basically as fast as writing 512 bytes


SSD writes and writes: hundreds of microseconds designed for writes/reads of kilobytes (not much smaller)














POSIX process management

essential operations

```
process information: getpid
process creation: fork
running programs: exec*
    also posix_spawn (not widely supported), ...
waiting for processes to finish: waitpid (or wait)
process destruction, 'signaling': exit, kill
```


POSIX process management


essential operations


```
process information: getpid
process creation: fork
running programs: exec*
    also posix_spawn (not widely supported), ...
waiting for processes to finish: waitpid (or wait)
process destruction, 'signaling': exit, kill
```


fork


```
pid_t fork() — copy the current process
returns twice:
     in parent (original process): pid of new child process
     in child (new process): 0
everything (but pid) duplicated in parent, child:
     memory
     file descriptors (later)
     registers
```











do we really need a complete copy?

bash	new copy of bash			
Used by OS	Used by OS			
Stack	Stack			
Heap / other dynamic	Heap / other dynamic			
Writable data	Writable data			
Code + Constants	Code + Constants			

do we really need a complete copy?

bash	new copy of bash			
Used by OS	Used by OS			
Stack	Stack			
Heap / other dynamic	Heap / other dynamic			
Writable data	Writable data			
Code + Constants	Code + Constants			

shared as read-only

do we really need a complete copy?

bash	new copy of bash		
Used by OS	Used by OS		
Stack	Stack		
Heap / other dynamic	Heap $/$ other dynamic		
Writable data	Writable data		
Code + Constants $Can't$ be $Code + Constants$			

trick for extra sharing

```
sharing writeable data is fine — until either process modifies it example: default value of global variables might typically not change (or OS might have preloaded executable's data anyways)
```

can we detect modifications?

trick for extra sharing

```
sharing writeable data is fine — until either process modifies it example: default value of global variables might typically not change (or OS might have preloaded executable's data anyways)
```

can we detect modifications?

trick: tell CPU (via page table) shared part is read-only processor will trigger a fault when it's written

VPN

... 0x00601 0x00602 0x00603 0x00604

0x00605

valid? write?

		page
•••	•••	•••
1	1	0x12345
1	1	0x12347
1	1	0x12340
1	1	0x200DF
1	1	0x200AF
•••	•••	•••

VPN
•••
0x00601
0x00602
0x00603
0x00604
0x00605
•••

physical valid? write? page				
•••	•••	•••		
1	0	0x12345		
1	0	0x12347		
1	0	0x12340		
1	0	0x200DF		
1	0	0x200AF		
•••	•••	•••		

V 1 1 V
•••
0x00601
0x00602
0x00603
0x00604
0x00605
•••

VPN

•••	•••	•••			
valiu:	WIILC:	page			
valid? write? page					

•••	•••	•••
1	0	0x12345
1	0	0x12347
1	0	0x12340
1	0	0x200DF
1	0	0x200AF
•••	•••	•••

copy operation actually duplicates page table both processes share all physical pages but marks pages in both copies as read-only

VPN	valid?	writa	? physical Page	VPN	valid?	write
VIIV	valiu:	WIILC	page	V I IV	valiu:	VVIILC
•••	•••	•••	•••	•••	•••	•••
0x00601	1	0	0x12345	0x00601	1	0
0x00602	1	0	0x12347	0x00602	1	0
0x00603	1	0	0x12340	0x00603	1	0
0x00604	1	0	0x200DF	<u>0x00604</u>	1	0
0x00605	1	0	0x200AF	0x00605	1	0
•••	•••	•••	•••	•••	•••	•••


VPN	valid? write?				
VIIV	vana:	WIILC	^f page		
•••	•••	•••	•••		
0x00601	1	0	0x12345		
0x00602	1	0	0x12347		
0x00603	1	0	0x12340		
0x00604	1	0	0x200DF		
0x00605	1	0	0x200AF		
•••	•••	•••	•••		


nhysical


when either process tries to write read-only page triggers a fault — OS actually copies the page


VPN	valid? write? page			VPN	physical valid? write? page		
VIIN	valid! write! page		page	VIIN	valid: Write: page		
•••	•••	•••	•••	•••	•••	•••	•••
0x00601	1	0	0x12345	0x00601	1	0	0x12345
0x00602	1	0	0x12347	0x00602	1	0	0x12347
0x00603	1	0	0x12340	0x00603	1	0	0x12340
0x00604	1	0	0x200DF	0x00604	1	0	0x200DF
0x00605	1	0	0x200AF	0x00605	1	1	0x300FD
•••	•••	•••	•••	•••	•••	•••	•••


after allocating a copy, OS reruns the write instruction














```
// not shown: #include various headers
int main(int argc, char *argv[]) {
    pid t pid = getpid();
    printf("Parent pid: %d\n", (int) pid);
    pid_t child_pid = fork();
    if (child_pid > 0) {
        /* Parent Process */
        pid_t my_pid = getpid();
        printf("[%d] parent of [%d]\n",
               (int) my_pid,
               (int) child_pid);
    } else if (child_pid == 0) {
       /* Child Process */
        pid_t my_pid = getpid();
        printf("[%d] child\n",
               (int) my_pid);
    } else {
        perror("Fork failed");
    return 0;
```

```
// not shown: #include various headers
int main(int argc, char *argv[])
    pid_t pid = getpid();
                              getpid — returns current process pid
    printf("Parent pid: %d\n".
    pid_t child_pid = fork();
    if (child_pid > 0) {
       /* Parent Process */
        pid_t my_pid = getpid();
        printf("[%d] parent of [%d]\n",
               (int) my_pid,
               (int) child_pid);
    } else if (child_pid == 0) {
       /* Child Process */
        pid_t my_pid = getpid();
        printf("[%d] child\n",
               (int) my_pid);
    } else {
        perror("Fork failed");
    return 0;
```

```
// not shown: #include various headers
int main(int arec char *arev[]
    pid_t pid cast in case pid_t isn't int
    printf("Pa
    pid_t chil POSIX doesn't specify (some systems it is, some not...)
    if (child_
               (not necessary if you were using C++'s cout, etc.)
        pid_t my_pra = gecpra();
        printf("[%d] parent of [%d]\n",
               (int) my_pid,
               (int) child_pid);
    } else if (child_pid == 0) {
       /* Child Process */
        pid_t my_pid = getpid();
        printf("[%d] child\n",
               (int) my_pid);
    } else {
        perror("Fork failed");
    return 0;
```

```
// not shown: #include various headers
int main (int argo char *ar
        prints out Fork failed: error message
   prin
   [example error message: "Resource temporarily unavailable")
        from error number stored in special global variable errno
       pra_t my_pra = getpra();
       printf("[%d] parent of [%d]\n",
              (int) my_pid,
              (int) child_pid);
    } else if (child_pid == 0) {
       /* Child Process */
       pid_t my_pid = getpid();
       printf("[%d] child\n",
              (int) my_pid);
    } else {
       perror("Fork failed");
    return 0;
```

```
// not shown: #include various headers
int main(int argc, char *argv[]) {
    pid_t pid = getpid();
    printf("Parent pid: %d\n", (int) pid);
    pid_t child_pid = fork();
    if (child_pid > 0) {
        /* Parent Process */
        pid_t my_pid = getpid();
        printf("[%d] parent of [%d]\n",
               (int) my_pid,
               (int) child_pid);
    } else if (child_pid == 0) {
        /* Child Process */
        pid_t my_pid = getpid();
        printf("[%d] child\n",
               (int) my_pid);
    } else {
        perror("Fork failed");
    return 0;
```

```
(parent pid: ...
parent of ..
```

```
Example output:
Parent pid: 100
[100] parent of [432]
[432] child
```

a fork question

```
int main() {
    pid_t pid = fork();
    if (pid == 0) {
        printf("In child\n");
    } else {
        printf("Child %d\n", pid);
    }
    printf("Done!\n");
}
```

Exercise: Suppose the pid of the parent process is 99 and child is 100. Give **two** possible outputs. (Assume no crashes, etc.)

POSIX process management

essential operations

```
process information: getpid
process creation: fork
running programs: exec*
    also posix_spawn (not widely supported), ...
waiting for processes to finish: waitpid (or wait)
process destruction, 'signaling': exit, kill
```

exec*

exec* — replace current program with new program

* — multiple variants
same pid, new process image

int execv(const char *path, const char
**argv)

path: new program to run

argv: array of arguments, termianted by null pointer

also other variants that take argv in different form and/or environment variables*

*environment variables = list of key-value pairs

execv example


```
child_pid = fork();
if (child_pid == 0) {
 /* child process */
  char *args[] = {"ls", "-l", NULL};
 execv("/bin/ls", args);
  /* execv doesn't return when it works.
     So, if we got here, it failed. */
  perror("execv");
  exit(1);
} else if (child pid > 0) {
 /* parent process */
```


execv example


```
child_pid = fork();
if (child_pid == 0) {
  /* child process */
  char *args[] = {"ls", "-l", NULL};
  execv("/bin/ls", args);
  /* execv doesn't return when it works.
  So, if we got used to compute argv, argc perror("execv"); when program's main is ru
                      when program's main is run
  exit(1);
} else if (child_p
  /* parent proces convention: first argument is program name
```


execv example


```
child_pid = fork();
if (child_pid == 0) {
  /* child process */
  char *args[] = {"ls", "-l", NULL};
  execv("/bin/ls", args);
  /* execv doesn't return when it works.
     So, if we got here, path of executable to run
  perror("execv");
                           need not match first argument
  exit(1);
} else if (child_pid > 0 (but probably should match it)
  /* parent process */
                           on Unix /bin is a directory
                           containing many common programs,
                           including ls ('list directory')
```











why fork/exec?

could just have a function to spawn a new program
 Windows CreateProcess(); POSIX's (rarely used) posix_spawn

some other OSs do this (e.g. Windows)

needs to include API to set new program's state

e.g. without fork: either:

need function to set new program's current directory, *or* need to change your directory, then start program, then change back e.g. with fork: just change your current directory before exec

but allows OS to avoid 'copy everything' code probably makes OS implementation easier

posix_spawn

```
pid_t new_pid;
const char argv[] = { "ls", "-l", NULL };
int error_code = posix_spawn(
    &new pid,
    "/bin/ls",
   NULL /* null = copy current process's open files;
            if not null, do something else */,
   NULL /* null = no special settings for new process */,
    argv,
    NULL /* null = copy current process's "environment variab
            if not null, do something else */
if (error_code == 0) {
   /* handle error */
```

some opinions (via HotOS '19)

A fork() in the road

Andrew Baumann Jo

Jonathan Appavoo Boston University Orran Krieger Boston University Timothy Roscoe
ETH Zurich

ABSTRACT

The received wisdom suggests that Unix's unusual combination of fork() and exec() for process creation was an inspired design. In this paper, we argue that fork was a clever hack for machines and programs of the 1970s that has long outlived its usefulness and is now a liability. We catalog the ways in which fork is a terrible abstraction for the modern programmer to use, describe how it compromises OS implementations, and propose alternatives.

POSIX process management

essential operations

```
process information: getpid
process creation: fork
running programs: exec*
    also posix_spawn (not widely supported), ...
waiting for processes to finish: waitpid (or wait)
process destruction, 'signaling': exit, kill
```


wait/waitpid

```
pid_t waitpid(pid_t pid, int *status,
                      int options)
wait for a child process (with pid=pid) to finish
sets *status to its "status information"
pid=-1 \rightarrow wait for any child process instead
options? see manual page (command man waitpid)
    0 — no options
```


waitpid example

```
#include <sys/wait.h>
...
  child_pid = fork();
  if (child_pid > 0) {
      /* Parent process */
      int status;
      waitpid(child_pid, &status, 0);
  } else if (child_pid == 0) {
      /* Child process */
      ...
}
```


typical pattern



typical pattern (alt)



typical pattern (detail)



POSIX process management

essential operations

```
process information: getpid
process creation: fork
running programs: exec*
    also posix_spawn (not widely supported), ...
waiting for processes to finish: waitpid (or wait)
process destruction, 'signaling': exit, kill
```

exercise (1)

```
int main() {
   pid_t pids[2]; const char *args[] = {"echo", "ARG", NULL};
   const char *extra[] = {"L1", "L2"};
    for (int i = 0; i < 2; ++i) {
        pids[i] = fork();
        if (pids[i] == 0) {
            args[1] = extra[i];
            execv("/bin/echo", args);
   for (int i = 0; i < 2; ++i) {
       waitpid(pids[i], NULL, 0);
```

Assuming fork and execv do not fail, which are possible outputs?

A. L1 (newline) L2

D. A and B

B. L1 (newline) L2 (newline) L2 E. A and C

C. L2 (newline) L1

F. all of the above

G. something else

exercise (2)

```
int main() {
    pid_t pids[2]; const char *args[] = {"echo", "0", NULL};
    for (int i = 0; i < 2; ++i) {
        pids[i] = fork();
        if (pids[i] == 0) { execv("/bin/echo", args); }
    }
    printf("1\n"); fflush(stdout);
    for (int i = 0; i < 2; ++i) {
        waitpid(pids[i], NULL, 0);
    }
    printf("2\n"); fflush(stdout);
}</pre>
```

Assuming fork and execv do not fail, which are possible outputs?

- **A.** 0 (newline) 0 (newline) 1 (newline) 2 **E.** A, B, and C
- **B.** 0 (newline) 1 (newline) 0 (newline) 2 **F.** C and D
- C. 1 (newline) 0 (newline) 0 (newline) 2 G. all of the above
- **D.** 1 (newline) 0 (newline) 2 (newline) 0 **H.** something else

shell

allow user (= person at keyboard) to run applications user's wrapper around process-management functions $\frac{1}{2}$

aside: shell forms

POSIX: command line you have used before

also: graphical shells

e.g. OS X Finder, Windows explorer

other types of command lines?

completely different interfaces?

some POSIX command-line features

```
searching for programs
    ls -l \approx /bin/ls -l
    make ≈ /usr/bin/make
running in background
    ./someprogram &
redirection:
    ./someprogram >output.txt
    ./someprogram <input.txt
pipelines:
    ./someprogram | ./somefilter
```

some POSIX command-line features

```
searching for programs
    ls -l \approx /bin/ls -l
    make ≈ /usr/bin/make
running in background
    ./someprogram &
redirection:
    ./someprogram >output.txt
    ./someprogram <input.txt
pipelines:
    ./someprogram | ./somefilter
```

searching for programs

```
POSIX convention: PATH environment variable
    example: /home/cr4bd/bin:/usr/bin:/bin
    list of directories to check in order
environment variables = key/value pairs stored with process
    by default, left unchanged on execve, fork, etc.
one way to implement: [pseudocode]
for (directory in path) {
     execv(directory + "/" + program_name, argv);
```

some POSIX command-line features

```
searching for programs
    ls -l \approx /bin/ls -l
    make ≈ /usr/bin/make
running in background
    ./someprogram &
redirection:
    ./someprogram >output.txt
    ./someprogram <input.txt
pipelines:
    ./someprogram | ./somefilter
```

some POSIX command-line features

```
searching for programs
    ls -l \approx /bin/ls -l
    make ≈ /usr/bin/make
running in background
    ./someprogram &
redirection:
    ./someprogram >output.txt
    ./someprogram <input.txt
pipelines:
    ./someprogram | ./somefilter
```

file descriptors

```
struct process info { /* <-- in the kernel somewhere */
    struct open_file *files;
};
process->files[file descriptor]
Unix: every process has
array (or similar) of open file descriptions
"open file": terminal · socket · regular file · pipe
file descriptor = index into array
     usually what's used with system calls
    stdio.h FILE*s usually have file descriptor index + buffer
```

special file descriptors

```
file descriptor 0= standard input file descriptor 1= standard output file descriptor 2= standard error
```

```
constants in unistd.h
STDIN_FILENO, STDOUT_FILENO, STDERR_FILENO
```

special file descriptors

```
file descriptor 0 = \text{standard input}
file descriptor 1 = \text{standard output}
file descriptor 2 = \text{standard error}
```

```
constants in unistd.h
STDIN_FILENO, STDOUT_FILENO, STDERR_FILENO
```

but you can't choose which number open assigns...?

more on this later

getting file descriptors

```
int read_fd = open("dir/file1", O_RDONLY);
int write_fd = open("/other/file2", O_WRONLY | ...);
int rdwr fd = open("file3", O RDWR);
used internally by fopen(), etc.
also for files without normal filenames ...:
int fd = shm_open("/shared_memory", 0_RDWR, 0666); // shared_memory
int socket_fd = socket(AF_INET, SOCK_STREAM, 0); // TCP socket
int term fd = posix openpt(0 RDWR); // pseudo-terminal
int pipe fds[2]; pipe(pipefds); // "pipes" (later)
```

close

returns 0 on success.

```
int close(int fd);
close the file descriptor, deallocating that array index
    does not affect other file descriptors
    that refer to same "open file description"
    (e.g. in fork()ed child or created via (later) dup2)

if last file descriptor for open file description, resources deallocated
```

returns -1 on error

e.g. ran out of disk space while finishing saving file


shell redirection

```
./my_program ... < input.txt:
    run ./my_program ... but use input.txt as input
    like we copied and pasted the file into the terminal</pre>
```


echo foo > output.txt:

runs echo foo, sends output to output.txt like we copied and pasted the output into that file (as it was written)


exec preserves open files




fork copies open file list




fork copies open file list



fork copies open file list



typical pattern with redirection parent



redirecting with exec

```
standard output/error/input are files
  (C stdout/stderr/stdin; C++ cout/cerr/cin)
```

(probably after forking) open files to redirect

...and make them be standard output/error/input
using dup2() library call

then exec, preserving new standard output/etc.

reassigning file descriptors

redirection: ./program >output.txt

step 1: open output.txt for writing, get new file descriptor

step 2: make that new file descriptor stdout (number 1)

reassigning and file table

```
struct process_info {
    ...
    struct open_file *files;
};
...
process->files[STDOUT_FILENO] = process->files[opened-fd];
syscall: dup2(opened-fd, STDOUT_FILENO);
```

reassigning file descriptors

```
redirection: ./program >output.txt
step 1: open output.txt for writing, get new file descriptor
step 2: make that new file descriptor stdout (number 1)
```

tool: int dup2(int oldfd, int newfd)
make newfd refer to same open file as oldfd
same open file description
shares the current location in the file
(even after more reads/writes)

what if newfd already allocated — closed, then reused

dup2 example

```
redirects stdout to output to output.txt:
fflush(stdout); /* clear printf's buffer */
int fd = open("output.txt",
              O WRONLY | O CREAT | O TRUNC);
if (fd < 0)
    do something about error();
dup2(fd, STDOUT_FILENO);
/* now both write(fd, ...) and write(STDOUT_FILENO, ...)
   write to output.txt
close(fd); /* only close original, copy still works! */
printf("This will be sent to output.txt.\n");
```

open/dup/close/etc. and fd array

```
struct process_info {
  struct file *files;
open: files[new fd] = ...;
dup2(from, to): files[to] = files[from];
close: files[fd] = NULL;
fork:
  for (int i = ...)
       child->files[i] = parent->files[i];
(plus extra work to avoid leaking memory)
```

exercise

```
int fd = open("output.txt", O_WRONLY|O_CREAT|O_TRUNC, 0666);
write(fd, "A", 1);
dup2(STDOUT_FILENO, 100);
dup2(fd, STDOUT_FILENO);
write(STDOUT_FILENO, "B", 1);
write(fd, "C", 1);
close(fd);
write(STDOUT_FILENO, "D", 1);
write(100, "E", 1);
```

Assume fd 100 is not what open returns. What is written to output.txt?

- **A.** ABCDE **C.** ABC **E.** something else
- **B.** ABCD **D.** ACD

pipes

```
special kind of file: pipes
```

bytes go in one end, come out the other — once

created with pipe() library call

intended use: communicate between processes like implementing shell pipelines


pipe()

```
int pipe_fd[2];
if (pipe(pipe_fd) < 0)</pre>
    handle error();
/* normal case: */
int read_fd = pipe_fd[0];
int write fd = pipe fd[1];
then from one process...
write(write_fd, ...);
and from another
read(read fd, ...);
```

pipe and pipelines

```
ls -1 | grep foo
pipe(pipe_fd);
ls_pid = fork();
if (ls pid == 0) {
    dup2(pipe_fd[1], STDOUT_FILENO);
    close(pipe_fd[0]); close(pipe_fd[1]);
    char *argv[] = {"ls", "-1", NULL};
    execv("/bin/ls", argv);
grep_pid = fork();
if (grep pid == 0) {
    dup2(pipe fd[0], STDIN FILENO);
    close(pipe fd[0]); close(pipe fd[1]);
    char *argv[] = {"grep", "foo", NULL};
    execv("/bin/grep", argv);
close(pipe fd[0]); close(pipe fd[1]);
/* wait for processes, etc. */
```

example execution



Unix API summary

```
spawn and wait for program: fork (copy), then
     in child: setup, then execv, etc. (replace copy)
     in parent: waitpid
files: open, read and/or write, close
     one interface for regular files, pipes, network, devices, ...
file descriptors are indices into per-process array
     index 0, 1, 2 = \text{stdin}, stdout, stderr
     dup2 — assign one index to another
     close — deallocate index
redirection/pipelines
```

open() or pipe() to create new file descriptors dup2 in child to assign file descriptor to index 0, 1

backup slides

x86-64 page table entries (1)

```
present = valid
```

```
R/W = writes allowed?
```

$$U/S = user-mode allowed?$$
 ("user/supervisor")

XD = execute-disable?

 $\mathsf{A} = \mathsf{accessed?} \ (\mathsf{MMU} \ \mathsf{sets} \ \mathsf{to} \ \mathsf{1} \ \mathsf{on} \ \mathsf{page} \ \mathsf{read/write})$

D = dirty? (MMU sets to 1 on page write)

x86-64 page table entries (1)

```
present = valid
```

R/W = writes allowed?

U/S = user-mode allowed? ("user/supervisor")

XD = execute-disable?

A = accessed? (MMU sets to 1 on page read/write)

D = helps support replacement policies for swapping

x86-64 page table entries (1)

```
present = valid
```

$$R/W = writes allowed?$$

$$U/S = user-mode allowed?$$
 ("user/supervisor")

```
XD = execute-disable?
```

$$A = accessed? (MMU sets to 1 on page read/write)$$

helps support writeback policy for swapping

x86-64 page table entries (2)

```
| Frot. | Ignored | Rsvd. | Address of 4KB page frame | Ign. | Ig
```

```
G = global? (shared between all page tables)
```

```
PWT, PCD, PAT = control how caches work when accessing physical page: can disable using the cache entirely can disable write-back (use write-through instead) multicore-related cache settings (and some other settings)
```

x86-64 page table entries (2)


-		5 5 5 5 5 5 8 7 6 5 4 3 2	I M	M-1 2 1 0 9 8 7 6 5 4 3 2 1 0 9 8 7 6 5 4 3 2 1 0 9 8 7 6 5 4 3 2 1	0		
X D	Prot. Key ⁴	Ignored	Rsvd.	Address of 4KB page frame	1	PTE: 4KB page	
	Ignored Q						


G = global? (shared between all page tables)


P CPU won't evict TLB entries on most page table base registers changes


can disable using the cache entirely can disable write-back (use write-through instead) multicore-related cache settings (and some other settings)


pa=translate(va)













divide memory into pages (2^8 bytes in this case) "virtual" = addresses the program sees



page number is upper bits of address (because page size is power of two)



rest of address is called page offset

toy physical memory

program memory virtual addresses

11	0000	0000	to
11	1111	1111	
10	0000	0000	to
10	1111	1111	
01	0000	0000	to
01	1111	1111	
00	0000	0000	to
00	1111	1111	

real memory physical addresses

. ,			
111	0000	0000	to
111	1111	1111	
001	0000	0000	to
001	1111	1111	
000	0000	0000	to
000	1111	1111	

toy physical memory

program memory virtual addresses


11	0000	0000	to
11	1111	1111	
10	0000	0000	to
10	1111	1111	
01	0000	0000	to
01	1111	1111	
00	0000	0000	to
00	1111	1111	


real memory physical addresses


11	L1	0000	0000	to	l n
11	L1	1111	1111		p
00	91	0000	0000	to	lո
00	91	1111	1111		p
00	00	0000	0000	to	lո
00	90	1111	1111		۱۲

physical page 7

physical page 1 physical page 0









toy page table lookup

```
virtual page # valid? physical page # 00 1 010 (2, code) 01 1 111 (7, data) 10 0 ??? (ignored) 11 1 000 (0, stack)
```

toy page table lookup




toy page table lookup




t "virtual page number" | ookup 1101 0010 — address from CPU virtual page # valid? physical page #010 (2, code) 00 (7, data) 01 (ignored) 10 000 (0, stack) 11 1101 0010 to memory trigger exception if 0?

toy page table lookup



toy pag "page offset" ookup



exit statuses

```
int main() {
    return 0;  /* or exit(0); */
}
```

the status

"status code" encodes both return value and if exit was abnormal W* macros to decode it

the status

"status code" encodes both return value and if exit was abnormal W* macros to decode it


program


operating system


keyboard


disk


program












program

operating system


network


disk




network

disk








read/write operations

```
read()/write(): move data into/out of buffer
possibly wait if buffer is empty (read)/full (write)
```

actual I/O operations — wait for device to be ready trigger process to stop waiting if needed

layering



why the extra layer

```
better (but more complex to implement) interface:
     read line
     formatted input (scanf, cin into integer, etc.)
    formatted output
less system calls (bigger reads/writes) sometimes faster
     buffering can combine multiple in/out library calls into one system call
more portable interface
    cin, printf, etc. defined by C and C++ standards
```

exercise

```
pid_t p = fork();
int pipe_fds[2];
pipe(pipe_fds);
if (p == 0) { /* child */
  close(pipe_fds[0]);
  char c = 'A';
 write(pipe_fds[1], &c, 1);
  exit(0);
} else { /* parent */
  close(pipe_fds[1]);
  char c;
  int count = read(pipe_fds[0], &c, 1);
  printf("read %d bytes\n", count);
```

The child is trying to send the character A to the parent, but the above code outputs read 0 bytes instead of read 1 bytes. What happened?

exercise solution

```
int pipe fd[2];
if (pipe(pipe fd) < 0)</pre>
    handle_error(); /* e.g. out of file descriptors */
int read_fd = pipe_fd[0];
int write_fd = pipe_fd[1];
child_pid = fork();
if (child pid == 0) {
    /* in child process, write to pipe */
    close(read fd);
    write_to_pipe(write_fd); /* function not shown */
    exit(EXIT SUCCESS);
} else if (child pid > 0) {
    /* in parent process, read from pipe */
    close(write fd);
    read_from_pipe(read_fd); /* function not shown */
    waitpid(child_pid, NULL, 0);
    close(read fd);
} else { /* fork error */ }
```

'standard' pattern with fork()

```
int pipe fd[2];
if (pipe(pipe fd) < 0)</pre>
    handle_error(); /* e.g. out of file descriptors */
int read_fd = pipe_fd[0];
int write_fd = pipe_fd[1];
child_pid = fork();
if (child_pid == 0) {
    /* in child process, write to pipe */
    close(read fd);
    write_to_pipe(write_fd); /* function not shown */
    exit(EXIT SUCCESS);
} else if (child pid > 0) {
    /* in parent process, read from pipe */
    close(write fd);
    read_from_pipe(read_fd); /* function not shown */
    waitpid(child pid, NULL, 0);
    close(read fd);
} else { /* fork error */ }
```


```
read() will not indicate
int pipe fd[2];
                                           end-of-file if write fd is open
if (pipe(pipe fd) < 0)</pre>
    handle_error(); /* e.g. out of file | (any copy of it)
int read_fd = pipe_fd[0];
int write_fd = pipe_fd[1];
child_pid = fork();
if (child pid == 0) {
    /* in child process, write to pipe */
    close(read fd);
    write_to_pipe(write_fd); /* function not shown */
    exit(EXIT SUCCESS);
} else if (child pid > 0) {
    /* in parent process, read from pipe */
    close(write fd);
    read_from_pipe(read_fd); /* function not shown */
    waitpid(child pid, NULL, 0);
    close(read fd);
} else { /* fork error */ }
```

```
have habit of closing
int pipe fd[2];
                                        to avoid 'leaking' file descriptors
if (pipe(pipe fd) < 0)</pre>
    handle_error(); /* e.g. out of fi you can run out
int read_fd = pipe_fd[0];
int write_fd = pipe_fd[1];
child_pid = fork();
if (child pid == 0) {
    /* in child process, write to pipe */
   close(read fd);
    write_to_pipe(write_fd); /* function not shown */
    exit(EXIT SUCCESS);
} else if (child pid > 0) {
    /* in parent process, read from pipe */
    close(write fd);
    read_from_pipe(read_fd); /* function not shown */
    waitpid(child pid, NULL, 0);
    close(read fd);
} else { /* fork error */ }
```

pipe() and blocking

```
BROKEN example:
int pipe_fd[2];
if (pipe(pipe_fd) < 0)
    handle_error();
int read_fd = pipe_fd[0];
int write_fd = pipe_fd[1];
write(write_fd, some_buffer, some_big_size);
read(read_fd, some_buffer, some_big_size);
This is likely to not terminate. What's the problem?</pre>
```

pattern with multiple?



this class: focus on Unix


Unix-like OSes will be our focus

we have source code

used to from 2150, etc.?

have been around for a while

xv6 imitates Unix



POSIX: standardized Unix

Portable Operating System Interface (POSIX) "standard for Unix"

current version online: https://pubs.opengroup.org/onlinepubs/9699919799/ (almost) followed by most current Unix-like OSes

...but OSes add extra features

...and POSIX doesn't specify everything

what POSIX defines

POSIX specifies the library and shell interface source code compatibility

doesn't care what is/is not a system call...

doesn't specify binary formats...

idea: write applications for POSIX, recompile and run on all implementations

this was a very important goal in the 80s/90s at the time, no dominant Unix-like OS (Linux was very immature)

POSIX process management

essential operations

```
process information: getpid
process creation: fork
running programs: exec*
    also posix_spawn (not widely supported), ...
waiting for processes to finish: waitpid (or wait)
process destruction, 'signaling': exit, kill
```

getpid

```
pid_t my_pid = getpid();
printf("my pid is %ld\n", (long) my_pid);
```

process ids in ps

read/write

```
ssize_t read(int fd, void *buffer, size_t count);
ssize_t write(int fd, void *buffer, size_t count);
read/write up to count bytes to/from buffer
returns number of bytes read/written or -1 on error
    ssize t is a signed integer type
    error code in errno
read returning 0 means end-of-file (not an error)
    can read/write less than requested (end of file, broken I/O device, ...)
```

read'ing one byte at a time

```
string s;
ssize_t amount_read;
char c;
/* cast to void * not needed in C */
while ((amount_read = read(STDIN_FILENO, (void*) &c, 1)) > 0)
    /* amount read must be exactly 1 */
    s += c;
if (amount\_read == -1) {
    /* some error happened */
    perror("read"); /* print out a message about it */
} else if (amount read == 0) {
   /* reached end of file */
```

write example

```
/* cast to void * optional in C */
write(STDOUT_FILENO, (void *) "Hello, World!\n", 14);
```

read/write

```
ssize_t read(int fd, void *buffer, size_t count);
ssize_t write(int fd, void *buffer, size_t count);
read/write up to count bytes to/from buffer
returns number of bytes read/written or -1 on error
    ssize t is a signed integer type
    error code in errno
read returning 0 means end-of-file (not an error)
    can read/write less than requested (end of file, broken I/O device, ...)
```

read'ing a fixed amount

```
ssize t offset = 0;
const ssize t amount to read = 1024;
char result[amount to read];
do {
    /* cast to void * optional in C */
    ssize t amount read =
        read(STDIN FILENO,
             (void *) (result + offset),
             amount to read - offset);
    if (amount read < 0) {</pre>
        perror("read"); /* print error message */
        ... /* abort??? */
    } else {
        offset += amount_read;
} while (offset != amount_to_read && amount_read != 0);
```

partial reads

on regular file: read reads what you request

but otherwise: usually gives you what's known to be available after waiting for something to be available

partial reads

on regular file: read reads what you request

but otherwise: usually gives you what's known to be available after waiting for something to be available

reading from network — what's been received

reading from keyboard — what's been typed

write example (with error checking)

```
const char *ptr = "Hello, World!\n";
ssize t remaining = 14;
while (remaining > 0) {
    /* cast to void * optional in C */
    ssize_t amount_written = write(STDOUT_FILENO,
                                    ptr,
                                     remaining);
    if (amount written < 0) {</pre>
        perror("write"); /* print error message */
        ... /* abort??? */
    } else {
        remaining -= amount_written;
        ptr += amount_written;
```

partial writes

usually only happen on error or interruption

but can request "non-blocking" (interruption: via signal)

usually: write waits until it completes

= until remaining part fits in buffer in kernel does not mean data was sent on network, shown to user yet, etc.

aside: environment variables (1)

key=value pairs associated with every process: \$ printenv

MODULE VERSION_STACK=3.2.10 MANPATH=:/opt/puppetlabs/puppet/share/man XDG SESSION ID=754

HOSTNAME=labsrv01 SELINUX ROLE REQUESTED=

TERM=screen SHELL=/bin/bash HISTSIZE=1000

QTDIR=/usr/lib64/qt-3.3

USFR=cr4bd

LANG=en US.UTF-8

LOADEDMODULES=

SSH CLIENT=128.143.67.91 58432 22 SELINUX USE CURRENT RANGE=

OLDPWD=/zf14/cr4bd QTINC=/usr/lib64/qt-3.3/include

SSH TTY=/dev/pts/0 QT_GRAPHICSSYSTEM_CHECKED=1

LS_COLORS=rs=0:di=01;34:ln=01;36:mh=00:pi=40;33:so=01;35:do=01;35:bd=40;33;01:cd=40;33;01:or

MODULE VERSION=3.2.10 MAIL=/var/spool/mail/cr4bd

PWD=/zf14/cr4bd

PATH=/zf14/cr4bd/.cargo/bin:/zf14/cr4bd/bin:/usr/lib64/qt-3.3/bin:/usr/local/bin:/usr/bin:/u

MODULEPATH=/sw/centos/Modules/modulefiles:/sw/linux-any/Modules/modulefiles

139

aside: environment variables (2)

```
environment variable library functions:
    getenv("KEY") → value
    putenv("KEY=value") (sets KEY to value)
    setenv("KEY", "value") (sets KEY to value)

int execve(char *path, char **argv, char **envp)
    char *envp[] = { "KEY1=value1", "KEY2=value2", NULL };
    char *argv[] = { "somecommand", "some arg", NULL };
    execve("/path/to/somecommand", argv, envp);
```

normal exec versions — keep same environment variables

aside: environment variables (3)

interpretation up to programs, but common ones...

```
PATH=/bin:/usr/bin
to run a program 'foo', look for an executable in /bin/foo, then
/usr/bin/foo
```

```
HOME=/zf14/cr4bd current user's home directory is '/zf14/cr4bd'
```

```
TERM=screen-256color your output goes to a 'screen-256color'-style terminal
```

...

multiple processes?

```
while (...) {
    pid = fork();
    if (pid == 0) {
        exec ...
    } else if (pid > 0) {
        pids.push back(pid);
/* retrieve exit statuses in order */
for (pid t pid : pids) {
    waitpid(pid, ...);
```

waiting for all children

```
#include <sys/wait.h>
 while (true) {
   pid_t child_pid = waitpid(-1, &status, 0);
    if (child pid == (pid t) -1) {
      if (errno == ECHILD) {
       /* no child process to wait for */
        break;
      } else {
       /* some other error */
    /* handle child_pid exiting */
```

multiple processes?

```
while (...) {
    pid = fork();
    if (pid == 0) {
        exec ...
    } else if (pid > 0) {
        pids.push back(pid);
/* retrieve exit statuses as processes finish */
while ((pid = waitpid(-1, ...)) != -1) {
    handleProcessFinishing(pid);
```

'waiting' without waiting

```
#include <sys/wait.h>
...
pid_t return_value = waitpid(child_pid, &status, WNOHANG);
if (return_value == (pid_t) 0) {
    /* child process not done yet */
} else if (child_pid == (pid_t) -1) {
    /* error */
} else {
    /* handle child_pid exiting */
}
```

parent and child processes

every process (but process id 1) has a parent process
(getppid())

this is the process that can wait for it

creates tree of processes (Linux pstree command):

```
init(1)-+-ModemManager(919)-+-{ModemManager}(972)
                                                                           -mongod(1336)-+-{mongod}(1556)
                                {ModemManager}(1864)
                                                                                           mongod)(1557)
         -NetworkManager(1160)-+-dhclient(1755)
                                                                                            rongod}(1983)
                                 |-dnsmasq(1985)
                                  -{NetworkManager}(1180)
                                   -{NetworkManager}(1194)
                                   {NetworkManager}(1195)
         |-accounts-daemon(1649)-+-{accounts-daemon}(1757)
                                   -{accounts-daemon}(1758)
                                                                                          {mongod}(2052)
         I-acpid(1338)
                                                                           -mosh-server(19898)---bash(19891)---tmux(5442)
         -apache2(3165)-+-apache2(4125)-+-{apache2}(4126)
                                                                           -mosh-server(21996)---bash(21997)
                                            -{apache2}(4127)
                                                                           -mosh-server(22533)---bash(22534)---tmux(22588)
                            apache2(28920)-+-{apache2}(28926)
                                                                           -nm-applet(2580)-+-{nm-applet}(2739)
                                              {apache2}(28960)
                                                                                            -{nm-applet}(2743)
                            apache2(28921)-+-{apache2}(28927)
                                                                           -nmbd(2224)
                                              {apache2}(28963)
                                                                          -ntpd(3891)
                                                                           -polkitd(1197)-+-(polkitd)(1239)
                            apache2(28922)-+-{apache2}(28928)
                                                                                          -(polkitd)(1248)
                                              -{apache2}(28961)
                                                                           -pulseaudio(2563)-+-{pulseaudio}(2617)
                            apache2(28923)-+-{apache2}(28930)
                                                                                             -{pulseaudio}(2623)
                                              -{apache2}(28962)
                                                                           -puppet(2373)---{puppet}(32455)
                            apache2(28925)-+-{apache2}(28958)
                                                                          -rpc.1dmapd(875)
                                              -{apache2}(28965)
                                                                          -rpc.statd(954)
                            apache2(32165)-+-{apache2}(32166)
                                                                           -rpcbind(884)
                                             -{apache2}(32167)
                                                                           -rserver(1501)-+-{rserver}(1786)
                                                                                          -{rserver}(1787)
          -at-spi-bus-laun(2252)-+-dbus-daemon(2269)
                                  I-{at-spi-bus-laun}(2266)
                                                                           -rsyslogd(1090)-+-{rsyslogd}(1092)
                                                                                          |-{rsyslogd}(1093)
                                   |-{at-spi-bus-laun}(2268)
                                                                                            (rsysload)(1894)
                                   -{at-spi-bus-laun}(2270)
                                                                           -rtkit-daenon(2565)-+-{rtkit-daenon}(2566)
         -at-spi2-registr(2275)---{at-spi2-registr}(2282)
                                                                                               -{rtkit-daemon}(2567)
         l-atd(1633)
                                                                           -sd cicero(2852)-+-sd cicero(2853)
         |-automount(13454)-+-{automount}(13455)
                                                                                             {sd ctcero}(2854)
                              -{automount}(13456)
                                                                                             (sd ctcero)(2855)
                                                                           -sd dunny(2849)-+-{sd dunny}(2850)
                               -{automount}(13461)
                                                                                            -{sd dunny}(2851)
                               {automount}(13464)
                                                                           -sd espeak(2749)-+-{sd espeak}(2845)
                               -{automount}(13465)
                                                                                             (sd espeak)(2846)
         -avaht-daemon(934)---avaht-daemon(944)
                                                                                             {sd_espeak}(2847)
         |-bluetoothd(924)
                                                                                             (sd espeak)(2848)
         |-colord(1193)-+-{colord}(1329)
                                                                          -sd_generic(2463)-+-{sd_generic}(2464)
```

parent and child questions...

```
what if parent process exits before child?
        child's parent process becomes process id 1 (typically called init)
what if parent process never waitpid()s (or equivalent) for child?
        child process stays around as a "zombie"
        can't reuse pid in case parent wants to use waitpid()
what if non-parent tries to waitpid() for child?
        waitpid fails
```


program


operating system


keyboard


disk


program












program

operating system


network


disk




network

disk







read/write operations

```
read()/write(): move data into/out of buffer
possibly wait if buffer is empty (read)/full (write)
```

actual I/O operations — wait for device to be ready trigger process to stop waiting if needed

filesystem abstraction

```
regular files — named collection of bytes also: size, modification time, owner, access control info, ...
```

directories — folders containing files and directories
hierarchical naming: /net/zf14/cr4bd/fall2018/cs4414
mostly contains regular files or directories

open

open

other.txt in directory quux in

```
int open(const char *path, int flags);
int open(const char *path, int flags, int mode);
path = filename
e.g. "/foo/bar/file.txt"
    file.txt in
   directory bar in
   directory foo in
    "the root directory"
e.g. "quux/other.txt
```

"the current working directory" (set with chdir())

153

open: file descriptors

```
int open(const char *path, int flags);
int open(const char *path, int flags, int mode);
return value = file descriptor (or -1 on error)
index into table of open file descriptions for each process
used by system calls that deal with open files
```

POSIX: everything is a file

```
the file: one interface for
devices (terminals, printers, ...)
regular files on disk
networking (sockets)
local interprocess communication (pipes, sockets)
```

basic operations: open(), read(), write(), close()

exercise

```
int pipe_fds[2]; pipe(pipe_fds);
pid_t p = fork();
if (p == 0) {
  close(pipe_fds[0]);
  for (int i = 0; i < 10; ++i) {
   char c = '0' + i;
   write(pipe_fds[1], &c, 1);
 exit(0);
close(pipe_fds[1]);
char buffer[10];
ssize_t count = read(pipe_fds[0], buffer, 10);
for (int i = 0; i < count; ++i) {
 printf("%c", buffer[i]);
```

Which of these are possible outputs (if pipe, read, write, fork don't fail)?

A. 0123456789 B. 0 C. (nothing)

D. A and B E. A and C F. A, B, and C

partial reads

read returning 0 always means end-of-file by default, read always waits *if no input available yet* but can set read to return *error* instead of waiting

read can return less than requested if not available e.g. child hasn't gotten far enough

pipe: closing?

```
if all write ends of pipe are closed
can get end-of-file (read() returning 0) on read end
exit()ing closes them
```

 \rightarrow close write end when not using

generally: limited number of file descriptors per process

→ good habit to close file descriptors not being used (but probably didn't matter for read end of pipes in example)

swapping almost mmap

```
access mapped file for first time, read from disk (like swapping when memory was swapped out)
```

```
write "mapped" memory, write to disk eventually (like writeback policy in swapping) use "dirty" bit
```

extra detail: other processes should see changes all accesses to file use same physical memory