

threads versus processes

so far, was showing each process has one thread

thread = part that gets run on CPU

- saved register values (including own stack pointer)

- save program counter

rest of process

- address space (accessible memory)


- open files

- current working directory


- ...

single and multithread processes

single-threaded process



multi-threaded process



thread versus process state

thread state

- registers (including stack pointer, program counter)

- ...

process state

- address space

- open files

- process id

- list of thread states

- ...

process info with threads

parent process info

thread infos	thread 0: {PC = 0x123456, rax = 42, rbx = ...} thread 1: {PC = 0x584390, rax = 32, rbx = ...} ...
page tables	
open files	fd 0: ... fd 1: ...
...	...

Linux idea: `task_struct`

Linux model: single “task” structure = thread

pointers to address space, open file list, etc.

pointers **can be shared**

e.g. shared open files: open fd 4 in one task → all sharing can use fd 4

`fork()`-like system call “clone”: **choose what to share**

`clone(0, ...)` — similar to `fork()`

`clone(CLONE_FILES, ...)` — like `fork()`, but **sharing** open files

`clone(CLONE_VM, new_stack_pointer, ...)` — like `fork()`, but **sharing** address space

Linux idea: `task_struct`

Linux model: single “task” structure = thread

pointers to address space, open file list, etc.

pointers **can be shared**

e.g. shared open files: open fd 4 in one task → all sharing can use fd 4

`fork()`-like system call “clone”: **choose what to share**

`clone(0, ...)` — similar to `fork()`

`clone(CLONE_FILES, ...)` — like `fork()`, but **sharing** open files


`clone(CLONE_VM, new_stack_pointer, ...)` — like `fork()`, but **sharing** address space

advantage: no special logic for threads (mostly)

two threads in same process = tasks sharing everything possible

pthread_create

```
void *ComputePi(void *argument) { ... }  
void *PrintClassList(void *argument) { ... }  
int main() {  
    pthread_t pi_thread, list_thread;  
    pthread_create(&pi_thread, NULL, ComputePi, NULL);  
    pthread_create(&list_thread, NULL, PrintClassList, NULL);  
    ... /* more code */  
}
```



pthread_create

```
void *ComputePi(void *argument) { ... }  
void *PrintClassList(void *argument) { ... }  
int main() {  
    pthread_t pi_thread, list_thread;  
    pthread_create(&pi_thread, NULL, ComputePi, NULL);  
    pthread_create(&list_thread, NULL, PrintClassList, NULL);  
    ... /* more code */  
}
```

pthread_create arguments:

thread identifier

function to run

thread starts here, terminates if this function returns

thread attributes (extra settings) and function argument

pthread_create

```
void *ComputePi(void *argument) { ... }  
void *PrintClassList(void *argument) { ... }  
int main() {  
    pthread_t pi_thread, list_thread;  
    pthread_create(&pi_thread, NULL, ComputePi, NULL);  
    pthread_create(&list_thread, NULL, PrintClassList, NULL);  
    ... /* more code */  
}
```

pthread_create arguments:

thread identifier

function to run

thread starts here, terminates if this function returns

thread attributes (extra settings) and function argument

pthread_create

```
void *ComputePi(void *argument) { ... }
void *PrintClassList(void *argument) { ... }
int main() {
    pthread_t pi_thread, list_thread;
    pthread_create(&pi_thread, NULL, ComputePi, NULL);
    pthread_create(&list_thread, NULL, PrintClassList, NULL);
    ... /* more code */
}
```

pthread_create arguments:

thread identifier

function to run

thread starts here, terminates if this function returns

thread attributes (extra settings) and function argument

pthread_create

```
void *ComputePi(void *argument) { ... }  
void *PrintClassList(void *argument) { ... }  
int main() {  
    pthread_t pi_thread, list_thread;  
    pthread_create(&pi_thread, NULL, ComputePi, NULL);  
    pthread_create(&list_thread, NULL, PrintClassList, NULL);  
    ... /* more code */  
}
```

pthread_create arguments:

thread identifier

function to run

thread starts here, terminates if this function returns

thread attributes (extra settings) and function argument

a threading race


```
#include <pthread.h>
#include <stdio.h>
void *print_message(void *ignored_argument) {
    printf("In the thread\n");
    return NULL;
}
int main() {
    printf("About to start thread\n");
    pthread_t the_thread;
    pthread_create(&the_thread, NULL, print_message, NULL);
    printf("Done starting thread\n");
    return 0;
}
```

My machine: outputs In the thread about 4% of the time.
What happened?

a race

returning from main **exits the entire process** (all its threads)
same as calling exit; not like other threads

race: main's return 0 or print_message's printf first?



fixing the race (version 1)

```
#include <pthread.h>
#include <stdio.h>
void *print_message(void *ignored_argument) {
    printf("In the thread\n");
    return NULL;
}
int main() {
    printf("About to start thread\n");
    pthread_t the_thread;
    pthread_create(&the_thread, NULL, print_message, NULL);
    printf("Done starting thread\n");
    pthread_join(the_thread, NULL); /* WAIT FOR THREAD */
    return 0;
}
```

fixing the race (version 2; not recommended)

```
#include <pthread.h>
#include <stdio.h>
void *print_message(void *ignored_argument) {
    printf("In the thread\n");
    return NULL;
}
int main() {
    printf("About to start thread\n");
    pthread_t the_thread;
    pthread_create(&the_thread, NULL, print_message, NULL);
    printf("Done starting thread\n");
    pthread_exit(NULL);
}
```


pthread_join, pthread_exit

`pthread_join`: wait for thread, retrieves its return value
like `waitpid`, but for a thread
return value is pointer to anything

`pthread_exit`: exit current thread, returning a value
like `exit` or returning from `main`, but for a single thread
same effect as returning from function passed to `pthread_create`

sum example (only globals)

```
int values[1024];
int results[2];
void *sum_front(void *ignored_argument) {
    int sum = 0;
    for (int i = 0; i < 512; ++i)
        sum += values[i];
    results[0] = sum;
    return NULL;
}
void *sum_back(void *ignored_argument) {
    int sum = 0;
    for (int i = 512; i < 1024; ++i)
        sum += values[i];
    results[1] = sum;
    return NULL;
}
int sum_all() {
    pthread_t sum_front_thread, sum_back_thread;
    pthread_create(&sum_front_thread, NULL, sum_front, NULL);
    pthread_create(&sum_back_thread, NULL, sum_back, NULL);
    pthread_join(sum_front_thread, NULL);
    pthread_join(sum_back_thread, NULL);
    return results[0] + results[1];
}
```

sum example (only globals)

```
int values[1024];
int results[2];
void *sum_front(void *ignored_argument) {
    int sum = 0;
    for (int i = 0; i < 512; ++i)
        sum += values[i];
    results[0] = sum;
    return NULL;
}
void *sum_back(void *ignored_argument) {
    int sum = 0;
    for (int i = 512; i < 1024; ++i)
        sum += values[i];
    results[1] = sum;
    return NULL;
}
int sum_all() {
    pthread_t sum_front_thread, sum_back_thread;
    pthread_create(&sum_front_thread, NULL, sum_front, NULL);
    pthread_create(&sum_back_thread, NULL, sum_back, NULL);
    pthread_join(sum_front_thread, NULL);
    pthread_join(sum_back_thread, NULL);
    return results[0] + results[1];
}
```

values, results: global variables — shared

sum example (only globals)

two different functions

happen to be the same except for some numbers

```
int values[1024];
int results[2];
void *sum_front(void) {
    int sum = 0;
    for (int i = 0; i < 512; ++i)
        sum += values[i];
    results[0] = sum;
    return NULL;
}
void *sum_back(void *ignored_argument) {
    int sum = 0;
    for (int i = 512; i < 1024; ++i)
        sum += values[i];
    results[1] = sum;
    return NULL;
}
int sum_all() {
    pthread_t sum_front_thread, sum_back_thread;
    pthread_create(&sum_front_thread, NULL, sum_front, NULL);
    pthread_create(&sum_back_thread, NULL, sum_back, NULL);
    pthread_join(sum_front_thread, NULL);
    pthread_join(sum_back_thread, NULL);
    return results[0] + results[1];
}
```

sum example (only global)

values returned from threads


via global array instead of return value

(partly to illustrate that memory is shared,

partly because this pattern works when we don't join (later))

```
int values[1024];
int results[2];
void *sum_front(void *ignored_argument) {
    int sum = 0;
    for (int i = 0; i < 512; ++i)
        sum += values[i];
    results[0] = sum;
    return NULL;
}
void *sum_back(void *ignored_argument) {
    int sum = 0;
    for (int i = 512; i < 1024; ++i)
        sum += values[i];
    results[1] = sum;
    return NULL;
}
int sum_all() {
    pthread_t sum_front_thread, sum_back_thread;
    pthread_create(&sum_front_thread, NULL, sum_front, NULL);
    pthread_create(&sum_back_thread, NULL, sum_back, NULL);
    pthread_join(sum_front_thread, NULL);
    pthread_join(sum_back_thread, NULL);
    return results[0] + results[1];
}
```

thread_sum memory layout



0xFFFF FFFF FFFF FFFF


0xFFFF 8000 0000 0000

0x7F...

values, results (global)

0x0000 0000 0040 0000

thread_sum memory layout



sum example (to global, with thread IDs)

```
int values[1024];
int results[2];
void *sum_thread(void *argument) {
    int id = (int) argument;
    int sum = 0;
    for (int i = id * 512; i < (id + 1) * 512; ++i) {
        sum += values[i];
    }
    results[id] = sum;
    return NULL;
}
int sum_all() {
    pthread_t thread[2];
    for (int i = 0; i < 2; ++i) {
        pthread_create(&threads[i], NULL, sum_thread, (void *) i);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return results[0] + results[1];
}
```


sum example (to global, with thread IDs)

```
int values[1024];
int results[2];
void *sum_thread(void *argument) {
    int id = (int) argument;
    int sum = 0;
    for (int i = id * 512; i < (id + 1) * 512; ++i) {
        sum += values[i];
    }
    results[id] = sum;
    return NULL;
}
int sum_all() {
    pthread_t thread[2];
    for (int i = 0; i < 2; ++i) {
        pthread_create(&threads[i], NULL, sum_thread, (void *) i);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return results[0] + results[1];
}
```

values, results: global variables — shared

sum example (info struct)

```
int values[1024];
struct ThreadInfo {
    int start, end, result;
};
void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i) {
        sum += values[i];
    }
    my_info->result = sum;
    return NULL;
}
int sum_all() {
    pthread_t thread[2]; ThreadInfo info[2];
    for (int i = 0; i < 2; ++i) {
        info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&threads[i], NULL, sum_thread, &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return info[0].result + info[1].result;
}
```

sum example (info struct)

```
int values[1024];
struct ThreadInfo
{
    int start, end, result;
};

void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i) {
        sum += values[i];
    }
    my_info->result = sum;
    return NULL;
}

int sum_all() {
    pthread_t thread[2]; ThreadInfo info[2];
    for (int i = 0; i < 2; ++i) {
        info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&threads[i], NULL, sum_thread, &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return info[0].result + info[1].result;
}
```

values: global variable — shared

sum example (info struct)


```
int values[1024];
struct ThreadInfo {
    int start, end, result;
};
void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i)
        sum += values[i];
    my_info->result = sum;
    return NULL;
}
int sum_all() {
    pthread_t thread[2]; ThreadInfo info[2];
    for (int i = 0; i < 2; ++i) {
        info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&thread[i], NULL, sum_thread, &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(thread[i], NULL);
    return info[0].result + info[1].result;
}
```

my_info: pointer to sum_all's stack
only okay because sum_all waits!

sum example (info struct)

```
int values[1024];
struct ThreadInfo {
    int start, end, result;
};
void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i) {
        sum += values[i];
    }
    my_info->result = sum;
    return NULL;
}
int sum_all() {
    pthread_t thread[2]; ThreadInfo info[2];
    for (int i = 0; i < 2; ++i) {
        info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&threads[i], NULL, sum_thread, &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return info[0].result + info[1].result;
}
```

thread_sum memory layout (info struct)



0xFFFF FFFF FFFF FFFF

0xFFFF 8000 0000 0000

0x7F...

info array

my_info

my_info

values (global)

0x0000 0000 0040 0000

sum example (to main stack)

```
struct ThreadInfo { int *values; int start; int end; int result };
void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i) {
        sum += my_info->values[i];
    }
    my_info->result = sum;
    return NULL;
}

int sum_all(int *values) {
    ThreadInfo info[2]; pthread_t thread[2];
    for (int i = 0; i < 2; ++i) {
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&threads[i], NULL, sum_thread, (void *) &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return info[0].result + info[1].result;
}
```

sum example (to main stack)

```
struct ThreadInfo { int *values; int start; int end; int result };
void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i) {
        sum += my_info->values[i];
    }
    my_info->result = sum;
    return NULL;
}

int sum_all(int *values) {
    ThreadInfo info[2]; pthread_t thread[2];
    for (int i = 0; i < 2; ++i) {
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&threads[i], NULL, sum_thread, (void *) &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return info[0].result + info[1].result;
}
```


sum example (to main stack)


```
struct ThreadInfo { int *values; int start; int end; int result };  
void *sum_thread(void *argument) {  
    ThreadInfo *my_info = (ThreadInfo *) argument;  
    int sum = 0;  
    for (int i = my_info->start; i < my_info->end; ++i) {  
        sum += my_info->values[i];  
    }  
    my_info->result = sum;  
    return NULL;  
}  
  
int sum_all(int *values) {  
    ThreadInfo info[2]; pthread_t thread[2];  
    for (int i = 0; i < 2; ++i) {  
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;  
        pthread_create(&threads[i], NULL, sum_thread, (void *) &info[i]);  
    }  
    for (int i = 0; i < 2; ++i)  
        pthread_join(threads[i], NULL);  
    return info[0].result + info[1].result;  
}
```

sum example (to main stack)

```
struct ThreadInfo { int *values; int start; int end; int result };
void *sum_thread(void *argument) {
    ThreadInfo *my_info = (ThreadInfo *) argument;
    int sum = 0;
    for (int i = my_info->start; i < my_info->end; ++i) {
        sum += my_info->values[i];
    }
    my_info->result = sum;
    return NULL;
}

int sum_all(int *values) {
    ThreadInfo info[2]; pthread_t thread[2];
    for (int i = 0; i < 2; ++i) {
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&threads[i], NULL, sum_thread, (void *) &info[i]);
    }
    for (int i = 0; i < 2; ++i)
        pthread_join(threads[i], NULL);
    return info[0].result + info[1].result;
}
```

program memory (to main stack)



0xFFFF FFFF FFFF FFFF

0xFFFF 8000 0000 0000

0x7F...

info array

values (stack? heap?)

my_info

my_info

0x0000 0000 0040 0000

sum example (on heap)

```
struct ThreadInfo { pthread_t thread; int *values; int start; int end; int result;
void *sum_thread(void *argument) {
    ...
}

ThreadInfo *start_sum_all(int *values) {
    ThreadInfo *info = new ThreadInfo[2];
    for (int i = 0; i < 2; ++i) {
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&info[i].thread, NULL, sum_thread, (void *) &info[i]);
    }
    return info;
}

int finish_sum_all(ThreadInfo *info) {
    for (int i = 0; i < 2; ++i)
        pthread_join(info[i].thread, NULL);
    int result = info[0].result + info[1].result;
    delete[] info;
    return result;
}
```

sum example (on heap)

```
struct ThreadInfo { pthread_t thread; int *values; int start; int end; int result;
void *sum_thread(void *argument) {
    ...
}

ThreadInfo *start_sum_all(int *values) {
    ThreadInfo *info = new ThreadInfo[2];
    for (int i = 0; i < 2; ++i) {
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&info[i].thread, NULL, sum_thread, (void *) &info[i]);
    }
    return info;
}

int finish_sum_all(ThreadInfo *info) {
    for (int i = 0; i < 2; ++i)
        pthread_join(info[i].thread, NULL);
    int result = info[0].result + info[1].result;
    delete[] info;
    return result;
}
```


sum example (on heap)

```
struct ThreadInfo { pthread_t thread; int *values; int start; int end; int result;
void *sum_thread(void *argument) {
    ...
}

ThreadInfo *start_sum_all(int *values) {
    ThreadInfo *info = new ThreadInfo[2];
    for (int i = 0; i < 2; ++i) {
        info[i].values = values; info[i].start = i*512; info[i].end = (i+1)*512;
        pthread_create(&info[i].thread, NULL, sum_thread, (void *) &info[i]);
    }
    return info;
}

int finish_sum_all(ThreadInfo *info) {
    for (int i = 0; i < 2; ++i)
        pthread_join(info[i].thread, NULL);
    int result = info[0].result + info[1].result;
    delete[] info;
    return result;
}
```

thread_sum memory (heap version)



0xFFFF FFFF FFFF FFFF

0xFFFF 8000 0000 0000

0x7F...

my_info

my_info

info array


values (stack? heap?)

0x0000 0000 0040 0000

what's wrong with this?

```
/* omitted: headers */
#include <string>
using std::string;
void *create_string(void *ignored_argument) {
    string result;
    result = ComputeString();
    return &result;
}
int main() {
    pthread_t the_thread;
    pthread_create(&the_thread, NULL, create_string, NULL);
    string *string_ptr;
    pthread_join(the_thread, (void*) &string_ptr);
    cout << "string is " << *string_ptr;
}
```


program memory



0xFFFF FFFF FFFF FFFF

0xFFFF 8000 0000 0000


0x7F...

} dynamically allocated stacks
} string result allocated here
} string_ptr pointed to here

...stacks deallocated when
threads exit/are joined

0x0000 0000 0040 0000

program memory



0xFFFF FFFF FFFF FFFF

0xFFFF 8000 0000 0000

0x7F...

} dynamically allocated stacks
} string result allocated here
} string_ptr pointed to here

...stacks deallocated when
threads exit/are joined

0x0000 0000 0040 0000

thread resources

to create a thread, allocate:

new stack (how big???)

thread control block

deallocated when ...

thread resources

to create a thread, allocate:

new stack (how big???)

thread control block

deallocated when ...

can deallocate stack when thread exits

but need to allow collecting return value

same problem as for processes and waitpid

pthread_detach

```
void *show_progress(void * ...) { ... }  
void spawn_show_progress_thread() {  
    pthread_t show_progress_thread;  
    pthread_create(&show_progress_thread, NULL, show_progress, NULL)  
  
    /* instead of keeping pthread_t around to join thread later: */  
    pthread_detach(show_progress_thread);  
}  
  
int main() {  
    spawn_show_progress_thread();  
    do_other_stuff();  
    ...  
}
```

detach = don't care about return value, etc.
system will deallocate when thread terminates

starting threads detached

```
void *show_progress(void * ...) { ... }  
void spawn_show_progress_thread() {  
    pthread_t show_progress_thread;  
    pthread_attr_t attrs;  
    pthread_attr_init(&attrs);  
    pthread_attr_setdetachstate(&attrs, PTHREAD_CREATE_DETACHED);  
    pthread_create(&show_progress_thread, attrs,  
                  show_progress, NULL);  
    pthread_attr_destroy(&attrs);  
}
```

setting stack sizes

```
void *show_progress(void * ...) { ... }  
void spawn_show_progress_thread() {  
    pthread_t show_progress_thread;  
    pthread_attr_t attrs;  
    pthread_attr_init(&attrs);  
    pthread_attr_setstacksize(&attrs, 32 * 1024 /* bytes */);  
    pthread_create(&show_progress_thread, attrs,  
                  show_progress, NULL);  
}
```

a note on error checking

from `pthread_create` manpage:

ERRORS

EAGAIN Insufficient resources to create another thread, or a system-imposed limit on the number of threads was encountered. The latter case may occur in two ways: the **RLIMIT_NPROC** soft resource limit (set via `setrlimit(2)`), which limits the number of process for a real user ID, was reached; or the kernel's system-wide limit on the number of threads, [`/proc/sys/kernel/threads-max`](#), was reached.

EINVAL Invalid settings in `attr`.

EPERM No permission to set the scheduling policy and parameters specified in `attr`.

special constants for *return value*

same pattern for many other pthreads functions

will often omit error checking in slides for brevity

error checking pthread_create

```
int error = pthread_create(...);  
if (error != 0) {  
    /* print some error message */  
}
```

backup slides

why threads?

concurrency: different things happening at once

- one thread per user of web server?

- one thread per page in web browser?

- one thread to play audio, one to read keyboard, ...?

- ...

parallelism: do same thing with more resources

- multiple processors to speed-up simulation (life assignment)

aside: alternate threading models

we'll talk about **kernel threads**

OS scheduler deals **directly** with threads

alternate idea: library code handles threads

kernel doesn't know about threads w/in process

hierarchy of schedulers: one for processes, one within each process

not currently common model — awkward with multicore