check_passphrase

```
int check_passphrase(const char *versus) {
    int i = 0;
    while (passphrase[i] == versus[i] &&
           passphrase[i]) {
        i += 1;
    }
    return (passphrase[i] == versus[i]);
}
```

number of iterations = number matching characters

leaks information about passphrase, oops!

exploiting check_passphrase (1)

guess	measured time
aaaa	100 ± 5
baaa	103 ± 4
caaa	102 ± 6
daaa	111 ± 5
eaaa	99 ± 6
faaa	101 ± 7
gaaa	104 ± 4
…	…

exploiting check_passphrase (2)

guess	measured time
daaa	102 ± 5
dbaa	99 ± 4
dcaa	104 ± 4
ddaa	100 ± 6
deaa	102 ± 4
dfaa	109 ± 7
dgaa	103 ± 4
...	...

timing and cryptography

lots of asymmetric cryptography uses big-integer math

example: multiplying 500+ bit numbers together

how do you implement that?

big integer multiplcation

say we have two 64-bit integers x, y

and want to 128-bit product, but our multiply instruction only does 64-bit products

one way to multiply:

divide x, y into 32-bit parts: $x = x_1 \cdot 2^{32} + x_0$ and $y = y_1 \cdot 2^{32} + y_0$

then $xy = x_1 y_1 2^{64} + x_1 y_0 \cdot 2^{32} + x_0 y_1 \cdot 2^{32} + x_0 y_0$

big integer multiplcation

say we have two 64-bit integers x, y

and want to 128-bit product, but our multiply instruction only does 64-bit products

one way to multiply:

divide x, y into 32-bit parts: $x = x_1 \cdot 2^{32} + x_0$ and $y = y_1 \cdot 2^{32} + y_0$

then $xy = x_1 y_1 2^{64} + x_1 y_0 \cdot 2^{32} + x_0 y_1 \cdot 2^{32} + x_0 y_0$

can extend this idea to arbitrarily large numbers

number of smaller multiplies depends on size of numbers!

big integers and cryptography

naive multiplication idea:

- number of steps depends on size of numbers

problem: sometimes the value of the number is a secret

- e.g. part of the private key

oops! revealed through timing

big integer timing attacks in practice (1)

early versions of OpenSSL (TLS implementation)had timing attack

- Brumley and Boneh, “Remote Timing Attacks are Practical” (Usenix Security ’03)

attacker could figure out bits of private key from timing

why? variable-time mulitplication and modulus operations

- got faster/slower depending on how input was related to private key

big integer timing attacks in practice (2)



(a) The zero-one gap $T_g - T_{g_{hi}}$ indicates that we can distinguish between bits that are 0 and 1 of the RSA factor q for 3 different randomly-generated keys. For clarity, bits of q that are 1 are omitted, as the x-axis can be used for reference for this case.

Figure 3a from Brumley and Boneh, "Remote Timing Attacks are Practical"

browsers and website leakage

web browsers run code from untrusted webpages

one goal: can't tell what other webpages you visit

some webpage leakage (1)

...as you can see here, here, and here ...

convenient feature 1: browser marks visited links

```
<script>
var the_color = window.getComputedStyle(
    document.querySelector('a[href=~"foo.com"]')
).color
if (color == ...) { ... }
</script>
```

convenient feature 2: scripts can query current color of something

some webpage leakage (1)

...as you can see here, here, and here ...

convenient feature 1: browser marks visited links

```
<script>
var the_color = window.getComputedStyle(
    document.querySelector('a[href=~"foo.com"]')
).color
if (color == ...) { ... }
</script>
```

~~convenient feature 2: scripts can query current color of something~~

fix 1: getComputedStyle lies about the color

fix 2: limited styling options for visited links

some webpage leakage (2)

one idea: script in webpage times loop that writes big array

variation in timing depends on other things running on machine

some webpage leakage (2)

one idea: script in webpage times loop that writes big array

variation in timing depends on other things running on machine



Figure 3: Example loop-counting traces collected over 15 seconds. Darker shades indicate smaller counter values and lower instruction throughput.

turns out, other webpages create distinct "signatures"

Figure from Cook et al, "There's Always a Bigger Fish: Clarifying Analysis of a Machine-Learning-Assisted Side-Channel Attack" (ISCA '22)

inferring cache accesses (1)

suppose I time accesses to array of chars:

- reading array[0]: 3 cycles
- reading array[64]: 4 cycles
- reading array[128]: 4 cycles
- reading array[192]: 20 cycles
- reading array[256]: 4 cycles
- reading array[288]: 4 cycles
- ...

what could cause this difference?

- array[192] not in some cache, but others were

inferring cache accesses (2)

some psuedocode:

```
char array[CACHE_SIZE];
AccessAllOf(array);
*other_address += 1;
TimeAccessingArray();
```

suppose during these accesses I discover that `array[128]` is slower to access

probably because `*other_address` loaded into cache + evicted it

what do we know about `other_address`? (select all that apply)

A. same cache tag B. same cache index C. same cache offset
D. diff. cache tag E. diff. cache index F. diff. cache offset

some complications

caches often use physical, not virtual addresses

(and need to know about physical address to compare index bits)
(but can infer physical addresses with measurements/asking OS)
(and often OS allocates contiguous physical addresses esp. w/'large pages')

storing/processing timings evicts things in the cache

(but can compare timing with/without access of interest to check for this)

processor "pre-fetching" may load things into cache before access is timed

(but can arrange accesses to avoid triggering prefetcher
and make sure to measure with memory barriers)

some L3 caches use a simple hash function to select index instead

exercise: inferring cache accesses (1)

```
char *array;
array = AllocateAlignedPhysicalMemory(CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
if (mystery) {
    *pointer += 1;
}
if (TimeAccessTo(&array[index]) > THRESHOLD) {
    /* pointer accessed */
}
```

suppose `pointer` is `0x1000188`

and cache (of interest) is direct-mapped, 32768 (2^{15}) byte, 64-byte blocks

what array index should we check?

solution

```
array = AllocateAlignedPhysicalMemory(CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
if (mystery) { *pointer = 1; }
if (TimeAccessTo(&array[index]) > THRESHOLD) { /* pointer accessed */ }
```

2^{15} byte direct mapped cache, $64 = 2^6$ byte blocks

9 index bits, 6 offset bits

`0x1000188`: …*0000 0001 1000* 1000

`array[0]` starts at multiple of cache size — index 0, offset 0

to get index 6, offset 0 array[`0b`*`1 10`*`00 0000`] = array[`0x180`]

solution

```
array = AllocateAlignedPhysicalMemory(CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
if (mystery) { *pointer = 1; }
if (TimeAccessTo(&array[index]) > THRESHOLD) { /* pointer accessed */ }
```

2^{15} byte direct mapped cache, $64 = 2^6$ byte blocks

9 index bits, 6 offset bits

`0x1000188`: …0*000 0001 10*00 1000

`array[0]` starts at multiple of cache size — index 0, offset 0

to get index 6, offset 0 array[`0b`*`1 10`*`00 0000`] = array[`0x180`]

aside

```
array = AllocateAlignedPhysicalMemory(CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
if (mystery) { *pointer += 1; }
if (TimeAccessTo(&array[index]) > THRESHOLD) {
    /* pointer accessed */
}
```

will this detect when pointer accessed? yes

will this detect if mystery is true? not quite

…because branch prediction could started cache access

exercise: inferring cache accesses (2)

```
char *other_array = ...;
char *array;
array = AllocateAlignedPhysicalMemory(CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
other_array[mystery] += 1;
for (int i = 0; i < CACHE_SIZE; i += BLOCK_SIZE) {
    if (TimeAccessTo(&array[i]) > THRESHOLD) {
        /* found something interesting */
    }
}
```

other_array at 0x200400, and interesting index is i=0x800, then what was mystery?

solution

```
array = AllocateAlignedPhysicalMemory(CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
other_array[mystery] += 1;
for (int i = 0; i < CACHE_SIZE; i += BLOCK_SIZE) {
    if (TimeAccessTo(&array[i]) > THRESHOLD) { ... }
}
```

at i=0x800: ...0*000 1000 00*00 0000 (cache index = 0x20)

other_array at 0x200400

Q: 0x200400 + X has cache index 0x20?

0x200400	...0	000	0100	00	00	0000
+ X	...?	000	0100	00	??	????
0x200400+X	...?	000	1000	00	??	????

exercise: inferring cache accesses (2)

```
char *array;
posix_memalign(&array, CACHE_SIZE, CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
if (mystery) {
    *pointer = 1;
}
if (TimeAccessTo(&array[index1]) > THRESHOLD ||
    TimeAccessTo(&array[index2]) > THRESHOLD) {
    /* pointer accessed */
}
```

pointer is 0x1000188

cache is 2-way, 32768 (2^{15}) byte, 64-byte blocks, ???? replacement

what array indexes should we check?

PRIME+PROBE

name in literature: PRIME + PROBE

PRIME: fill cache (or part of it) with values

do thing that uses cache

PROBE: access those values again and see if it's slow

(one of several ways to measure how cache is used)

coined in attacks on AES encryption

example: AES (1)

from Osvik, Shamir, and Tromer, “Cache Attacks and Countermeasures: the Case of AES” (2004)

early AES implementation used lookup tables

goal: detect index into lookup table

- index depended on key + data being encrypted

tricks they did to make this work

- vary data being encrypted
- subtract average time to look for what changes
- lots of measurements

example: AES (2)

from Osvik, Shamir, and Tromer, “Cache Attacks and Countermeasures: the Case of AES” (2004)



Fig. 5. Prime+Probe attack using 30,000 encryption calls on a 2GHz Athlon 64, attacking Linux 2.6.11 **dm-crypt**. The horizontal axis is the evicted cache set (i.e., $\langle y \rangle$ plus an offset due to the table's location) and the vertical axis is p_0. Left: raw timings (lighter is slower). Right: after subtraction of the average timing of the cache set. The bright diagonal reveals the high nibble of $p_0 = 0x00$.

reading a value

```
char *array;
posix_memalign(&array, CACHE_SIZE, CACHE_SIZE);
AccessAllOf(array);
other_array[mystery * BLOCK_SIZE] += 1;
for (int i = 0; i < CACHE_SIZE; i += BLOCK_SIZE) {
    if (CheckIfSlowToAccess(&array[i])) {
        ...
    }
}
```

with 32KB direct-mapped cache

suppose we find out that `array[0x400]` is slow to access

and other_array starts at address 0x100000

what was mystery?

revisiting an earlier example (1)

```
char *array;
posix_memalign(&array, CACHE_SIZE, CACHE_SIZE);
LoadIntoCache(array, CACHE_SIZE);
if (mystery) {
    *pointer += 1;
}
if (TimeAccessTo(&array[index]) > THRESHOLD) {
    /* pointer accessed */
}
```

what if mystery is false *but* branch mispredicted?

revisiting an earlier example (2)

cycle #	0	1	2	3	4	5	6	7	8	9	10	11
`movq mystery, %rax`	F	D	R	I	E	E	E	W	C			
`test %rax, %rax`	F	D	R				I	E	W	C		
`jz skip` (mispred.)		F	D	R				I	E	W	C	
`mov pointer, %rax`		F	D	R	I	E	E	E	W			
`mov (%rax), %r8`			F	D	R				I	E	W	
`add $1, %r8`			F	D	R							
`mov %r8, %rax`				F	D	R						
…												
`skip: ...`								F	D	R		

avoiding/triggering this problem

```
if (something false) {
    access *pointer;
}
```

what can we do to make access more/less likely to happen?

reading a value without really reading it

```
char *array;
posix_memalign(&array, CACHE_SIZE, CACHE_SIZE);
AccessAllOf(array);
if (something false) {
    other_array[mystery * BLOCK_SIZE] += 1;
}
for (int i = 0; i < CACHE_SIZE; i += BLOCK_SIZE) {
    if (CheckIfSlowToAccess(&array[i])) {
        ...
    }
}
```

if branch mispredicted, cache access may still happen

can find the value of `mystery`

seeing past a segfault? (1)

```
Prime();
if (something false) {
    triggerSegfault();
    Use(*pointer);
}
Probe();
```

could cache access for `*pointer` still happen?

yes, if:

- branch for if statement mispredicted, and
- `*pointer` starts before segfault detected

seeing past a segfault? (2)

operations in virtual memory lookup:

- translate virtual to physical address
- check if access is permitted by permission bits

Intel processors: looks like these were separate steps, so...

```
Prime();
if (something false) {
    int value = ReadMemoryMarkedNonReadableInPageTable();
    access other_array[value * ...];
}
Probe();
```

seeing past a segfault? (2)

operations in virtual memory lookup:

- translate virtual to physical address
- check if access is permitted by permission bits

Intel processors: looks like these were separate steps, so...

```
Prime();
if (something false) {
    int value = ReadMemoryMarkedNonReadableInPageTable();
    access other_array[value * ...];
}
Probe();
```

seeing past a segfault? (2)

operations in virtual memory lookup:

- translate virtual to physical address
- check if access is permitted by permission bits

Intel processors: looks like these were separate steps, so...

```
Prime();
if (something false) {
    int value = ReadMemoryMarkedNonReadableInPageTable();
    access other_array[value * ...];
}
Probe();
```

seeing past a segfault? (2)

operations in virtual memory lookup:

- translate virtual to physical address
- check if access is permitted by permission bits

Intel processors: looks like these were separate steps, so...

```
Prime();
if (something false) {
    int value = ReadMemoryMarkedNonReadableInPageTable();
    access other_array[value * ...];
}
Probe();
```

Meltdown

from Lipp et al, “Meltdown: Reading Kernel Memory from User Space”

```
    // %rcx = kernel address
    // %rbx = array to load from to cause eviction
    xor %rax, %rax      // rax <- 0
retry:
    // rax <- memory[kernel address] (segfaults)
        // but check for segfault done out-of-order on Intel
    movb (%rcx), %al
    // rax <- memory[kernel address] * 4096 [speculated]
    shl $0xC, %rax
    jz retry                    // not-taken branch
    // access array[memory[kernel address] * 4096]
    mov (%rbx, %rax), %rbx
```

Meltdown

from Lipp et al, “Meltdown: Reading Kernel Memory from User Space”

```
    // %rcx = ker
    // %rbx = ar                                       viction
    xor %rax, %ra
retry:
    // rax <- memory[kernel address] (segfaults)
        // but check for segfault done out-of-order on Intel
    movb (%rcx), %al
    // rax <- memory[kernel address] * 4096 [speculated]
    shl $0xC, %rax
    jz retry                    // not-taken branch
    // access array[memory[kernel address] * 4096]
    mov (%rbx, %rax), %rbx
```

space out accesses by 4096
ensure separate cache sets and
avoid triggering prefetcher

Meltdown

from Lipp et al, “Meltdown: Reading Kernel Memory from User Space”

```
    // %rcx
    // %rbx                                           on
    xor %rax
retry:
    // rax <- memory[kernel address] (segfaults)
        // but check for segfault done out-of-order on Intel
    movb (%rcx), %al
    // rax <- memory[kernel address] * 4096 [speculated]
    shl $0xC, %rax
    jz retry                     // not-taken branch
    // access array[memory[kernel address] * 4096]
    mov (%rbx, %rax), %rbx
```

repeat access if zero
apparently value of zero speculatively read
when real value not yet available

Meltdown

from Lipp et al, “Meltdown: Reading Kernel Memory from User Space”

```
    // %rcx =
    // %rbx =                                              ion
    xor %rax
retry:
    // rax <- memory[kernel address] (segfaults)
        // but check for segfault done out-of-order on Intel
    movb (%rcx), %al
    // rax <- memory[kernel address] * 4096 [speculated]
    shl $0xC, %rax
    jz retry                    // not-taken branch
    // access array[memory[kernel address] * 4096]
    mov (%rbx, %rax), %rbx
```

access cache to allow measurement later in paper with FLUSH+RELOAD instead of PRIME+PROBE technique

Meltdown

from Lipp et al, "Meltdown: Reading Kernel Memory from User Space"

segfault actually happens eventually

option 1: okay, just start a new process every time

option 2: way of suppressing exception (transactional memory support)

```
// rax <- memory[kernel address] (segfaults)
    // but check for segfault done out-of-order on Intel
movb (%rcx), %al
// rax <- memory[kernel address] * 4096 [speculated]
shl $0xC, %rax
jz retry                     // not-taken branch
// access array[memory[kernel address] * 4096]
mov (%rbx, %rax), %rbx
```

Meltdown fix

HW: permissions check done with/before physical address lookup

- was already done by AMD, ARM apparently?
- now done by Intel

SW: separate page tables for kernel and user space

- don't have sensitive kernel memory pointed to by page table
- when user-mode code running
- unfortunate performance problem
- exceptions start with code that switches page tables

reading a value without really reading it

```
char *array;
posix_memalign(&array, CACHE_SIZE, CACHE_SIZE);
AccessAllOf(array);
if (something false) {
    other_array[mystery * BLOCK_SIZE] += 1;
}
for (int i = 0; i < CACHE_SIZE; i += BLOCK_SIZE) {
    if (CheckIfSlowToAccess(&array[i])) {
        ...
    }
}
```

if branch mispredicted, cache access may still happen

can find the value of `mystery`

mistraining branch predictor?

```
if (something) {
    CodeToRunSpeculatively()
}
```

how can we have 'something' be false, but predicted as true

run lots of times with something true

then do actually run with something false

contrived(?) vulnerable code (1)

suppose this C code is run with extra privileges

(e.g. in system call handler, library called from JavaScript in webpage, etc.)

assume x chosen by attacker

(example from original Spectre paper)

```
if (x < array1_size)
        y = array2[array1[x] * 4096];
```

the out-of-bounds access (1)

```
char array1[...];
...
int secret;
...
y = array2[array1[x] * 4096];
```

suppose array1 is at `0x1000000` and

secret is at `0x103F0003`;

what x do we choose to make `array1[x]` access first byte of secret?

the out-of-bounds access (2)

```
char array1[...];
...
int secret;
...
y = array2[array1[x] * 4096];
```

suppose our cache has 64-byte blocks and 8192 sets

and `array2[0]` is stored in cache set 0

if the above evicts something in cache set 128,
then what do we know about `array1[x]`?

the out-of-bounds access (2)

```
char array1[...];
...
int secret;
...
y = array2[array1[x] * 4096];
```

suppose our cache has 64-byte blocks and 8192 sets

and `array2[0]` is stored in cache set 0

if the above evicts something in cache set 128,
then what do we know about `array1[x]`?

is 2 or 130

exploit with contrived(?) code

```
/* in kernel: */
int systemCallHandler(int x) {
    if (x < array1_size)
        y = array2[array1[x] * 4096];
    return y;
}
```

```
/* exploiting code */
    /* step 1: mistrain branch predictor */
for (a lot) {
    systemCallHandler(0 /* less than array1_size */);
}
    /* step 2: evict from cache using misprediction */
Prime();
systemCallHandler(targetAddress - array1Address);
int evictedSet = ProbeAndFindEviction();
int targetValue = (evictedSet - array2StartSet) / setsPer4K;
```

really contrived?

```
char *array1; char *array2;
if (x < array1_size)
    y = array2[array1[x] * 4096];
```

times 4096 shifts so we can get lower bits of target value

so all bits effect what cache block is used

really contrived?

```
char *array1; char *array2;
if (x < array1_size)
    y = array2[array1[x] * 4096];
```

times 4096 shifts so we can get lower bits of target value

so all bits effect what cache block is used

```
int *array1; int *array2;
if (x < array1_size)
    y = array2[array1[x]];
```

will still get *upper* bits of array1[x] (can tell from cache set)

can still read arbitrary memory!

want memory at 0x10000?

upper bits of 4-byte integer at 0x0FFFE

bounds check in kernel

```
if (x < array1_size) {
    y = array2[array1[x]]);
}
```

our template

```
void SomeSystemCallHandler(int index) {
    if (index > some_table_size)
        return ERROR;
    int kind = table[index];
    switch (other_table[kind].foo) {
        ...
    }
}
```

actual code

bounds check in kernel

```
if (x < array1_size) {
    y = array2[array1[x]]);
}
```

our template

```
void SomeSystemCallHandler(int index) {
    if (index > some_table_size)
        return ERROR;
    int kind = table[index];
    switch (other_table[kind].foo) {
        ...
    }
}
```

actual code

bounds check in kernel

```
if (x < array1_size) {
    y = array2[array1[x]]);
}
```

our template

```
void SomeSystemCallHandler(int index) {
    if (index > some_table_size)
        return ERROR;
    int kind = table[index];
    switch (other_table[kind].foo) {
        ...
    }
}
```

actual code

bounds check in kernel

```
if (x < array1_size) {
    y = array2[array1[x]];
}
```

our template

```
void SomeSystemCallHandler(int index) {
    if (index > some_table_size)
        return ERROR;
    int kind = table[index];
    switch (other_table[kind].foo) {
        ...
    }
}
```

actual code

privilege levels?

vulnerable code runs with higher privileges

so far: higher privileges = kernel mode

but other common cases of higher privileges

example: scripts in web browsers

JavaScript

JavaScript: scripts in webpages

not supposed to be able to read arbitrary memory, but...

can access arrays to examine caches

and could take advantage of some browser function being vulnerable

JavaScript

JavaScript: scripts in webpages

not supposed to be able to read arbitrary memory, but…

can access arrays to examine caches

and could take advantage of some browser function being vulnerable

or — doesn't even need browser to supply vulnerable code itself!

just-in-time compilation?

for performance, compiled to machine code, run in browser

not supposed to be access arbitrary browser memory

example JavaScript code from paper:

```
if (index < simpleByteArray.length) {
    index = simpleByteArray[index | 0];
    index = (((index * 4096)|0) & (32*1024*1024-1))|0;
    localJunk ^= probeTable[index|0]|0;
}
```

web page runs a lot to train branch predictor

then does run with out-of-bounds index

examines what's evicted by probeTable access

supplying own attack code?

JavaScript: could supply own attack code

turns out also possible with kernel mode scenario

trick: don't need to *actually run* code

...just need branch predictor to fetch it!

other misprediction

so far: talking about mispredicting direction of branch

what about mispredicting target of branch in, e.g.:

```
// possibly from C code like:
//   (*function_pointer)();
jmp *%rax

// possibly from C code like:
//       switch(rcx) { ... }
jmp *(%rax,%rcx,8)
```

an idea for predicting indirect jumps

for jmps like `jmp *%rax` predict target with cache:

bottom 12 bits of jmp address	last seen target
0x0–0x7	0x200000
0x8–0xF	0x440004
0x10-0x18	0x4CD894
0x18-0x20	0x510194
0x20-0x28	0x4FF194
…	…
0xFF8–0xFFF	0x3F8403

Intel Haswell CPU did something similar to this

- uses bits of last several jumps, not just last one

can mistrain this branch predictor

using mispredicted jump

1: find some kernel function with `jmp *%rax`

2: mistrain branch target predictor for it to jump to chosen code

use code at address that conflicts in "recent jumps cache"

3: have chosen code be attack code (e.g. array access)

either write special code OR

find suitable instructions (e.g. array access) in existing kernel code

Spectre variants

- showed Spectre variant 1 (array bounds), 2 (indirect jump)
  - from original paper

- other possible variations:
  - could cause other things to be mispredicted
    - prediction of where functions return to?
    - values instead of which code is executed?
  - could use side-channel other than data cache changes
    - instruction cache
    - cache of pending stores not yet committed
    - contention for resources on multi-threaded CPU core
    - branch prediction changes
    - …

some Linux kernel mitigations (1)

replace `array[x]` with

`array[x & ComputeMask(x, size)]`

...where ComputeMask() returns

- 0 if $x > \text{size}$
- `0xFFFF..F` if $x \leq \text{size}$

...and ComputeMask() does not use jumps:

```
mov x, %r8
mov size, %r9
cmp %r9, %r8
sbb %rax, %rax  // sbb = subtract with borrow
    // either 0 or -1
```

some Linux kernel mitigations (2)

for indirect branches:

with hardware help:

- separate indirect (computed) branch prediction for kernel v user mode
- other branch predictor changes to isolate better

without hardware help:

- transform `jmp *(%rax)`, etc. into code that will only predicted to jump to safe locations (by writing assembly very carefully)

only safe prediction

as replacement for `jmp *(%rax)`

code from Intel's "Retpoline: A Branch Target Injection Mitigation"

```
        call load_label
    capture_ret_spec:    /* <-- want prediction to go here */
        pause
        lfence
        jmp capture_ret_spec
    load_label:
        mov %rax, (%rsp)
        ret
```

backup slides