

intro

themes

automating building software

- libraries, taking advantage of incremental compilation

sharing machines

- multiple users/programs on one system

parallelism and concurrency

- doing two+ things at once

communicating between machines

- layered design of networks

- implementing secure communication

make

```
$ ./foo.exe
...
...
$ edit readline.c
$ make
clang -g -O -Wall -c readline.c -o readline.o
ar rcs libreadline.a terminal.o readline.o
clang -o foo.exe foo.o foo-utility.o -L. -lreadline
$
```

themes

automating building software

- libraries, taking advantage of incremental compilation

sharing machines

- multiple users/programs on one system

parallelism and concurrency

- doing two+ things at once


communicating between machines

- layered design of networks


- implementing secure communication

address translation


address translation



address translation




address translation




program addresses are 'virtual'
real addresses are 'physical'
can be *different sizes*!

address translation




address spaces

illusion of *dedicated memory*



address spaces

illusion of *dedicated memory*



themes

automating building software

- libraries, taking advantage of incremental compilation

sharing machines

- multiple users/programs on one system

parallelism and concurrency


- doing two+ things at once

communicating between machines

- layered design of networks

- implementing secure communication

keyboard input timeline



time multiplexing

time multiplexing



time multiplexing




```
...  
loop: ...  
      ...  
      jmp loop
```

```
loop: ...  
      ...
```

—— million cycle delay ——

```
      ...  
      jmp loop  
loop: ...  
      ...
```

time multiplexing



```
...  
loop: ...  
      ...  
      jmp loop
```


```
loop: ...  
      ...
```

—— million cycle delay ——

```
      ...  
      jmp loop  
loop: ...  
      ...
```


multiple cores+threads

multiple cores+threads



multiple cores? each core still divided up

multiple cores+threads



multiple cores? each core still divided up

one program with multiple threads

themes

automating building software

- libraries, taking advantage of incremental compilation

sharing machines

- multiple users/programs on one system

parallelism and concurrency

- doing two+ things at once

communicating between machines

- layered design of networks

- implementing secure communication

permissions

```
$ ls /u/other/secret
```

```
ls: cannot open directory '/u/other/secret': Permission denied
```

```
$ shutdown
```

```
shutdown: Permission denied
```

themes

automating building software

- libraries, taking advantage of incremental compilation

sharing machines

- multiple users/programs on one system

parallelism and concurrency

- doing two+ things at once

communicating between machines

- layered design of networks

- implementing secure communication

networking layers

application	HTTP, SSH, SMTP, ...	application-defined meanings
transport	TCP, UDP, ...	reach correct program,\linebreak{ reliability/streams
network	IPv4, IPv6	reach correct machine\linebreak{}(across networks)
link	Ethernet, Wi-Fi, ...	coordinate shared wire/radio

networking layers

application	HTTP, SSH, SMTP, ...	application-defined meanings
transport	TCP, UDP, ...	reach correct program, \linebreak{ <i>reliability/streams</i>
network	IPv4, IPv6	reach correct machine \linebreak{}(across networks)
link	Ethernet, Wi-Fi, ...	coordinate shared wire/radio

networking layers

application	HTTP, SSH, SMTP, ...	application-defined meanings
transport	TCP, UDP, ...	reach correct program,\linebreak{ reliability/streams
network	IPv4, IPv6	reach correct machine\linebreak{}(across networks)
<i>link</i>	Ethernet, Wi-Fi, ...	coordinate shared wire/radio

networking layers

application	HTTP, SSH, SMTP, ...	application-defined meanings
transport	TCP, UDP, ...	reach correct program, \linebreak{ reliability/streams
<i>network</i>	IPv4, IPv6	reach correct machine \linebreak{}(across networks)
link	Ethernet, Wi-Fi, ...	coordinate shared wire/radio

networking layers

application	HTTP, SSH, SMTP, ...	application-defined meanings
<i>transport</i>	TCP, UDP, ...	reach correct program,\linebreak{ reliability/streams
network	IPv4, IPv6	reach correct machine\linebreak{}(across networks)
link	Ethernet, Wi-Fi, ...	coordinate shared wire/radio

networking layers

<i>application</i>	HTTP, SSH, SMTP, ...	application-defined meanings
transport	TCP, UDP, ...	reach correct program, \linebreak{ reliability/streams
network	IPv4, IPv6	reach correct machine \linebreak{}(across networks)
link	Ethernet, Wi-Fi, ...	coordinate shared wire/radio

layers terminology

application	application-defined meanings	
transport	reach correct program, \linebreak{ reliability/streams	segments/datagrams
network	reach correct machine \linebreak{ (across networks)	packets
link	coordinate shared wire/radio	frames

names and addresses

name

\large{}*logical identifier*

variable counter

DNS name `www.virginia.edu`

DNS name `mail.google.com`

DNS name `mail.google.com`

DNS name `reiss-`

`t3620.cs.virginia.edu`

DNS name `reiss-`

`t3620.cs.virginia.edu`

address

\large{}*location/how to locate*

memory address `0x7FFF9430`

IPv4 address `128.143.22.36`

IPv4 address `216.58.217.69`

IPv6 address

`2607:f8b0:4004:80b::2005`

IPv4 address `128.143.67.91`

MAC address `18:66:da:2e:7f:da`

secure communication?

how do you know who your socket is to?

who can read what's on the socket?

what can you do to restrict this?

themes

automating building software

- libraries, taking advantage of incremental compilation

sharing machines

- multiple users/programs on one system

parallelism and concurrency

- doing two+ things at once

communicating between machines

- layered design of networks

- implementing secure communication

2004 CPU

Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU





Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU



▲ Registers

Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU




Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU




Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU




Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU





Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

2004 CPU




Image: approx 2004 AMD press image of Opteron die;
approx register location via chip-architect.org (Hans de Vries)

some performance examples

some performance examples

```
example1:  
    movq $1000000000000, %rax  
loop1:  
    addq %rbx, %rcx  
    decq %rax  
    jge loop1  
    ret
```

about 30B instructions
my desktop: approx 2.65 sec

```
example2:  
    movq $1000000000000, %rax  
loop2:  
    addq %rbx, %rcx  
    addq %r8, %r9  
    decq %rax  
    jge loop2  
    ret
```

about 40B instructions
my desktop: approx 2.65 sec

some performance examples

```
example1:
    movq $1000000000000, %rax
loop1:
    addq %rbx, %rcx
    decq %rax
    jge loop1
    ret
```

about 30B instructions

my desktop: approx *2.65 sec*

```
example2:
    movq $1000000000000, %rax
loop2:
    addq %rbx, %rcx
    addq %r8, %r9
    decq %rax
    jge loop2
    ret
```

about 40B instructions

my desktop: approx *2.65 sec*

C exercise

```
int array[4] = {10,20,30,40};  
int *p;  
p = &array[0];  
p += 2;  
p[1] += 1;
```

array =

- | | |
|-----------------------------|------------------|
| A. compile or runtime error | B. {10,20,30,41} |
| C. {10,20,32,41} | D. {10,21,30,40} |
| E. {12,21,30,40} | F. none of these |

C exercise (2)

```
int *array2[4]; int array1[4] = {10,20,30,40};
void mystery(int **p) {
    *p = &array1[2];
}
int main() {
    int **q;
    q = array2;
    mystery(q);
    array1[1] = *q;
    ...
}
```

array1 =

- | | |
|-----------------------------|------------------|
| A. compile or runtime error | B. {10,10,30,40} |
| C. {10,30,30,40} | D. {10,10,20,30} |
| E. {10,20,10,20} | F. none of these |

C exercise (2)

```
int *array2[4]; int array1[4] = {10,20,30,40};
void mystery(int **p) {
    *p = &array1[2];
}
int main() {
    int **q;
    q = array2;
    mystery(q);
    array1[1] = *q;
    ...
}
```

array1 =

- | | |
|------------------------------------|-------------------------|
| A. compile or runtime error | B. {10,10,30,40} |
| C. {10,30,30,40} | D. {10,10,20,30} |
| E. {10,20,10,20} | F. none of these |

some avenues for review

review CSO1 stuff

labs 10–13, homeworks 7–8 of last Spring

`\url{https://researcher111.github.io/uva-cso1-F23-DG/}`


exercises we've used in the past:

implement `strsep` library function


implement conversion from dynamic array to linked list

some pointer stuff


some pointer stuff




some pointer stuff



some pointer stuff



some pointer stuff



some pointer stuff

0x040	
0x038	array[2]: 0x67
	array[1]: 0x45
0x030	array[0]: 0x12
	single: 0x78
0x028	ptr: 0x28
0x020	
0x018	
0x010	
0x008	
0x000	


```
int single = 0x78;  
int *ptr;
```

```
ptr = &single;  
ptr = (int*) 0x28; addr. of single
```

~~ptr = 0x28; compile error (hopefully)~~

~~ptr = (int*) single;~~
pointer to unknown place

some pointer stuff



some pointer stuff

0x040

0x038

0x030

0x028

0x020

0x018

0x010

0x008

0x000

array[2]: 0x67
array[1]: 0x45
array[0]: 0x12
single: 0x78
ptr: 0x2C

```
int single = 0x78;
int *ptr;

ptr = array;
ptr = &array[0];
ptr = (int*) 0x2C;
```

some pointer stuff

0x040	
0x038	array[2]: 0x67
	array[1]: 0x45
0x030	array[0]: 0x12
	single: 0x78
0x028	ptr: 0x2C
0x020	
0x018	
0x010	
0x008	
0x000	

```
int single = 0x78;  
int *ptr;
```

```
ptr = array;  
ptr = &array[0];  
ptr = (int*) 0x2C;
```

~~ptr = array[0]; compile error*~~

~~ptr = (int*) array[0];~~
pointer to unknown place

some pointer stuff

0x040	
0x038	array[2] : 0xFF
	array[1] : 0x45
0x030	array[0] : 0x12
	single: 0x78
0x028	ptr: 0x2C
0x020	
0x018	
0x010	
0x008	
0x000	

```
int single = 0x78;  
int *ptr;  
ptr = &array[0];
```

```
ptr[2] = 0xFF;  
*(ptr + 2) = 0xFF;
```

```
int *temp1; temp1 = ptr + 2;  
*temp1 = 0xFF;
```

```
int *temp2; temp2 = &ptr[2];  
*temp2 = 0xFF;
```

some pointer stuff

0x040	
0x038	array[2]: 0x67
	array[1]: 0x45
0x030	array[0]: 0x12
	single: ...
0x028	ptr: 0x2C
0x020	
0x018	
0x010	
0x008	
0x000	

```
int single = 0x10;  
int *ptr;
```

```
void change_arg(int *x) {  
    *x = compute_some_value();  
}  
...  
change_arg(&single);
```