



building

files in building C programs [dynamic linking]




files in building C programs [dynamic linking]




```
clang -c main.c  
clang -c extra.c
```

files in building C programs [dynamic linking]




```
clang -S -c main.c  
clang -S -c extra.c
```

files in building C programs [dynamic linking]




`clang -o program main.o extra.o`

files in building C programs [dynamic linking]



`./program ...`

files in building C programs [static linking]



file extensions

name		
.h		C header file
.s	(or .asm)	assembly file
.o	(or .obj)	object file (binary of assembly)
(none)	(or .exe)	executable file
.a	(or .lib)	statically linked library (collection of .o files)
.so	(or .dll or .dylib)	dynamically linked library (‘shared object’)

static libraries

Unix-like static libraries: libfoo.a

internally: archive of .o files with index

create: `ar rcs libfoo.a file1.o file2.o ...`

‘archive’ utility `ar` and not normal C compiler

use: `cc ... -o program -L/path/to/lib ... -lfoo`

no space between `-l` and library name

`cc` could be `clang`, `gcc`, `clang++`, `g++`, etc.

`-L/path/to/lib` not needed if in standard location

shared libraries (AKA dynamically-linked libraries)

Linux shared libraries: libfoo.so

create:

compile .o files with `-fPIC` (position independent code)

then: `cc -shared ... -o libfoo.so`

use: `cc ... -o program -L/path/to/lib ... -lfoo`

`cc` = C compiler (clang, gcc, etc.)

`-L...` sets path only when making executable

runtime path set separately

shared libraries (AKA dynamically-linked libraries)

Linux shared libraries: libfoo.so

create:

compile .o files with *-fPIC* (position independent code)

then: `cc -shared ... -o libfoo.so`

use: `cc ... -o program -L/path/to/lib ... -lfoo`

`cc` = C compiler (clang, gcc, etc.)

`-L...` sets path only when making executable

runtime path set separately

shared libraries (AKA dynamically-linked libraries)

Linux shared libraries: libfoo.so

create:

compile .o files with `-fPIC` (position independent code)

then: `cc -shared ... -o libfoo.so`

use: `cc ... -o program -L/path/to/lib ... -lfoo`

`cc` = C compiler (clang, gcc, etc.)

`-L...` sets path *only when making executable*

runtime path set separately

finding shared libraries (1)

```
$ ls
libexample.so  main.c
$ clang -o main main.c -lexample
/usr/bin/ld: cannot find -lexample
clang: error: linker command failed with exit code 1 (use -v to see invocation)
$ clang -o main main.c -L. -lexample
$ ./main
./main: error while loading shared libraries:
  libexample.so: cannot open shared object file: No such
  file or directory
```


finding shared libraries (1)

```
$ ls
libexample.so  main.c
$ clang -o main main.c -lexample
/usr/bin/ld: cannot find -lexample
clang: error: linker command failed with exit code 1 (use -v to see invocation)
$ clang -o main main.c -L. -lexample
$ ./main
./main: error while loading shared libraries:
  libexample.so: cannot open shared object file: No such
  file or directory
```

```
$ LD_LIBRARY_PATH=. ./main
```

or

```
$ export LD_LIBRARY_PATH=.
$ ./main
```

or

```
$ clang -o main main.c -L. -lexample -Wl,-rpath .
$ ./main
```

finding shared libraries (1)

```
cc ... -o program -L/path/to/lib ... -lfoo
```

on Linux: `/path/to/lib` only used to create program

program contains `libfoo.so` without full path

Linux default: `libfoo.so` expected to be in `/usr/lib`, `/lib`, and other 'standard' locations

possible overrides:

`LD_LIBRARY_PATH` environment variable

paths specified with `-Wl,-rpath=/path/to/lib` when creating executable

exercise (1)

a.c:

```
void foo() { puts("A"); }
```

main.c:

```
int main() {foo();}
```

```
$ clang -c main.c -o main.o
$ clang -c a.c -o a.o
$ ar rcs libfoo.a a.o
$ clang main.o -L. -lfoo -o program
$ ./program
```

A

```
$ rm libfoo.a
$ clang -c b.c -o b.o
$ ar rcs libfoo.a b.o
$ ./program
```

b.c:

```
void foo() { puts("B"); }
```

exercise: output?

exercise (2)

a.c:

```
void foo() { puts("A"); }
```

main.c:

```
int main() {foo();}
```

b.c:

```
void foo() { puts("B"); }
```

```
$ clang -c main.c -o main.o
$ clang -fPIC -c a.c -o a.o
$ clang -shared -o libfoo.so a.o
$ clang main.o -Wl,-rpath . -L. -lfoo -o program
$ ./program
A
$ rm libfoo.so
$ clang -fPIC -c b.c -o b.o
$ clang -shared -o libfoo.so b.o
$ ./program
```

exercise: output?

libraries and command line

when linking against libraries use:

```
clang -o executable foo.o bar.o -lName
```

rather than

```
clang -o executable -lName foo.o bar.o
```

by default, linker processes files in order

might only grab things that previous files needed from library

(especially for static libraries)

exercise (incremental compilation)

program built from main.c + extra.c

main.c, extra.c both include extra.h, stdio.h

```
clang -c main.c           # command 1  
clang -c extra.c          # command 2  
clang -o program main.o extra.o # command 3
```

What commands need to be rerun if...

Question A: ... main.c changes?

Question B: ... extra.h changes?

make

make — Unix program for “making” things...

... by running commands based on what's changed

what commands? based on rules in makefile

(text file called `makefile` or `Makefile` (no extension))

make rules

```
main.o: main.c main.h extra.h
```

```
► clang -Wall -c main.c
```

before colon: target(s) (file(s) generated/updated)

after colon: prerequisite(s) (also known as dependencies)

following lines prefixed by a tab character: command(s) to run

make runs commands if any prereq modified date after target

... *after making sure prerequisites up to date*

make rules

main.o: main.c main.h extra.h

► clang -Wall -c main.c

before colon: *target(s)* (file(s) generated/updated)

after colon: prerequisite(s) (also known as dependencies)

following lines prefixed by a tab character: command(s) to run

make runs commands if any prereq modified date after target

... *after making sure prerequisites up to date*

make rules

main.o: *main.c main.h extra.h*

► clang -Wall -c main.c

before colon: target(s) (file(s) generated/updated)

after colon: *prerequisite(s)* (also known as dependencies)

following lines prefixed by a tab character: command(s) to run

make runs commands if any prereq modified date after target

... *after making sure prerequisites up to date*

make rules

```
main.o: main.c main.h extra.h
```

```
▶ clang -Wall -c main.c
```

before colon: target(s) (file(s) generated/updated)

after colon: prerequisite(s) (also known as dependencies)

following lines prefixed by a *tab* character: command(s) to run

make runs commands if any prereq modified date after target

... *after making sure prerequisites up to date*

make rules

main.o: main.c main.h extra.h

► *clang -Wall -c main.c*

before colon: target(s) (file(s) generated/updated)

after colon: prerequisite(s) (also known as dependencies)

following lines prefixed by a tab character: *command(s) to run*

make runs commands if any prereq modified date after target

... *after making sure prerequisites up to date*

make rules

```
main.o: main.c main.h extra.h
```

```
► clang -Wall -c main.c
```

before colon: target(s) (file(s) generated/updated)

after colon: prerequisite(s) (also known as dependencies)

following lines prefixed by a tab character: command(s) to run

make runs commands *if any prereq modified date after target*

... *after making sure prerequisites up to date*

make rule chains

program: main.o extra.o

► clang -Wall -o program main.o extra.o

extra.o: extra.c extra.h

► clang -Wall -c extra.c

main.o: main.c main.h extra.h

► clang -Wall -c main.c

to make program, first...

update main.o and extra.o if they aren't

running make

“make target”

- look in Makefile in current directory for rules

- check if target is up-to-date

- if not, rebuild it (and prerequisites, if needed) so it is

“make target1 target2”

- check if both target1 and target2 are up-to-date

- if not, rebuild it as needed so they are

“make”

- if “firstTarget” is the first rule in Makefile,

- same as ‘make firstTarget’

exercise: what will run?

W: X Y

► buildW

X: Q

► buildX

Y: X Z

► buildY

W modified 1 minute ago

X modified 3 hours ago

Y does not exist

Z modified 1 hour ago

Q modified 2 hours ago

exercise: “make W” will run what commands?

A. none

D. buildY then buildW


F. buildX then buildW

B. buildY only C. buildW then buildY

E. buildX then buildY then buildW

G. something else

explanation



first: to make W, need X, Y up to date

to make X up to date:

need Q up to date ✓

then build X if less recent than Q (yes) ✓


to make Y up to date: need X up to date ✓

need Z up to date ✓

then build Y if less recent than X (yes) or Z (yes) ✓

then build W if less recent than X (yes, now) or Y (yes) ✓

explanation



first: to make W, *need X, Y up to date*

to make X up to date:

need Q up to date ✓

then build X if less recent than Q (yes) ✓


to make Y up to date: need X up to date ✓

need Z up to date ✓

then build Y if less recent than X (yes) or Z (yes) ✓

then build W if less recent than X (yes, now) or Y (yes) ✓

explanation



first: to make W, need X, Y up to date

to make X up to date:

need Q up to date ✓

then build X if less recent than Q (yes) ✓


to make Y up to date: need X up to date ✓

need Z up to date ✓

then build Y if less recent than X (yes) or Z (yes) ✓

then build W if less recent than X (yes, now) or Y (yes) ✓

explanation



first: to make W, need X, Y up to date

to make X up to date:

need Q up to date ✓

then build X if less recent than Q (yes) ✓


to make Y up to date: need X up to date ✓

need Z up to date ✓

then build Y if less recent than X (yes) or Z (yes) ✓

then build W if less recent than X (yes, now) or Y (yes) ✓

explanation



first: to make W, need X, Y up to date

to make X up to date:

need Q up to date ✓

then build X if less recent than Q (yes) ✓

to make Y up to date: need X up to date ✓

need Z up to date ✓

then build Y if less recent than X (yes) or Z (yes) ✓

then build W if less recent than X (yes, now) or Y (yes) ✓

'phony' targets (1)

common to have Makefile targets that aren't files

```
all: program1 program2 libfoo.a
```

“make all” effectively shorthand for “make program1
program2 libfoo.a”

no actual file called “all”

'phony' targets (2)

sometimes want targets that don't actually build file

example: "make clean" to remove generated files

clean:

► `rm --force main.o extra.o`

but what if I create

clean:

► `rm --force main.o extra.o`

`all: program1 program2 libfoo.a`

Q: if I make a file called “all” and then “make all” what happens?

Q: same with “clean” and “make clean”?

marking phony targets

clean:

► `rm --force main.o extra.o`

`all: program1 program2 libfoo.a`

`.PHONY: all clean`

special .PHONY rule says “ ‘all’ and ‘clean’ not real files”

(not required by POSIX, but in every make version I know)

conventional targets

common convention:

target name	purpose
(default), all	build everything
install	install to standard location
test	run tests
clean	remove generated files

redundancy (1)

program: main.o extra.o

► clang -Wall -o program main.o extra.o

extra.o: extra.c extra.h

► clang -Wall -o extra.o -c extra.c

main.o: main.c main.h extra.h

► clang -o main.o -c main.c

what if I want to run clang with -fsanitize=address instead of -Wall?

what if I want to change clang to gcc?

variables/macros (1)

CC = gcc

CFLAGS = -Wall -pedantic -std=c11 -fsanitize=address

LDFLAGS = -Wall -pedantic -fsanitize=address

LDLIBS = -lm

program: main.o extra.o

► \$(CC) \$(LDFLAGS) -o program main.o extra.o \$(LDLIBS)

extra.o: extra.c extra.h

► \$(CC) \$(CFLAGS) -o extra.o -c extra.c

main.o: main.c main.h extra.h

► \$(CC) \$(CFLAGS) -o main.o -c main.c

aside: conventional names

chose names CC, CFLAGS, LDFLAGS, etc.

not required, but conventional names (incomplete list follows)

CC	C compiler
CFLAGS	C compiler options
LDFLAGS	linking options
LIBS or LDLIBS	libraries

variables/macros (2)

```
CC = gcc
CFLAGS = -Wall
LDFLAGS = -Wall
LDLIBS = -lm
```

`$@`: target
`$<`: first dependency
`$$`: all dependencies

```
program: main.o extra.o
▶ $(CC) $(LDFLAGS) -o $$ $$ $(LDLIBS)
```

```
extra.o: extra.c extra.h
▶ $(CC) $(CFLAGS) -o $$ -c $<
```

```
main.o: main.c main.h extra.h
▶ $(CC) $(CFLAGS) -o $$ -c $<
```

aside: `$$` works on GNU make (usual on Linux), but not portable.

aside: make versions

multiple implementations of make

for stuff we've talked about so far, no differences

most common on Linux: GNU make

will talk about 'pattern rules', which aren't supported by some other make versions

older, portable, (in my opinion less intuitive) alternative: suffix rules

pattern rules

```
CC = gcc
```

```
CFLAGS = -Wall
```

```
LDFLAGS = -Wall
```

```
LDLIBS = -lm
```

```
program: main.o extra.o
```

```
▶ $(CC) $(LDFLAGS) -o $@ $^ $(LDLIBS)
```

```
%.o: %.c
```

```
▶ $(CC) $(CFLAGS) -o $@ -c $<
```

```
extra.o: extra.c extra.h
```

```
main.o: main.c main.h extra.h
```

aside: these rules work on GNU make (usual on Linux), but less portable than “suffix rules” (which have somewhat less intuitive syntax/are less flexible).

built-in rules

‘make’ has the ‘make .o from .c’ rule built-in already, so:

```
CC = gcc
```

```
CFLAGS = -Wall
```

```
LDFLAGS = -Wall
```

```
LDLIBS = -lm
```

```
program: main.o extra.o
```

```
► $(CC) $(LDFLAGS) -o $@ $^ $(LDLIBS)
```

```
extra.o: extra.c extra.h
```

```
main.o: main.c main.h extra.h
```

(don't actually need to write supplied rule!)

built-in rules

‘make’ has the ‘make .o from .c’ rule built-in already, so:

```
CC = gcc
```

```
CFLAGS = -Wall
```

```
LDFLAGS = -Wall
```

```
LDLIBS = -lm
```

```
program: main.o extra.o
```

```
► $(CC) $(LDFLAGS) -o $@
```

```
extra.o: extra.c
```

```
main.o: main.c main.h extra.h
```

note: built-in rules not allowed on the make lab

(don't actually need to write supplied rule!)

writing Makefiles?

error-prone to write all .h dependencies

- MM (and related) options to gcc or clang
- outputs make rule
- ways of having make run this + use output

Makefile generators

other programs that write Makefiles

other build systems

alternatives to writing Makefiles:

other make-ish build systems

ninja, scons, bazel, maven, xcodebuild, msbuild, ...

tools that generate inputs for make-ish build systems

cmake, autotools, qmake, ...