port numbers

we run multiple programs on a machine

- IP addresses identifying machine — not enough

port numbers

we run multiple programs on a machine

- IP addresses identifying machine — not enough

so, add 16-bit *port numbers*

- think: multiple PO boxes at address

port numbers

we run multiple programs on a machine

- IP addresses identifying machine — not enough

so, add 16-bit *port numbers*

- think: multiple PO boxes at address

0–49151: typically assigned for particular services

- 80 = http, 443 = https, 22 = ssh, ...
- usually <1024 reserved for sysadmin-only-use

49152–65535: allocated on demand

- default "return address" for client connecting to server

port number independence

typically "5-tuple" identifies socket:
(protocol=TCP or UDP, source IP, dest IP, source port, dest port)

means can have:

- two sockets with same source IP+source port, but different destinations
- two sockets with same dest IP+des port, but different sources
- two sockets with different protocols, but everything else same


special cases:

- dest IP/port can be 'wildcard' (all zeroes usually)
- used for server that can be connected to
- used for unconnected UDP sockets

three-way TCP handshake

from →to	flags	seq	ack	data	
client →server	SYN	X	—	—	
server→client	SYN+ACK	Y	$X+1$	—	X, Y
client →server	ACK	$X+1$	$Y+1$	—	
client →server	ACK	$X+1$	$Y+1$	initial data	

selected at random


No. Time Source Destination Protocol Length Info
187 6.448307253 192.168.1.232 128.143.63.230 TCP 74 40664 → 22 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 S
188 6.456234243 128.143.63.230 192.168.1.232 TCP 74 22 → 40664 [SYN, ACK] Seq=0 Ack=1 Win=65160 Len=0
189 6.456246847 192.168.1.232 128.143.63.230 TCP 66 40664 → 22 [ACK] Seq=1 Ack=1 Win=64256 Len=0 TSva
190 6.456478980 192.168.1.232 128.143.63.230 TCP 108 40664 → 22 [PSH, ACK] Seq=1 Ack=1 Win=64256 Len=4
191 6.464056057 128.143.63.230 192.168.1.232 TCP 66 22 → 40664 [ACK] Seq=1 Ack=43 Win=65152 Len=0 TSv
192 6.484719348 128.143.63.230 192.168.1.232 TCP 108 22 → 40664 [PSH, ACK] Seq=1 Ack=43 Win=65152 Len=
193 6.484728685 192.168.1.232 128.143.63.230 TCP 66 40664 → 22 [ACK] Seq=43 Ack=43 Win=64256 Len=0 TS
194 6.485016343 192.168.1.232 128.143.63.230 TCP 1514 40664 → 22 [ACK] Seq=43 Ack=43 Win=64256 Len=1448
195 6.485018757 192.168.1.232 128.143.63.230 TCP 154 40664 → 22 [PSH, ACK] Seq=1491 Ack=43 Win=64256 Le
196 6.487302992 128.143.63.230 192.168.1.232 TCP 1178 22 → 40664 [PSH, ACK] Seq=43 Ack=43 Win=65152 Len
197 6.491479580 128.143.63.230 192.168.1.232 TCP 66 22 → 40664 [ACK] Seq=1155 Ack=1579 Win=64128 Len=
198 6.522745146 192.168.1.232 128.143.63.230 TCP 1274 40664 → 22 [PSH, ACK] Seq=1579 Ack=1155 Win=64128
199 6.555022872 128.143.63.230 192.168.1.232 TCP 1694 22 → 40664 [PSH, ACK] Seq=1155 Ack=2787 Win=64128
200 6.555031899 192.168.1.232 128.143.63.230 TCP 66 40664 → 22 [ACK] Seq=2787 Ack=2783 Win=64128 Len=
201 6.570288124 192.168.1.232 128.143.63.230 TCP 82 40664 → 22 [PSH, ACK] Seq=2787 Ack=2783 Win=64128
Frame 188: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface eno1, id 0
Ethernet II, Src: TpLinkTechno_d9:ae:50 (d8:07:b6:d9:ae:50), Dst: ASUSTekCOMPU_ab:8c:2c (c8:7f:54:ab:8c:2c)
Internet Protocol Version 4, Src: 128.143.63.230, Dst: 192.168.1.232
Transmission Control Protocol, Src Port: 22, Dst Port: 40664, Seq: 0, Ack: 1, Len: 0
Source Port: 22
Destination Port: 40664
[Stream index: 15]
[Conversation completeness: Complete, WITH_DATA (31)]
[TCP Segment Len: 0]
Sequence Number: 0 (relative sequence number)
Sequence Number (raw): 3937746435
[Next Sequence Number: 1 (relative sequence number)]
Acknowledgment Number: 1 (relative ack number)
Acknowledgment number (raw): 2073778370
1010 .... = Header Length: 40 bytes (10)
Flags: 0x012 (SYN, ACK)
Window: 65160
[Calculated window size: 65160]
Checksum: 0xfecd [unverified]
[Checksum Status: Unverified]
Urgent Pointer: 0
Options: (20 bytes), Maximum segment size, SACK permitted, Timestamps, No-Operation (NOP), Window scale
[Timestamps]

so many messages?

TCP waits full round-trip before sending data; can do better

example: QUIC (figure from RFC 9000, TCP+TLS replacement)





Figure 6: Example 0-RTT Handshake

TCP state machine



notation: event/action

connection close

FIN (I want to close) + ACK (confirm close)

ACK side needs to wait just in case FIN resent

- keep port number from being reused
- TIME_WAIT state

RST

RST (reset) flag often used to respond to unexpected packets

example: data packet for never-established connection

connections on my desktop

```
cr4bd@reiss-t3620
: /zf14/cr4bd ; netstat --inet --inet6 --numeric
Active Internet connections (w/o servers)
Proto Recv-Q Send-Q Local Address           Foreign Address         State
tcp        0      0 128.143.67.91:49202     128.143.63.34:22        ESTABLISHE
tcp        0      0 128.143.67.91:803       128.143.67.236:2049     ESTABLISHE
tcp        0      0 128.143.67.91:50292     128.143.67.226:22       TIME_WAIT
tcp        0      0 128.143.67.91:54722     128.143.67.236:2049     TIME_WAIT
tcp        0      0 128.143.67.91:52002     128.143.67.236:111      TIME_WAIT
tcp        0      0 128.143.67.91:732       128.143.67.236:63439    TIME_WAIT
tcp        0      0 128.143.67.91:40664     128.143.67.236:2049     TIME_WAIT
tcp        0      0 128.143.67.91:54098     128.143.67.236:111      TIME_WAIT
tcp        0      0 128.143.67.91:49302     128.143.67.236:63439    TIME_WAIT
tcp        0      0 128.143.67.91:50236     128.143.67.236:111      TIME_WAIT
tcp        0      0 128.143.67.91:22        172.27.98.20:49566      ESTABLISHE
tcp        0      0 128.143.67.91:51000     128.143.67.236:111      TIME_WAIT
tcp        0      0 127.0.0.1:50438         127.0.0.1:631           ESTABLISHE
tcp        0      0 127.0.0.1:631           127.0.0.1:50438         ESTABLISHE
```

BSD sockets

BSD = Berkely Standard Distribution (of Unix)

interface designed for stream connections


current C version standardized by POSIX

pretty much default interface programming with TCP connections

...across all platforms

connected sockets

sockets can represent a connection



size mismatch? (1)

one end

other end

(get fds/socks:)

```
sock.send(b"12345")
```



```
b"123" == sock.recv(3)
b"45" == sock.recv(2)
```


size mismatch? (2)

one end

other end

(get fds/socks:)

```
sock.send(b"12")
sock.send(b"345")
```



```
b"12345" == sock.recv(5)
```


partial reads?

one end

other end

(get fds/socks:)

```
sock.send(b"X" * 6000)
```



sometimes `b"X" * 6000 == sock.recv(6000)`
or sometimes

```
b"X" * 1490 == sock.recv(6000)
b"X" * 2980 == sock.recv(4510)
b"X" * 1530 == sock.recv(1530)
```


partial writes

one end

other end

(get fds/socks:)

```
sock.setblocking(False)
sock.send(b"X" * 6000) == 1480
```



```
b"X" * 1480 == sock.recv(6000)
(+ no more data)
```

partial reads/writes

read/recv can have read less than requested

- read of zero bytes = end of file

send/write can write less than requested...
but only on error or if non-blocking mode requested

incomplete writes


`write` might write less than requested

- error after writing some data
- if blocking disabled


`read` might read less than requested

- error after reading some data
- not enough data got there in time


sockets and server sockets (C)




sockets and server sockets (C)




sockets and server sockets (C)



sockets and server sockets (C)




sockets and server sockets (C)




sockets and server sockets (Python)

```
client:
sock = socket.socket(…)
```



client


```
server:
ssock = \
 socket.socket(…)
ssock.bind(…)
ssock.listen()
```




server

sockets and server sockets (Python)

```
client:
sock = socket.socket(…)
```



client





```
server:
ssock = \
 socket.socket(…)
ssock.bind(…)
ssock.listen()
```


socket() function — create socket fd

server


sockets and server sockets (Python)



sockets and server sockets (Python)



sockets and server sockets (Python)



connection setup: client, TCP+IPv4

```
sock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
# to select local host/port: socket.bind(('128.143.71.27', 54444))
# if no local host/port selected, OS assigns
sock.connect(('128.143.67.8', 443))
...
sock.send(...)
sock.recv(...)
```

connection setup: client, TCP+IPv6

```
sock = socket.socket(socket.AF_INET6, socket.SOCK_STREAM)
# to select local host/port: socket.bind(('3fff:1234::1', 54444))
# if no local host/port selected, OS assigns
sock.connect(('2607:f8b0:4004:c06::67', 443))
...
sock.send(...)
sock.recv(...)
```

connection setup: generic TCP, addrinfo

```
import socket
possible_addrs = socket.getaddrinfo(
        'www.cs.virginia.edu', '443',
        socket.AF_UNSPEC, socket.SOCK_STREAM)

for af, socktype, proto, canonname, sockaddr in possible_addrs:
    try:
        sock = socket.socket(af, socktype, proto)
    except OSError:
        sock = None
        continue
    try:
        sock.connect(sa)
    except OSError:
        sock.close()
        sock = None
        continue

if sock == None:
    # not successful
```

connection setup: server, IPv4

```
import socket
ssock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
# 0.0.0.0 == "any IP address"
ssock.bind(('0.0.0.0', 12345))
ssock.listen()
sock, remote_addr = ssock.accept()
Use(sock)
```

connection setup: server, IPv4


```
import socket
ssock = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
# 0.0.0.0 == "any IP address"
ssock.bind(('0.0.0.0', 12345))
ssock.listen()
sock, remote_addr = ssock.accept()
Use(sock)
```

connection setup: server, generic


```
import select
import socket
all_addrs = socket.getaddrinfo(
        None, '12345',
        socket.AF_UNSPEC, socket.SOCK_STREAM)
ssocks = []
for af, socktype, proto, canonname, sockaddr in possible_addrs:
    ssock = socket.socket(af, socktype, proto)
    try:
        ssock.bind(sockaddr)
        ssock.listen()
        ssocks.append(ssock)
    except OSError:
        pass

which_ready, _, _ = select.select(ssocks, [], [])
for item in which_ready:
    sock, remote_addr = which_ready.accept()
    Use(sock)
```


client/server flow (one connection at a time)




client/server flow (one connection at a time)




client/server flow (one connection at a time)




client/server flow (one connection at a time)




client/server flow (one connection at a time)




client/server flow (one connection at a time)



client/server flow (one connection at a time)



client/server flow (multiple threads)



aside: I/O multiplexing

APIs for asking "tell me when any connection ready to read/write"

select, poll, epoll, IO completions, etc.

combine with 'non-blocking' writes to serve many connections from one thread

aside: send/recv

sockets have some alternate read/write-like functions:

recv, recvfrom, recvmsg

send, sendmsg

have some additional options we won't need in this class

reading and writing at once

so far assumption: alternate between reading+writing

- sufficient for FTP assignment
- how many protocols work

"half-duplex"

don't have to use sockets this way, but tricky

threads: one reading thread, one writing thread *OR*

event-loop: use *non-blocking I/O* and select()/poll()/etc. functions

- non-blocking I/O setup with fcntl() function
- non-blocking write() fills up buffer as much as possible, then returns
- non-blocking read() returns what's in buffer, never waits for more

aside: getting addresses

Python: sock.getsockname() == (addr, port) of local side

Python: sock.getpeername() == (addr, port) of remote side

socket options

'socket options' for extra settings

Python: `sock.setsockopt(level, key, value)`

C: `setsockopt(sock, level, key, value)`

common level values

- `SOL_SOCKET` — OS-level
- `IPPROTO_IP`
- `IPPROTO_IPV4`
- `IPPROTO_TCP`

common SOL_SOCKET options

SO_REUSEADDR — allow bind()ing even if another socket for this port active

> common problem: server can't bind() because old session in TIME_WAIT

SO_RCVBUF — buffer size used by OS for receiving bytes

SO_SNDBUF — buffer size used by OS for sending bytes

(full list on Linux: `man 7 socket`)

efficiency problem

```
sock = ...
sock.send(b'About to send file with 16Kbytes')
sock.send(b'File is HTML; updated 16 November')
sock.send(file_data)
```

Naive approach:

- one packet for ‘about to send file with...’
- one packet for ‘file is HTML; ...’
- some number of packets for `file_data`

sending small TCP packets, so lots of overhead

Nagle's algorithm

(RFC 896)

delay sending data when smaller than full TCP segment

hope: by waiting we'll get a full TCP segment

typical wait: 200 ms?

TCP_NODELAY socket option can disable (at least on Linux)

connected UDP sockets (Python)

```
import socket
# ipv4
sock = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
# ipv6
sock = socket.socket(socket.AF_INET6, socket.SOCK_DGRAM)

sock.bind((host, port))
sock.connect((host, port))
sock.send(b"one datagram")
sock.send(b"another datagram")
data = sock.recv(MAX_SIZE)
```

unconnected UDP sockets (Python)

```
sock = ...
sock.bind((host, port))
# no connect() operation

data, addr = sock.recvfrom(MAX_SIZE)

sock.sendto(data, (addr, port))
```

broadcast/multicast

IPv4: can broadcast to every machine on local network

- set the SO_BROADCAST socket option to 1
- send to special address 255.255.255.255
- received at that port number on all machines

multicast (send-to-many) groups

- request to receive: IP_ADD_MEMBERSHIP (v4), IPV6_ADD_MEMBERSHIP (v6)
- each 'multicast group' has IP address
- 224.0.0.0/24 and ff02::/16 = local network only
- local network version usually implemented by broadcasting + filtering by IP
- (non-local-network multicast is more complex...)

service disocvery

example: find printers on local network automatically

typical protocol mDNS (‘multicast DNS’)

uses IP addressses 224.0.0.251 / ff02::fb + port 5353

all machines on local network receive from all other machines on local network

backup slides