


# recall: multi-access media




# recall: multi-access media






Ali at gwc.org.uk / Alistair1978 via Wikimedia commons / CC-BY-SA 2.5

# recall: multi-access media







Ali at gwc.org.uk / Alistair1978 via Wikimedia commons / CC-BY-SA 2.5




# recall: switched network




# recall: switched network



# recall: switched network




# recall: switched network



# hubs and switches

Switch




Hub




difference is hidden inside

hub: electrically connects hosts — as if shared wires

switch: decides what to send on each output

# history: multi-access to switched

a lot of early networking technology was multi-access

wireless (wifi, cellular) and most home broadband still is

most wired networks are *switched*

- frames mostly directed to correct machine

# switching versus routing

switches — forward frames for common network

routers — forward packets between networks


basically same functionality

differences:


- extra layer for internetwork packets
- different mechanism to decide where to forward
- switch forwarding typically simpler

will start with simpler switching


# typically sent on Ethernet




# typically sent on Ethernet




# typically sent on Ethernet



# typically sent on Ethernet




# typically sent on Ethernet




destination address indicates who frame is for
present regardless of whether switching is in use

each host filters out frames for ‘wrong’ destination address


# typically sent on Ethernet





since destination address always present
as last resort, switches can send every frame to everyone

will still work, just much less efficient

# typically sent on Ethernet



# typically sent on Ethernet



# MAC addresses

MAC [media access control] addresses

used by Ethernet, Wifi, and lots of other protocols

48-bit number written in hex: `01:23:45:67:89:AB`

(sometimes seperated with `-` instead of `:`)

assigned by IEEE to networking manufacturers in blocks

Institution of Electrical and Electronics Engineers

example: `00:02:B3:`..., `00:03:47:`..., (and many more) for Intel

individual addresses hard-coded in networking hardware

uniquely identify port/device

# special MAC addresses

`00:00:00:00:00:00` (all zeroes)

`FF:FF:FF:FF:FF:FF` (all ones), `FF:`...

special destination meaning "send to everyone" (on this network)
called *broadcast*

`01:80:C2:`..., `33:33:`..., (and some more)

special destinations representing multiple receivers
example: 'all IPv6 routers on this network' (`33:33:00:00:00:02`)
called *multicast*

# larger MAC addresses

IEEE now calls MAC address EUI-48 (48-bit Extended Unique Identifier)

also created EUI-64, with 64-bit addresses

- way of mapping EUI-48s to EUI-64s
- turns out 48 bits might have been low

I'm not sure what status is on switching to 64-bit addresses

- IEEE 802.15.4 (used in ZigBee, 6LoWPAN, some others) uses EUI-64
- I don't know other local network protocols that do

# datagram idea

can always send something to anyone on network

- just put destination MAC in frame

no need for reservations/'connections'/etc.

- not like the interface you've seen with [TCP] sockets

not the only model for networks (and internetworks)

# virtual circuit

other model: virtual circuit

two machines setup a 'circuit'

- some sort of 'special' messages to do this

switches/routers reserve resources for circuit

- "gaurenteed" bandwidth

transmitted data must be part of estabished circuit

example: ATM (Asynchronous Transfer Mode)

- used (?historically?) by some telephone networks

# an annoyance

traditionally, switches/routers have been 'fixed function' specialized hardware

special hardware needed for multigigabit performance

limited configuration options

usually non-automated configuration

- login to each managed switch/router to change settings
- no standardization for configuration across vendors

little visibility into internal design

- even though switches/routers often running complicated programs

# the historical situation

let's say I want to design a new extension to Ethernet

historical options if want to test/deploy it...

- implement it in slow/low-capacity software/FPGA switch
- convince switch HW company to implement it + release new version of switches
- contort my modification to fit with switch features not intended for this use
  - example: using VPN support to change path of frames on network

# software defined networking (SDN)

movement toward *programmable* networks

# control plane and data plane

control plane

- decides *how* to handle traffic
- "slow path", where complicated decisions are

data plane

- actually implements the decisions made by the control plane
- "fast path", implementing simple rules

probably what switches did internally before SDN was a thing

# separate control/data plane

one SDN key idea: separate control and data plane

allow new vendor-neutral implementations of control plane

- requires standard interface for programming data plane
- most prominent example: OpenFlow

easily allows for central 'control plane' server

- instead of separate control plane running on each switch/router

# separate control/data plane

one SDN key idea: separate control and data plane

allow new vendor-neutral implementations of control plane

- requires standard interface for programming data plane
- most prominent example: OpenFlow

easily allows for central 'control plane' server

- instead of separate control plane running on each switch/router

# P4

P4 — programming langauge for data planes

intended to be compiled to run on fast switches

includes ‘runtime’ defining how control plane configures data plane

# future P4 assignment

given:


- simple P4 switch that doesn't know where to direct frames
- simpler controller (in Python) that configures switch
- simulated 4-machine network in VM

your task will be:


- have controller write static configuration to direct to right place
- modify data plane to send information to control plane
- have controller change configuration based on info from data plane

(we'll discuss more details later)

# P4 switch architecture




# P4 switch architecture





queues of frames to be processed
if needed, hold packets in between processing steps

# P4 switch architecture




# P4 switch architecture





ingress pipeline: processes every input frame
primary job: decide where to forward frame (if anywhere)

# P4 switch architecture





egress pipeline: process every output frame run one time for each copy output

# P4 switch architecture





parser: decode frame fields into temporary storage

# P4 switch architecture




deparser: converted decoded fields back into bytes for network

# P4 switch architecture




"match/action pipelines"
do series of table lookups based on parsed fields
each table lookup specifies next action

# P4: declaring headers (1)

```
typedef bit<48> macAddr_t;
header ethernet_t {
    macAddr_t srcAddr;
    macAddr_T dstAddr;
    bit<16>   etherType;
}
```

# P4: declaring headers (1)

```
typedef bit<48> macAddr_t;
header ethernet_t {
    macAddr_t srcAddr;
    macAddr_T dstAddr;
    bit<16>   etherType;
}
```

kinda like `typedef struct { ... } ethernet_t;`

# P4: declaring headers (1)

```
typedef bit<48> macAddr_t;
header ethernet_t {
    macAddr_t srcAddr;
    macAddr_T dstAddr;
    bit<16>   etherType;
}
```

kinda like `typedef struct { ... } ethernet_t;`

order needs to *exactly* match what's sent on network

- switch will do bit-by-bit copy into this struct

# P4: declaring headers (2)

```
struct headers {
    ethernet_t   ethernet;
    ipv4_t       ipv4;
    ipv6_t       ipv6;
}
```

# P4: declaring headers (2)

```
struct headers {
    ethernet_t   ethernet;
    ipv4_t       ipv4;
    ipv6_t       ipv6;
}
```

struct of all possible headers

- from all layers the switch/router handles
- not all frames will use all of them, some may be mutually exclusive
- order does not need to match frame storage (will write code to handle that)

# P4: declaring headers (2)

```
struct headers {
    ethernet_t   ethernet;
    ipv4_t       ipv4;
    ipv6_t       ipv6;
}
```

struct of all possible headers

- from all layers the switch/router handles
- not all frames will use all of them, some may be mutually exclusive
- order does not need to match frame storage (will write code to handle that)

references header types defined previously

# P4: parsing

```
parser MyParser(
    packet_in packet,
    out headers hdr,
    inout metadata meta,
    inout standard_metadata_t standard_metadata) {
```

function modifies 'out' parameters instead of returning

parser function — takes parameters:

- packet — the input frame
- headers — extracted headers (`struct headers`)
- meta — program's local variables about frame (`struct metadata`)
- standard_metadata — info for system about frame
  - where frame came from, where it should go, etc.

# P4: parsing

```
parser MyParser(...) {
    state start {
        transition parse_ethernet;
    }
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
            TYPE_IPV4: parse_ipv4;
            TYPE_IPV6: parse_ipv6
            default: accept;
        }
    }
    ....
}
```

# P4: parsing

```
parser MyParser(...) {
    state start {
        transition parse_ethernet;
    }
    state parse_ethernet {
        packet.
        transit                                    Type) {
            TYP
            TYPE_IPV6: parse_ipv6
            default: accept;
        }
    }
    ....
}
```

functions written as state machine
exectuion starts in state `start`
follows instructions in each state

# P4: parsing

```
parser MyParser(...) {
    state start {
        transition parse_ethernet;
    }
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
        }
    }
    ....
}
```

transition statements say which state to go to next
can be conditional using switch-statement-like syntax

# P4: parsing

```
parser MyParser(...) {
    state start {
        transition parse_ethernet;
    }
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
        }
    }
    ....
}
```

transition statements say which state to go to next
can be conditional using switch-statement-like syntax

# P4: parsing

```
parser MyParser(...) {
    state start {
        transition parse_ethernet;
    }
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
            TYPE_IPV4: parse_ipv4;
            T
            d
        }
    }
    ....
}
```

`extract` operation copies from packet into specific `header` object

# P4: parsing

```
parser MyParser(...) {
    ...
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
            TYPE_IPV4: parse_ipv4;
            TYPE_IPV6: parse_ipv6
            default: accept;
        }
    }

    state parse_ipv4 {
        packet.extract(hdr.ipv4)
        transition accept;
    }
```

# P4: parsing

```
parser MyParser(...) {
    ...
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
            TYPE_IPV4: parse_ipv4;
            TYPE_IPV6: parse_ipv6
            default: accept;
        }
    }

    state parse_ipv4 {
        packet.extract(hdr.ipv4)
        transition accept;
    }
```

extract operations
can be chained
to extract multiple headers
(for multiple layers
or variable-length headers)

# P4: deparsing

```
control MyDeparser(packet_out packet, in headers hdr) {
    apply {
        packet.emit(hdr.ethernet);
        packet.emit(hdr.ipv4);
        packet.emit(hdr.ipv6);
    }
}
```

# P4: deparsing

```
control MyDeparser(packet_out packet, in headers hdr) {
    apply {
        packet.emit(hdr.ethernet);
        packet.emit(hdr.ipv4);
        packet.emit(hdr.ipv6);
    }
}
```

use emit to put extracted bits back in packet

if header is not marked valid, emit does nothing
(`extract(hdr.foo)` marks `hdr.foo` valid,
can also use `hdr.foo.setValid()` and undo with
`hdr.foo.setInvalid()`)

# P4: ingress processing

example: send *everything* to output port number 4

```
control MyIngress(...) {
    apply {
        standard_metadata.egress_spec = 4;
    }
}
```

# P4: ingress processing

example: send *everything* to output port number 4

```
control MyIngress(...) {
    apply {
        standard_metadata.egress_spec = 4;
    }
}
```

standard_metadata — 'hard-coded' phase reads `egress_spec`

special `egress_spec` value for "discard frame"

# switch decisions

most decisions switches/routers make are table lookups

take field from packet (e.g. destination)

lookup in table what to do with that (e.g. send to port X, throw error, etc.)

P4 has special syntax for tables and table lookups

# P4: tables

```
table mac_dst_exact {
    key = {
        hdr.ethernet.dstAddr : exact;
    }
    actions = {
        drop,
        forward_to,
    }
    size = 1024;
    default_action = drop();
}
```

# P4: tables

```
table mac_dst_exact {
    key = {
        hdr.ethernet.dstAddr : exact;
    }
    actions = {
        drop,
        forward_to,
    }
    size = 1024;
    default_action = drop();
}
```

declare a table with a name
done has part of ingress/outgress

# P4: tables

```
table mac_dst_exact {
    key = {
        hdr.ethernet.dstAddr : exact;
    }
    actions = {
        drop,
        forward_to,
    }
    size = 1024;
    default_action = drop();
}
```

key/value structure
keys usually from headers
values are actions to run

# P4: tables

```
table mac_dst_exact {
    key = {
        hdr.ethernet.dstAddr : exact;
    }
    actions = {
        drop,
        forward_to,
    }
    size = 1024;
    default_action = drop();
}
```

here, each table entry contains whole address
P4 also supports partially matched keys

# P4 table key types

exact — full entry

lpm — longest prefix match

- table entries contain ‘prefixes’ of header field(s)
- we’ll see motivation for this when we talk about routing
- if multiple entries match, take longest one

ternary — 0/1/don’t care

- table entries contain key and mask
- entry matches if bits included in mask match
- other view: keys represented with 0/1/don’t care ‘trits’

# content-addressable memory

high-end routers/switches have *content addressable memory* (CAM)

...including *ternary content addressable memory* (TCAM)

= hardware that implements a table lookup

- 'content' $\approx$ key being looked up
- looks kinda like highly associative cache
- porbably lots of comparators

allows multigigabit frame processing speeds

P4 goal: P4 programs compile to use CAM/TCAM when available

# P4: using a table

```
control MyIngress(...) {
    ...
    table mac_dst_exact = {
        /* seen earlier */ ...
    }
    apply {
        mac_dst_exact.apply();
    }
}
```

# P4: using a table

```
control MyIngress(...) {
    ...
    table mac_dst_exact = {
        /* seen earlier */ ...
    }
    apply {
        mac_dst_exact.apply();
    }
}
```

apply operation invokes the actio

# P4: actions

```
control MyIngress(...) {
    action drop() {
        mark_to_drop(standard_metadata);
    }
    action forward_to(egressSpec_t port) {
        standard_metadata.egress_spec = port;
    }
    action mark_and_forward(egressSpec_t port) {
        hdr.some_proto.value = 1;
        standard_metadata.egress_spec = port;
    }
    ...
}
```

# P4: actions

```
control MyIngress(...) {
    action drop() {
        mark_to_drop(standard_metadata);
    }
    action forward_to(egressSpec_t port) {
        standard_metadata.egress_spec = port;
    }
    action mark_and_forward(egressSpec_t port) {
        hd
        st
    }
    ...
}
```

actions basically function calls for packet
can include parameters that are stored in table

# P4: actions

```
control MyIngress(...) {
    action drop() {
        mark_to_drop(standard_metadata);
    }
    action forward_to(egressSpec_t port) {
        standard_metadata.egress_spec = port;
    }
    action mark_and_forward(egressSpec_t port) {
        hdr
        sta
    }
    ...
}
```

typically, actions set standard metadata
to indicate where to send frame next

actual sending/not sending frame done later

# P4: actions

```
control MyIngress(...) {
    action drop() {
        mark_to_drop(standard_metadata);
    }
    action forward_to(egressSpec_t port) {
        standard_metadata.egress_spec = port;
    }
    action mark_and_forward(egressSpec_t port) {
        hdr.so
        standa
    }
    ...
}
```

actions can also edit packet headers
or do other table lookups
(which we will need in the future)

# P4: special actions

some ways switch can direct packet (incomplete list)

send to the control plane

- special output port that goes to 'general purpose' CPU

multicast/broadcast to multiple ports

- control plane can set *multicast groups*
- makes multiple copies of packets

# P4: control plane

P4 control plane is a program

sends commands to one or more switches:

- load P4 program into data plane
- set table entries
- configure multicast groups
- receive frames to process them

# aside: wrappers

I'll show code from a P4 controller for upcoming assignment

written in Python, using custom library to make things convenient

works with softawre based reference switch

no requirement to use Python or other specific language

- controller sends commands over network/IPC to data plane

real raw code has more boilerplate/etc.

probably several things different for hardware-based switches

# P4: control plane

P4 control plane is a program

sends commands to one or more switches:

- load P4 program into data plane
- set table entries
- configure multicast groups
- receive frames to process them

# P4: loading P4 program

```
p4info_helper =  ....
switch = ....
switch.MasterArbitrationUpdate()
switch.SetForwardingPipelineConfig(
    p4info=p4info_helper.p4info,
    bmv2_json_file_path=bmv2_file_path
)
```

# P4: loading P4 program

```
p4info_helper =  ....
switch = ....
switch.MasterArbitrationUpdate()
switch.SetForwardingPipelineConfig(
    p4info=p4info_helper.p4info,
    bmv2_json_file_path=bmv2_file_path
)
```

swtich supports having primary + backup controller, so need to indicate this is primary controller now

# P4: loading P4 program

```
p4info_helper =  ....
switch = ....
switch.MasterArbitrationUpdate()
switch.SetForwardingPipelineConfig(
    p4info=p4info_helper.p4info,
    bmv2_json_file_path=bmv2_file_path
)
```

"forwarding pipeline" = dataplane

# P4: loading P4 program

```
p4info_helper =  ....
switch = ....
switch.MasterArbitrationUpdate()
switch.SetForwardingPipelineConfig(
    p4info=p4info_helper.p4info,
    bmv2_json_file_path=bmv2_file_path
)
```

P4 code compiled to file to load, specified here

# P4: control plane

P4 control plane is a program

sends commands to one or more switches:

- load P4 program into data plane
- set table entries
- configure multicast groups
- receive frames to process them

# P4: setting table entries

```
write_or_overwrite_table_entry(
    p4info_helper=p4info_helper, switch=switch,
    table_name='MyIngress.mac_dst_exact',
    match_fields={
        'hdr.ethernet.dstAddr': some_address,
    },
    action_name='forward_to',
    action_params={'port': port},
)
```

# P4: setting table entries

```
write_or_overwrite_table_entry(
    p4info_helper=p4info_helper, switch=switch,
    table_name='MyIngress.mac_dst_exact',
    match_fields={
        'hdr.ethernet.dstAddr': some_address,
    },
    action_name='forward_to',
    action_params={'port': port},
)
```

p4info_helper, switch objects created by setup code

# P4: setting table entries

```
write_or_overwrite_table_entry(
    p4info_helper=p4info_helper, switch=switch,
    table_name='MyIngress.mac_dst_exact',
    match_fields={
        'hdr.ethernet.dstAddr': some_address,
    },
    action_name='forward_to',
    action_params={'port': port},
)
```

full name of table, including stage it is defined in

# P4: setting table entries

```
write_or_overwrite_table_entry(
    p4info_helper=p4info_helper, switch=switch,
    table_name='MyIngress.mac_dst_exact',
    match_fields={
        'hdr.ethernet.dstAddr': some_address,
    },
    action_name='forward_to',
    action_params={'port': port},
)
```

match value — format would be different if key was `lpm` or `ternary` instead of exact match

# P4: setting table entries

```
write_or_overwrite_table_entry(
    p4info_helper=p4info_helper, switch=switch,
    table_name='MyIngress.mac_dst_exact',
    match_fields={
        'hdr.ethernet.dstAddr': some_address,
    },
    action_name='forward_to',
    action_params={'port': port},
)
```

`write_or_overwrite_table_entry` not the 'raw' function
(one I wrote based on one P4 tutorial authors wrote)
uses gRPC (remote procedure call) library, which adds some extra steps

# P4: control plane

P4 control plane is a program

sends commands to one or more switches:

- load P4 program into data plane
- set table entries
- configure multicast groups
- receive frames to process them

# P4: multicast groups

```
switch.WritePREEntry(
    p4info_helper.buildMulticastGroupEntry(
        multicast_group_id=1,
        replicas=[
            {'egress_port': 1, 'instance': 0},
            {'egress_port': 2, 'instance': 0},
            {'egress_port': 3, 'instance': 0},
            {'egress_port': 4, 'instance': 0},
        ]
    )
)
```

# P4: multicast groups

```
switch.WritePREEntry(
    p4info_helper.buildMulticastGroupEntry(
        multicast_group_id=1,
        replicas=[
            {'egress_port': 1, 'instance': 0},
            {'egress_port': 2, 'instance': 0},
            {'egress_port': 3, 'instance': 0},
            {'egress_port': 4, 'instance': 0},
        ]
    )
)
```

in P4 dataplane code can write `standard_metadata.mcast_grp = 1` to use this

# P4: multicast groups

```
switch.WritePREEntry(
    p4info_helper.buildMulticastGroupEntry(
        multicast_group_id=1,
        replicas=[
            {'egress_port': 1, 'instance': 0},
            {'egress_port': 2, 'instance': 0},
            {'egress_port': 3, 'instance': 0},
            {'egress_port': 4, 'instance': 0},
        ]
    )
)
```

list of ports to output to when group selected

`instance` can be inspected by dataplane code for the egress step

# P4: multicast groups

```
switch.WritePREEntry(
    p4info_helper.buildMulticastGroupEntry(
        multicast_group_id=1,
        replicas=[
            {'egress_port': 1, 'instance': 0},
            {'egress_port': 2, 'instance': 0},
            {'egress_port': 3, 'instance': 0},
            {'egress_port': 4, 'instance': 0},
        ]
)
```

PRE = packet replication engine

supports multicast groups (shown) and "clone sessions" (not shown)
(clone sessions make extra copy of packet,
but process original normally)

# P4: control plane

P4 control plane is a program

sends commands to one or more switches:

- load P4 program into data plane
- set table entries
- configure multicast groups
- receive frames to process them

# P4: receiving frame

```
for item in switch.stream_msg_resp:
    if item.HasField('packet'):
        do_something_with(item.packet.payload,
                          item.packet.metadata)
```

# P4: receiving frame

```
for item in switch.stream_msg_resp:
    if item.HasField('packet'):
        do_something_with(item.packet.payload,
                          item.packet.metadata)
```


payload = bytes of frame
(what would normally be sent on network)

# P4: receiving frame


```
for item in switch.stream_msg_resp:
    if item.HasField('packet'):
        do_something_with(item.packet.payload,
                          item.packet.metadata)
```

extra metadata can be set by dataplane
example: which port packet came from


# typically sent on Ethernet




# network and switch tables




# network and switch tables



# network and switch tables



# network and switch tables



# constructing switch tables

could have system administrator input these by hand

- through an SSH-like interface, probably

works, but error-prone, hard to change, etc.

# constructing switch tables

could have system administrator input these by hand


through an SSH-like interface, probably

works, but error-prone, hard to change, etc.

alternative: switch should figure it out


# MAC learning

forwarding table



# MAC learning

forwarding table



# MAC learning

forwarding table

| dst MAC addr | port |
|---|---|
| | |
| | |
| | |
| | |
| | |
| | |
| (default) | ALL* |

incoming frame 1

| input port=2, output port = ??? | |
|---|---|
| data = | src=00:11:22:33:44:AA<br>dst=00:11:22:33:44:FF<br>type = IPV4<br>data = 33 45 43 42 ... |

# MAC learning

forwarding table

| dst MAC addr | port |
|---|---|
| | |
| | |
| | |
| | |
| | |
| | |
| (default) | ALL* |

incoming frame 1

| input port=2, output port = all but 2 | |
|---|---|
| data = | src=00:11:22:33:44:AA<br>dst=00:11:22:33:44:FF<br>type = IPV4<br>data = 33 45 43 42 ... |

# MAC learning

forwarding table

| dst MAC addr | port |
|---|---|
| 00:11:22:33:44:AA | 2 |
| | |
| | |
| | |
| | |
| | |
| (default) | ALL* |

incoming frame 1

| input port=2, output port = all but 2 | |
|---|---|
| data = | src=00:11:22:33:44:AA<br>dst=00:11:22:33:44:FF<br>type = IPV4<br>data = 33 45 43 42 ... |

# MAC learning

forwarding table

| dst MAC addr | port |
|---|---|
| 00:11:22:33:44:AA | 2 |
| | |
| | |
| | |
| | |
| | |
| (default) | ALL* |

incoming frame 1

| input port=2, output port = all but 2 | |
|---|---|
| data = | src=00:11:22:33:44:AA<br>dst=00:11:22:33:44:FF<br>type = IPV4<br>data = 33 45 43 42 ... |

incoming frame 2

| input port=3, output port = ??? | |
|---|---|
| data = | src=00:11:22:33:44:FF<br>dst=00:11:22:33:44:AA<br>type = IPV4<br>data = 34 45 43 42 ... |

# MAC learning

forwarding table

| dst MAC addr | port |
|---|---|
| 00:11:22:33:44:AA | 2 |
| | |
| | |
| | |
| | |
| | |
| (default) | ALL* |

incoming frame 1

| input port=2, output port = all but 2 | |
|---|---|
| data = | src=00:11:22:33:44:AA<br>dst=00:11:22:33:44:FF<br>type = IPV4<br>data = 33 45 43 42 ... |

incoming frame 2

| input port=3, output port = 2 | |
|---|---|
| data = | src=00:11:22:33:44:FF<br>dst=00:11:22:33:44:AA<br>type = IPV4<br>data = 34 45 43 42 ... |

# MAC learning

forwarding table

| dst MAC addr | port |
|---|---|
| 00:11:22:33:44:AA | 2 |
| 00:11:22:33:44:FF | 3 |
| | |
| | |
| | |
| | |
| (default) | ALL* |

incoming frame 1

| input port=2, output port = all but 2 | |
|---|---|
| data = | src=00:11:22:33:44:AA<br>dst=00:11:22:33:44:FF<br>type = IPV4<br>data = 33 45 43 42 ... |

incoming frame 2

| input port=3, output port = 2 | |
|---|---|
| data = | src=00:11:22:33:44:FF<br>dst=00:11:22:33:44:AA<br>type = IPV4<br>data = 34 45 43 42 ... |

# aside: no backwards broadcast

recall: broadcast sent to all but incoming port


question: what would happen if we didn't do this?

multiple may apply

A. might cause host to receive duplicates
B. might cause copies sent to non-incoming port to be dropped
C. might cause frames sent at same time to be dropped
D. might cause frames sent much later to be dropped


# loop from backwards broadcast

time step 1




# loop from backwards broadcast

time step 2




# loop from backwards broadcast

time step 3



# loop from backwards broadcast

time step 4



# loops

each packet keeps getting sent indefinitely


remember: happens for *every packet sent*

quickly overwhelms link between switches

but can just avoid by not sending back?


# loops with only-to-other

time step 1




# loops with only-to-other

time step 2




# loops with only-to-other

time step 3




# loops with only-to-other

time step 4



# loops with only-to-other

time step 5



# explosion from loops

avoiding sending back is not enough

will get catastrophic failure of network!

simple fix: only have one path from A to B

BUT means network is more fragile

we'll have better solutions when we talk about routing later

# preview: routing

better ways to decide where to send packets

...but require coordinating between switches

- avoid loops
- choose between multiple paths
- avoid 'flooding' for each new machine

problem also very important for large networks...

...like the Internet

we will revisit it when we talk about IP routing

# backup slides