

on a remote network


actual connections



logical connections



connecting two networks



encapsulation: why? (1)

some possible scnearios (1/2):

add encryption/authentication to data in flight

more explicit way to decide what goes through firewall

be “on University/company network” from home

hide original location of Internet connection

make virtual machines running on different servers appear to be plugged into one switch

encapsulation: why? (2)

some possible scnearios (2/2):

evade overally restrictive firewall rules

make two datacenters connected via Internet appear to be one big network

'separate' networks for phones v. desktops without buying two sets of switches

encapsulation options [incomplete]

left in above	TCP/UDP/higher layers	IP	link-layer
above TCP/UDP	HTTP proxy, DNS over HTTP(S)	—	—
TCP/UDP	SOCKS, HTTP CONNECT, SSH conn forwarding, TLS	—	—
IP	OpenVPN, WireGuard	GRE, IPsec	MPLS
link-layer	OpenVPN, ...	?	VLAN, MPLS

encapsulation steps

1. getting the stuff to encapsulate
2. sending it encapsulated

encapsulation steps

1. getting the stuff to encapsulate
2. sending it encapsulated

encapsulating w/ app changes

application might have special code to handle connecting differently

\+ might take advantage of extra information in encapsulation

example: many application's TLS support

example: web browser HTTP/SOCKS proxy support

encapsulating w/o app changes

generally: easier to do for lower layers

link-layer in something

- "virtual" (probably Ethernet) device
- sends/receives from 'tunnel'

IP in something

- "virtual" IP link
- destination routing table can go to

UDP/TCP in something

- replace socket API
- convince application to connect to different IP address?
- terminate UDP/TCP connection at 'wrong' machine

encapsulating w/o app changes

generally: easier to do for lower layers

link-layer in something

- "virtual" (probably Ethernet) device
- sends/receives from 'tunnel'

IP in something

- "virtual" IP link
- destination routing table can go to

UDP/TCP in something

- replace socket API
- convince application to connect to different IP address?
- terminate UDP/TCP connection at 'wrong' machine

Linux tap devices

```
# create virtual ethernet device mydev
$ ip tuntap add dev mydev mode tap
# mark ethernet device as up
$ ip link set mydev up
$ dhclient mydev # or other commands to use/config device
```

(dhclient is a DHCP client)

—

```
int opentap(const char * name) {
    ... /* setup code, not shown*/
}
...
int fd = opentap("mydev");
...
write(fd, ethernetPacket, packetSize)
/* and (probably in separate threads) */
read(fd, buffer, SIZE); processEthernetPacket(buffer);
```

encapsulating w/o app changes

generally: easier to do for lower layers

link-layer in something

- "virtual" (probably Ethernet) device
- sends/receives from 'tunnel'

IP in something

- "virtual" IP link
- destination routing table can go to

UDP/TCP in something

- replace socket API
- convince application to connect to different IP address?
- terminate UDP/TCP connection at 'wrong' machine

Linux tun devices

same as ‘tap’ devices, but...

get IP packets, not ethernet packets

```
# create virtual ethernet device mydev
$ ip tuntap add dev mydev mode tun
# setup device to be routed to, example:
$ ip address add 10.0.0.2 dev mydev
$ ip route add 10.0.0.0/24 dev mydev
$ ip -6 address add 3fff:1234::1 dev mydev
$ ip -6 route add 3fff:1234::/32 dev mydev
```

tunneling program can then open device and read/write IP packets

full tunnel routing table

say 198.51.100.5 is running tunnel sever,
and 10.0.2.5 is gateway beyond tunnel,
and 203.0.113.54 is local gateway:

address	next hop	dev	priority
10.0.2.0/24	—	tunnel	normal
198.51.100.5/32	208.0.113.54	real	high
(default)	203.0.113.54	real	normal
(default)	10.0.2.5	tunnel	high

alternate idea

shown: creating special route for tunnel destination

alternate idea: tell OS to use correct interface/IP address

most OSes: which IP address is bound = which network interface to use

- but would need to discover correct IP address
- might be tricky if wireless + wifi connections, or wifi changes

split tunnel routing table

say 198.51.100.5 is running tunnel sever,
and 10.0.2.5 is gateway beyond tunnel,
and 10.0.0.0/16, 198.51.100.0/24 are tunneled networks
and 203.0.113.54 is local gateway:

address	next hop	dev	priority
10.0.2.0/24	—	tunnel	normal
10.0.0.0/16	10.0.2.5	tunnel	normal
198.51.100.0/24	10.0.2.5	tunnel	normal
198.51.100.5/32	208.0.113.54	real	high
(default)	203.0.113.54	real	normal

encapsulating w/o app changes

generally: easier to do for lower layers

link-layer in something

- "virtual" (probably Ethernet) device
- sends/receives from 'tunnel'

IP in something

- "virtual" IP link
- destination routing table can go to

UDP/TCP in something

- replace socket API
- convince application to connect to different IP address?
- terminate UDP/TCP connection at 'wrong' machine

‘transparent’ proxy via library

```
ProxyChains README
current version: 3.1
=====================

This is open source software for GNU/Linux systems.

proxychains - a tool that forces any TCP connection made by any given application
to follow through proxy like TOR or any other SOCKS4, SOCKS5 or HTTP(S) proxy.
Supported auth-types: "user/pass" for SOCKS4/5, "basic" for HTTP.
```

configures dynamic library loader to load its library

LD_PRELOAD

with special versions of `connect`

encapsulating w/o app changes

generally: easier to do for lower layers

link-layer in something

- "virtual" (probably Ethernet) device
- sends/receives from 'tunnel'

IP in something

- "virtual" IP link
- destination routing table can go to

UDP/TCP in something

- replace socket API
- convince application to connect to different IP address?
- terminate UDP/TCP connection at 'wrong' machine

socket-in-socket

example: SSH connection forwarding

```
ssh -L X:remotehost:remoteport hostname
```

example: `stunnel` for 'tunneling' TCP in TLS

run on port X, configure to connect to some remote host

configure program to connect to localhost port X

...instead of remote host

encapsulating w/o app changes

generally: easier to do for lower layers

link-layer in something

- "virtual" (probably Ethernet) device
- sends/receives from 'tunnel'

IP in something

- "virtual" IP link
- destination routing table can go to

UDP/TCP in something

- replace socket API
- convince application to connect to different IP address?
- terminate UDP/TCP connection at 'wrong' machine

‘transparent’ proxy via IP interception

example use case: shared HTTP cache used automatically

- if company/ISP wants everyone to use cache for performance
- if company wants to audit all HTTP proxy

configure router/firewall to diret all HTTP TCP connections to proxy

either:

- configure proxy machine to accept connections on all IP addresses *or*
- have router/firewall do network address translation (other direction)

HTTP proxy `squid` on Linux, some firewall boxes support this mode

I don’t think this is a good idea...

- problematic with encryption

encapsulation steps

1. getting the stuff to encapsulate
2. sending it encapsulated

encapsulation options [incomplete]


left in above	TCP/UDP/higher layers	IP	link-layer
above TCP/UDP	HTTP proxy, DNS over HTTP(S)	—	—
TCP/UDP	SOCKS, HTTP CONNECT, SSH conn forwarding, TLS	—	—
IP	OpenVPN, WireGuard	GRE, IPsec	MPLS
link-layer	OpenVPN, ...	?	VLAN, MPLS

SOCKS (RFC 1928)


SOCKS motivation in RFC: firewall traversal

supports both TCP and UDP

SOCKS TCP operation (client)




SOCKS TCP operation (server)



SOCKS UDP operation

use TCP to get UDP port for proxy to use

send/receives UDP packets with "request header":



FRAG = which fragment number

- added header means we might need to split UDP packets up
- 0 = not fragmented, most sig bit = last fragment

ATYP = address type (IPv4/IPv6/DNS name)

what if...

consider SOCKS TCP connection forwarding...

what happens to bandwidth, latency, resource usage, error-reporting if...

sending lots of data and proxy to remote link is slow?

remote host goes down in middle of connection?

SSH protocol overview

SSH transport layer protocol

- handles encryption + integrity + host authentication
- uses key exchange, with key share signed by host key
- rest of connection uses symmetric encryption + MACs

transport layer supports sending packets

- initial 1-type "message number" identifies type
- packets encrypted+MAC'd once that is negotiated

on top of transport layer:

SSH (user) authentication protocol

- handles passwords, etc.

SSH connection protocol

SSH connection protocol

open channels identified by 32-bit integers

each channel has:

- type (`session` or `pty-req` or `tcpip-forward` or ...)
- "window size"
- maximum packet size

seperate packets for

- opening/closing channels
- adjusting "window size"
- sending data
- sending metadata (example: terminal window size)

SSH connection protocol

open channels identified by 32-bit integers

each channel has:

- type (`session` or `pty-req` or `tcpip-forward` or …)
- "window size"
- maximum packet size

seperate packets for

- opening/closing channels
- adjusting "window size"
- sending data
- sending metadata (example: terminal window size)

SSH connection protocol

open channels identified by 32-bit integers

each channel has:

- type (`session` or `pty-req` or `tcpip-forward` or ...)
- "window size"
- maximum packet size

seperate packets for

- opening/closing channels
- adjusting "window size"
- sending data
- sending metadata (example: terminal window size)

SSH window sizes

SSH connection protocol considers *window size* to be amount of data that can be sent

not same as TCP idea since no acknowledgments

decrements by X when X bytes sent

increases by Y on window adjust message with Y

SSH window sizes?

SSH has way of managing channel window sizes

how should SSH server do that?

(OpenSSH: 2MB max/init window size, not adjusted immediately)

Tor

Tor — "onion routing"

suppose connecting from A to B and A to C

goal: connection is anonymous

method: proxy through several 'onion routers'

attacker should only know:

- A is sending to someone via Tor
- B is receiving from someone via Tor
- C is receiving from someone via Tor

not be able to tie A and B or A and C or B and C together otherwise

Tor threat model

(from Digledine, Mathewson, Syverson, "Tor: A Second-Generation Onion Router")

an advserary "who can observe some fraction of network traffic; who can generate, modify, delete, or delay traffic; who can operate onion routers of their own; and who can compromise some fraction of onion routers"

Tor circuit idea (1)

$E_X(Y)$ = Y encrypted to X

to create 'circuit': A $\leftrightarrow$ OR1 $\leftrightarrow$ OR2 $\leftrightarrow$ B

- A = probably browser, B = probably webserver
- OR = onion router
- can choose different number of ORs if desired

A sends OR1 via TLS:
"please setup circuit to OR2: " + E_{OR2}("please connect to B")

OR1 sends A's encrypted data to OR2 with OR1's circuit ID

OR2 sends back responses via OR1 + OR1's circuit iD

OR1 uses circuit ID to send back to A

Tor circuit idea (2)

A $\leftrightarrow$ OR1 $\leftrightarrow$ OR2 $\leftrightarrow$ B

A = probably browser, B = probably webserver

OR1 doesn't know who A is sending to

OR2 doesn't know who is sending to B

fine if OR1, OR2 independently operated

in practice: probably add additional OR to circuit

otherwise, require large portion of ORs to be independent

Tor circuit




Figure 1: Alice builds a two-hop circuit and begins fetching a web page.

traffic analysis problem

problem 1: if I see A send 1000 bytes, then receive 1749 bytes, and...

at about the same time I see B receive 1000 bytes, then send 1749 bytes

...would be a big tell

worse: B or OR 1 or OR 3 can deliberately generate patterns of traffic to help ID A

mitigations for traffic analysis?

general idea: add data or delay to make everything 'the same'

add padding to traffic sent on 'circuit'

- 512-byte cells only (can't see exact sizes in bytes)
- additional padding cells added, too

"cover traffic" sent periodically between A and OR1

- 1.5 s to 9.5 s in each direction if no traffic
- idea: hard for attacker to tell when user active

but real-time nature limits possible mitigations

- similar idea for email avoids with random delays
- ...but can't really browse the web that way

application-layer tells

browser reveals a lot of information:

- browser, OS version
- screen size
- fonts available
- timezone
- ...

problematic for anonymity

- helps B limit possible other ends very seriously

Tor browser (modified Firefox, essentially) mitigation:
limited set of screen sizes, OS versions, fonts, etc. allowed

other Tor browser paranoia

scripts disabled by default

- seriously limits ‘ordinary’ browser security vulnerabilities

cookies, caches cleared when browser closed


HTTPS-only by default

- really dangerous otherwise since we don’t trust last onion router


encapsulation options [incomplete]

left in above	TCP/UDP/higher layers	IP	link-layer
above TCP/UDP	HTTP proxy, DNS over HTTP(S)	—	—
TCP/UDP	SOCKS, HTTP CONNECT, SSH conn forwarding, TLS	—	—
IP	OpenVPN, WireGuard	GRE, IPsec	MPLS
link-layer	OpenVPN, ...	?	VLAN, MPLS


connecting two networks



GRE segment format




GRE segment format



checksum, 'key' ($\sim$ port), sequence number optional

GRE segment format



key to allow multiple connections
if over UDP, could use separate ports instead
(but usualy not over UDP)

encapsulatoin with encryption

GRE = sends packets as is

often want to add encryption + authentication

typically:

- TLS-handshake like *key exchange* protocol to setup conncetion
- add space for message authentication code, nonce
- encrypt data with symmetric keys

example protocols:

- IKE (key exchange) + IPsec ESP (actual tunnel)
- OpenVPN (both)
- WireGuard (both)

TCP-in-TCP problems

sometimes run IP tunnel over TCP

- example: picky firewall rules, or non-UDP-supporting NAT

outer TCP connection adds extra buffering

- more than UDP, because will usually buffer instead of dropping

$\rightarrow$ very high round-trip time if not careful

can result in very poor TCP performance

VLAN idea

multiple ('virtual') local networks over one network

links/ports either shared or assigned to just one network

most common implementation: Ethernt 802.1q:

on shared links, frames tagged with their 'VLAN ID'

- special case: untagged frames part of VLAN ID 0x0

tags added/removed when going to unshared links


- and broadcast frames filtered out if VLAN ID doesn't match

Ethernet encapsulation

unencapsulated:



encapsulated:



encapsulation typically added/removed by switches

- sysadmin configures specific ports to be on a VLAN
- another common case: virtual machine software


network IDs ('VLAN identifiers') configured by sysadmins

- special case: 0x0 = default (untagged), 0xFFF = reserved

usually increase in supported frame size to accomodate tag


multiprotocol label switching (MPLS)

MPLS: combines encapsulation and routing tables




multiprotocol label switching (MPLS)

MPLS: combines encapsulation and routing tables




multiprotocol label switching (MPLS)

MPLS: combines encapsulation and routing tables



multiprotocol label switching (MPLS)

MPLS: combines encapsulation and routing tables



in	label	dest	op	out
0	---	3fff:1::/32	push 4	2
0	---	3fff:2::/32	push 7	2
2	9	---	pop	0
…	…	…	…	…

		dest	op	out
1	---	3fff:2::/32	push 7	0
1	---	default	push 8	0
0	1	---	pop	1
0	2	---	pop	2
…	…	…	…	…

multiprotocol label switching (MPLS)


MPLS: combines encapsulation and routing tables

label	op	out
4	swap 1	1
5	swap 2	1
7	swap 1	2
8	swap 9	0
…	…	…

routers in 'middle' of network
have *very simple* routing decisions
no prefix matching

in	label	dest	op	out
0	---	3fff:1::/32	push 4	2
0	---	3fff:2::/32	push 7	2
2	9	---	pop	0
…	…	…	…	…

1	---	3fff:2::/32	push 7	0
1	---	default	push 8	0
0	1	---	pop	1
0	2	---	pop	2
…	…	…	…	…



label distribution protocol

share with neighbors list of:

(ultimate destination, desired label)


use entries to

allocate new local labels

setup appropriate swap entries

send other neighbors update about new labels

MPLS tunnel


logical view — ‘virtual wire’
A
B
actual network
A
0
1
0
4
3
6
1
0
B
in label op out
0 --- push 12 1
--- 1 pop 0
… … … …
label op out
12 swap 17 4
6 swap 1 0
… … …
label op out
17 swap 0 6
19 swap 12 3
… … …
in label op out
0 --- push 17 1
--- 0 swap 9 6
… … … …

nested labels

label *stack* allows ...

nested tunnels

marking different types of packet

...

protocol-independence

only first/last routers care about actual protocol

easily allows for...

mix of Ethernet and IP tunnels

using routers that don't support IP (e.g. ATM)

...

backup slides