## CS 280 ASSIGNMENT 2:

## Accelerators

NAME: Xiaopeng Xu KAUST ID: 129052

## Task 1:

- Annotate the rtm\_kernel code (original, uploaded for the first assignment) with openMP directives to get a multithreaded code. Apply changes to the code if needed.
- Compile your openMP code using the Intel compiler on the MIC system for the Intel Xeon CPU (Sandy bridge)
- Run the code with 1, 2, 4, 8 and 16 threads on the CPU and report the corresponding speedups in a **graph**
- Compile the code for the coprocessor, run it using 60, 120, 180 and 240 threads natively on the coprocessor and report the corresponding speedups in a graph

CPU speedup report:

No. of threads (CPU)	1	2	4	8	16
Time (s)	373.6395	188.4551	94.8865	48.3044	36.7293
Speedup	1.00	1.98	3.94	7.74	10.17




Figure 1. CPU speedup

Coprocessor speedup report:

No. of threads (mic0)	60	120	180	240
Time (s)	71.6174	58.2261	59.5833	56.6691
Speedup	5.22	6.42	6.27	6.59




Figure 2. Coprocessor speedup

The directives I added are shown on figure 3. I added pragma for the two for loops in the time loop. Also I make i, x, y, z, lap private in order to make the threads independent, i is firstprivate in order to copy the value from outside.

CPU running shows that multiple threads give me a better performance. However, coprocessor speedup is not proportional to the number of threads. One possible reason is that there are race conditions among multiple threads. The CPU is 16 core with 2.60GHz frequency for each core. (Detailed information about the CPU is shown on attachment file cpuinfo.)

```
posix_memalign((void **)&source, p.alignment, sizeof(float)*nt);
        csource( nt, fmax, dt, source);
149
150
         // run the performance experiments of the target kernel
        154
        printf("*
157
        gettimeofday(&tvStart, NULL);
for (i=0; i<nt/2; i+=2) { // time loop</pre>
158
159
            //printf("Time step: %d\n", i);
160
    #pragma omp parallel for firstprivate(i) private(x,y,z,lap)
for(x=4; x< p.ip-4; x++) {</pre>
161
162
163
164
165
166
                                                    )+Vc(x-1,y
                                                    )+Vc(x
167
                             +coef[2]*(Vc(x+2,y
169
                             +coef[2]*(Vc(x,y+2,z))
                             +coef[2]*(Vc(x
                             +coef[3]*(Vc(x+3,y
172
                             +coef[3]*(Vc(x
                            +coef[3]*(Vc(x ,y
+coef[4]*(Vc(x+4,y
174
                                                     )+Vc(x-
175
                             +coef[4]*(Vc(x ,y+4,z
176
                            +coef[4]*(Vc(x
                                                ,z+4)+Vc(x
178
                        179
180
                            Uc(ixs, iys, izs) = Uc(ixs, iys, izs) + source[i];
181
183
184
185
                parallel for firstprivate(i) private(x,y,z,lap)
186
             for(x=4; x< p.ip-4; x++) {
187
188
189
190
                              coef[1]*(Uc(x+1,y)
                                                    )+Uc(x-1,y)
191
192
                             +coef[1]*(Uc(x ,y+1,z )+Uc(x ,y-
                             +coef[1]*(Uc(x ,y ,z+1)+Uc(x
193
                             +coef[2]*(Uc(x+2,y ,z )+Uc(x-2,y
```

Figure 3. Directives added for OpenMP

## Task 2:

Annotate the rtm\_kernel code (original, uploaded for the first assignment) with openACC directives

- Compile it using the PGI compiler on the SMC system
- Run it using a fermi GPU and report the corresponding speedup
- Run it using a K20 GPU and report the corresponding speedup

GPU speedup report:

GPUs	Fermi	K20	
Time (s)	24.3965	17.8206	
Speedup	15.32	20.97	




Figure 4. GPU speedup

The directives I added for OpenACC is shown on Figure 5. I copy the data outside of time loop, copy coeff, U3, source, and create/copy tempU1 and tempU2 (At first I just create tempU1, and tempU2. Then, in order to check the result I copied tempU1 and tempU2). I add two pragmas for each loop inside the time loop in order to achieve parallelism. Here collapse is used to make the 3 for loops collapse in serial codes, thus can easily be parallelized.

The running results shows that K20 gives me a better performance over Fermi.

```
#pragma acc data copy(coef[0:5],U3[0:p.domain_size],source[0:nt]) copy(tempU1[0:p.domain_size],tempU2
   [0:p.domain_size])
   for (i=0; i<nt/2; i+=2) { // time loop
        //printf("Time step: %d\n", i);
#pragma acc karpels</pre>
  161
                                                                                       164
165
166
167
168
169
170
171
172
173
174
175
176
177
                                                                                                                                                                                                                                                                                                                       ,z+3)+Vc(x
,z )+Vc(x
                                                                                                                                                                                           +coef[3]*(Vc(x ,y
+coef[4]*(Vc(x+4,y
 178
179
 180
181
 182
183
                                                                                                                                                               Uc(x,y,z) = 2.*Vc(x,y,z) - Uc(x,y,z) + ROC2(x,y,z)*lap;
if( (x==ixs) && (y==iys) && (z==izs) ){
    Uc(ixs,iys,izs) = Uc(ixs,iys,izs) + source[i];
 184
185
186
187
188
189
190
191
                           192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
                                                                                                                                                                                     =coef[0]*Uc(x,y,z)
+coef[1]*(Uc(x+1,y ,z )+Uc(x-1,y +coef[1]*(Uc(x ,y+1,z )+Uc(x ,y +coef[1]*(Uc(x ,y ,z+1)+Uc(x ,y +coef[2]*(Uc(x+2,y ,z )+Uc(x-2,y +coef[2]*(Uc(x ,y+2,z )+Uc(x ,y +coef[3]*(Uc(x ,y ,z+2)+Uc(x ,y +coef[3]*(Uc(x ,y ,z+2)+Uc(x ,y +coef[3]*(Uc(x ,y ,z+2)+Uc(x ,y +coef[3]*(Uc(x ,y ,z+3)+Uc(x ,y +coef[3]*(Uc(x ,y ,z+3)+Uc(x ,y +coef[4]*(Uc(x ,y ,z+3)+Uc(x ,y +coef[4]*(Uc(x ,y ,z+4)+Uc(x ,y +coef[4]*(Uc(x ,y ,z+4)+Uc(x ,z ,z ,z )+Uc(x ,z
                                                                                                                                                               Vc(x,y,z) = 2.*Uc(x,y,z) - Vc(x,y,z) + ROC2(x,y,z)*lap;
if( (x==ixs) && (y==iys) && (z==izs) && ((i+1) <nt)){
    Vc(ixs,iys,izs) = Vc(ixs,iys,izs) + source[i+1];
}</pre>
```

Figure 5. Directives added for OpenACC