

Payment Search API — Field Descriptions

Top-level (`data`)

- ``id`` — Unique payment identifier (Base32 encoded Charge ID).
- ``status`` — Current payment status (e.g. Approved, Declined).
- ``amount`` — The payment request amount in its original currency.
- ``currency`` — The original currency the payment was requested in (three-letter ISO code), e.g. GBP, USD.
- ``reference`` — An optional reference (such as an order ID) a merchant can use to identify the charge.
- ``metadata`` — Arbitrary key-value metadata attached to the payment by the merchant.
- ``requested_on`` — The time when the payment request was made.
- ``processing_channel_id`` — The identifier of the processing channel, e.g. ``pc_6k7jcjztullutk6ahxsozrlw6q``.
- ``response_code`` — The latest relevant gateway response code for acceptance.
- ``response_summary`` — Short description of the acceptance gateway response code.
- ``last_four_card_digits`` — Last four digits of the card used for the payment.
- ``bin`` — Bank Identification Number — first 6 digits of the card used.
- ``card_expiry_month`` — Card expiry month.
- ``card_expiry_year`` — Card expiry year.
- ``issuer`` — Name of the card-issuing bank.
- ``issuer_country`` — Two-letter ISO country code of the card-issuing bank.
- ``avs_check`` — Address Verification Service check result.
- ``card_scheme_local`` — Local card scheme name (e.g. Visa, Mastercard).
- ``payment_method`` — For card payments: card scheme (e.g. visa). For alternative payment methods: the APM (e.g. klarna).
- ``scheme`` — The name of the scheme used for acquiring (e.g. Visa, Mastercard).
- ``card_type`` — Card type (Credit or Debit).
- ``card_wallet_type`` — Wallet type associated with the card (e.g. Apple Pay, Google Pay).
- ``is_disputed`` — Boolean indicating whether the payment has an open dispute.
- ``recommendation_code`` — Risk recommendation code returned by the risk engine.
- ``total_authorized`` — The authorised amount in its original currency.
- ``total_captured`` — The total value of captures and partial captures in the original currency.
- ``total_refunded`` — The total value of refunds and partial refunds in the original currency. Does not include unreferenced refunds.
- ``eci`` — Electronic Commerce Indicator — authentication assurance level used in the 3DS flow.
- ``three_ds_protocol_version`` — 3D Secure protocol version used for authentication.
- ``arn`` — Acquirer Reference Number — used for chargeback and dispute tracking.
- ``payment_type`` — An indicator that determines the type of charge as required by the card scheme, e.g. Regular, MOTO (Merchant-Offline/Telephone Order).
- ``type`` — Direction of the transaction (e.g. payin, payout).

``authentication_status`` — Outcome of the payment during authentication. Can be authenticated, failed, expired or rejected.

``risk_flagged`` — Boolean indicating whether the payment was flagged by the risk engine.

``risk_score`` — Numerical risk score assigned by the risk engine.

``actions[]` (per-action detail)`

``id`` — Identifier for the specific action within the payment.

``transaction_id`` — Identifier linking this action to the parent transaction.

``type`` — Action type (e.g. Authorization, Capture, Refund, Credit).

``processed_on`` — The time this specific action was processed.

``status`` — Outcome status of this action (e.g. Approved, Declined).

``amount`` — Amount associated with this action in the payment's original currency.

``auth_code`` — Authorisation code returned by the issuer.

``response_code`` — Gateway response code for this specific action.

``response_summary`` — Short description of the gateway response code for this action.

``reference`` — Reference associated with this specific action.

``fraud_score`` — Fraud score assigned to this action by the risk engine.

``authentication_experience`` — 3DS authentication flow used for this action (e.g. frictionless, challenge).

``reason_code`` — Reason code for the action outcome (e.g. decline reason code).

``sanction_screening`` — Result of sanction/AML screening applied to this action.

``processing.acquirer_reference_number`` — Acquirer-assigned reference number for this action.

``processing.acquirer_transaction_id`` — Acquirer-assigned transaction ID for this action.

``recommendation_code`` — Risk recommendation code for this specific action.

``processing_channel_name`` — Human-readable name of the processing channel used for this action.

``transaction_retrieval_reference_number`` — Retrieval reference number used for dispute and chargeback lookups with the scheme.

``scheme_merchant_id`` — The merchant ID assigned by the card scheme.

``card_acceptor_id`` — An ID which identifies the merchant account, generated by the acquirer.

``dispute_details``

``id`` — Unique dispute identifier.

``status`` — Current status of the dispute.

``reason`` — Human-readable reason for the dispute (e.g. Fraudulent transaction).

``reason_code`` — Scheme-specific reason code for the dispute.

``initiated_on_date`` — Date the dispute was raised by the cardholder.

``submit_evidence_by_date`` — Deadline by which the merchant must submit dispute evidence.

``amount`` — Disputed amount in the payment's original currency.

``method`` — Payment method involved in the dispute (e.g. card).

``currency`` — Currency of the disputed amount (three-letter ISO code).

``description`` — Description of the disputed transaction.

`relevant\_evidence` — List of evidence types relevant to contesting this dispute.

`acquirer\_response`

`authorisation\_code` — Authorisation code returned by the acquirer.

`acquirer\_response\_code` — Raw response code returned by the acquirer for the authorisation.

`authorisation\_description` — Human-readable description of the authorisation outcome from the acquirer.

`authorisation\_codes` — List of all authorisation codes associated with this payment (e.g. where multiple authorisation attempts occurred).

`capture\_code` — Acquirer response code for the capture action.

`capture\_description` — Human-readable description of the capture outcome.

`refund\_code` — Acquirer response code for the refund action.

`refund\_description` — Human-readable description of the refund outcome.