

Noble Build Notes

Last Modified Mon July 27 2026

Introduction

...

Build Order

Core GPU/MPI Libraries

- Nvidia Driver
- CUDA Toolkit
- UCX
- libevent
- hwloc
- OpenPMIx
- PRRTE
- OpenMPI

OpenFOAM Tools

- ParaView
- Umpire
- Hypre
- Apt Installs (CGAL, Boost, etc)
- FFTW
- KaHIP
- GKlib
- METIS
- ParMETIS
- Scotch
- Zoltan
- AMGX
- PETSc
- OpenFOAM
- AmgX4Foam

Nvidia driver

Starting from a fresh install of 24.04.4. Haswell's trio of GTX 1080 TIs need:

```
nvidia-smi
| NVIDIA-SMI 570.211.01      Driver Version: 570.211.01      CUDA Version
| 12.8
```

Nvidia Prerequisites

```
# register the CUDA keyring
wget https://developer.download.nvidia.com/compute/cuda/repos/ubuntu2404/x86_64/
  /cuda-keyring_1.1-1_all.deb
sudo dpkg -i cuda-keyring_1.1-1_all.deb
```

```
sudo apt update

# Threadripper needs Compute Architecture sm_86 and sm_120
sudo apt install nvidia-driver-570
```

CUDA Toolkit

```
# maintain compatibility with Haswell's sm_61, hence Toolkit 12.8
sudo apt install cuda-toolkit-12-8
reboot
```

CUDA_HOME Variable

Inside `~/.bashrc`, add the `CUDA_HOME` variable which some tools look for.

```
...
export CUDA_HOME=/usr/local/cuda
export PATH=$CUDA_HOME/bin
export LD_LIBRARY_PATH=$CUDA_HOME/lib64
```

Track PATH, and LD_LIBRARY_PATH Variables

Moving forward, inside `~/.bashrc`, track changes following each successful installation of a tool, e.g.:

```
...
export PATH=/opt/mytool/bin:$PATH
export LD_LIBRARY_PATH=/opt/mytool/lib:$LD_LIBRARY_PATH
```

UCX

Prerequisites

```
mkdir repos && cd repos

# collect the codebase
git clone --recursive https://github.com/openucx/ucx
cd ucx
sudo apt update
sudo apt install build-essential automake autoconf pkg-config libtool
```

Configure UCX

```
./autogen.sh

# For Haswell:
./configure --prefix=/opt/ucx --with-cuda=/usr/local/cuda --with-nvcc-gencode
    ="-gencode=arch=compute_61,code=sm_61" --enable-mt
```

OpenMPI Dependencies

libevent

```
cd libevent
./autogen.sh
./configure --help
mkdir build && cd build
../configure --prefix=/opt/libevent
make
make verify
sudo make install
```

hwloc

```
cd hwloc
git checkout tags/hwloc-2.14.0
./autogen.sh
./configure --help
mkdir build && cd build
../configure --with-cuda=/usr/local/cuda --prefix=/opt/hwloc
make
sudo make install
```

Prerequisites

```
sudo apt install perl python3 python3-pip virtualenv flex bison gfortran
```

OpenPMIx

```
cd openpmix
git checkout tags/v6.1.1rc2
./autogen.pl
./configure --help
mkdir build && cd build
../configure --prefix=/opt/pmix --with-hwloc=/opt/hwloc --with-libevent=/opt/
libevent
make -j$(nproc)
sudo make install
```

PRRTE

```
cd prrte
./autogen.pl
mkdir build && cd build
../configure --prefix=/opt/prrte --with-libevent=/opt/libevent --with-hwloc=/
opt/hwloc --with-pmix=/opt/pmix
make -j$(nproc)
sudo make install
```

OpenMPI

```
cd ompi/  
./autogen.pl  
mkdir build && cd build  
../configure --prefix=/opt/mpi --with-libevent=/opt/libevent --with-hwloc=/opt/  
hwloc --with-pmix=/opt/pmix --with-prte=/opt/prte --with-ucx=/opt/ucx --  
with-ucx-libdir=/opt/ucx/lib --with-cuda=/usr/local/cuda --with-cuda-libdir  
=/usr/local/cuda/lib64/stubs  
make -j$(nproc)  
sudo make install
```

Changes to etc/openmpi-mca-params.conf

This appears to be an important tweak for a custom UCX set-up with multiple gencodes. Doing this prevents ob1 from being the highest prioritized provider in the stack. Instead, ucx is always picked. This helps in most cases and passes the PETSc tests, but in theory this configuration could also cause errors too. It is still a little early to say anything certain.

This is confirmed for Haswell too 7/26.

```
# Point-to-point Messaging Layer  
pml=ucx  
# One-sided Communication Layer  
osc=ucx
```

OpenMPI etc/prefs.sh Changes

```
export MPI_ARCH_PATH=/opt/mpi
```

ParaView

Pre-Requisites

```
sudo apt install cmake ninja-build libtbb-dev mesa-common-dev mesa-utils  
freeglut3-dev xsltproc libxkbcommon-dev qt6-5compat-dev qt6-base-dev qt6-  
tools-dev qt6-svg-dev
```

Cmake Configuration

```
cd repos  
git clone --recursive https://github.com/Kitware/ParaView.git  
cd ParaView  
mkdir paraview-build && cd paraview-build  
cmake -GNinja -DCMAKE_INSTALL_PREFIX=/opt/paraview -DPARAVIEW_USE_PYTHON=ON -  
DPARAVIEW_USE_CUDA=ON -DPARAVIEW_USE_MPI=ON -DCMAKE_CUDA_ARCHITECTURES="61"  
-DVTK_SMP_IMPLEMENTATION_TYPE=TBB -DCMAKE_BUILD_TYPE=Release ..  
  
# ninja -j runs out of memory and always has to be re-run a couple of times on  
both machines.  
# build feedback is minimal. some libraries take several minutes to build.  
# Update: ninja -j$(nproc) ultimately failed on TR.  
# I had to use cmake --build . -j$(nproc) to finally complete the process.
```

```
# Apparently, there are known issues with how ninja handles large core sizes on
    some AMD CPUs.

# ninja -j$(nproc)
cmake --build . -j$(nproc)
sudo ninja install
```

ParaView and VTK etc/prefs.sh Changes

```
export ParaView_VERSION="none"
export VTK_VERSION="none"
```

Umpire

Like PRRTE, and OpenPMIx, Umpire is used by Hypr and is a configurable installation inside Hypr's build process. Here is the authoritative source.

Collect Umpire Code

```
git clone --recursive https://github.com/LLNL/Umpire.git
cd Umpire
mkdir build && cd build
```

Cmake Configuration and Build

```
cmake -DENABLE_MPI=ON -DENABLE_CUDA=ON -DBLT_ENABLE_CUDA=ON -DBLT_ENABLE_OPENMP
=ON -DBLT_ENABLE_MPI=ON -DBUILD_SHARED_LIBS=ON -DUMPIRE_ENABLE_CUDA=ON -
DUMPIRE_ENABLE_OPENMP=ON -DUMPIRE_ENABLE_MPI=ON -
DUMPIRE_ENABLE_IPC_SHARED_MEMORY=ON -DUMPIRE_ENABLE_MPI3_SHARED_MEMORY=ON -
DCMAKE_BUILD_TYPE=Release -DCMAKE_CUDA_ARCHITECTURES="61" -
DUMPIRE_ENABLE_C=ON -DCMAKE_INSTALL_PREFIX=/opt/umpire ..

make -j$(nproc)
sudo make install
```

LD_LIBRARY_PATH and PATH changes in ~/.bashrc:

```
export PATH=/opt/paraview/bin:/opt/umpire/bin:/opt/mpi/bin:/opt/prrte/bin:/opt
/pmix/bin:/opt/ucx/bin:$CUDA_HOME/bin:$PATH
export LD_LIBRARY_PATH=/opt/paraview/lib:/opt/umpire/lib:/opt/mpi/lib:/opt/
prrte/lib:/opt/pmix/lib:/opt/ucx/lib:/opt/ucx/lib/ucx:$CUDA_HOME/lib64
```

Umpire etc/prefs.sh Changes

```
export UMPIRE_ARCH_PATH=/opt/umpire
```

Hypre

```
cd repos
git clone --recursive https://github.com/hypre-space/hypre.git
cd hypre
mkdir build && cd build

# Haswell
cmake -DBUILD_SHARED_LIBS=ON -DCMAKE_POSITION_INDEPENDENT_CODE=ON -
      DCMMAKE_BUILD_TYPE=Release -DCMAKE_C_COMPILER=mpicc -DCMAKE_CXX_COMPILER=
      mpicxx -DHYPRE_ENABLE_CUDA=ON -DMPI_INCLUDE_PATH=/opt/mpi/include -
      DCMMAKE_CUDA_ARCHITECTURES="61" -DHYPRE_ENABLE_GPU_AWARE_MPI=ON -
      DHYPRE_ENABLE_OPENMP=ON -DHYPRE_ENABLE_UMPIRE=ON -DHYPRE_ENABLE_UMPIRE_HOST
      =ON -DHYPRE_ENABLE_UMPIRE_DEVICE=ON -DCMAKE_INSTALL_PREFIX=/opt/hypre -
      DTPL_UMPIRE_INCLUDE_DIRS=/opt/umpire/include -DTPL_UMPIRE_LIBRARIES=/opt/
      umpire/lib/libumpire.so ../src

# Threadripper
cmake -DBUILD_SHARED_LIBS=ON -DCMAKE_POSITION_INDEPENDENT_CODE=ON -
      DCMMAKE_BUILD_TYPE=Release -DCMAKE_C_COMPILER=mpicc -DCMAKE_CXX_COMPILER=
      mpicxx -DHYPRE_ENABLE_CUDA=ON -DMPI_INCLUDE_PATH=/opt/mpi/include -
      DCMMAKE_CUDA_ARCHITECTURES="86;120" -DHYPRE_ENABLE_GPU_AWARE_MPI=ON -
      DHYPRE_ENABLE_OPENMP=ON -DHYPRE_ENABLE_UMPIRE=ON -DHYPRE_ENABLE_UMPIRE_HOST
      =ON -DHYPRE_ENABLE_UMPIRE_DEVICE=ON -DCMAKE_INSTALL_PREFIX=/opt/hypre -
      DTPL_UMPIRE_INCLUDE_DIRS=/opt/umpire/include -DTPL_UMPIRE_LIBRARIES=/opt/
      umpire/lib/libumpire.so ../src

make -j$(nproc)
sudo make install
```

Hypre etc/prefs.sh Changes

```
export HYPRE_ARCH_PATH=/opt/hypre
```

CGAL

```
sudo apt update
sudo apt install libcgall-dev libgmp-dev libmpfr-dev libboost-system-dev
```

CGAL prefs.sh Changes

```
#can use default cgal
export CGAL_ARCH_PATH=/usr
```

FFTW

```
# Use lscpu to identify supported architectures to enable
lscpu

cd fftw-3.3.11
```

```

mkdir build && cd build

# Haswell
../configure --prefix=/opt/fftw --enable-openmp --enable-shared --enable-
  threads --enable-mpi --enable-sse2 --enable-avx --enable-avx2

# Threadripper
../configure --prefix=/opt/fftw --enable-openmp --enable-shared --enable-
  threads --enable-mpi --enable-sse2 --enable-avx --enable-avx2 --enable-
  avx512

make -j$(nproc)
sudo make install

```

KaHIP

```

mkdir build && cd build

cmake -DCMAKE_INSTALL_PREFIX=/opt/kahip -DCMAKE_BUILD_TYPE=Release -
  DBUILD_SHARED_LIBS=ON -DMPI_HOME=/opt/mpi -DCMAKE_INSTALL_LIBDIR=/opt/
  kahip/lib ..

make -j$(nproc)
sudo make install

```

Karypis Labs

Create a [consolidated repository] containing all three Karypis Labs tools used by PETSc and OpenFOAM.

GKlib

```

cd GKlib
mkdir build && cd build

cmake -DCMAKE_INSTALL_PREFIX=/opt/karypis -DCMAKE_BUILD_TYPE=Release -DSHARED=
  ON -DOPENMP=ON ..

make -j$(nproc)
sudo make install

```

METIS

For me, METIS had a couple of bugs in the root folder's `CMakeLists.txt`. I changed these lines:

```

(line 55) include_directories(include)
...
(line 73) add_subdirectory("include")

```

Pre-Make Step

Uncomment the `#defines` for `IDXTYPEWIDTH` and `REALTYPEWIDTH` inside `/opt/karypis/include/metis.h`:

```
(line 33) #define IDXTYPEWIDTH 32
...
(line 43) #define REALTYPEWIDTH 64 /* note the 64 for double precision */
```

Cmake Configuration and Build

```
cd METIS
mkdir build && cd build

cmake -DCMAKE_BUILD_TYPE=Release -DSHARED=ON -DOPENMP=ON -DCMAKE_INSTALL_PREFIX
    =/opt/karypis -DGKLIB_PATH=/opt/karypis ..

make -j$(nproc)
sudo make install
```

ParMETIS

```
cd ParMETIS
mkdir build && cd build

cmake -DCMAKE_BUILD_TYPE=Release -DSHARED=ON -DOPENMP=ON -DCMAKE_INSTALL_PREFIX
    =/opt/karypis -DGKLIB_PATH=/opt/karypis -DMETIS_PATH=/opt/karypis -
    DCMAKE_C_COMPILER=mpicc ..

make -j$(nproc)
sudo make install
```

Scotch

Clone Repository

```
# Need Scotch for orthogonal decomposition
git clone --recursive https://gitlab.inria.fr/scotch/scotch.git
```

Cmake Configuration

```
cd Scotch
mkdir build && cd build

cmake -DCMAKE_BUILD_TYPE=Release -DBUILD_SHARED_LIBS=ON -DCMAKE_INSTALL_PREFIX
    =/opt/scotch -DINSTALL_METIS_HEADERS=OFF -DMPI_THREAD_MULTIPLE=ON -
    DCMAKE_C_COMPILER=mpicc ..

make -j$(nproc)
sudo make install
```

Scotch openfoam/etc/config.sh/scotch and openfoam/etc/prefs.sh Changes

```
export SCOTCH_ARCH_PATH=/opt/scotch
```


Zoltan

```
cd Zoltan
mkdir build && cd build

# Use CFLAGS and CXXFLAGS to force shared libraries
../configure --prefix=/opt/zoltan --enable-mpi --with-mpi=/opt/mpi --with-
    parmetis=1 --with-parmetis-incdir=/opt/karypis/include --with-parmetis-
    libdir=/opt/karypis/lib --with-scotch=1 --with-scotch-incdir=/opt/scotch/
    include --with-scotch-libdir=/opt/scotch/lib CFLAGS="-O3 -fPIC" CXXFLAGS="-
    O3 -fPIC"

make everything -j$(nproc)

# Create the shared library version of libzoltan manually
cd src

# ran on Haswell 7/26
mpicxx -shared -o libzoltan.so *.o -L/opt/scotch/lib -lptscotch -lscotch -L/opt
    /karypis/lib -lparmetis -lmetis

# Create the system installation folders
sudo mkdir -p /opt/zoltan/lib /opt/zoltan/include

# Copy shared object library
sudo cp libzoltan.so /opt/zoltan/lib/

# Copy the Zoltan_config.h file into include
sudo cp include/Zoltan_config.h /opt/zoltan/include

# Copy the Zoltan header files into include
cd ../../src
sudo cp include/*.h /opt/zoltan/include
```

AMGX

Clone Repository

```
git clone https://github.com/amgx/amgx.git
cd amgx
mkdir build && cd build
```

Test launcher Issues

Change a line in src/CMakeLists.txt prior to running cmake:

```
(line 55) target_link_libraries(amgx_tests_launcher "/opt/mpi/lib/libmpi.so")
```

Cmake Configuration and Build

```
# Haswell
```

```
cmake -DCMAKE_BUILD_TYPE=Release -DCMAKE_INSTALL_PREFIX=/opt/amgx -
      DCMCMAKE_CUDA_ARCHITECTURES="61" -DCMAKE_C_COMPILER=mpicc -
      DCMCMAKE_CXX_COMPILER=mpicxx -DCMAKE_CUDA_FLAGS="-I/opt/mpi/include" -
      DCMCMAKE_EXE_LINKER_FLAGS="-L/opt/mpi/lib -lmpi" ..

make -j$(nproc)
sudo make install
```

PETSc

Repository and Prerequisites

```
# We need PETSc for scientific computation
git clone --recursive https://github.com/petsc/PETSc.git

# We need blas and lapack for PETSc
sudo apt install libopenblas-dev liblapack-dev
```

Configure

```
cd PETSc
mkdir build

sudo mkdir /opt/petsc
sudo chown user:user /opt/petsc

# works after removing Scotch's duplicate metis.h insertion
./configure --prefix=/opt/petsc --with-openmp=1 --with-bison=1 --with-boost=1
--with-cuda=1 --with-ucx-dir=/opt/ucx --with-mpi-dir=/opt/mpi --with-amgx-
dir=/opt/amgx --with-hwloc-dir=/opt/hwloc --with-umpire-dir=/opt/umpire --
with-scotch-dir=/opt/scotch --with-ptscotch-dir=/opt/scotch --with-fftw-dir
=/opt/fftw --with-zoltan-dir=/opt/zoltan --with-hypre-dir=/opt/hypre --with
-parmetis-dir=/opt/karypis --with-metis-dir=/opt/karypis

make PETSC_DIR=/media/skooby/data/repos/petsc PETSC_ARCH=arch-linux-c-debug all

make PETSC_DIR=/media/skooby/data/repos/petsc PETSC_ARCH=arch-linux-c-debug
install

sudo chown root:root /opt/petsc
```

PETSc etc/prefs.sh Changes

```
export PETSC_ARCH_PATH=/opt/petsc
```

OpenFOAM

Introduction

Similar to most `make` tools, `Allwmake` looks for an `Allwmake` file and only builds subfolders containing one. You can run `./Allwmake` multiple times and it just picks up where it left off.

Although built from a relatively simple set of `Allwmake` commands, OpenFOAM uses a complex and opaque configuration and build process under the hood that automatically sets and edits multiple environment variables, and creates numerous new paths and folders. As part of the normal documented build process, users are directed to source the `etc/bashrc` in the root OpenFOAM directory to kick off this process. This `bashrc` file generates or changes 60 environment variables.

Some of the expected functionality is broken for my Ubuntu instance, in particular regarding external tool mappings. OpenFOAM uses a `etc/config.sh/tool-name` convention for settings paths, along with an associated, user-created `etc/prefs.sh` file for customization and overriding. However, in addition to defining variables in these `tool-name` files, there is also some embedded logic in some cases, and that logic didn't always end up producing the expected results, in my case.

Instead, I wound up needing to both add a `prefs.sh` file and also overwrite some of the values and/or logic set in some of those `etc/config.sh/tool-name` files as well. In particular, I needed to both include a `prefs.sh` file, and override the `metis`, `kahip`, `scotch`, and `zoltan` files before I could build their associated artifacts (`libmetis.so`, `libkahip.so`, etc) without issues. The entire tools configuration infrastructure is mostly a black box to me, so I can't really explain why this is would be the case. I've included all the file edits here in the `OpenFOAM` folder, inside this repository, for your review.

Installation Topology

Like all the external tools, this build assumes a target installation path of `/opt/openfoam`. Create a new folder in `/opt` called `openfoam`, and give temporary ownership to your regular user:

```
sudo mkdir /opt/openfoam
sudo chown username:username /opt/openfoam
cp -r repos/OpenFOAM/* /opt/openfoam
```

External Tools Configuration

Hacking `etc/config.sh/*`

OpenFOAM has several quirks regarding its external dependencies.

OpenFOAM uses the convention `etc/config.sh/tool_name` to set default external tool folder locations, and a optional `prefs.sh` file inside `etc/` for preferences. So in theory, any configuration changes in `prefs.sh` get picked up during the standard calls to `./Allwmake`. You do not have to put `prefs.sh` there, and calling `foamEtcFile -list` shows all the searched locations.

However, when I tried calling `./Allwmake` when inside a subfolder, for some reason, it didn't find the `prefs.sh` file and reverted to OpenFOAM's default locations for those tools. But there was also some strange behavior involving the `prefs.sh` file being removed from `etc/` at some point, which may have caused the issue.

Eventually, I just hard-coded some of the paths inside `etc/config.sh/*` directly to push through and complete the build. I also had to add `export FFTW_DIR=/opt/fftw` to the `etc/config.sh/FFTW` folder.

Ignored Third-Party Tools

- ADIOS2
- CCMIO
- HDF5
- MGridGen

Stale ParaView Libraries

I built the current version of ParaView after trying `v5.12.1`, the version used in the tarball associated with OpenFOAM `v2606` on OpenFOAM.com's website. Note that brittle dependencies exist between VTK and QT 5 in the only ParaView-aware OpenFOAM component, a module named `PVFoamReader`. `PV-FoamReader` is also the only tool that requires HDF5 support. There is also an associated visualization

component, an in-process off-screen renderer, that uses VTK libraries as well. It may have built on Haswell without issues.

Due to the issues with those incompatible ParaView libraries, rename two `Allwmake` files to `xxxAllwmake`, in the following `openfoam` locations:

- `src/plugins/bindings/vtk-hdf`
- `src/modules/visualization`.

Copy This Repository's OpenFOAM/etc Contents into Target Folder

From this repository, copy the contents of `OpenFOAM/etc` into `/opt/openfoam/etc/` and overwrite existing files.

Source `openfoam/etc/bashrc`

```
cd /opt/openfoam

# sources prefs.sh, but later bashrc overwrites some vars
source /opt/openfoam/etc/bashrc

# source prefs again, overwriting the overwrites
source /opt/openfoam/etc/prefs.sh
```

Run Allwmake

```
# Execute both Allwmake and Allwmake-modules
./Allwmake -j

# Plugins
./Allwmake-plugins -j
```

Post-Install Environment Clean-Up and Consolidation

Once the installation is complete, I consolidated my environment and generated folders, and locked down the installation by granting ownership to root.

```
# move everything that Allwmake built into ...
# one lib folder
mv $FOAM_USER_LIBBIN/* $FOAM_LIBBIN

# and one bin folder
mv $FOAM_USER_APPBIN/* $FOAM_APPBIN

# remove dummy libs
rm -rf $FOAM_LIBBIN/dummy

# don't use a separate folder for the omp libs
mv $FOAM_LIBBIN/sys-openmpi/* $FOAM_LIBBIN

# clean up the now empty folder
rm -rf $FOAM_LIBBIN/sys-openmpi

# move these tools into the bin folder
mv $FOAM_LIBBIN/../../tools/linux64Gcc/* $FOAM_APPBIN/
```

```
# clean up the now empty folder
rm -rf $FOAM_LIBBIN/../../tools

# just move all the lib files into a folder named lib
mv $FOAM_LIBBIN /opt/openfoam/lib

# just move all the bin files into the existing bin folder
mv $FOAM_APPBIN/* /opt/openfoam/bin

# remove the now empty legacy paths
rm -rf /opt/openfoam/platforms

exit
```

Now, source a new version of `.bashrc` with the following contents:

```
# OpenFOAM environment variables
export CUDA_HOME=/usr/local/cuda
export WM_PROJECT=openfoam
export WM_PROJECT_DIR=/opt/$WM_PROJECT
export FOAM_APPBIN=$WM_PROJECT_DIR/bin
export FOAM_LIBBIN=$WM_PROJECT_DIR/lib

# Just setting these to main application folders for now
export FOAM_SITE_APPBIN=$FOAM_APPBIN
export FOAM_SITE_LIBBIN=$FOAM_LIBBIN

# Set to user's custom projects folder
export WM_PROJECT_USER_DIR=/home/user/My-OpenFOAM-Stuff
export FOAM_USER_APPBIN=$WM_PROJECT_USER_DIR/bin
export FOAM_USER_LIBBIN=$WM_PROJECT_USER_DIR/lib
export FOAM_RUN=$WM_PROJECT_USER_DIR/run
export WM_THIRD_PARTY_DIR=none

export PATH=$FOAM_USER_APPBIN:$FOAM_APPBIN:/opt/scotch/bin:/opt/karypis/bin:/
    opt/kahip/bin:/opt/fftw/bin:/opt/umpire/bin:/opt/paraview/bin:/opt/mpi/bin
    :/opt/prt/bin:/opt/pmix/bin:/opt/hwloc/bin:/opt/libevent/bin:/opt/ucx/bin
    :$CUDA_HOME/bin:$PATH
export LD_LIBRARY_PATH=$FOAM_USER_LIBBIN:$FOAM_LIBBIN:/opt/petsc/lib:/opt/amg/
    lib:/opt/zoltan/lib:/opt/scotch/lib:/opt/karypis/lib:/opt/kahip/lib:/opt/
    fftw/lib:/opt/hypre/lib:/opt/umpire/lib:/opt/paraview/lib:/opt/mpi/lib:/
    opt/prt/lib:/opt/pmix/lib:/opt/hwloc/lib:/opt/libevent/lib:/opt/ucx/lib:
    $CUDA_HOME/lib64
```

Check Paths

From a new terminal, check the paths are resolved.

```
ldd /opt/openfoam/lib/libOpenFOAM.so
ldd $FOAM_APPBIN/simpleFoam
# other tools, libs, etc...
```

Finally, lock the folder down:

```
sudo chown root:root /opt/openfoam
```

AmgX4Foam

Hacks

AmgX4Foam's `src/csrMatrix/csrMatrix.h` was missing a `#include <cuda_runtime.h>` statement.

Out of the box, AmgX4Foam's default configuration options limit only a single CUDA arch code, so I changed the behavior of the `-cu` flag so that it is no longer responsible for passing the architecture. Instead, I replaced line 12 in the `wmake/cuda` file: `cuARCH := -m64 -arch=sm_$(NVARCH)` with `cuARCH := -m64 -gencode arch=compute_61,code=sm_61`. I still had to enable CUDA by including the flag though: `./Allwmake -cu 1`.

Lines 17 in `src/Make/options` and 12 in `wmake/c++` were also removed to complete the build.

I also had to add 3 lines to the top of `src/Make/options`:

```
LIB_SRC = $(FOAM_SRC)
AMGX_INC = /opt/amgx/include
AMGX_LIB = /opt/amgx/lib
```

Finally, I had to add these two lines to `EXE_INC` and `LIB_LIBS` accordingly:

```
EXE_INC = \
    ...
    -I/usr/local/cuda/include \
    -I/opt/mpi/include \
    ...

LIB_LIBS = \
    ...
    -L/usr/local/cuda/lib64 -lcudart \
    ...
```

By default, this installs to the `FOAM_USER_LIBBIN` folder, whether or not that folder exists. `FOAM_USER_LIBBIN` is one of the non-standard directories using OpenFOAM's variable-based naming convention: `~/OpenFOAM/<user name>-<version>/platforms/<arch><compiler><precision><index size><third party folder>/lib`.

```
./Allwmake -cu 1
```

Final ~/.bashrc Settings

```
export CUDA_HOME=/usr/local/cuda
export PATH=/opt/scotch/bin:/opt/karypis/bin:/opt/fftw/bin:/opt/umpire/bin:/opt/paraview/bin:/opt/mpi/bin:/opt/prrte/bin:/opt/pmix/bin:/opt/hwloc/bin:/opt/libevent/bin:/opt/ucx/bin:$CUDA_HOME/bin:$PATH
export LD_LIBRARY_PATH=/opt/petsc/lib:/opt/zoltan/lib:/opt/scotch/lib:/opt/karypis/lib:/opt/amgx/lib:/opt/kahip/lib:/opt/fftw/lib:/opt/hypre/lib:/opt/umpire/lib:/opt/paraview/lib:/opt/mpi/lib:/opt/prrte/lib:/opt/pmix/lib:/opt/hwloc/lib:/opt/libevent/lib:/opt/ucx/lib:$CUDA_HOME/lib64

source /media/skooby/data/repos/OpenFOAM_com/OpenFOAM/etc/bashrc
```