

# 6.009

# Fundamentals of Programming

## Lecture 5: Custom Types

Adam Hartz  
hz@mit.edu

## 6.009: Goals

---

Our goals involve helping you develop as a programmer, in multiple aspects:

- **Programming:** Analyzing problems, developing plans
- **Coding:** Translating plans into Python
- **Debugging:** Developing test cases, verifying correctness, finding and fixing errors

So we will spend time discussing (**and practicing!**):

- High-level design strategies
- Ways to manage complexity
- Details and “goodies” of Python
- A mental model of Python's operation
- Testing and debugging strategies



# The Power of Abstraction

---

Thinking about complicated systems is *complicated*.

# The Power of Abstraction

---

Thinking about complicated systems is *complicated*.  
Thinking about simpler systems is often simpler.

# The Power of Abstraction

---

Thinking about complicated systems is *complicated*.  
Thinking about simpler systems is often simpler.

Framework for thinking about complicated systems:

- **Primitives**
- Means of **Combination**
- Means of **Abstraction**
- Recognizing meaningful **Patterns**

# The Power of Abstraction

---

Thinking about complicated systems is *complicated*.  
Thinking about simpler systems is often simpler.

Framework for thinking about complicated systems:

- **Primitives**
- Means of **Combination**
- Means of **Abstraction**
- Recognizing meaningful **Patterns**

Example:

- Primitives: `+`, `*`, `==`, `!=`, ...
- Combination: `if`, `while`, `f(g(x))`, ...
- Abstraction: `def`

# Custom Types *très classy!*

---

Python also provides a means of creating custom *types*: the `class` keyword.

Today:

- Extending our notional machine to include classes
- What is `self`?
- Examples of creating new types and integrating them into Python

# Example: 2-D Vectors

---

```
class Vec2D:  
    pass
```



## Example: 2-D Vectors

---

```
class Vec2D:  
    pass  
  
v = Vec2D()
```

## Example: 2-D Vectors

---

```
class Vec2D:  
    pass
```

```
v = Vec2D()
```

```
v.x = 3
```

```
v.y = 4
```

## Example: 2-D Vectors

---

```
class Vec2D:
    pass

v = Vec2D()

v.x = 3
v.y = 4

def mag(vec):
    return (vec.x**2 + vec.y**2) ** 0.5
```

## Example: 2-D Vectors

---

```
class Vec2D:
    pass

v = Vec2D()

v.x = 3
v.y = 4

def mag(vec):
    return (vec.x**2 + vec.y**2) ** 0.5

print(mag(v))
```

## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def mag(vec):
        return (vec.x**2 + vec.y**2) ** 0.5
```

## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def mag(vec):
        return (vec.x**2 + vec.y**2) ** 0.5

v = Vec2D()
v.x = 3
v.y = 4
print(v.x)
print(v.ndims)
```

## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def mag(vec):
        return (vec.x**2 + vec.y**2) ** 0.5

v = Vec2D()
v.x = 3
v.y = 4
print(v.x)
print(v.ndims)

print(Vec2D.mag(v))
```

## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def mag(vec):
        return (vec.x**2 + vec.y**2) ** 0.5

v = Vec2D()
v.x = 3
v.y = 4
print(v.x)
print(v.ndims)

print(Vec2D.mag(v))

print(v.mag())
```



## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def mag(self):
        return (self.x**2 + self.y**2) ** 0.5
```

## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def mag(self):
        return (self.x**2 + self.y**2) ** 0.5

v = Vec2D(3, 4)
```

## Example: 2-D Vectors

---

```
class Vec2D:
    ndims = 2

    def __init__(self, x, y):
        self.x = x
        self.y = y

    def mag(self):
        return (self.x**2 + self.y**2) ** 0.5

v = Vec2D(3, 4)

print(v.mag())
```

# Integrating More Closely With Python

---

Python offers ways to integrate things more tightly into the language: “magic” methods or “dunder” methods. For example:

- `print(x)` is translated implicitly to `print(x.__str__())`
- `abs(x)` is translated implicitly to `x.__abs__()`
- `x + y` is translated implicitly to `x.__add__(y)`
- `x - y` is translated implicitly to `x.__sub__(y)`
- `x[y]` is translated implicitly to `x.__getitem__(y)`
- `x[y] = z` is translated implicitly to `x.__setitem__(y, z)`

For a full list, see:

<https://docs.python.org/3/reference/datamodel.html>, Section 3.3

Let's add a couple of these to `Vec2D` and see the effects.

# The Rest of Today: More Examples

---

We'll see how many we have time for...

- Linked List
- Polynomial
- Infinite List
- Memoized Function