Certificate of Analysis: SR26-04323.001

Date: 17-Jul-2026

CHARM INDUSTRIAL
440 N BARRANCA AVE # 1637
COVINA
CA
UNITED STATES
91723

The results shown in this test report specifically refer to the sample(s) tested as received unless otherwise stated. All tests have been performed using the latest revision of the methods indicated, unless specifically marked otherwise on the report. Precision parameters apply in the determination of the above results. Users of analytical results, when establishing conformance with commercial or regulatory requirements should note the full provisions of ASTM D3244, IP 367 and ISO 4259 in that context, the default confidence level of petroleum testing having been set at the 95% confidence level. Your attention is specifically drawn to Sections 7.3.6., 7.3.7 and 7.3.8 of ASTM D3244. With respect to the UOP methods listed in the report below the user is referred to the method and the statement within it specifying that the precision statements were determined using UOP Method 999. This Test Report is issued under the Company's General Conditions of Service (copy available upon request or on the company website at https://www.sgs.com/en/terms-and-conditions). Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. This report shall not be reproduced except in full, without the written approval of the laboratory.

The sample(s) to which the findings recorded herein (the "Findings") relate was(were) drawn and / or provided by the Client or by a third party acting at the Client's direction. The Findings constitute no warranty of the sample's representativeness of any goods and strictly relate to the sample(s). The Company accepts no liability with regard to the origin or source from which the sample(s) is/are said to be extracted.

CLIENT ORDER NUMBER :		SGS ORDER NO.:	5470884
CLIENT ID :	6-2026-W2	VESSEL :	-
LOCATION :	FORT LUPTON, CO	PRODUCT DESCRIPTION :	Oil - QOWV
SAMPLE SOURCE :	Submitted Sample		
SAMPLE TYPE :	As Submitted	SAMPLED BY :	Client
SAMPLED :	--	RECEIVED	17-Jul-2026 10:25
ANALYSED :	17-Jul-2026 11:45 - 17-Jul-2026 13:58	COMPLETED :	17-Jul-2026 13:58

PROPERTY	METHOD	RESULT	UNITS	MIN	MAX
Kinematic Viscosity at 40 °C (104 °F)	ASTM D445	1.005	cSt	--	--
Titration Solvent Volume	ASTM D664 (Method A)	60 mL	---	--	--
Acid Number (Inflection end-point)	ASTM D664 (Method A)	33	mg KOH/g	--	--
Density at 15°C	ASTM D4052	1.048	g/cm³	--	--

**** End of Analytical Results ****

AUTHORISED SIGNATORY

Jaszmine Eugene
Chemist

SGS North America Inc.

Oil, Gas & Chemicals Services 151 James Drive West, St. Rose, LA, 70087, U.S.A. Tel: +1-(504)-469-6401 Fax: +1-(504)-463-3300

Member of the SGS Group (Société Générale de Surveillance)