



Quick Start Guide

Get the Food Ordering Platform running in 5 minutes!

Option 1: Docker Compose (Easiest)

Prerequisites

- Docker and Docker Compose installed

Steps

1. Clone and navigate to project

```
bash
cd food-ordering-platform
```

2. Start all services

```
bash
docker-compose up -d
```

3. Wait for services to be healthy (30-60 seconds)

```
bash
docker-compose ps
```

4. Access the application

- Frontend: <http://localhost:3000>
- Backend API: <http://localhost:8080/api>
- Database: localhost:5432

5. Login with demo account

- Email:
- Password:

Stop services

```
bash
```

```
docker-compose down
```

Option 2: Manual Setup (More Control)

Prerequisites

- Java 17+
- Node.js 18+
- PostgreSQL 15+
- Maven 3.8+

Step 1: Setup Database (2 minutes)

```
bash
```

```
# Start PostgreSQL
```

```
# On Mac: brew services start postgresql
```

```
# On Ubuntu: sudo service postgresql start
```

```
# Create database
```

```
psql -U postgres
```

```
sql
```

```
CREATE DATABASE foodordering;
```

```
CREATE USER fooduser WITH PASSWORD 'foodpass123';
```

```
GRANT ALL PRIVILEGES ON DATABASE foodordering TO fooduser;
```

```
\c foodordering
```

```
GRANT ALL ON SCHEMA public TO fooduser;
```

```
\q
```

Step 2: Start Backend (2 minutes)

```
bash
```

```
# Terminal 1
```

```
cd food-ordering-backend
```

```
# Run application (will auto-create tables and seed data)
```

```
mvn spring-boot:run
```

Wait for:

Step 3: Start Frontend (1 minute)

```
bash

# Terminal 2
cd food-ordering-frontend

# Install dependencies (first time only)
npm install

# Start dev server
npm run dev
```

Wait for:

Step 4: Access Application

Open browser to: <http://localhost:3000>

First Steps in the Application

1. Browse Restaurants

- Home page shows 3 sample restaurants
- Click on any restaurant to view menu

2. Add Items to Cart

- Browse menu items
- Click + button to add items
- View cart in top-right corner

3. Place an Order

- Click cart icon
- Review items
- Click "Proceed to Checkout"
- Login with demo credentials:
 - Email:
 - Password:
- Enter delivery address
- Click "Place Order"

4. View Your Orders

- Click "Orders" in navigation
- See order status and details

Sample Data

The application seeds with:

- **3 Restaurants:** Pizza Paradise, Burger Bonanza, Spice Garden
- **12 Menu Items:** Various pizzas, burgers, and Indian dishes
- **4 Test Users:** Customer, Restaurant Owner, Delivery Partner, Admin

Test Accounts

Role	Email	Password
Customer	john@example.com	password123
Restaurant Owner	jane@restaurant.com	password123
Delivery Partner	bob@delivery.com	password123
Admin	admin@foodapp.com	password123

Troubleshooting

Backend won't start

Error: "Connection refused"

```
bash

# Check if PostgreSQL is running
pg_isready

# If not running, start it
# Mac: brew services start postgresql
# Ubuntu: sudo service postgresql start
```

Error: "Port 8080 already in use"

```
bash
```

```
# Find and kill process using port 8080
```

```
# Mac/Linux:
```

```
lsof -ti:8080 | xargs kill -9
```

```
# Windows:
```

```
netstat -ano | findstr :8080
```

```
taskkill /PID <PID> /F
```

Frontend can't reach backend

Check backend is running:

```
bash
```

```
curl http://localhost:8080/api/restaurants
```

Should return JSON with restaurants

Database connection issues

Verify database exists:

```
bash
```

```
psql -U fooduser -d foodordering -c "\dt"
```

Reset database if needed:

```
bash
```

```
# Drop and recreate
```

```
psql -U postgres -c "DROP DATABASE foodordering;"
```

```
psql -U postgres -c "CREATE DATABASE foodordering;"
```

```
psql -U postgres -c "GRANT ALL PRIVILEGES ON DATABASE foodordering TO fooduser;"
```

Clear everything and start fresh

```
bash
```

Stop all services

`docker-compose down -v` *# If using Docker*

Or manually:

1. Stop backend (Ctrl+C)

2. Stop frontend (Ctrl+C)

3. Drop database

`psql -U postgres -c "DROP DATABASE foodordering;"`

`psql -U postgres -c "CREATE DATABASE foodordering;"`

Restart from Step 2 above

Development Tips

Hot Reload

- **Frontend:** Changes auto-reload (Vite HMR)
- **Backend:** Restart with `mvn spring-boot:run`

View Logs

`bash`

Backend logs

`tail -f logs/spring-boot-application.log`

Frontend console

Just open browser DevTools (F12)

Docker logs

`docker-compose logs -f backend`

`docker-compose logs -f frontend`

Database GUI

Use any PostgreSQL client:

- **pgAdmin:** <https://www.pgadmin.org/>
- **DBeaver:** <https://dbeaver.io/>
- **TablePlus:** <https://tableplus.com/>

Connection details:

- Host: localhost
 - Port: 5432
 - Database: foodordering
 - Username: fooduser
 - Password: foodpass123
-

Next Steps

1.  Application is running
 2.  Read full [README.md](#) for detailed documentation
 3.  Review architecture in [Spec document](Spec-1-online Food Ordering App_update7_Final.pdf)
 4.  Start building Phase 2 features!
-

Still Having Issues?

1. Check that all prerequisites are installed and correct versions
 2. Ensure no other applications are using ports 3000, 8080, or 5432
 3. Try the Docker Compose option if manual setup fails
 4. Create an issue with full error logs
-

Congratulations! Your food ordering platform is now running! 🎉