

Machine Learning(ML): Assignment 10 (KNN)

Charvi Dave J015

Importing the libraries

```
In [1]: import numpy as np
import pandas as pd
from scipy.stats import mode
from sklearn.metrics import accuracy_score
from sklearn.datasets import load_iris
from numpy.random import randint

In [2]: iris = load_iris()

In [3]: X = iris.data
Y = iris.target
```

Splitting Train-Test dataset

```
In [4]: from sklearn.model_selection import train_test_split

X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size=0.2, random_state=10)
print(X_train.shape, X_test.shape, Y_train.shape, Y_test.shape)

(120, 4) (30, 4) (120,) (30,)
```

Creating Function

```
In [5]: #Euclidean Distance
def eucledian(p1,p2):
    dist = np.sqrt(np.sum((p1-p2)**2))
    return dist

#Function to calculate KNN
def knn_predict(x_train, y , x_input, k):
    op_labels = []

    #Loop through the Datapoints to be classified
    for item in x_input:
        #Array to store distances
        point_dist = [eucledian(np.array(x_train[j,:]) , item) for j in range(len(x_train))]
        point_dist = np.array(point_dist)

        #Sorting the array while preserving the index
        #Keeping the first K datapoints in variable 'dist'
        dist = np.argsort(point_dist)[:k]

        #Labels of the K datapoints from above
        labels = y[dist]

        #Majority voting
        lab = mode(labels)[0]
        op_labels.append(lab)

    return op_labels

In [6]: #Applying our function
Y_pred = knn_predict(X_train, Y_train, X_test , 5)
```

sklearn

```
In [7]: from sklearn.neighbors import KNeighborsClassifier

model = KNeighborsClassifier(n_neighbors=5)

In [8]: model.fit(X_train, Y_train)

Out[8]: KNeighborsClassifier(algorithm='auto', leaf_size=30, metric='minkowski',
metric_params=None, n_jobs=None, n_neighbors=5, p=2,
weights='uniform')

In [9]: Y_pred_sk = model.predict(X_test)
```

Comparison

```
In [10]: print(f'Accuracy using self-made function : {accuracy_score(Y_test, Y_pred)}')
print(f'Accuracy using sklearn : {accuracy_score(Y_test, Y_pred_sk)}')

Accuracy using self-made function : 0.9666666666666667
Accuracy using sklearn : 0.9666666666666667

In [10]:
```