

v1.0 OpenAPI 3.0.4

Nordiska.FrontendApi

[Download OpenAPI Document](#)

Authentication Optional

Auth Type ▾

No authentication selected

Client Libraries

>_ Shell

📦 Ruby

📦 Node.js

📦 PHP

📦 Python

📦 More

C# HttpClient

Auth

Operations

POST /api/auth/bankid/initiate**POST** /api/auth/bankid/collect**POST** /api/auth/register**GET** /api/auth/me**POST** /api/auth/logout[/api/auth/bankid/initiate](#)

🔒 Auth Optional

Body · [BankIdInitiateRequest](#)

application/json ▾

personalNum string | null

Responses

> 200 OK

POST /api/auth/bankid/initiate

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/api/auth/bankid/initiate");
4 request.Content = new StringContent(
5     """
6     {
7         "personalNum": null
8     }
9     """,
10    System.Text.Encoding.UTF8, "application/json");
11
12 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

/api/auth/bankid/collect

Auth Optional

Body · [BankIdCollectRequest](#)

application/json ▾

orderRef string | null

Responses

> 200 OK

POST /api/auth/bankid/collect

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/api/auth/bankid/collect");
4 request.Content = new StringContent(
5     """
6     {
7         "orderRef": null
8     }
9     """,
10    System.Text.Encoding.UTF8, "application/json");
11
12 using var response = await client.SendAsync(request);
```

▶ Test Request

200
No Body
OK

/api/auth/register

Auth Optional

Body · RegisterCustomerRequestDto

application/json

email string | null

name string | null

personalNum string | null

phoneNumber string | null

Responses

> 200 OK

POST /api/auth/register

C# HttpClient

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/api/auth/register");
4 request.Content = new StringContent(
5     ""
6 {
7     "name": null,
8     "email": null,
9     "personalNum": null,
10    "phoneNumber": null
11 }
12 "",
13 System.Text.Encoding.UTF8, "application/json");
14
15 using var response = await client.SendAsync(request);
```

Test Request

200
No Body
OK

Returns the currently authenticated user's profile information extracted from the JWT.

Responses

> 200 OK

GET /api/auth/me

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/api/auth/me");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

Logs out the user by clearing the HTTP-only authentication cookie.

Responses

> 200 OK

POST /api/auth/logout

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/api/auth/logout");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

BankIdUiAuth

Operations

GET /ActiveLogin/BankId/Auth

/ActiveLogin/BankId/Auth

Auth Optional

Query Parameters

returnUrl string

Responses

> 200 OK

GET /ActiveLogin/BankId/Auth

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/ActiveLogin/BankId/Auth");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

BankIdUiAuthApi

- Operations
- POST /ActiveLogin/BankId/Auth/Api/Initialize
 - POST /ActiveLogin/BankId/Auth/Api/Status
 - POST /ActiveLogin/BankId/Auth/Api/QrCode
 - POST /ActiveLogin/BankId/Auth/Api/Cancel

/ActiveLogin/BankId/Auth/Api/Initialize

Auth Optional

Body · [BankIdUiApiInitializeRequest](#)

application/json ▾

`returnUrl` string · min length: 1 **required**

Responses

> 200 OK

POST /ActiveLogin/BankId/Auth/Api/Initialize

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/ActiveLogin/BankId/Auth/
4 request.Content = new StringContent(
5     """
6 {
7     "returnUrl": ""
8 }
9 """,
10 System.Text.Encoding.UTF8, "application/json");
11
12 using var response = await client.SendAsync(request);
```

▶ Test Request

200

Show Schema ▮

```
{
  "isAutoLaunch": true,
  "deviceMightRequireUserInteractionToLaunchBankIdApp": true,
  "checkStatus": true,
  "orderRef": null,
  "redirectUri": null,
  "qrStartState": null,
  "qrCodeAsBase64": null
}
```

OK

[/ActiveLogin/BankId/Auth/Api/Status](#)

Auth Optional

Body · [BankIdUiApiStatusRequest](#)

application/json ▾

orderRef string · min length: 1 **required**

returnUrl string · min length: 1 **required**

autoStartAttempts integer · int32
Signed 32-bit integers (commonly used integer type).

Responses

> 200 OK

POST /ActiveLogin/BankId/Auth/Api/Status

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/ActiveLogin/BankId/Auth/
4 request.Content = new StringContent(
5     ""
6     {
7         "orderRef": "",
8         "returnUrl": "",
9         "autoStartAttempts": 1
10    }
11    "",
12    System.Text.Encoding.UTF8, "application/json");
13
14 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

/ActiveLogin/BankId/Auth/Api/QrCode

Auth Optional

Body · [BankIdUiApiQrCodeRequest](#)

application/json ▾

qrStartState string · min length: 1 **required**

Responses

> 200 OK

POST /ActiveLogin/BankId/Auth/Api/QrCode

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/ActiveLogin/BankId/Auth/
4 request.Content = new StringContent(
5     ""
6     {
7         "qrStartState": ""
8     }
9     "",
10    System.Text.Encoding.UTF8, "application/json");
11
12 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

/ActiveLogin/BankId/Auth/Api/Cancel

Auth Optional

Body · [BankIdUiApiCancelRequest](#)

application/json ▾

orderRef string · min length: 1 **required**

Responses

> 200 OK

POST /ActiveLogin/BankId/Auth/Api/Cancel

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/ActiveLogin/BankId/Auth/
4 request.Content = new StringContent(
5     ""
6     {
7         "orderRef": ""
8     }
9     "",
10    System.Text.Encoding.UTF8, "application/json");
11
12 using var response = await client.SendAsync(request);
```

▶ Test Request

200


No Body

OK

Faq

Operations

- POST /api/faqs
- DELETE /api/faqs/{id}
- GET /api/faqs/{id}



Nordiska.FrontendApi


Operations

[GET](#) /health/database

SavingsAccounts

Operations

`GET /api/savingsaccounts`
`POST /api/savingsaccounts`
`GET /api/savingsaccounts/{id}`



Retrieves a savings account by id.

 Auth Optional

Path Parameters

id integer · int64 **required**

Savings account id.

Responses

> **200** OK

GET /api/savingsaccounts/{id}

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/api/savingsaccounts/1");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

Show Schema 

```
{
  "id": 1,
  "customerId": 1,
  "accountNumber": null,
  "accountType": null,
  "balance": 1,
  "interestRate": 1,
  "createdAt": "2026-09-14T13:37:04.071Z"
}
```

OK

Test

Operations

[GET](#) /api/test/secure

Returns information extracted from the authenticated user's JWT claims.

 Auth Optional

Responses

> 200 OK

[GET](#) /api/test/secure

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/api/test/secure");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

No Body

OK

Transactions

Operations

```
GET /api/transactions
POST /api/transactions
GET /api/transactions/{id}
GET /api/transactions/balance/{accountId}
```

Queries transactions, optionally filtered by account id.

Auth Optional

Query Parameters

accountId integer · int64

Optional account id to filter by.

Responses

> 200 OK

GET /api/transactions

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/api/transactions");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

Show Schema

```
[
  {
    "id": 1,
    "accountId": 1,
    "type": null,
    "amount": 1,
    "createdAt": "2026-09-14T13:37:04.071Z"
  }
]
```

OK

Executes a transaction (deposit or withdrawal) on an account.

Auth Optional

Body · [TransactionRequest](#)

application/json ▾

Transaction request payload.

accountId integer · int64

Signed 64-bit integers (long type).

amount number · double**type** string | null**Responses**> **200** OK**POST** /api/transactions

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Post, "/api/transactions");
4 request.Content = new StringContent(
5     """
6     {
7         "accountId": 1,
8         "type": null,
9         "amount": 1
10    }
11    """,
12    System.Text.Encoding.UTF8, "application/json");
13
14 using var response = await client.SendAsync(request);
```

▶ Test Request

200

Show Schema ▮

```
{
  "id": 1,
  "accountId": 1,
  "type": null,
  "amount": 1,
  "createdAt": "2026-09-14T13:37:04.071Z"
}
```

OK

Retrieves a transaction by id.

Auth Optional

Path Parameters**id** integer · int64 **required**

Transaction id.

Responses> **200** OK**GET** /api/transactions/{id}

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/api/transactions/1");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

Show Schema

```
{
  "id": 1,
  "accountId": 1,
  "type": null,
  "amount": 1,
  "createdAt": "2026-09-14T13:37:04.071Z"
}
```

OK

Gets the current verified balance for an account computed from all ledger entries.

Auth Optional

Path Parameters

accountId integer · int64 **required**

Account id.

Responses

> 200 OK

GET /api/transactions/balance/{accountId}

C# HttpClient ▾

```
1 using var client = new HttpClient();
2
3 var request = new HttpRequestMessage(HttpMethod.Get, "/api/transactions/balance/1");
4
5 using var response = await client.SendAsync(request);
```

▶ Test Request

200

Show Schema

1

OK

Models

▾ BankIdCollectRequest

orderRef string | null

▾ BankIdInitiateRequest

personalNum string | null

▼ BankIdUiApiCancelRequest

orderRef string · min length: 1 **required**

▼ BankIdUiApiInitializeRequest

returnUrl string · min length: 1 **required**

▼ BankIdUiApiInitializeResponse

checkStatus boolean **read-only**

deviceMightRequireUserInteractionToLaunchBankIdApp boolean **read-only**

isAutoLaunch boolean **read-only**

orderRef string | null **read-only**

qrCodeAsBase64 string | null

qrStartState string | null

redirectUri string | null **read-only**

▼ BankIdUiApiQrCodeRequest

qrStartState string · min length: 1 **required**

▼ BankIdUiApiStatusRequest

orderRef string · min length: 1 **required**

returnUrl string · min length: 1 **required**

autoStartAttempts integer · int32

Signed 32-bit integers (commonly used integer type).

▼ CreateFaqRequest

answer string | null

category string | null

keywords string | null

question string | null

▼ FaqCreatedResponse

id integer · int32

Signed 32-bit integers (commonly used integer type).

▼ FaqEntryResponse

answer string | null**category** string | null**helpfulCount** integer · int32
Signed 32-bit integers (commonly used integer type).**id** integer · int32
Signed 32-bit integers (commonly used integer type).**keywords** string | null**question** string | null

▼ OpenSavingsAccountRequest

accountNumber string | null**accountType** string | null**customerId** integer · int64
Signed 64-bit integers (long type).**initialDeposit** number · double**interestRate** number · double

▼ ProblemDetails

detail string | null**instance** string | null**status** integer | null · int32
Signed 32-bit integers (commonly used integer type).**title** string | null**type** string | null

▼ RegisterCustomerRequestDto

email string | null**name** string | null**personalNum** string | null**phoneNumber** string | null

▼ SavingsAccountResponse

accountNumber	string null
accountType	string null
balance	number · double
createdAt	string · date-time the date-time notation as defined by RFC 3339, section 5.6, for example, 2017-07-21T17:32:28Z
customerId	integer · int64 Signed 64-bit integers (long type).
id	integer · int64 Signed 64-bit integers (long type).
interestRate	number · double

▼ TransactionRequest

accountId	integer · int64 Signed 64-bit integers (long type).
amount	number · double
type	string null

▼ TransactionResponse

accountId	integer · int64 Signed 64-bit integers (long type).
amount	number · double
createdAt	string · date-time the date-time notation as defined by RFC 3339, section 5.6, for example, 2017-07-21T17:32:28Z
id	integer · int64 Signed 64-bit integers (long type).
type	string null

▼ ValidationProblemDetails

detail	string null
errors	object null + errors
instance	string null

status	integer null · int32
Signed 32-bit integers (commonly used integer type).	
title	string null
type	string null