A Critical Academic Review and Empirical Re-Evaluation of the ARIMA-DBO-CNN-LSTM Air Quality Forecasting Model

Coursework Phase 3: Formal Technical Review Report (40 Marks) | Comparative Audit of Base vs. Enhanced Models

Student Name & ID:	K.W.G.C.D.B. Karunarathne | Student ID: **KIC-BSCCSAI-251P-036**
Module & Programme:	Machine Learning and Related Applications | BSc (Hons) Computing & AI
Awarding Institution:	National Institute of Business Management (NIBM), Kandy Innovation Centre
Target Research Study:	Duan, J., Gong, Y., Luo, J., & Zhao, Z. (2023). *Scientific Reports*, 13:12127.
Interactive Appendices:	notebooks/phase1_base_replication.ipynb & notebooks/phase2_enhanced_study.ipynb

Executive Abstract

Accurate forecasting of atmospheric pollutants and the composite Air Quality Index (AQI) represents a fundamental challenge in computational environmental science and municipal public health management. In *Scientific Reports*, Duan et al. (2023) proposed a multi-stage hybrid forecasting architecture combining an Autoregressive Integrated Moving Average (ARIMA) model, a one-dimensional Convolutional Neural Network (CNN), a Long Short-Term Memory (LSTM) network, and a nature-inspired meta-heuristic—the Dung Beetle Optimizer (DBO)—for hyperparameter selection. The authors reported exceptional predictive accuracy across four Chinese megacities (Beijing, Chengdu, Guangzhou, and Wuhan), citing coefficients of determination (R^2) between 0.962 and 0.989 and Root Mean Squared Errors (RMSE) as low as 14.94.

This technical report provides a rigorous academic critique and a comprehensive empirical audit of Duan et al.'s methodology, contrasting the Base Model Implementation (author paper replication) against our Enhanced Audited Implementation (Phase 1 conceptual deconstruction and Phase 2 empirical enhancements). Using the identical 7-year multi-station dataset (2,528 daily observations per city, 2014–2020), we reconstruct the complete pipeline, complete the missing Exploratory Data Analysis (EDA) audit from Phase 1, eliminate look-ahead data leakage through a strict 3-way chronological split, benchmark against the omitted naive persistence heuristic ($\blacksquare_t = x_{t-1}$), and test statistical significance via Diebold–Mariano tests.

[AUDIT SUMMARY] *The audited ARIMA-DBO-CNN-LSTM model achieves $R^2 = 0.388$ under leak-free validation (vs. authors' claimed 0.962). A Diebold-Mariano test confirms that the complex hybrid is statistically indistinguishable from naive persistence ($p = 0.5316$) and statistically inferior to pure ARIMA ($p = 0.0077$).*

1. Architectural Deconstruction: Base Model vs. Enhanced Framework

Figure 1 contrasts the Base Model pipeline against our Enhanced Audited Framework.




Figure 1: Architectural Workflow Comparison: Base Model (Duan et al., 2023) vs. Enhanced Audited Framework (Phase 2 & 3).

Table 1: Methodological and Architectural Comparison (Base Model vs. Enhanced Framework)

Dimension	Base Model (Duan et al. 2023)	Enhanced Audited Framework	Academic Rationale
Code Implementation	notebooks/phase1_base_replication.ipynb & main.py	notebooks/phase2_enhanced_study.ipynb & run_phase2_experiments.py	Full separation of replication and audit.
Data Partitioning	80% Train / 20% Test single chronological split	3-Way Chronological Split: 70% Train / 15% Val / 15% Test	Quarantined validation partition for DBO.
Feature Scaling	Global Min-Max across all 7 years (2014-2020)	Strict Train-Only Normalization ([1, T_train])	Eliminates look-ahead leakage of future bounds.
ARIMA Modeling	Fixed orders: Beijing (3,1,1), etc.	Grid-search BIC verification + Seasonal SARIMA	Audits linearity and annual cycle (s=365).
DBO Fitness	Swarm evaluated directly on 20% test data	Swarm evaluated strictly on 15% validation data	Prevents test memorization.
Benchmark Suite	Linear SVM, Random Forest, Standalone LSTM	+ Naive Persistence (■_t = x_{t-1}) + GBDT (0.42s)	Tests whether model beats atmospheric inertia.
Evaluation Metrics	RMSE, MAE, R^2 only	+ Scale-Free MASE & MAPE + Diebold–Mariano Tests	Assesses statistical significance ($p < 0.05$).
Risk Stratification	Aggregate test set average only	Stratified Peak Analysis (AQI ≥ 100, 150, 200)	Audits emergency warning capability.

2. Dataset Synthesis & Exploratory Data Analysis (EDA) Audit

Table 2 provides the completed EDA audit across 4 cities, completing the Phase 1 deconstruction.

Table 2: Comprehensive Exploratory Data Analysis (EDA) & Stationarity Audit (2014–2020)

City	Count	Mean	Median	Variance	StdDev	Skewness	Kurtosis	Shapiro p	ADF Stat	ADF p	Missing
Beijing	2,528	82.46	65.18	3,488.46	59.06	+2.098	5.978	6.75e-43	-5.383	3.69e-06	7 (0.28%)
Chengdu	2,528	73.16	64.44	1,434.74	37.88	+1.517	3.196	8.42e-36	-4.687	8.90e-05	7 (0.28%)
Guangzhou	2,528	52.71	48.44	544.15	23.33	+1.481	4.272	9.31e-32	-5.849	3.63e-07	7 (0.28%)
Wuhan	2,528	75.41	66.75	1,632.13	40.40	+1.824	5.837	1.78e-37	-4.958	2.68e-05	7 (0.28%)




Figure 2: Daily Air Quality Index (AQI) Trends (2014–2020) across Beijing, Chengdu, Guangzhou, and Wuhan (Paper Figure 5 Replication).

3. Technical Summary of the Reviewed Base Model

Duan et al. (2023) formulate an additive decomposition: $x_t = L_t + N_t$. The linear component is modeled via Box-Jenkins ARIMA(p, d, q) with order determination via the Bayesian Information Criterion (BIC), yielding Beijing (3,1,1), Chengdu (3,1,1), Guangzhou (2,1,2), and Wuhan (2,1,2). Non-linear residuals $e_t = x_t - L■_t$ are modeled by a 1D-CNN + multi-layer LSTM architecture optimized via the Dung Beetle Optimizer (DBO) across 4 phenotypes: ball-rolling (N_1=6), breeding (N_2=6), foraging (N_3=7), and stealing (N_4=11). Predictions are recombined additively: $x■_t = L■_t + \hat{e}_t$.

4. Methodological Critique & Forensic Audit

4.1 The R^2 Inflation Illusion: High variance in the denominator ($\sigma^2 = 3{,}488.46$) artificially guarantees high R^2 for models tracking seasonal trends. Under honest leak-free evaluation, the audited hybrid achieves $R^2 = 0.388$.
4.2 Omission of Naive Persistence: Naive persistence ($\blacksquare_t = x_{t-1}$) achieves RMSE = 37.47, MAE = 23.36, $R^2 = 0.336$, and MASE = 0.608. The 110,000-parameter hybrid provides no statistically significant gain ($p = 0.5316$).
4.3 Data Leakage: Global normalization across 7 years leaked test bounds into training, while DBO was evaluated on evaluation data.
4.4 Regression Imbalance: On hazardous days (AQI ≥ 200), hybrid RMSE explodes to 145.67 (MAE = 138.58), failing the public health early-warning mission.

5. Comparative Empirical Analysis (Base vs. Enhanced Models)

Table 3: Master Model Benchmarking on Beijing Daily AQI Test Horizon (N = 370)

Model Architecture	Category	Params	Train Time	RMSE	MAE	R^2	MAPE (%)	MASE
Author Claimed Hybrid (Paper)	Base Paper Model	> 110k	Unreported	**14.940**	**10.839**	**0.962**	Unreported	Unreported
Audited Hybrid (Honest Split)	Enhanced Audit	112,450	1,480.2 s	**35.980**	**22.899**	**0.388**	35.57%	0.596
Pure ARIMA(3, 1, 1)	Statistical	5	0.24 s	34.633	22.935	0.433	41.80%	0.597
Naive Persistence (■_t = x_{t-1})	Zero-Cost Heuristic	0	0.00 s	37.473	23.361	0.336	41.83%	0.608
Gradient Boosted Trees (Alt. 1)	Proposed Alt.	100 trees	0.42 s	36.420	25.490	0.373	54.63%	0.664
Random Forest Regressor	Tree Baseline	100 trees	1.18 s	37.265	25.447	0.343	51.46%	0.663
Linear Support Vector Machine	Convex Baseline	11	0.08 s	38.939	31.110	0.283	72.63%	0.810

Table 4: Diebold–Mariano Statistical Hypothesis Testing (Reference: Audited Hybrid Model)

Competing Model (M_2)	Loss Differential	DM Statistic	p-value	Significance ($\alpha = 0.05$)	Academic Conclusion
Naive Persistence	Squared Error (e_{hyb}^2 - e_{pers}^2)	+0.6255	0.5316	Not Significant	Hybrid provides no statistically significant gain.
Pure ARIMA(3, 1, 1)	Squared Error (e_{hyb}^2 - e_{arima}^2)	-2.6668	**0.0077**	**Significant**	Pure ARIMA is statistically superior ($p < 0.01$).
Gradient Boosted Trees	Squared Error (e_{hyb}^2 - e_{gbdt}^2)	+0.3788	0.7048	Not Significant	Hybrid offers no advantage over simple GBDT.

Table 5: Operational Safety & Public Health Performance Across Severity Tiers

Severity Tier	AQI Range	Samples (N)	Share (%)	Hybrid RMSE	Hybrid MAE	Persistence RMSE	ARIMA RMSE	GBDT RMSE
Good to Moderate	AQI < 100	296	80.0%	17.65	13.06	18.96	18.02	19.12
Unhealthy (Warning)	AQI ≥ 100	74	20.0%	69.87	62.24	72.84	66.86	68.45
Severe Pollution	AQI ≥ 150	29	7.8%	104.99	95.91	108.77	99.41	101.20
Hazardous (Emergency)	AQI ≥ 200	11	3.0%	**145.67**	**138.58**	149.80	136.21	139.40

Table 6: Computational Complexity, Runtime Latency, and Resource Footprint

Model Architecture	Trainable Params	Time Complexity	Training Latency	Compute Hardware	Energy Profile
ARIMA-DBO-CNN-LSTM Hybrid	112,450	O(N_swarm · I_iter · E · L)	1,480.2 s (~25 min)	GPU / Apple MPS	High (1,500 backprop passes)
Gradient Boosted Trees (GBDT)	100 shallow trees	O(M · K · N log N)	0.42 s	Standard CPU	Ultra-low (sub-second)
Random Forest Regressor	100 trees	O(M · K · N log N)	1.18 s	Standard CPU	Ultra-low
Pure ARIMA(3, 1, 1)	5 parameters	O(N · p^2)	0.24 s	Standard CPU	Negligible
Naive Persistence Heuristic	0 parameters	O(1)	0.00 s	Any processor	Zero footprint




Figure 3: Visual Forecast Overlay on Out-of-Sample Beijing Test Horizon (Actual vs. Proposed Hybrid vs. Naive Persistence vs. ARIMA vs. GBDT).




Figure 4: Diagonal Scatter Alignment and Model Flattening at Severe Pollution Peaks (AQI > 150).




Figure 5: Multi-Metric Bar Charts (RMSE, MAE, R², and scale-free MASE).

6. Proposed Technical Alternatives & Justifications

6.1 Gradient Boosted Decision Trees (LightGBM/XGBoost): Constructs an additive ensemble of trees minimizing a second-order Taylor expansion. Fits in 0.42 seconds on CPU—over 3,500x faster than DBO-CNN-LSTM—with zero vanishing gradients, monotonic invariance, and empirical parity (RMSE = 36.42, R^2 = 0.373, p = 0.7048).
6.2 Seasonal ARIMAX with Exogenous Meteorology: Ground-level air quality is governed by meteorological dispersion. Incorporating Planetary Boundary Layer Height (PBLH) and wind velocity informs the model of temperature inversions, resolving peak under-prediction with interpretable coefficients.
6.3 Dilated Temporal Convolutional Networks with Asymmetric Loss: Eliminates recurrence latency via causal dilated convolutions. An Asymmetric MSE loss (α = 0.75) penalizes peak under-prediction three times more severely, preserving extreme variance for early warnings.

7. Stress-Testing & Robustness Analysis

7.1 Sensor Jitter Noise: Gaussian jitter doubles differencing error variance in ARIMA, while GBDT maintains high stability due to threshold interval splitting.
7.2 Multi-Dimensionality & Swarm Stagnation: Expanding from univariate AQI to 16 multi-pollutant variables expands DBO search space from 7 to > 40 dimensions. The 30 beetle agents suffer severe swarm stagnation without mathematical convergence guarantees.
7.3 Distribution Shift & Structural Breaks: The COVID-19 lockdowns in January 2020 caused an abrupt structural break. Deep hybrid models persistently over-predicted post-lockdown air quality, whereas simple persistence adapted within a single lag step.

8. Conclusion & Actionable Recommendations

8.1 Synthesis of Findings: Claimed R^2 = 0.962 is an evaluation artifact; honest validation yields R^2 = 0.388. The 110,000-parameter hybrid provides no statistically significant gain over persistence (p = 0.5316) and is outperformed by pure ARIMA (p = 0.0077). On hazardous days (AQI ≥ 200), RMSE explodes to 145.67. Gradient Boosted Trees match accuracy while fitting in 0.42 seconds.
8.2 Recommendations for Atmospheric Agencies:
1. Mandate Zero-Cost Heuristic Benchmarks: Always compare against naive persistence ($\blacksquare_t = x_{t-1}$).
2. Prioritize Scale-Free Relative Metrics: Report Mean Absolute Scaled Error (MASE) rather than misleading R^2 scores.
3. Enforce Leak-Free Protocols: Preprocessing scalers must be fitted strictly on training data, and hyperparameter tuning quarantined from evaluation sets.
4. Deploy Efficient GBDT Baselines: Municipal agencies should deploy Gradient Boosted Decision Trees for fast, robust, interpretable forecasting.
5. Integrate Meteorological Physics: Operational systems must transition to physics-informed multivariate models incorporating PBLH and wind dynamics.

9. Formal Academic References

Armstrong, J. S. (Ed.). (2001). *Principles of forecasting: A handbook for researchers and practitioners*. Springer Science & Business Media.

Bai, S., Kolter, J. Z., & Koltun, V. (2018). An empirical evaluation of generic convolutional and recurrent networks for sequence modeling. *arXiv preprint arXiv:1803.01271*.

Bergstra, J., & Bengio, Y. (2012). Random search for hyper-parameter optimization. *Journal of Machine Learning Research*, 13(2), 281–305.

Box, G. E., Jenkins, G. M., Reinsel, G. C., & Ljung, G. M. (2015). *Time series analysis: Forecasting and control* (5th ed.). John Wiley & Sons.

Breiman, L. (2001). Random forests. *Machine Learning*, 45(1), 5–32. https://doi.org/10.1023/A:1010933404324

Chen, T., & Guestrin, C. (2016). XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining* (pp. 785–794).

Diebold, F. X., & Mariano, R. S. (1995). Comparing predictive accuracy. *Journal of Business & Economic Statistics*, 13(3), 253–263. https://doi.org/10.1080/07350015.1995.10524599

Duan, J., Gong, Y., Luo, J., & Zhao, Z. (2023). Air-quality prediction based on the ARIMA-CNN-LSTM combination model optimized by dung beetle optimizer. *Scientific Reports*, 13(1), Article 12127. https://doi.org/10.1038/s41598-023-36620-4

Hyndman, R. J., & Athanasopoulos, G. (2021). *Forecasting: Principles and practice* (3rd ed.). OTexts: Melbourne, Australia.

Hyndman, R. J., & Koehler, A. B. (2006). Another look at measures of forecast accuracy. *International Journal of Forecasting*, 22(4), 679–688. https://doi.org/10.1016/j.ijforecast.2006.03.001

Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., & Liu, T. Y. (2017). LightGBM: A highly efficient gradient boosting decision tree. *Advances in Neural Information Processing Systems*, 30, 3146–3154.

Kingma, D. P., & Ba, J. (2015). Adam: A method for stochastic optimization. In *International Conference on Learning Representations (ICLR)*.

Xue, J., & Shen, B. (2022). Dung beetle optimizer: A new meta-heuristic algorithm for global optimization. *The Journal of Supercomputing*, 79(7), 7305–7348. https://doi.org/10.1007/s11227-022-04959-6