

[Chathurya V R 251801045-2025-AIDS](#) ▾**C2****Started on** Thursday, 27 August 2026, 8:08 AM**State** Finished**Completed on** Thursday, 27 August 2026, 8:10 AM**Time taken** 1 min 43 secs**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int ascending(const void *a, const void *b) {
5      int x = *(const int *)a;
6      int y = *(const int *)b;
7      return x - y;
8  }
9
10 int descending(const void *a, const void *b) {
11     int x = *(const int *)a;
12     int y = *(const int *)b;
13     return y - x;
14 }
15
16 int main() {
17     int n;
18     scanf("%d", &n);
19
20     int A[n], B[n];
21
22     for (int i = 0; i < n; i++) {
23         scanf("%d", &A[i]);
24     }
25
26     for (int i = 0; i < n; i++) {
27         scanf("%d", &B[i]);
28     }
29
30     // Sort A in ascending order
31     qsort(A, n, sizeof(int), ascending);
32
33     // Sort B in descending order
34     qsort(B, n, sizeof(int), descending);
35
36     long long sum = 0;
37
38     for (int i = 0; i < n; i++) {
39         sum += (long long)A[i] * B[i];
40     }
41
42     printf("%lld\n", sum);
43
44     return 0;
45 }
46

```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)