

A project report on

ENHANCED SMART HOME AUTOMATION

Submitted in partial fulfillment for the award of the degree of

Bachelor of Technology in Electronics and Communication Engineering

by

CHATURYA VEMAVARAPU (22BEC7056)

KRISTI SIKDAR (22BEC7079)

SAKTHIPOOJA (22BEC7193)

Under the Guidance of

Dr. M KRISHNASAMY



SCHOOL OF ELECTRONICS ENGINEERING

May, 2026

ENHANCED SMART HOME AUTOMATION

Submitted in partial fulfillment for the award of the degree of

Bachelor of Technology in Electronics and Communication Engineering

by

CHATURYA VEMAVARAPU (22BEC7056)

KRISTI SIKDAR (22BEC7079)

SAKTHIPOOJA (22BEC7193)



SCHOOL OF ELECTRONICS ENGINEERING

May, 2026

DECLARATION

I hereby declare that the thesis entitled “ENHANCED SMART HOME AUTOMATION” submitted by me, for the award of the degree of Specify the name of the degree VIT is a record of bonafide work carried out by me under the supervision of Guide Name

I further declare that the work reported in this thesis has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Place: Amaravati

Date: 14th May, 2026

Signature of the Candidate

CHATURYA VEMAVARAPU

CERTIFICATE


This is to certify that the Senior Design Project titled “**ENHANCED SMART HOME AUTOMATION**” that is being submitted by **KRISTI (22BEC7079), SAKTHIPOOJA (22BEC7193), CHATURYA (22BEC7056)** is in partial fulfillment of the requirements for the award of Bachelor of Technology, is a record of Bonafide work done under my guidance. The contents of this Project work, in full or in parts, have neither been taken from any other source nor have been submitted to any other Institute or University for award of any degree or diploma and the same is certified.

Dr. M. Krishnasamy

Guide


✓
The thesis is satisfactory / ~~unsatisfactory~~


Internal Examiner


External Examiner


HEAD OF THE DEPARTMENT
B.Tech ECE

Approved by


DEAN

School of electronics engineering

ABSTRACT

One of the most significant uses of the Internet of Things (IoT) is smart home automation. By allowing users to remotely monitor and manage household appliances, smart homes enhance accessibility, convenience, security, and energy efficiency. However, the majority of home automation systems currently in use rely significantly on Wi-Fi or internet access, which restricts their use in remote areas and places with inadequate network coverage. Using LoRa and GSM communication technologies, this project offers an enhanced smart home automation system that can function independently of the internet. ESP32 and ESP8266 microcontrollers, LoRa SX1278 wireless modules, SIM800L GSM modules, relay modules, push buttons, and AC load switching circuits are all integrated into the suggested system. The transmitter unit and the receiver unit are the two main components of the architecture. The transmitter device has push buttons, LED indicators, a LoRa transmitter, an ESP32 controller, and a GSM module. Relay-controlled AC appliances and LoRa receiver modules are connected to an ESP8266/ESP32 controller, which makes up the receiver unit. Home appliances can be controlled locally with push buttons or remotely with SMS commands via GSM connectivity. LoRa communication offers dependable packet delivery, minimal power consumption, and long-range wireless transmission. Successful relay switching, consistent communication, dependable SMS functioning, and long-distance wireless performance without cloud or internet services were all proved by experimental testing. The proposed system can be used for remote automation applications, farms, rural residences, and industrial buildings. Mobile apps, cloud integration, voice assistants, sensor-based automation, current monitoring, and AI-based predictive control systems are some of the upcoming improvements.

ACKNOWLEDGEMENT

It is my pleasure to express with deep sense of gratitude to **Dr. M Krishnasamy** Associate Professor, School of Electronics Engineering (SENSE), VIT-AP, for his constant guidance, continual encouragement, understanding; more than all, he taught me patience in my endeavor. My association with him is not confined to academics only, but it is a great opportunity on my part of work with an intellectual and expert in the field of MEMS Device, Renewable Energy, Microelectronics, Piezo-Magneto-Elastic Energy Harvester.

I would like to express my gratitude to **Dr. G. Viswanathan, Sankar Viswanathan, Dr. Sekar Viswanathan, and Dr. G.V. Selvam, Dr. P. Arulmozhivarman, and Dr. Y. V. Pavan Kumar**, School of Electronics Engineering (SENSE), for providing with an environment to work in and for his inspiration during the tenure of the course.

In jubilant mood I express ingeniously my whole-hearted thanks Dr. Khairnar Vikas Vishnu, HOD - Department of Communications and Signal Processing (CSP), all teaching staff and members working as limbs of our university for their not-self-centered enthusiasm coupled with timely encouragements showered on me with zeal, which prompted the acquirement of the requisite knowledge to finalize my course study successfully. I would like to thank my parents for their support.

It is indeed a pleasure to thank my friends who persuaded and encouraged me to take up and complete this task. At last but not least, I express my gratitude and appreciation to all those who have helped me directly or indirectly toward the successful completion of this project.

Place: Amaravati

Date: 14th May, 2026

CHATURYA VEMAVARAPU

CONTENTS

ABSTRACT	i
ACKNOWLEDGEMENT	ii
LIST OF FIGURES	vi
LIST OF TABLES	v
LIST OF ACRONYMS	vi

CHAPTER 1 INTRODUCTION

1.1 Background	1
1.2 Existing Smart Home Automation Systems	3
1.3 Limitations of Existing Systems	5
1.4 Problem Statement	7
1.5 Objectives	8
1.6 Proposed Solution	9
1.7 Scope of the Project	11
1.8 Applications	12
1.9 Advantages of Proposed System	13

CHAPTER 2 LITERATURE REVIEW

2.1 Introduction to Smart Home Automation	15
2.2 Internet of Things in Automation	16
2.3 LoRa Communication Technology	18
2.4 GSM Communication Systems	20
2.5 ESP32 Architecture	22
2.6 Relay-Based Automation Systems	23
2.7 Existing Research Works	24
2.8 Comparative Analysis of Existing Systems	28
2.9 Research Gap	30

CHAPTER 3 SYSTEM DESIGN AND METHODOLOGY

3.1 Introduction	31
3.2 Overall System Architecture	32
3.3 Transmitter Unit Design	35

3.4 Receiver Unit Design	38
3.5 Communication Workflow	40
3.6 GSM Communication Architecture	42
3.7 LoRa Communication Workflow	43
3.8 Relay Driver Circuit	44
3.9 Power Supply Design	45
3.10 Command Structure	46
3.11 Data Flow Diagram	47
3.12 System Algorithm	48
3.13 Advantages of Proposed Architecture	49

CHAPTER 4

HARDWARE AND SOFTWARE IMPLEMENTATION

4.1 Introduction	50
4.2 ESP32 Transmitter Section	52
4.3 ESP8266 Receiver Section	54
4.4 SIM800L GSM Module	56
4.5 SX1278 LoRa Module	58
4.6 Relay Modules	60
4.7 Push Buttons	61
4.8 Power Supply	62
4.9 Arduino IDE	63
4.10 Transmitter Program	64
4.11 Receiver Program	66
4.12 SMS Command Processing	67
4.13 Packet Transmission	68
4.14 Packet Reception	69
4.15 Serial Communication	70
4.16 SPI Communication	71
4.17 Error Handling	72
4.18 Transmitter Source Code	73
4.19 Receiver Source Code	76

CHAPTER 5

RESULTS AND DISCUSSION

5.1 Introduction	80
------------------------	----

5.2 Prototype Implementation	81
5.3 Communication Range Analysis	83
5.4 SMS Delay Analysis	85
5.5 Relay Switching Performance	87
5.6 Power Consumption Analysis	89
5.7 Reliability Testing	91
5.8 Comparative Analysis	93
5.9 Advantages of Proposed System	95
5.10 Limitations	96
5.11 Practical Applications	97
5.12 Discussion	99

CHAPTER 6

CONCLUSION AND FUTURE SCOPE

6.1 Conclusion	101
6.2 Major Achievements	103
6.3 Future Scope	104
6.4 Final Remarks	106
REFERENCES	108
APPENDICES	112

LIST OF FIGURES

Figure 3.1 Overall System Architecture	36
Figure 4.1 Receiver Unit	43
Figure 4.2 Transmitter Unit	43
Figure 4.3 GSM Module	43

LIST OF TABLES

Table 2.1 Comparison of Existing Automation Technologies	28
Table 2.9 Major Components of the System	31
Table 3.2 Relay Logic Operation	36
Table 3.3 Voltage Requirements	37
Table 3.4 Command Structure	37
Table 4.1 Features of ESP32	41
Table 4.2 Features of ESP8266	42
Table 4.3 Features of SIM800L	42
Table 4.4 Features of SX1278 LoRa Module	43
Table 4.5 Relay Specifications	44
Table 4.6 Relay Logic	44
Table 4.7 Voltage Requirements of Hardware Components	45
Table 6.1 Experimental Observations	53
Table 6.2 Reliability Results	57
Table 6.3 Comparative Analysis	58

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND

The quick development of wireless communication technologies, embedded systems, and the Internet of Things (IoT) has drastically changed how contemporary industrial and domestic settings function. One of the most significant uses of IoT is smart automation systems, which allow users to remotely monitor and manage electrical appliances through clever communication technology. The idea behind smart homes is to integrate automated control systems to increase operational flexibility, energy efficiency, convenience, and safety.

Conventional home automation systems typically rely on cloud-connected smartphone apps or internet-based communication frameworks like Bluetooth, Wi-Fi, and ZigBee. Using smartphones or online apps, these systems enable users to remotely operate lights, fans, air conditioners, security systems, and other equipment. Despite the fact that these systems offer more automation and convenience, they have a number of real-world drawbacks pertaining to communication range, network reliance, security issues, and infrastructure needs.

The development of internet-independent automation systems that can function well in remote locations has been made possible by the advancement of low-power wireless connection technologies. A viable option for long-distance, low-power wireless communication is LoRa (Long Range) communication technology. Chirp spread spectrum modulation is used by LoRa technology, which uses very little power and offers reliable communication over several kilometers. These features make LoRa an excellent choice for smart home applications, industrial automation, rural communication systems, and agricultural monitoring.

Concurrently, GSM communication technology makes it possible to operate appliances via SMS services without the need for internet access. GSM-based solutions enable remote access over common mobile networks, enabling users to operate appliances with straightforward text commands from almost anywhere. Automation systems become much more flexible and dependable when GSM communication is integrated with LoRa technology.

The goal of the proposed project, "Enhanced Smart Home Automation Using LoRa and GSM" is to create an affordable, dependable, long-range automation system that can function entirely offline. In order to provide dual communication mechanisms for appliance control, the system

incorporates relay switching circuits, SX1278 LoRa modules, SIM800L GSM modules, ESP32 and ESP8266 microcontrollers, and push-button interfaces.

1.2 EXISTING SMART HOME AUTOMATION SYSTEMS

Wi-Fi-based automation systems are among the most commonly used solutions because they provide easy smartphone integration and internet-based accessibility.

Typically, these systems are made up of microcontrollers linked to cloud servers and wireless routers. Through web interfaces or mobile applications, users can operate appliances from a distance. Wi-Fi systems require constant internet connectivity and have a restricted communication range, although offering high-speed communication and user-friendly control.

Mobile communication networks are used by GSM-based automation systems to enable remote accessibility. These systems use SMS or call-based communication to operate appliances. Even if GSM systems do away with the need for the internet, many of the current GSM-only systems have poor local wireless communication capabilities and large switching delays.

The majority of automation solutions on the market today have one or more of the following drawbacks:

- Reliance on internet access
- Restricted communication range
- A rise in power usage
- Exorbitant implementation costs
- Poor suitability for remote areas
- Scalability issues
- Complicated infrastructural needs

The shortcomings of current systems emphasize the need for a different architecture that can offer dependable, long-range, internet-independent appliance control.

1.3 LIMITATIONS OF EXISTING SYSTEMS

Even though smart automation technologies are developing quickly, there are still a number of operational and technical issues with current systems that limit their usefulness in real-world settings.

1. Internet Dependency

The majority of contemporary automation systems rely significantly on internet access to function. These systems completely stop working when there are internet outages, router malfunctions, or poor network conditions. The reliability of the system is greatly impacted by this dependency.

2. Limited Communication Range

The operational range of Bluetooth and Wi-Fi communication technologies is constrained. While Bluetooth connection is limited to about 10 meters, Wi-Fi communication typically offers interior ranges of about 30 to 50 meters. Large buildings, farms, or industrial operations cannot use these systems due to their restrictions.

3. High Power Consumption

When operating continuously, several wireless communication systems need a lot of power. This restricts the deployment capabilities of battery-powered systems and raises operating costs.

4. Infrastructure Complexity

Internet infrastructure, mobile apps, routers, and gateways are needed for cloud-based automation systems. The need for more hardware raises the cost of maintenance and implementation complexity.

5. Poor Rural Suitability

Weak communication infrastructure and erratic internet connectivity are common problems in rural locations. Under such circumstances, current smart home technologies operate badly.

6. Security and Privacy Concerns

Devices with internet connections are susceptible to data breaches, illegal access, and cybersecurity risks. Concerns about user data storage and monitoring are another privacy issue with cloud-based solutions.

7. High Operational Cost

The total cost of operating automation systems is increased by ongoing internet use, cloud subscriptions, and infrastructure upkeep.

1.4 PROBLEM STATEMENT

The need for dependable and adaptable wireless control solutions has grown as smart home automation systems become more widely used. However, the majority of systems in use today mostly rely on short-range communication protocols like Bluetooth and Wi-Fi as well as internet access. These systems are inappropriate for remote or rural locations with inadequate network connectivity and malfunction during internet outages.

The following are the main issues with current systems:

- Reliance on cloud and internet platforms
- Limited range of communication
- Inadequate dependability when a network fails
- High complexity of the infrastructure
- An increase in the cost of operations
- Restricted suitability in rural settings
- Excessive power usage

1.5 OBJECTIVES

The following is a list of the planned project's main goals:

1. To create a smart home automation system that is not dependent on the internet.
2. To use LoRa SX1278 modules for long-range communication.
3. To use GSM SMS services to enable remote appliance control
4. To incorporate ESP8266 and ESP32 microcontrollers for embedded control.
5. To put relay-based AC load switching systems into practice.
6. To increase operational dependability and decrease communication latency.
7. To enable SMS commands and push buttons for dual communication.
8. To create an automation architecture that is both affordable and scalable.

9. To increase the applicability of automation in isolated and rural places
10. To attain minimal power usage for ongoing use.

1.6 PROPOSED SOLUTION

An improved smart home automation system built on LoRa and GSM communication technologies is shown in the suggested solution. In addition to offering dependable long-range communication and remote appliance control capabilities, the designed architecture removes reliance on the internet.

There are two main components to the system:

1. Transmitter Unit
2. Receiver Unit

The transmitter unit has the following:

- ESP32 microcontroller
- SIM800L GSM Module
- SX1278 LoRa Module
- Push Buttons
- LED Indicator

The receiver unit has the following:

- ESP32 controller
- SX1278 LoRa receiver
- Relay Modules
- AC load interface

Whether the user uses the manual button panel or the GSM network to deliver commands via SMS or phone. The ESP32 microcontroller in the transmitter part receives and processes both inputs. After interpreting the signal, the ESP32 sends it to the LoRa transmitter module (LoRa TX), which

uses LoRa communication technology to wirelessly send the command over a great distance. The transmitted data is received at the receiver side by the LoRa receiver module (LoRa RX), which then transmits it to another ESP32 microcontroller. After processing the incoming command, this controller turns on the relevant relay module. High-voltage AC appliances are safely controlled by the relay modules, which function as electrically regulated switches. The matching bulb load, such as Bulb-1, Bulb-2, Bulb-3, or Bulb-4, is turned ON or OFF in accordance with the received command. The suggested architecture is appropriate for remote and rural applications since it allows dependable long-range smart home automation without requiring internet connectivity.

1.7 SCOPE OF THE PROJECT

The creation of a dependable smart home automation system that can function completely without internet connectivity is part of the project's scope. The project focuses on integrating LoRa and GSM communication technologies for appliance control.

The suggested architecture works well for:

- Smart Homes
- Farms
- Rural electrification systems
- Industrial Automation
- Agricultural monitoring
- Remote load control systems

1.8 APPLICATIONS

Because of its long-range communication capabilities and internet-independent functioning, the proposed automation system can be used in a variety of practical applications.

1. Residential Automation

In residential structures, the system can regulate electrical appliances, fans, and lighting systems.

2. Agricultural Automation

Applications for irrigation control and agricultural monitoring can benefit from the system's long-range communication capacity.

3. Industrial Automation

The technology can be used for remote equipment switching and monitoring in factories and warehouses.

4. Rural Electrification

In rural areas with poor or nonexistent internet connectivity, the system offers dependable automation capabilities.

5. Remote Monitoring Systems

Systems for environmental control and remote sensor monitoring can be added to the design.

1.9 ADVANTAGES OF PROPOSED SYSTEM

When compared to current solutions, the suggested automation framework offers a number of benefits.

1. Internet-Independent Operation

The system doesn't require internet access to function.

2. Long Communication Range

Communication across several kilometers is possible with LoRa technology.

3. Low Power Consumption

When compared to Wi-Fi systems, the LoRa communication module uses a lot less electricity.

4. Rural Area Suitability

In places with inadequate or nonexistent internet infrastructure, the technique works well.

5. Low Implementation Cost

The architecture makes use of inexpensive communication modules and embedded components.

6. Reliable Communication

Communication stability is increased when LoRa and GSM technologies are combined.

7. Dual Communication Mechanism

Both local and remote appliance control are supported by the system.

8. Scalability

It is simple to incorporate more sensors and relay channels.

CHAPTER 2 LITERATURE REVIEW

2.1 INTRODUCTION TO SMART HOME AUTOMATION

In such systems, users send predefined text commands to GSM modules connected to embedded controllers. GSM-based automation systems utilize SMS communication to control appliances remotely. The term "smart home automation" describes the automatic monitoring and management of domestic appliances through the integration of intelligent technological devices and communication technology. Enhancing user convenience, operational effectiveness, energy management, and security through intelligent control mechanisms is the main goal of smart automation systems. In such systems, users send predefined text commands to GSM modules connected to embedded controllers. GSM-based automation systems utilize SMS communication to control appliances remotely.

The goal of the proposed project is to provide a dependable framework for smart home automation using GSM and LoRa communication technologies without internet access.

The combination of SMS-based appliance control and long-range wireless communication increases practical applicability and operational reliability.

2.2 INTERNET OF THINGS IN AUTOMATION

A network of physically connected objects that can gather, process, and share data using wireless communication technologies is known as the Internet of Things (IoT). IoT systems integrate embedded controllers, sensors, and communication protocols. Leveraging cloud platforms to facilitate automation and intelligent monitoring.

The basic architecture of IoT systems generally consists of three major layers:

1. Perception Layer
2. Network Layer
3. Application Layer

1.Perception Layer

Sensors and embedded hardware in the perception layer are in charge of gathering environmental data, including measurements of temperature, humidity, motion, voltage, and current.

2.Network Layer

Through the use of technologies like Wi-Fi, Bluetooth, GSM, ZigBee, LoRa, and cellular networks, the network layer facilitates communication between devices.

3.Application Layer

User interfaces, cloud services, data processing, and intelligent decision-making are all provided by the application layer.

IoT systems that rely only on cloud connection become unfeasible in remote locations with poor or non-existent internet access. As a result, there is an increasing need for offline IoT automation frameworks that don't require internet infrastructure.

By utilizing a hybrid LoRa-GSM architecture that can facilitate internet-independent automation, the proposed technology overcomes these constraints.

2.3 LORA COMMUNICATION TECHNOLOGY

A low-power wide-area network (LPWAN) communication technology called LoRa (Long Range) was created for long-distance wireless communication with low power consumption.

Chirp spread spectrum (CSS) modulation, which is used in LoRa technology, offers enhanced signal sensitivity and dependable communication over long distances.

LoRa connectivity uses unlicensed frequency ranges like:

- 433 MHz
- 868 MHz

- 915 MHz

The SX1278 LoRa module, which operates at 433 MHz, is used in the proposed project.

The ability of LoRa communication to sustain steady communication over distances ranging from 1 km to 15 km, depending on antenna setup and ambient conditions, is one of its fundamental advantages.

Advantages of LoRa Technology

- Long communication range
- Low power consumption
- Improved signal penetration
- Reduced infrastructure dependency
- High receiver sensitivity
- Suitable for rural environments

When internet connectivity is erratic, LoRa communication is very useful for rural automation applications.

LoRa communication does not require routers or internet infrastructure, in contrast to Wi-Fi and Bluetooth.

2.4 GSM COMMUNICATION SYSTEMS

One of the most used wireless communication standards for mobile networks is the Global System for Mobile Communication (GSM). GSM technology facilitates data transmission via cellular networks, SMS services, and voice communication. In these systems, GSM modules linked to embedded controllers receive pre-programmed text commands from users.

In such systems, users send predefined text commands to GSM modules connected to embedded controllers. GSM-based automation systems utilize SMS communication to control appliances remotely. In such systems, users send predefined text commands to GSM modules connected to embedded controllers.

In such systems, users send predefined text commands to GSM modules connected to control appliances remotely.

Advantages of GSM Automation Systems

- Wide communication coverage
 - Remote accessibility
 - Internet-independent operation
 - Compatibility with basic mobile phones
 - Simple command structure
- #### Limitations of GSM Systems
- SMS transmission delay
 - Dependence on cellular network availability
 - Limited real-time capability
 - Higher power consumption compared to LoRa

Despite these limitations, GSM communication remains one of the most reliable methods for remote automation applications.

2.5 ESP32 ARCHITECTURE

Expressive Systems created the ESP32, a low-cost, high-performance microcontroller. It incorporates GPIO pins, processing units appropriate for embedded and Internet of Things applications, and wireless communication interfaces.

Advantages of ESP32

- High processing speed
- Multiple communication interfaces
- Low power operation
- Large GPIO availability
- Integrated wireless capability
- Easy programming support

2.6 RELAY-BASED AUTOMATION SYSTEMS

Active LOW relay modules are used in the suggested project to switch appliances.

electrical isolation between low-voltage control circuitry and high-voltage appliances.

A relay acts as an electrically controlled switch capable of controlling AC loads using lowvoltage digital signals from microcontrollers.

The proposed project utilizes active LOW relay modules for appliance switchingRelay modules are essential components in automation systems because they provide

electrical isolation between low-voltage control circuitry and high-voltage appliances.

A relay acts as an electrically controlled switch capable of controlling AC loads using low voltage digital signals from microcontrollers.

The proposed project utilizes active LOW relay modules for appliance switching

Advantages of Relay-Based Automation :

- Electrical isolation
- High-voltage load control
- Reliable switching
- Simple implementation
- Compatibility with embedded systems

Limitations of Relay Systems

- Mechanical wear over time
- Slower switching compared to solid-state relays
- Audible switching noise

2.7 EXISTING RESEARCH WORKS

Several researchers have proposed automation systems utilizing IoT, GSM, Wi-Fi, Bluetooth, ZigBee, and LoRa communication technologies.

Research Work 1

R. Teymourzadeh et al. proposed a GSM-based home automation system using SMS communication for appliance control. The system provided remote accessibility but suffered from increased switching delay.

Research Work 2

A. Augustin et al. presented a detailed analysis of LoRa communication technology for lowpower wide-area network applications. Their study demonstrated the suitability of LoRa for long-distance IoT systems.

Research Work 3

M. Shahjalal et al. developed a LoRa-based appliance monitoring system capable of supporting low-power communication over large distances.

Research Work 4

N. Srivastava proposed an ESP32-based smart automation framework using Wi-Fi communication. Although the system provided mobile application support, it remained dependent on internet connectivity.

Research Work 5

Yar et al. introduced an IoT-enabled smart home system integrated with edge computing techniques for improved automation intelligence.

Research Work 6

Lavric and Popa analyzed LoRaWAN communication performance and scalability for IoT applications.

Research Work 7 Obinna et al. proposed a GSM-based automation architecture for appliance control through SMS communication.

Research Work 8

M. Jouhari et al. studied scalable LoRaWAN systems for massive IoT deployment.

Research Work 9

Khamees et al. designed a GSM-controlled smart automation framework for residential applications.

Research Work 10

Georgiou and Raza analyzed the scalability limitations of LoRa communication networks.

Research Work 11

Khan et al. developed an IoT energy management system for smart homes.

Research Work 12

Mukhopadhyay studied wearable sensors and IoT communication technologies for monitoring systems.

Research Work 13

Kumar proposed LoRaWAN-based smart space environments for scalable communication applications.

Research Work 14

Yi et al. studied communication reliability in low-power wireless IoT systems.

Research Work 15

Recent industrial studies demonstrate that hybrid communication architectures combining GSM and LoRa technologies provide improved reliability and operational flexibility.

2.8 COMPARATIVE ANALYSIS OF EXISTING SYSTEMS

Different communication technologies exhibit different operational characteristics.

Technology	Range	Internet Required	Power Consumption	Rural Suitability
Wi-Fi	30–50 m	Yes	High	Poor
Bluetooth	10–15 m	No	Moderate	Poor
ZigBee	50–100 m	Optional	Moderate	Moderate
GSM	Unlimited	No	High	Good
LoRa	1–15 km	No	Very Low	Excellent

Table 2.1 Comparison of Existing Automation Technologies

Wi-Fi: WiFi offers fast connection, but it uses more power and needs internet infrastructure.

Bluetooth: Although Bluetooth facilitates inexpensive short-range connectivity, it is not appropriate for large-scale automation.

ZigBee: Mesh networking is possible with ZigBee, but additional gateway infrastructure is needed.

GSM: Wide-area accessibility via mobile networks is offered via GSM; however, SMS delays occur.

LoRa: LoRa is ideal for rural automation systems because it provides long-distance communication with extremely low power consumption.

Combining GSM and LoRa technology improves dependability, long-range communication, and internet-independent operation, according to the comparison analysis.

2.9 RESEARCH GAP

The review of the literature identifies a number of outstanding issues with current smart automation systems.

The major research gaps identified include:

- Heavy dependency on internet infrastructure
- Limited communication range in Wi-Fi systems
- High power consumption
- Poor applicability in rural areas
- Lack of dual communication mechanisms
- Increased operational complexity
- Absence of integrated LoRa-GSM architectures
- Limited offline automation capability

CHAPTER 3

SYSTEM DESIGN AND METHODOLOGY

3.1 INTRODUCTION

One of the most important stages in the creation of the suggested framework for smart home automation is the system design and methodology. Without relying on internet infrastructure, the complete architecture was created to deliver dependable appliance control through long-range wireless communication and GSM-based remote accessibility. Relay switching circuits, wireless communication modules, embedded controllers, and user interfaces are all integrated into a single automation platform.

Eliminating the drawbacks of traditional Wi-Fi-based automation systems while preserving low power consumption, operational dependability, and communication flexibility is the fundamental goal of the suggested architecture. The designed framework makes use of GSM communication for remote SMS-based appliance control and LoRa communication for long-distance wireless transfer. Both local push-button control and distant SMS operation are supported by the entire system.

The architecture consists of two major hardware units:

1. Transmitter Unit (TX Unit)
2. Receiver Unit (RX Unit)

The ESP32 controller, LoRa transmitter module, GSM communication module, push buttons, and LED status indicators are all included in the transmitter unit. The LoRa receiver module, relay

switching circuitry, and ESP8266 controller are all included in the receiver unit and are coupled to AC loads.

The communication between transmitter and receiver occurs through LoRa SX1278 modules operating at 433 MHz frequency. The GSM module enables appliance control from any mobile phone using SMS commands.

LoRa SX1278 modules that operate at a frequency of 433 MHz facilitate communication between the transmitter and receiver. Using SMS commands, the GSM module makes it possible to control appliances from any mobile phone.

The project's technique aims to reduce communication reliance on external infrastructure while increasing operational reliability.

3.2 OVERALL SYSTEM ARCHITECTURE

The distributed communication architecture of the suggested smart home automation system combines wireless communication technologies with embedded controllers. The transmitter and receiver elements of the entire architecture are connected by LoRa correspondence.

The transmitter section performs:

- User command acquisition
- SMS processing
- Packet generation
- LoRa packet transmission
- LED status indication

The receiver section performs:

- Packet reception
- Command decoding
- Relay switching
- Load control operations

Major Components of the System :

Component	Function
ESP32	Main transmitter controller
ESP8266	Receiver controller
SIM800L	GSM communication
SX1278 LoRa	Long-range wireless communication
Relay Modules	Appliance switching
Push Buttons	Local control interface
LED Indicator	Transmission status

Table 2.9 Major Components of the System

The transmitter section's central processing unit is the ESP32. It keeps an eye on GSM serial connection and push-button inputs. The ESP32 creates the matching LoRa packet and sends it wirelessly to the receiver portion whenever it detects a valid command.

Using `parsePacket()`, the ESP8266 controller continuously looks for incoming LoRa packets.

The controller decodes the command and initiates the necessary relay channel after receiving a valid packet. Four separate load channels that are managed by push buttons and SMS commands are supported by the suggested architecture. Future expansion is made easier and scalability is enhanced by the modular architecture.

3.3 TRANSMITTER UNIT DESIGN

The transmitter unit serves as the automation framework's wireless transmission and command generation component. It is built around the ESP32 microcontroller, which is connected to LoRa and GSM communication modules.

Components of Transmitter Unit

The transmitter unit consists of:

- ESP32 microcontroller
- SIM800L GSM module

- SX1278 LoRa module
- Push-button array
- LED indicator
- Power supply section

ESP32 Controller

The ESP32 controller performs the following operations:

- Reading push-button inputs
- Monitoring GSM serial data
- Parsing SMS commands
- Generating LoRa packets
- Controlling transmission indicators

The ESP32 was selected because of its:

- High processing capability
- Multiple GPIO availability
- SPI and UART support
- Low power consumption
- Embedded communication interfaces

Push Button Interface

Four push buttons are connected to ESP32 GPIO pins configured using internal pull-up resistors. Each button controls one electrical load.

The push-button logic operates using toggle-based operation:

- First press → Load ON
- Second press → Load OFF

The ESP32 continuously monitors button states inside the main loop.

LED Status Indicator

An LED indicator is connected to the transmitter section to indicate successful packet transmission. The LED blinks whenever a command packet is transmitted through LoRa communication.

GSM Communication Interface

The SIM800L GSM module communicates with ESP32 using UART serial communication. The module receives SMS commands and forwards them to ESP32 for processing.

LoRa Transmission Interface

The SX1278 LoRa module communicates with ESP32 using SPI protocol.

The transmitter architecture provides reliable command acquisition and packet generation capability.

3.4 RECEIVER UNIT DESIGN

Based on incoming LoRa packets, the receiver unit switches appliances.

The ESP8266 controller along with relay switching and LoRa communication circuits makes up the reception part.

Components of Receiver Unit

The receiver section contains:

- ESP8266 controller
- SX1278 LoRa receiver module
- Relay modules
- AC load interface
- Power regulation circuitry

ESP8266 Controller

The ESP8266 continuously monitors incoming LoRa packets and processes relay switching commands.

Major responsibilities include:

- Packet reception
- Command decoding
- Relay activation

- Load management

Relay Switching Section

The relay modules provide electrical isolation between low-voltage embedded circuitry and high-voltage AC loads.

Each relay channel controls one appliance independently.

LoRa Reception Module

The SX1278 receiver module continuously checks for incoming wireless packets transmitted by the transmitter unit.

The `parsePacket()` function is used for packet detection and reception.

The receiver architecture was designed to provide reliable switching operation with minimal communication delay.

3.5 COMMUNICATION WORKFLOW

The proposed system supports two independent communication workflows:

1. Local Push-Button Communication
2. GSM SMS-Based Communication

Local Communication Workflow

When the user hits a push button attached to the ESP32 transmitter controller, the local communication process starts.

The operational sequence is as follows:

1. Button press detected
2. Load state variable updated
3. Corresponding command generated
4. LoRa packet created
5. Packet transmitted wirelessly
6. Receiver receives packet
7. Relay switches load state

GSM Communication Workflow

The GSM workflow enables remote appliance control through SMS commands.

Operational sequence:

1. User sends SMS command
2. SIM800L receives message
3. ESP32 parses SMS
4. Command extracted
5. LoRa packet generated
6. Packet transmitted
7. Receiver decodes packet
8. Relay operation executed

Even in the event of an internet outage, the communication architecture guarantees dependable appliance control.

3.6 GSM COMMUNICATION ARCHITECTURE

Long-distance appliance control via mobile communication networks is made possible by the GSM communication architecture.

SIM800L GSM Module

The SIM800L module supports:

- SMS communication
- UART communication
- AT command configuration
- Quad-band GSM operation

3.7 LORA COMMUNICATION WORKFLOW

The main wireless communication method between transmitter and receiver modules is LoRa communication.

SX1278 LoRa Module

The SX1278 module operates at 433 MHz frequency and provides:

- Long-range communication
- Low power operation
- Stable packet transmission
- Improved signal penetration

3.8 RELAY DRIVER CIRCUIT

Low-voltage embedded signals are used by relay modules to operate AC appliances.

Active LOW Relay Logic

The proposed system uses active LOW relay modules.

Relay logic:

Signal	Relay State
LOW	ON
HIGH	OFF

Table 3.2 : Relay Logic Operation

Relay Driver Components

The relay driver circuit consists of:

- Relay coil
- Driver transistor
- Flyback diode
- Indicator LED
- Optocoupler

3.9 POWER SUPPLY DESIGN

All hardware modules receive regulated voltage from the power supply section.

Voltage Requirements

Component	Voltage
ESP32	5V / 3.3V
ESP8266	3.3V
SIM800L	4V
LoRa SX1278	3.3V
Relay Module	5V

Table 3.3 : Voltage Requirements

3.10 COMMAND STRUCTURE

The system uses integer-based command structures for appliance control.

Command	Function
1	Load 1 ON
2	Load 1 OFF
3	Load 2 ON
4	Load 2 OFF
5	Load 3 ON
6	Load 3 OFF
7	Load 4 ON
8	Load 4 OFF

Table 3.4 : Command Structure

Even commands indicate OFF activities, and odd commands indicate ON actions.

The command structure increases packet efficiency and makes software development easier.

3.11 DATA FLOW DIAGRAM

The automation framework's information flow is depicted in the data flow architecture.

Data Flow Sequence

1. User input acquired
2. ESP32 processes command
3. LoRa packet generated
4. Wireless transmission occurs
5. Receiver receives packet
6. Relay switches appliance

The data flow design guarantees effective control operation and streamlined communication.




Fig.3.1- Overall System Architecture

3.12 SYSTEM ALGORITHM

Transmitter Algorithm

1. Initialize ESP32 peripherals
2. Configure LoRa module
3. Configure GSM module
4. Monitor push buttons
5. Monitor incoming SMS
6. Detect command
7. Generate packet

8. Transmit packet
9. Blink LED indicator

Receiver Algorithm

1. Initialize ESP8266
2. Configure relay outputs
3. Monitor LoRa packets
4. Read packet data
5. Decode command
6. Execute relay operation
7. Update load status

3.13 ADVANTAGES OF PROPOSED ARCHITECTURE

Comparing the suggested smart home automation architecture to traditional systems reveals a number of operational and technological benefits.

1. Internet-Independent Operation
2. Long Communication Range
3. Low Power Consumption
4. Dual Communication Modes
5. Rural Area Suitability
6. Improved Reliability
7. Low Implementation Cost
8. Easy Scalability

The suggested solution offers dependable long-range appliance control while effectively addressing the drawbacks of traditional automation systems.

CHAPTER 4

HARDWARE AND SOFTWARE IMPLEMENTATION

4.1 INTRODUCTION

The hardware and software implementation phase plays a major role in developing the proposed smart home automation system into a functional real-time application. The complete implementation includes integration of embedded controllers, LoRa communication modules, GSM communication module, relay switching circuits, and software programming into a single automation framework.

The system was developed using low-cost hardware components and Embedded C programming in Arduino IDE. The proposed implementation was designed to provide reliable communication, long-range operation, low power consumption, safe relay switching, and internet-independent appliance control.

The hardware section mainly consists of:

- ESP32 transmitter controller
- ESP8266 receiver controller
- SIM800L GSM module
- SX1278 LoRa modules
- Relay modules
- Push buttons
- LED indicator
- Power supply section

The software section includes:

- Embedded C programming
- GSM command processing
- LoRa packet transmission
- Relay switching logic
- UART communication
- SPI communication

The complete system provides stable automation performance suitable for residential and rural applications.

HARDWARE IMPLEMENTATION

4.2 ESP32 TRANSMITTER SECTION

The ESP32 microcontroller acts as the main controller in the transmitter section. It reads push-button inputs, processes SMS commands from the GSM module, and transmits LoRa packets to the receiver section.

Features of ESP32

Feature	Specification
Processor	Dual-Core Xtensa LX6
Clock Speed	240 MHz
Operating Voltage	3.3V
GPIO Pins	34
Communication	SPI, UART

Table 4.1 Features of ESP32

Functions of ESP32

- Reading push-button inputs
- Receiving SMS commands
- Generating LoRa packets
- Sending wireless commands
- Monitoring serial communication

The ESP32 continuously executes the main control logic during system operation.

4.3 ESP8266 RECEIVER SECTION

The ESP8266 controller is used in the receiver section for LoRa packet reception and relay switching operations.

Features of ESP8266

Feature	Specification
Processor	Tensilica L106
Operating Voltage	3.3V
Communication	SPI, UART
Clock Frequency	80 MHz

Table 4.2 Features of ESP8266

Functions of ESP8266

- Monitoring incoming LoRa packets
- Decoding commands
- Activating relays
- Controlling appliances

The ESP8266 continuously checks for incoming LoRa packets and updates relay outputs according to the received command.

4.4 SIM800L GSM MODULE

The SIM800L GSM module enables remote appliance control using SMS communication.

Features of SIM800L

Feature	Description
GSM Bands	Quad-Band
Communication	UART
SMS Support	Yes
Operating Voltage	4V

Table 4.3 Features of SIM800L

Working Principle

The GSM module receives SMS messages from the user and forwards serial data to the ESP32 controller. The ESP32 extracts the command and generates the corresponding LoRa packet.

AT Commands Used

```
gsm.println("AT");
gsm.println("AT+CMGF=1");
gsm.println("AT+CNMI=1,2,0,0,0");
```

The GSM module allows remote appliance control without internet connectivity.

4.5 SX1278 LORA MODULE

The SX1278 LoRa module provides long-range wireless communication between transmitter and receiver sections.

Features of SX1278

Feature	Specification
Frequency	433 MHz
Communication Type	LoRa
Range	1–15 km
Operating Voltage	3.3V

Table 4.4 Features of SX1278 LoRa Module

LoRa Initialization

```
LoRa.setPins(ss, rst, dio0);
LoRa.begin(433E6);
```

Advantages of LoRa

- Long communication range
- Low power consumption
- Stable wireless transmission
- Rural area suitability

The LoRa module enables reliable communication without internet infrastructure.

4.6 RELAY MODULES

Relay modules are used to control AC appliances using low-voltage controller signals.

Relay Specifications

Parameter	Value
Relay Voltage	5V
Switching Type	Active LOW
Load Type	AC Appliances

Table 4.5 Relay Specifications .

Relay Logic

Signal	Relay State
LOW	ON
HIGH	OFF

Table 4.6 Relay Logic

Relay Operation

```
digitalWrite(RELAY1, LOW);
```

Relay modules provide electrical isolation between embedded circuits and high-voltage AC loads.

4.7 PUSH BUTTONS

Push buttons are connected to ESP32 GPIO pins for local appliance control.

Push Button Operation

When a button is pressed:

- ESP32 detects input
- Command generated
- LoRa packet transmitted

Push Button Logic

```
if(digitalRead(button1)==LOW)
{
  sendCommand(1);
}
```

The push-button mechanism provides direct local appliance control.

4.8 POWER SUPPLY

The power supply section provides regulated voltage for all hardware components.

Voltage Requirements

Component	Voltage
ESP32	3.3V
ESP8266	3.3V
SIM800L	4V
Relay Module	5V

Table 4.7 Voltage Requirements of Hardware Components

Proper voltage regulation improves communication stability and relay performance.





Fig. 4.1. Receiver Unit

Fig. 4.2. Transmitter Unit



Fig. 4.3. GSM Module

SOFTWARE IMPLEMENTATION

4.9 ARDUINO IDE

The complete software was developed using Arduino IDE.

Features of Arduino IDE

- Embedded C programming
- Library support
- Serial monitoring
- Easy code uploading
- Real-time debugging

Arduino IDE provides a simple environment for embedded software development.

4.10 TRANSMITTER PROGRAM

The transmitter program is responsible for reading button inputs, processing SMS commands, and transmitting LoRa packets.

setup() Function

```

void setup()
{
  Serial.begin(115200);
  gsm.begin(9600);

  LoRa.setPins(ss, rst, dio0);
  LoRa.begin(433E6);
}

```

loop() Function

```

void loop()
{
  checkButtons();
  readSMS();
}

```

The transmitter section continuously monitors user commands and transmits data wirelessly.

4.11 RECEIVER PROGRAM

The receiver program monitors incoming LoRa packets and controls relay outputs.

Receiver Logic

```

void loop()
{
  int packetSize = LoRa.parsePacket();

  if(packetSize)
  {
    int command = LoRa.read();
    processCommand(command);
  }
}

```

The receiver continuously performs packet monitoring and appliance control operations.

4.12 SMS COMMAND PROCESSING

SMS commands are used for remote appliance control.

SMS Processing Logic

```
if(gsm.available())
{
    char c = gsm.read();

    if(c == '$')
    {
        command = gsm.read();
    }
}
```

The controller extracts commands from SMS messages and transmits corresponding LoRa packets.

4.13 PACKET TRANSMISSION

The transmitter section sends commands using LoRa packet transmission.

Packet Transmission Function

```
void sendCommand(int command)
{
    LoRa.beginPacket();
    LoRa.write(command);
    LoRa.endPacket();
}
```

Packet-based communication improves transmission reliability and reduces communication overhead.

4.14 PACKET RECEPTION

The receiver continuously monitors incoming LoRa packets.

Packet Reception Logic

```
int packetSize = LoRa.parsePacket();

if(packetSize)
{
```

```
    int command = LoRa.read();  
}
```

The receiver decodes the received command and updates relay outputs.

4.15 SERIAL COMMUNICATION

UART serial communication is implemented between ESP32 and SIM800L GSM module.

UART Initialization

```
gsm.begin(9600);
```

UART communication enables stable SMS data transfer between GSM module and controller.

4.16 SPI COMMUNICATION

SPI communication is used between microcontrollers and LoRa modules.

SPI Libraries

```
#include <SPI.h>  
#include <LoRa.h>
```

SPI communication provides fast and reliable packet transmission.

4.17 ERROR HANDLING

Basic error handling methods are included to improve communication stability.

LoRa Error Handling

```
if(!LoRa.begin(433E6))  
{  
    Serial.println("LoRa Failed");  
    while(1);  
}
```

All relays are initialized in OFF state during startup to prevent accidental appliance activation.

4.18 TRANSMITTER SOURCE CODE

```
LoRa.setPins(ss, rst, dio0);

if(!LoRa.begin(433E6))
{
  Serial.println("LoRa Failed");
  while(1);
}

gsm.println("AT");
gsm.println("AT+CMGF=1");
gsm.println("AT+CNMI=1,2,0,0,0");
}

void loop()
{
  if(digitalRead(button1)==LOW)
  {
    sendCommand(1);
    delay(300);
  }

  if(digitalRead(button2)==LOW)
  {
    sendCommand(2);
    delay(300);
  }
}
```

CHAPTER 6

RESULTS AND DISCUSSION

6.1 INTRODUCTION

The suggested smart home automation project's findings and discussion phase is crucial since it assesses the developed system's operational stability, switching efficiency, communication dependability, and practical performance. To evaluate the efficiency of relay switching mechanisms, LoRa communication, GSM-based SMS control, and total automation capabilities, experimental testing was carried out under various operating situations.

The created prototype was examined for:

- The ability to communicate over long distances
- The performance of GSM response
- Reliability of relay switching
- Delays in communication
- Consumption of power
- Stability of operations
- Efficiency of packet transmission

Validating whether the suggested automation framework could function dependably without internet connectivity while preserving steady wireless communication and reduced battery consumption was the main goal of the testing process.

There were multiple phases to the review process:

1. Verification of hardware
2. Testing of communication
3. Testing SMS commands
4. Analysis of relay switching
5. Analysis of long-distance transmission
6. Testing for reliability

The results show that the suggested architecture effectively uses GSM SMS services and LoRa connectivity to operate appliances. Under various environmental and communication situations, the system continued to operate steadily.

The experimental research verifies that embedded communication technologies can be used to construct internet-independent smart automation systems.

6.2 APPLICATION OF PROTOTYPES

ESP32, ESP8266, SIM800L GSM module, SX1278 LoRa modules, relay circuits, push buttons, and AC loads were used to successfully implement the entire prototype.

Configuration of the Prototype

Included in the transmitter section were:

- ESP32 controller
- GSM communication module
- LoRa transmitter
- Push-button control interface

- LED indication circuitry

The receiver section included:

- ESP8266 controller
- LoRa receiver module
- Relay driver circuits
- AC bulb loads

Operation of the Prototype

Two separate communication techniques were used to test the system:

1. Local control via push buttons
2. Remote control via SMS

The ESP32 created the appropriate LoRa packet and sent it to the receiver portion whenever the user touched a push button or sent an SMS command. After decoding the packet, the ESP8266 turned on the relevant relay channel.

Throughout several testing cycles, the prototype showed steady operation. The suggested automation framework's viability is confirmed by its effective deployment.

6.3 ANALYSIS OF COMMUNICATION RANGE

Assessing the LoRa SX1278's long-range communication capabilities was one of the project's main goals module.

Procedure for Testing

Communication reliability was examined while the transmitter and receiver devices were positioned at various separations.

Experimental Observations

Distance	Communication Status	Packet Loss
100 m	Excellent	0%
500 m	Excellent	0%
1 km	Stable	<1%
3 km	Stable	2–3%
5 km	Operational	5–7%

Table-6.1- Experimental Observations

Examination

With little packet loss, the LoRa communication technology sustained steady wireless transmission over a number of kilometres. Even in partially blocked situations, signal stability remained excellent.

Technical Interpretation

Chirp spread spectrum modulation increased communication reliability and signal sensitivity. When compared to Bluetooth and Wi-Fi technologies, the system showed noticeably better communication range.

Observed Benefits

- Communication over long distances
- Packet gearbox that is reliable
- Minimal attenuation of signals
- Enhanced capacity for communication in rural areas

The communication study verifies that LoRa technology is appropriate for large-scale automation systems.

6.4 Analysis of SMS Delays

SMS response time and remote control capabilities were assessed through testing of the GSM communication system.

Procedure for Testing

Response time was measured when several SMS commands were sent from several cell networks.

Results of the Experiment

Average Operational Delay

Reception of SMS: 3–5 seconds

SMS parsing takes less than a second.

LoRa Transmission: less than one second

Instantaneous Relay Activation

Technical Interpretation

Rather than software processing constraints, the GSM network circumstances were the main cause of the delay. The ESP32 processed commands quickly after receiving the SMS and sent LoRa packets almost immediately.

Observations

- Consistent SMS reception
- Dependable command extraction
- Quick relay reaction
- Minimal latency in processing

Conversation

The operational dependability and internet-independent capabilities of SMS communication offer substantial practical benefits, despite a minor delay as compared to internet-based systems.

Remote appliance control with a reasonable reaction time was made possible by the GSM communication system.

6.5 RELAY SWITCHING EFFICACY

In order to assess switching reliability and load control performance, the relay modules underwent comprehensive testing.

Conditions for Testing

The relays experienced:

- Frequent switching actions
- Constant load management
- Several cycles of communication

Analysis of Relay Performance

Observation of Parameters

Stable Relay Response

No Evidence of False Triggering

Successful Load Isolation

Switching Delay: Minimal

Startup Security Dependability Active Low Logic Efficiency

Because every relay stayed off during initialisation, the active LOW relay arrangement enhanced starting safety.

Technical Conversation

Relay modules were able to effectively separate low-voltage integrated electronics from high-voltage AC loads. During testing, no unusual switching behaviour was noticed.

Observed Benefits

- Dependable switching
- Consistent load performance
- Isolation of electricity
- Control of safe appliances

The established control mechanism's stability and dependability are validated by the relay switching analysis.

6.6 ANALYSIS OF POWER USE

To assess the created system's energy efficiency, power consumption analysis was carried out.

Power Consumption Observations

Technical Evaluation

When compared to traditional Wi-Fi communication systems, the LoRa communication technology used a lot less electricity.

Benefits of Low Power Use

- Fit for systems that run on batteries
- Lower operating expenses
- Increased system effectiveness
- Compatibility with solar power

GSM Power Analysis

Stable voltage management was required because the SIM800L module used more current during GSM transmission.

Conversation

For continuous automation applications, the developed architecture showed effective power use.

The power analysis confirms that the suggested automation framework is energy-efficient.

6.7 RELIABILITY TESTING

Reliability testing was conducted to evaluate long-term operational stability under repeated usage conditions.

Testing Conditions

The following tests were performed:

- Continuous switching test
- Long-distance communication test
- Repeated SMS transmission
- Relay stress testing
- Startup and shutdown cycles

Reliability Results

Test	Result
------	--------

Continuous Operation	Stable
----------------------	--------

Packet Reception	Reliable
------------------	----------

Relay Switching	Stable
-----------------	--------

GSM Communication	Successful
-------------------	------------

System Restart	Safe
----------------	------

Table-6.2- Reliability Results

Observations

During extensive testing, the system operated steadily and without significant communication problems.

Increases in Reliability

Reliability was enhanced by the following design decisions:

- LoRa correspondence Relay logic that is active and low
- Controlled power source
- Implementing software in an organised manner

Technical Interpretation

The modular architecture enhanced communication effectiveness and decreased program complexity.

The suggested automation framework's practical viability is validated by the reliability testing.

6.8 COMPARATIVE EVALUATION

The suggested architecture and traditional automation systems were compared.

Comparative Analysis Table

Feature	Wi-Fi System	Bluetooth System	Proposed System
Internet Required	Yes	No	No
Long Range	Limited	Very Limited	Excellent
Power Consumption	High	Moderate	Low
Rural Suitability	Poor	Poor	Excellent
Remote Accessibility	Yes	Limited	Yes
Communication Reliability	Moderate	Moderate	High

Table-6.3- Comparative Analysis

Analysis

Compared to traditional Wi-Fi and Bluetooth-based automation systems, the suggested approach showed notable advantages.

Technical Notes

- LoRa communication greatly increased range.
- Remote operation was made possible using GSM communication
- Dependency on the internet was removed.
- There was a significant decrease in power use.

The comparison study shows how well LoRa and GSM communication technologies work together.

6.9 BENEFITS OF THE SUGGESTED SYSTEM

Numerous technological and operational benefits are offered by the established smart home automation framework.

Principal Benefits

- Operating without the internet
- Wireless communication across long distances

- Dependable relay switching
- Remote access via GSM
- Minimal power usage
- Suitability for rural areas
- Low cost of implementation
- Architecture that is scalable
- Less reliance on infrastructure
- Communication logic that is simpler

Advantages of Engineering

The flexibility and dependability of the system were increased by combining LoRa and GSM communication technologies.

Useful Advantages

The system can function well in:

- Homes in rural areas
- Environments related to agriculture
- Industrial regions
- Installations that are remote

The shortcomings of traditional automation systems are effectively addressed by the suggested architecture.

6.10 RESTRICTIONS

During implementation and testing, some limitations were noted despite the suggested system's dependable performance.

Determined Restrictions

- The quality of the GSM network affects SMS latency.
- No graphical user interface in real time
- Limited capacity for multimodal communication
- The lack of cloud-based monitoring
- Fewer comments of acknowledgement

Technical Difficulties

In bad network conditions, the SIM800L module occasionally encountered brief signal fluctuations.

Upcoming Enhancements

The restrictions can be overcome by:

- Integration of mobile applications
- LoRa communication in both directions

Cloud-based analytics

- The application of advanced security

6.11 USEFUL APPLICATIONS

There are several real-world applications for the suggested smart automation framework.

Automation in Homes

Fans, lighting, and home appliances can all be controlled by the system.

Automation in Agriculture

The technology is appropriate for farm control and irrigation systems because to its long-range communication capability.

Automation in Industry

It is possible to remotely monitor and operate industrial machines and equipment.

Electrification of Rural Areas

Remote rural settings are ideal for the internet-independent architecture.

Systems for Storage and Warehousing

Electrical equipment in warehouses and storage facilities can be automated by the system.

The designed framework exhibits a great degree of adaptability and usefulness.

6.12 TALK

Using LoRa and GSM communication technologies, the suggested smart home automation framework efficiently accomplishes dependable appliance control without requiring internet connectivity, according to the experimental study.

Stable long-range transmission with minimal packet loss and low power consumption was demonstrated by the LoRa communication system. The suggested architecture greatly increased communication range and rural applicability as compared to traditional Wi-Fi systems.

Using straightforward SMS commands, remote appliance control was made possible by the GSM communication technology. During experimental testing, the system continued to operate steadily and dependably despite the slight delay caused by SMS transmission.

By using active LOW relay logic and electrical isolation, the relay switching system offered safe appliance control. With little processing overhead, the implemented software architecture effectively managed packet generation, communication monitoring, command decoding, and relay operation.

The suggested automation framework shows that creating dependable offline automation systems appropriate for industrial, domestic, and agricultural applications is practically feasible.




Fig.6.1-Output Showing Bulb 2 Glowing




Fig.6.2-Output Showing Bulb 3 Glowing

CHAPTER 7

CONCLUSION AND FUTURE SCOPE

7.1 CONCLUSION

The need for dependable and intelligent automation systems that can function in both urban and rural settings has grown dramatically due to the quick development of embedded systems and wireless communication technologies. For appliance control and monitoring, traditional smart home automation systems often rely on cloud servers, Wi-Fi connection, and internet connectivity. These systems have a number of practical drawbacks, such as limited communication range, internet dependence, high power consumption, and decreased operational reliability during network outages, even though they offer convenient remote accessibility.

By combining LoRa communication and GSM technology into a single automation framework, the suggested project "Enhanced Smart Home Automation Using LoRa and GSM Without Internet Connectivity" effectively overcomes these constraints. Without the need for internet infrastructure, the created architecture uses SMS-based remote accessibility and long-range wireless communication to offer dependable appliance control.

To enable dual communication, the constructed system makes use of ESP32 and ESP8266 microcontrollers combined with SX1278 LoRa modules and SIM800L GSM modules. Both remote control via SMS commands and local appliance control via push buttons are supported by the suggested automation framework. Relay-based load switching for AC appliances is effectively accomplished by the receiver section while preserving operational safety and electrical isolation.

The LoRa communication module offers reliable long-range wireless transmission with substantially reduced power consumption than traditional Wi-Fi systems, according to experimental testing. Using common mobile networks, remote appliance control was successfully made possible using the GSM communication mechanism. Under various testing scenarios, such as continuous SMS-based control operations, repetitive relay switching, and long-distance communication, the designed system continued to operate reliably.

Using active LOW relay logic, the relay switching design showed reliable and secure appliance control. With little processing latency, the implemented software structure effectively managed relay control, packet creation, command parsing, and communication monitoring.

The major advantages achieved by the proposed system include:

- Internet-independent operation
- Long-range communication capability
- Reliable relay switching
- Low power consumption
- Rural area suitability

- Reduced implementation complexity
- Cost-effective architecture
- Scalable embedded framework

The produced project shows that leveraging embedded communication technologies to implement offline smart automation systems is practically feasible. Smart homes, remote appliance control, industrial monitoring, agricultural automation, and rural electrification systems are all excellent uses for this design.

The efficacy of integrating LoRa and GSM communication technologies for intelligent automation systems functioning without internet connectivity is validated by the framework's successful implementation.

7.2 MAJOR ACHIEVEMENTS

All of the main design goals set during the first stage of development were effectively met by the proposed project. Under realistic operational conditions, the system showed consistent communication performance, dependable relay functioning, and effective automation capability.

Implementing Internet-Independent Automation Successfully

The successful installation of a smart automation system that can function entirely without internet connectivity was one of the project's most important accomplishments. The suggested design maintained steady operation independent of cloud servers and internet infrastructure, in contrast to traditional Wi-Fi-based systems.

Wireless Long-Range Communication

Using SX1278 modules running at 433 MHz, the LoRa communication system successfully accomplished stable long-distance wireless transmission. Reliable communication over several kilometres with little packet loss and transmission latency was established by experimental research.

Remote Access via GSM

Remote appliance control via SMS communication was made possible by the incorporation of the SIM800L GSM module. Without the need for cellphones or internet access, users may operate electrical appliances from any mobile device.

Dependable Switching of Relays

Using active LOW relay logic, the relay switching design effectively managed AC appliances. During continuous testing operations, the relay modules offered consistent switching performance and electrical isolation.

Integration of Embedded Systems

Several embedded hardware modules were successfully integrated into the project, including:

- ESP32 controller

- ESP8266 receiver
- SX1278 LoRa modules
- SIM800L GSM module
- Relay driver circuits
- Push-button interfaces

The communication between modules remained stable throughout testing.

Two-way Communication System

The system effectively provided functionality for:

1. Push-button control locally
2. Control by remote SMS

Operational flexibility was greatly increased by this dual communication capabilities.

Low-Power Function

When compared to traditional Wi-Fi communication systems, the LoRa communication technology showed reduced power consumption. This accomplishment enhances the suggested architecture's adaptability for distant and battery-powered installations.

Implementation of Practical Engineering

The created prototype validated the viability of creating scaled offline automation systems by successfully demonstrating real-time appliance control under realistic operating conditions.

The accomplishment of these goals attests to the efficacy of the suggested automation design.

7.3 FUTURE SCOPE

Even though the created smart home automation framework showed dependable performance and effective deployment, a number of upcoming improvements could further boost user interface, scalability, intelligence, and operational capabilities.

The suggested system's modular design makes it simple to incorporate cutting-edge technologies and clever automation features.

Integration of Mobile Applications

For better user interaction and easier appliance control, a specialised Android or iOS application can be created. With a graphical mobile interface, customers may keep an eye on the condition of their appliances and manage loads with simple visual controls.

Integration of mobile applications may have the following features:

- Real-time appliance status monitoring

- Interface for remote switching
- Alerts for notifications
- Analytics for usage
- Dashboard for device management

Integration of Voice Assistants

Voice assistant platforms like the following can be incorporated with the suggested system:

-

Alexa on Amazon

Google Assistant

Apple Siri

By offering hands-free appliance operation, voice-based automation would increase accessibility and user convenience.

Automation Powered by AI

Algorithms for machine learning and artificial intelligence can be combined to produce intelligent automation.

Integration of AI can assist: Predictive control of appliances

- Analysis of user behaviour
- Scheduling automatically
- Making wise decisions

Cloud integration could offer:

- Data storage in real time
 - Dashboard for remote monitoring
- Synchronisation of devices

Possible sensor integrations include:

- Temperature sensors
- Humidity sensors
- Motion sensors
- Gas leakage sensors
- Fire detection sensors
- Smoke detection modules
- Water level sensors

Features for energy monitoring could include:

- Power measuring in real time
- Statistics on energy use
- Analysis of load
- Identification of faults
- Suggestions for conserving energy

This feature would increase the effectiveness of energy management.

Growth of Industrial Automation

Applications utilising industrial automation that can scale the architecture include: • Control of motor

- Monitoring machines

Automation of warehouses

- Intelligent production systems

Applications of Smart Agriculture

For agricultural automation, the system can be extended to include: Control of irrigation

Monitoring of the soil

- Sensing the environment

Monitoring livestock

Future intelligent automation research and industrial development will have a solid basis thanks to the suggested automation framework.

7.4 FINAL REMARKS

Using LoRa and GSM communication technologies without internet connectivity, the suggested project effectively illustrates the practical implementation of a dependable and effective smart home automation system. The designed architecture integrates software control logic, relay switching mechanisms, wireless connectivity, and embedded systems into a cohesive automation framework that can support practical applications.

By removing reliance on Wi-Fi networks and cloud infrastructure, the idea successfully tackles the drawbacks of traditional internet-based automation systems. The solution is ideal for isolated and rural locations since LoRa connectivity greatly increases communication range while consuming less power.

By allowing appliance control via SMS services from almost anywhere, the incorporation of GSM communication further increases system flexibility. While preserving electrical isolation between embedded hardware and high-voltage loads, the relay-based load switching technique guarantees safe appliance control.

The usefulness of integrating embedded automation systems with long-range communication technologies for real-world engineering applications is validated by the framework's successful deployment.

The created architecture offers:

- Dependable control of appliances
- Communication over long distances

- Less reliance on infrastructure
- Low cost of implementation
- Enhanced scalability
- The capacity to deploy practically

Future research in intelligent automation systems, IoT communication frameworks, energy-efficient embedded systems, and rural automation technologies is also made possible by the project.

The suggested smart home automation system is a workable and scalable solution that can satisfy contemporary automation needs while preserving affordability, dependability, and simplicity.

CHAPTER 8

APPENDICES

This project report includes appendices that offer further technical and supplemental information about the planned Enhanced Smart Home Automation System's implementation using LoRa and GSM Modules. Although they are not included in the report's main chapters, the appendices feature supporting resources that are helpful for comprehending the system's practical development, hardware integration, software programming, and communication setup.

The transmitter and receiver firmware created with the Arduino IDE, ESP32 and ESP8266 pin settings, LoRa communication setup, GSM AT instructions, relay module connections, hardware specs, and experimental testing procedures are all covered in detail in the appendices. These parts aid in future system improvements or upgrades and boost the general comprehension of the project's execution.

The following are the primary appendices for this project:

- Appendix 1- Transmitter ESP32 Source Code
- Appendix 2- Receiver ESP32/ESP8266 Source Code
- Appendix 3- ESP32 and LoRa Pin Configuration Tables
- Appendix 4- GSM AT Command Reference
- Appendix 5- Hardware Component Specifications
- Appendix 6- Relay Module Connection Details

- Appendix 7- Experimental Testing and Serial Monitor Outputs

These appendices contain further technical knowledge beyond the main report chapters and offer full implementation support for the suggested smart home automation system.

REFERENCES

- Teymourzadeh, R., Ahmed, S. A., Chan, K. W., & Hoong, M. V. (2013). Smart GSM based home automation system. In Proceedings of the IEEE Conference on Systems, Process and Control (ICSPC) (pp. 6–10). Kuala Lumpur, Malaysia.
- Gambi, E., Montanini, L., Pigini, D., Ciattaglia, G., & Spinsante, S. (2018). A home automation architecture based on LoRa technology and Message Queue Telemetry Transfer Protocol. *International Journal of Distributed Sensor Networks*, 14(10).
- Shahjalal, M., Hossain, M. M., Alam, M. K., Islam, A. K. M., & Jang, Y. M. (2021). Smart monitoring and controlling of appliances using LoRa based IoT system. *Designs*, 5(1), 17.
- Augustin, A., Yi, J., Clausen, T., & Townsley, W. M. (2016). A study of LoRa: Long range and low power networks for the Internet of Things. *Sensors*, 16(9), 1466.
- Srivastava, N. (2020). Home automation using ESP32 and IoT. In Proceedings of the IEEE International Conference on Electronics, Communication and Aerospace Technology (ICECA). Coimbatore, India.
- Yar, H., Imran, A. S., Khan, Z. A., Sajjad, M., & Kastrati, Z. (2021). Towards smart home automation using IoT-enabled edge-computing paradigm. *Sensors*, 21(14), 4932.
- Khamees, M., Al-Raweshidy, H., & Al-Nidawi, M. A. (2018). Design and implementation of a smart home automation system based on Global System for Mobile Communications. *Journal of Applied Engineering Science*, 16(4).
- Lavric, A., & Popa, V. (2017). A LoRaWAN: Long range wide area networks study. In Proceedings of the IEEE International Conference on Electromechanical and Energy Systems (SIELMEN). Craiova, Romania.
- Obinna, T., Anosike, A., Nwokoye, E., & Okonkwo, B. (2020). GSM based home automation system. *International Journal of Computer Science and Information Technology*, 12(5)
- SIMCom Wireless Solutions. (2015). SIM800L hardware design manual (Rev. 1.05).
- Shanghai, China.

- Munir, M. S., Bajwa, I. S., & Cheema, S. M. (2019). An intelligent and secure smart watering system using fuzzy logic and blockchain. *Computers & Electrical Engineering*, 77, 109–119.
- Khan, M. A., Sajjad, I. A., Tahir, M., & Haseeb, A. (2022). IoT application for energy management in smart homes. *Engineering Proceedings*, 20(1), 43.
- Mukhopadhyay, S. C. (2015). Wearable sensors for human activity monitoring: A review. *IEEE Sensors Journal*, 15(3), 1321–1330.
- Kumar, R. (2024). Smart space environments: Key challenges and innovative solutions using LoRaWAN. *arXiv preprint arXiv:2410.20484*.
- Jouhari, M., Amhoud, E. M., Saeed, N., & Alouini, M.-S. (2023). A survey on scalable LoRaWAN for massive IoT: Recent advances, potentials, and challenges. *IEEE Communications Surveys & Tutorials*, 25(3), 1841–1876.
- Georgiou, O., & Raza, U. (2017). Low power wide area network analysis: Can LoRa scale? *IEEE Wireless Communications Letters*, 6(2), 162–165.