Drell-Yan Signal Efficiency and Acceptance Comparison Tables (RS57 – RS70)

November 3, 2026

Contents

1 Roadset RS57 Comparison Tables **2**
- 1.1 RS57 – LH2 Target . . . 2
- 1.2 RS57 – LD2 Target . . . 2

2 Roadset RS59 Comparison Tables **3**
- 2.1 RS59 – LH2 Target . . . 3
- 2.2 RS59 – LD2 Target . . . 3

3 Roadset RS62 Comparison Tables **4**
- 3.1 RS62 – LH2 Target . . . 4
- 3.2 RS62 – LD2 Target . . . 4

4 Roadset RS67 Comparison Tables **5**
- 4.1 RS67 – LH2 Target . . . 5
- 4.2 RS67 – LD2 Target . . . 5

5 Roadset RS70 Comparison Tables **6**
- 5.1 RS70 – LH2 Target . . . 6
- 5.2 RS70 – LD2 Target . . . 6

6 Combined All-Roadset Comparison Tables (RS57 – RS70) **7**
- 6.1 Combined LH2 Target (All Roadsets) . . . 7
- 6.2 Combined LD2 Target (All Roadsets) . . . 9

1 Roadset RS57 Comparison Tables

1.1 RS57 – LH2 Target

Table 1: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LH2 (RS57). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS57	[0.00, 0.32)	0.7254 ± 0.0078 (0.6994 ± 0.0078)	592.7504 ± 29.3719 (614.8076 ± 30.4648)	0.017079 ± 0.000772 (0.019414 ± 0.000441)
RS57	[0.32, 0.49)	0.7226 ± 0.0081 (0.7056 ± 0.0077)	629.6391 ± 30.7881 (644.8016 ± 31.5295)	0.015731 ± 0.000676 (0.018594 ± 0.000392)
RS57	[0.49, 0.63)	0.7056 ± 0.0084 (0.6983 ± 0.0069)	678.8519 ± 32.6578 (685.9827 ± 33.0008)	0.015673 ± 0.000671 (0.017444 ± 0.000378)
RS57	[0.63, 0.77)	0.7401 ± 0.0085 (0.7465 ± 0.0084)	559.3894 ± 29.7260 (554.6091 ± 29.4720)	0.013498 ± 0.000600 (0.016789 ± 0.000357)
RS57	[0.77, 0.95)	0.7200 ± 0.0083 (0.7226 ± 0.0078)	661.1379 ± 32.6328 (658.7607 ± 32.5155)	0.013773 ± 0.000532 (0.015105 ± 0.000297)
RS57	[0.95, 1.18)	0.7131 ± 0.0092 (0.7522 ± 0.0074)	602.9886 ± 33.4206 (571.6436 ± 31.6833)	0.011832 ± 0.000456 (0.012398 ± 0.000249)
RS57	[1.18, 1.80)	0.6848 ± 0.0104 (0.7632 ± 0.0072)	588.5218 ± 36.2155 (528.0118 ± 32.4920)	0.007889 ± 0.000280 (0.008227 ± 0.000153)

1.2 RS57 – LD2 Target

Table 2: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LD2 (RS57). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS57	[0.00, 0.32)	0.7272 ± 0.0055 (0.6939 ± 0.0073)	671.0350 ± 31.2961 (703.3049 ± 32.8011)	0.018048 ± 0.000557 (0.020298 ± 0.000441)
RS57	[0.32, 0.49)	0.7205 ± 0.0056 (0.6932 ± 0.0073)	766.1041 ± 33.9390 (796.3381 ± 35.2784)	0.017107 ± 0.000492 (0.019066 ± 0.000392)
RS57	[0.49, 0.63)	0.7256 ± 0.0055 (0.6928 ± 0.0073)	738.6735 ± 33.1896 (773.7250 ± 34.7645)	0.016748 ± 0.000486 (0.017807 ± 0.000378)
RS57	[0.63, 0.77)	0.7267 ± 0.0057 (0.7081 ± 0.0073)	682.5356 ± 32.5640 (700.4422 ± 33.4183)	0.015873 ± 0.000454 (0.017477 ± 0.000357)
RS57	[0.77, 0.95)	0.7214 ± 0.0056 (0.7060 ± 0.0076)	734.6896 ± 34.0680 (750.7020 ± 34.8105)	0.014461 ± 0.000381 (0.015424 ± 0.000297)
RS57	[0.95, 1.18)	0.7159 ± 0.0062 (0.7391 ± 0.0076)	645.3170 ± 34.1000 (625.0455 ± 33.0288)	0.012216 ± 0.000323 (0.013143 ± 0.000249)
RS57	[1.18, 1.80)	0.6945 ± 0.0071 (0.7405 ± 0.0070)	614.8302 ± 36.2267 (576.6023 ± 33.9743)	0.008176 ± 0.000199 (0.008446 ± 0.000153)

2 Roadset RS59 Comparison Tables

2.1 RS59 – LH2 Target

Table 3: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LH2 (RS59). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS59	[0.00, 0.32)	0.7447 ± 0.0083 (0.7294 ± 0.0094)	132.9470 ± 14.2752 (135.7203 ± 14.5730)	0.016768 ± 0.000765 (0.019414 ± 0.000441)
RS59	[0.32, 0.49)	0.7072 ± 0.0086 (0.7264 ± 0.0072)	164.0360 ± 16.3694 (159.6875 ± 15.9355)	0.016532 ± 0.000693 (0.018594 ± 0.000392)
RS59	[0.49, 0.63)	0.7568 ± 0.0085 (0.7655 ± 0.0094)	128.1719 ± 14.4143 (126.7100 ± 14.2499)	0.015708 ± 0.000672 (0.017444 ± 0.000378)
RS59	[0.63, 0.77)	0.7044 ± 0.0090 (0.6803 ± 0.0069)	141.9653 ± 15.0242 (146.9971 ± 15.5567)	0.014024 ± 0.000611 (0.016789 ± 0.000357)
RS59	[0.77, 0.95)	0.7184 ± 0.0080 (0.7169 ± 0.0087)	168.4233 ± 16.4106 (168.7801 ± 16.4454)	0.013390 ± 0.000525 (0.015105 ± 0.000297)
RS59	[0.95, 1.18)	0.7080 ± 0.0090 (0.7485 ± 0.0089)	131.3576 ± 15.7916 (124.2426 ± 14.9363)	0.011870 ± 0.000457 (0.012398 ± 0.000249)
RS59	[1.18, 1.80)	0.6911 ± 0.0106 (0.7610 ± 0.0076)	157.7256 ± 18.5874 (143.2316 ± 16.8793)	0.007876 ± 0.000279 (0.008227 ± 0.000153)

2.2 RS59 – LD2 Target

Table 4: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LD2 (RS59). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS59	[0.00, 0.32)	0.7491 ± 0.0056 (0.7130 ± 0.0083)	146.8516 ± 14.5020 (154.2849 ± 15.2360)	0.018048 ± 0.000557 (0.020298 ± 0.000441)
RS59	[0.32, 0.49)	0.7351 ± 0.0055 (0.7030 ± 0.0084)	180.9325 ± 16.3813 (189.1780 ± 17.1279)	0.017115 ± 0.000492 (0.019066 ± 0.000392)
RS59	[0.49, 0.63)	0.7128 ± 0.0058 (0.6782 ± 0.0068)	178.1819 ± 16.3015 (187.2527 ± 17.1313)	0.016740 ± 0.000486 (0.017807 ± 0.000378)
RS59	[0.63, 0.77)	0.7432 ± 0.0054 (0.7189 ± 0.0090)	164.1543 ± 15.5756 (169.6952 ± 16.1013)	0.015873 ± 0.000454 (0.017477 ± 0.000357)
RS59	[0.77, 0.95)	0.7170 ± 0.0062 (0.7206 ± 0.0077)	165.9681 ± 16.6781 (165.1449 ± 16.5953)	0.014461 ± 0.000381 (0.015424 ± 0.000297)
RS59	[0.95, 1.18)	0.7298 ± 0.0064 (0.7299 ± 0.0068)	124.6922 ± 14.6942 (124.6698 ± 14.6916)	0.012216 ± 0.000323 (0.013143 ± 0.000249)
RS59	[1.18, 1.80)	0.7149 ± 0.0084 (0.8249 ± 0.0086)	111.9065 ± 16.5512 (96.9806 ± 14.3436)	0.008176 ± 0.000199 (0.008446 ± 0.000153)

3 Roadset RS62 Comparison Tables

3.1 RS62 – LH2 Target

Table 5: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LH2 (RS62). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS62	[0.00, 0.32)	0.7185 ± 0.0082 (0.6998 ± 0.0071)	1238.6805 ± 42.8974 (1270.3264 ± 44.0197)	0.017346 ± 0.000778 (0.019414 ± 0.000441)
RS62	[0.32, 0.49)	0.7214 ± 0.0083 (0.7003 ± 0.0069)	1448.6328 ± 46.6613 (1492.1224 ± 48.0197)	0.016862 ± 0.000699 (0.018594 ± 0.000392)
RS62	[0.49, 0.63)	0.7178 ± 0.0084 (0.7055 ± 0.0070)	1178.6403 ± 42.5323 (1194.9243 ± 43.2502)	0.016977 ± 0.000698 (0.017444 ± 0.000378)
RS62	[0.63, 0.77)	0.7099 ± 0.0085 (0.7018 ± 0.0068)	1293.1758 ± 45.1220 (1310.9056 ± 45.5967)	0.015061 ± 0.000633 (0.016789 ± 0.000357)
RS62	[0.77, 0.95)	0.7097 ± 0.0086 (0.7245 ± 0.0073)	1247.0405 ± 45.8115 (1217.3742 ± 44.8526)	0.013884 ± 0.000534 (0.015105 ± 0.000297)
RS62	[0.95, 1.18)	0.7077 ± 0.0085 (0.7166 ± 0.0072)	1222.3132 ± 44.9750 (1198.7874 ± 44.2857)	0.011893 ± 0.000457 (0.012398 ± 0.000249)
RS62	[1.18, 1.80)	0.6767 ± 0.0099 (0.7499 ± 0.0067)	1186.6758 ± 49.8745 (1069.5006 ± 44.9860)	0.008053 ± 0.000282 (0.008227 ± 0.000153)

3.2 RS62 – LD2 Target

Table 6: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LD2 (RS62). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS62	[0.00, 0.32)	0.7264 ± 0.0056 (0.6903 ± 0.0070)	1266.5575 ± 43.1852 (1334.2574 ± 45.4210)	0.017935 ± 0.000555 (0.020298 ± 0.000441)
RS62	[0.32, 0.49)	0.7198 ± 0.0058 (0.6935 ± 0.0067)	1489.3426 ± 47.4405 (1545.8723 ± 49.2411)	0.017707 ± 0.000501 (0.019066 ± 0.000392)
RS62	[0.49, 0.63)	0.7061 ± 0.0059 (0.6861 ± 0.0064)	1421.9329 ± 47.2278 (1463.4280 ± 48.6060)	0.016331 ± 0.000480 (0.017807 ± 0.000378)
RS62	[0.63, 0.77)	0.7171 ± 0.0059 (0.6925 ± 0.0065)	1202.1053 ± 42.9378 (1244.7049 ± 44.4594)	0.015013 ± 0.000442 (0.017477 ± 0.000357)
RS62	[0.77, 0.95)	0.7085 ± 0.0059 (0.6955 ± 0.0065)	1335.2327 ± 46.5137 (1360.0948 ± 47.3798)	0.015065 ± 0.000388 (0.015424 ± 0.000297)
RS62	[0.95, 1.18)	0.7061 ± 0.0062 (0.7137 ± 0.0067)	1240.6728 ± 46.7162 (1224.6504 ± 46.2609)	0.012283 ± 0.000324 (0.013143 ± 0.000249)
RS62	[1.18, 1.80)	0.6814 ± 0.0069 (0.7197 ± 0.0065)	1119.8134 ± 48.1200 (1060.1873 ± 45.5578)	0.008446 ± 0.000202 (0.008446 ± 0.000153)

4 Roadset RS67 Comparison Tables

4.1 RS67 – LH2 Target

Table 7: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LH2 (RS67). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS67	[0.00, 0.32)	0.7529 ± 0.0042 (0.6985 ± 0.0067)	3576.9845 ± 70.9217 (3948.4393 ± 77.3611)	0.018325 ± 0.000428 (0.019414 ± 0.000441)
RS67	[0.32, 0.49)	0.7541 ± 0.0043 (0.6993 ± 0.0067)	3807.3049 ± 73.2256 (4224.1622 ± 80.3084)	0.017763 ± 0.000382 (0.018594 ± 0.000392)
RS67	[0.49, 0.63)	0.7504 ± 0.0043 (0.6978 ± 0.0068)	3560.5734 ± 72.3514 (3928.0505 ± 78.9231)	0.016939 ± 0.000373 (0.017444 ± 0.000378)
RS67	[0.63, 0.77)	0.7477 ± 0.0043 (0.6948 ± 0.0067)	3391.7117 ± 71.2736 (3714.6064 ± 77.5173)	0.015920 ± 0.000348 (0.016789 ± 0.000357)
RS67	[0.77, 0.95)	0.7448 ± 0.0044 (0.6937 ± 0.0068)	3700.2820 ± 76.2584 (4059.6564 ± 82.7908)	0.014951 ± 0.000296 (0.015105 ± 0.000297)
RS67	[0.95, 1.18)	0.7364 ± 0.0046 (0.6869 ± 0.0068)	3320.0846 ± 75.4220 (3636.6532 ± 81.7340)	0.012885 ± 0.000254 (0.012398 ± 0.000249)
RS67	[1.18, 1.80)	0.7203 ± 0.0050 (0.6738 ± 0.0070)	3240.1092 ± 81.0655 (3521.6016 ± 87.3563)	0.008912 ± 0.000159 (0.008227 ± 0.000153)

4.2 RS67 – LD2 Target

Table 8: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LD2 (RS67). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS67	[0.00, 0.32)	0.7383 ± 0.0044 (0.6824 ± 0.0062)	4144.5377 ± 77.2141 (4557.6537 ± 84.3385)	0.018992 ± 0.000431 (0.020298 ± 0.000441)
RS67	[0.32, 0.49)	0.7406 ± 0.0044 (0.6845 ± 0.0063)	4400.6172 ± 80.1012 (4860.7424 ± 87.6234)	0.018741 ± 0.000389 (0.019066 ± 0.000392)
RS67	[0.49, 0.63)	0.7356 ± 0.0044 (0.6813 ± 0.0062)	4053.8929 ± 77.2620 (4472.4684 ± 84.3330)	0.017840 ± 0.000378 (0.017807 ± 0.000378)
RS67	[0.63, 0.77)	0.7347 ± 0.0045 (0.6805 ± 0.0062)	3853.3000 ± 76.7429 (4242.3711 ± 83.7600)	0.016834 ± 0.000354 (0.017477 ± 0.000357)
RS67	[0.77, 0.95)	0.7287 ± 0.0045 (0.6759 ± 0.0063)	4398.3809 ± 83.4655 (4829.2597 ± 90.9895)	0.015321 ± 0.000296 (0.015424 ± 0.000297)
RS67	[0.95, 1.18)	0.7229 ± 0.0047 (0.6711 ± 0.0064)	3719.5086 ± 80.3108 (4069.2524 ± 87.2014)	0.013341 ± 0.000255 (0.013143 ± 0.000249)
RS67	[1.18, 1.80)	0.7129 ± 0.0053 (0.6635 ± 0.0066)	3509.4895 ± 85.0441 (3843.3789 ± 92.1741)	0.009213 ± 0.000160 (0.008446 ± 0.000153)

5 Roadset RS70 Comparison Tables

5.1 RS70 – LH2 Target

Table 9: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LH2 (RS70). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS70	[0.00, 0.32)	0.6946 ± 0.0092 (0.6912 ± 0.0061)	375.7334 ± 24.6418 (377.6268 ± 24.7660)	0.016654 ± 0.000762 (0.019414 ± 0.000441)
RS70	[0.32, 0.49)	0.7170 ± 0.0089 (0.6966 ± 0.0065)	425.4087 ± 25.2220 (437.8531 ± 25.9599)	0.017369 ± 0.000710 (0.018594 ± 0.000392)
RS70	[0.49, 0.63)	0.7045 ± 0.0087 (0.7015 ± 0.0069)	359.1260 ± 23.8792 (360.6578 ± 23.9810)	0.016235 ± 0.000683 (0.017444 ± 0.000378)
RS70	[0.63, 0.77)	0.6986 ± 0.0085 (0.6775 ± 0.0062)	393.6253 ± 24.3332 (405.8784 ± 25.0907)	0.015614 ± 0.000644 (0.016789 ± 0.000357)
RS70	[0.77, 0.95)	0.6990 ± 0.0086 (0.6913 ± 0.0065)	430.6447 ± 25.9508 (435.4225 ± 26.2387)	0.014777 ± 0.000551 (0.015105 ± 0.000297)
RS70	[0.95, 1.18)	0.6950 ± 0.0095 (0.7141 ± 0.0065)	384.1995 ± 25.8611 (373.9200 ± 25.1692)	0.012866 ± 0.000475 (0.012398 ± 0.000249)
RS70	[1.18, 1.80)	0.6624 ± 0.0110 (0.7206 ± 0.0062)	336.6620 ± 26.8794 (309.4476 ± 24.7065)	0.008346 ± 0.000287 (0.008227 ± 0.000153)

5.2 RS70 – LD2 Target

Table 10: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LD2 (RS70). Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS70	[0.00, 0.32)	0.7050 ± 0.0061 (0.6657 ± 0.0058)	442.5388 ± 25.5311 (468.6783 ± 27.0391)	0.018640 ± 0.000566 (0.020298 ± 0.000441)
RS70	[0.32, 0.49)	0.7218 ± 0.0061 (0.6924 ± 0.0064)	495.9520 ± 27.3583 (517.0795 ± 28.5237)	0.018456 ± 0.000511 (0.019066 ± 0.000392)
RS70	[0.49, 0.63)	0.7085 ± 0.0060 (0.6702 ± 0.0059)	464.3488 ± 26.2914 (490.8712 ± 27.7931)	0.017477 ± 0.000496 (0.017807 ± 0.000378)
RS70	[0.63, 0.77)	0.6984 ± 0.0062 (0.6740 ± 0.0059)	463.8876 ± 27.3161 (480.7470 ± 28.3089)	0.016688 ± 0.000465 (0.017477 ± 0.000357)
RS70	[0.77, 0.95)	0.6955 ± 0.0063 (0.6792 ± 0.0058)	488.8491 ± 28.3212 (500.5848 ± 29.0011)	0.014926 ± 0.000387 (0.015424 ± 0.000297)
RS70	[0.95, 1.18)	0.6840 ± 0.0067 (0.6980 ± 0.0059)	416.6742 ± 27.2343 (408.3257 ± 26.6887)	0.012947 ± 0.000333 (0.013143 ± 0.000249)
RS70	[1.18, 1.80)	0.6885 ± 0.0078 (0.7621 ± 0.0068)	318.0774 ± 26.5040 (287.3750 ± 23.9457)	0.008756 ± 0.000206 (0.008446 ± 0.000153)

6 Combined All-Roadset Comparison Tables (RS57 – RS70)

6.1 Combined LH2 Target (All Roadsets)

Table 11: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LH2. Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS57	[0.00, 0.32)	0.7254 ± 0.0078 (0.6994 ± 0.0078)	592.7504 ± 29.3719 (614.8076 ± 30.4648)	0.017079 ± 0.000772 (0.019414 ± 0.000441)
RS57	[0.32, 0.49)	0.7226 ± 0.0081 (0.7056 ± 0.0077)	629.6391 ± 30.7881 (644.8016 ± 31.5295)	0.015731 ± 0.000676 (0.018594 ± 0.000392)
RS57	[0.49, 0.63)	0.7056 ± 0.0084 (0.6983 ± 0.0069)	678.8519 ± 32.6578 (685.9827 ± 33.0008)	0.015673 ± 0.000671 (0.017444 ± 0.000378)
RS57	[0.63, 0.77)	0.7401 ± 0.0085 (0.7465 ± 0.0084)	559.3894 ± 29.7260 (554.6091 ± 29.4720)	0.013498 ± 0.000600 (0.016789 ± 0.000357)
RS57	[0.77, 0.95)	0.7200 ± 0.0083 (0.7226 ± 0.0078)	661.1379 ± 32.6328 (658.7607 ± 32.5155)	0.013773 ± 0.000532 (0.015105 ± 0.000297)
RS57	[0.95, 1.18)	0.7131 ± 0.0092 (0.7522 ± 0.0074)	602.9886 ± 33.4206 (571.6436 ± 31.6833)	0.011832 ± 0.000456 (0.012398 ± 0.000249)
RS57	[1.18, 1.80)	0.6848 ± 0.0104 (0.7632 ± 0.0072)	588.5218 ± 36.2155 (528.0118 ± 32.4920)	0.007889 ± 0.000280 (0.008227 ± 0.000153)
RS59	[0.00, 0.32)	0.7447 ± 0.0083 (0.7294 ± 0.0094)	132.9470 ± 14.2752 (135.7203 ± 14.5730)	0.016768 ± 0.000765 (0.019414 ± 0.000441)
RS59	[0.32, 0.49)	0.7072 ± 0.0086 (0.7264 ± 0.0072)	164.0360 ± 16.3694 (159.6875 ± 15.9355)	0.016532 ± 0.000693 (0.018594 ± 0.000392)
RS59	[0.49, 0.63)	0.7568 ± 0.0085 (0.7655 ± 0.0094)	128.1719 ± 14.4143 (126.7100 ± 14.2499)	0.015708 ± 0.000672 (0.017444 ± 0.000378)
RS59	[0.63, 0.77)	0.7044 ± 0.0090 (0.6803 ± 0.0069)	141.9653 ± 15.0242 (146.9971 ± 15.5567)	0.014024 ± 0.000611 (0.016789 ± 0.000357)
RS59	[0.77, 0.95)	0.7184 ± 0.0080 (0.7169 ± 0.0087)	168.4233 ± 16.4106 (168.7801 ± 16.4454)	0.013390 ± 0.000525 (0.015105 ± 0.000297)
RS59	[0.95, 1.18)	0.7080 ± 0.0090 (0.7485 ± 0.0089)	131.3576 ± 15.7916 (124.2426 ± 14.9363)	0.011870 ± 0.000457 (0.012398 ± 0.000249)
RS59	[1.18, 1.80)	0.6911 ± 0.0106 (0.7610 ± 0.0076)	157.7256 ± 18.5874 (143.2316 ± 16.8793)	0.007876 ± 0.000279 (0.008227 ± 0.000153)
RS62	[0.00, 0.32)	0.7185 ± 0.0082 (0.6998 ± 0.0071)	1238.6805 ± 42.8974 (1270.3264 ± 44.0197)	0.017346 ± 0.000778 (0.019414 ± 0.000441)
RS62	[0.32, 0.49)	0.7214 ± 0.0083 (0.7003 ± 0.0069)	1448.6328 ± 46.6613 (1492.1224 ± 48.0197)	0.016862 ± 0.000699 (0.018594 ± 0.000392)
RS62	[0.49, 0.63)	0.7178 ± 0.0084 (0.7055 ± 0.0070)	1178.6403 ± 42.5323 (1194.9243 ± 43.2502)	0.016977 ± 0.000698 (0.017444 ± 0.000378)
RS62	[0.63, 0.77)	0.7099 ± 0.0085 (0.7018 ± 0.0068)	1293.1758 ± 45.1220 (1310.9056 ± 45.5967)	0.015061 ± 0.000633 (0.016789 ± 0.000357)

Continued on next page

Table 11 – continued from previous page

RoadID	p_T bin [GeV]	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	Acceptance Correction
RS62	[0.77, 0.95)	0.7097 ± 0.0086 (0.7245 ± 0.0073)	1247.0405 ± 45.8115 (1217.3742 ± 44.8526)	0.013884 ± 0.000534 (0.015105 ± 0.000297)
RS62	[0.95, 1.18)	0.7077 ± 0.0085 (0.7166 ± 0.0072)	1222.3132 ± 44.9750 (1198.7874 ± 44.2857)	0.011893 ± 0.000457 (0.012398 ± 0.000249)
RS62	[1.18, 1.80)	0.6767 ± 0.0099 (0.7499 ± 0.0067)	1186.6758 ± 49.8745 (1069.5006 ± 44.9860)	0.008053 ± 0.000282 (0.008227 ± 0.000153)
RS67	[0.00, 0.32)	0.7529 ± 0.0042 (0.6985 ± 0.0067)	3576.9845 ± 70.9217 (3948.4393 ± 77.3611)	0.018325 ± 0.000428 (0.019414 ± 0.000441)
RS67	[0.32, 0.49)	0.7541 ± 0.0043 (0.6993 ± 0.0067)	3807.3049 ± 73.2256 (4224.1622 ± 80.3084)	0.017763 ± 0.000382 (0.018594 ± 0.000392)
RS67	[0.49, 0.63)	0.7504 ± 0.0043 (0.6978 ± 0.0068)	3560.5734 ± 72.3514 (3928.0505 ± 78.9231)	0.016939 ± 0.000373 (0.017444 ± 0.000378)
RS67	[0.63, 0.77)	0.7477 ± 0.0043 (0.6948 ± 0.0067)	3391.7117 ± 71.2736 (3714.6064 ± 77.5173)	0.015920 ± 0.000348 (0.016789 ± 0.000357)
RS67	[0.77, 0.95)	0.7448 ± 0.0044 (0.6937 ± 0.0068)	3700.2820 ± 76.2584 (4059.6564 ± 82.7908)	0.014951 ± 0.000296 (0.015105 ± 0.000297)
RS67	[0.95, 1.18)	0.7364 ± 0.0046 (0.6869 ± 0.0068)	3320.0846 ± 75.4220 (3636.6532 ± 81.7340)	0.012885 ± 0.000254 (0.012398 ± 0.000249)
RS67	[1.18, 1.80)	0.7203 ± 0.0050 (0.6738 ± 0.0070)	3240.1092 ± 81.0655 (3521.6016 ± 87.3563)	0.008912 ± 0.000159 (0.008227 ± 0.000153)
RS70	[0.00, 0.32)	0.6946 ± 0.0092 (0.6912 ± 0.0061)	375.7334 ± 24.6418 (377.6268 ± 24.7660)	0.016654 ± 0.000762 (0.019414 ± 0.000441)
RS70	[0.32, 0.49)	0.7170 ± 0.0089 (0.6966 ± 0.0065)	425.4087 ± 25.2220 (437.8531 ± 25.9599)	0.017369 ± 0.000710 (0.018594 ± 0.000392)
RS70	[0.49, 0.63)	0.7045 ± 0.0087 (0.7015 ± 0.0069)	359.1260 ± 23.8792 (360.6578 ± 23.9810)	0.016235 ± 0.000683 (0.017444 ± 0.000378)
RS70	[0.63, 0.77)	0.6986 ± 0.0085 (0.6775 ± 0.0062)	393.6253 ± 24.3332 (405.8784 ± 25.0907)	0.015614 ± 0.000644 (0.016789 ± 0.000357)
RS70	[0.77, 0.95)	0.6990 ± 0.0086 (0.6913 ± 0.0065)	430.6447 ± 25.9508 (435.4225 ± 26.2387)	0.014777 ± 0.000551 (0.015105 ± 0.000297)
RS70	[0.95, 1.18)	0.6950 ± 0.0095 (0.7141 ± 0.0065)	384.1995 ± 25.8611 (373.9200 ± 25.1692)	0.012866 ± 0.000475 (0.012398 ± 0.000249)
RS70	[1.18, 1.80)	0.6624 ± 0.0110 (0.7206 ± 0.0062)	336.6620 ± 26.8794 (309.4476 ± 24.7065)	0.008346 ± 0.000287 (0.008227 ± 0.000153)

6.2 Combined LD2 Target (All Roadsets)

Table 12: Comparison of Latest vs. Previous Signal Efficiency, Corrected Yield, and Acceptance Correction for LD2. Each cell displays the latest value ± error on top and the previous value in parentheses below.

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS57	[0.00, 0.32)	0.7272 ± 0.0055 (0.6939 ± 0.0073)	671.0350 ± 31.2961 (703.3049 ± 32.8011)	0.018048 ± 0.000557 (0.020298 ± 0.000441)
RS57	[0.32, 0.49)	0.7205 ± 0.0056 (0.6932 ± 0.0073)	766.1041 ± 33.9390 (796.3381 ± 35.2784)	0.017107 ± 0.000492 (0.019066 ± 0.000392)
RS57	[0.49, 0.63)	0.7256 ± 0.0055 (0.6928 ± 0.0073)	738.6735 ± 33.1896 (773.7250 ± 34.7645)	0.016748 ± 0.000486 (0.017807 ± 0.000378)
RS57	[0.63, 0.77)	0.7267 ± 0.0057 (0.7081 ± 0.0073)	682.5356 ± 32.5640 (700.4422 ± 33.4183)	0.015873 ± 0.000454 (0.017477 ± 0.000357)
RS57	[0.77, 0.95)	0.7214 ± 0.0056 (0.7060 ± 0.0076)	734.6896 ± 34.0680 (750.7020 ± 34.8105)	0.014461 ± 0.000381 (0.015424 ± 0.000297)
RS57	[0.95, 1.18)	0.7159 ± 0.0062 (0.7391 ± 0.0076)	645.3170 ± 34.1000 (625.0455 ± 33.0288)	0.012216 ± 0.000323 (0.013143 ± 0.000249)
RS57	[1.18, 1.80)	0.6945 ± 0.0071 (0.7405 ± 0.0070)	614.8302 ± 36.2267 (576.6023 ± 33.9743)	0.008176 ± 0.000199 (0.008446 ± 0.000153)
RS59	[0.00, 0.32)	0.7491 ± 0.0056 (0.7130 ± 0.0083)	146.8516 ± 14.5020 (154.2849 ± 15.2360)	0.018048 ± 0.000557 (0.020298 ± 0.000441)
RS59	[0.32, 0.49)	0.7351 ± 0.0055 (0.7030 ± 0.0084)	180.9325 ± 16.3813 (189.1780 ± 17.1279)	0.017115 ± 0.000492 (0.019066 ± 0.000392)
RS59	[0.49, 0.63)	0.7128 ± 0.0058 (0.6782 ± 0.0068)	178.1819 ± 16.3015 (187.2527 ± 17.1313)	0.016740 ± 0.000486 (0.017807 ± 0.000378)
RS59	[0.63, 0.77)	0.7432 ± 0.0054 (0.7189 ± 0.0090)	164.1543 ± 15.5756 (169.6952 ± 16.1013)	0.015873 ± 0.000454 (0.017477 ± 0.000357)
RS59	[0.77, 0.95)	0.7170 ± 0.0062 (0.7206 ± 0.0077)	165.9681 ± 16.6781 (165.1449 ± 16.5953)	0.014461 ± 0.000381 (0.015424 ± 0.000297)
RS59	[0.95, 1.18)	0.7298 ± 0.0064 (0.7299 ± 0.0068)	124.6922 ± 14.6942 (124.6698 ± 14.6916)	0.012216 ± 0.000323 (0.013143 ± 0.000249)
RS59	[1.18, 1.80)	0.7149 ± 0.0084 (0.8249 ± 0.0086)	111.9065 ± 16.5512 (96.9806 ± 14.3436)	0.008176 ± 0.000199 (0.008446 ± 0.000153)
RS62	[0.00, 0.32)	0.7264 ± 0.0056 (0.6903 ± 0.0070)	1266.5575 ± 43.1852 (1334.2574 ± 45.4210)	0.017935 ± 0.000555 (0.020298 ± 0.000441)
RS62	[0.32, 0.49)	0.7198 ± 0.0058 (0.6935 ± 0.0067)	1489.3426 ± 47.4405 (1545.8723 ± 49.2411)	0.017707 ± 0.000501 (0.019066 ± 0.000392)
RS62	[0.49, 0.63)	0.7061 ± 0.0059 (0.6861 ± 0.0064)	1421.9329 ± 47.2278 (1463.4280 ± 48.6060)	0.016331 ± 0.000480 (0.017807 ± 0.000378)
RS62	[0.63, 0.77)	0.7171 ± 0.0059 (0.6925 ± 0.0065)	1202.1053 ± 42.9378 (1244.7049 ± 44.4594)	0.015013 ± 0.000442 (0.017477 ± 0.000357)
RS62	[0.77, 0.95)	0.7085 ± 0.0059 (0.6955 ± 0.0065)	1335.2327 ± 46.5137 (1360.0948 ± 47.3798)	0.015065 ± 0.000388 (0.015424 ± 0.000297)

Continued on next page

Table 12 – continued from previous page

RoadID	p_T **bin [GeV]**	$\langle E_{\text{signal}} \rangle$	$Y_{\text{corrected}}$	**Acceptance Correction**
RS62	[0.95, 1.18)	0.7061 ± 0.0062	1240.6728 ± 46.7162	0.012283 ± 0.000324
		(0.7137 ± 0.0067)	(1224.6504 ± 46.2609)	(0.013143 ± 0.000249)
RS62	[1.18, 1.80)	0.6814 ± 0.0069	1119.8134 ± 48.1200	0.008446 ± 0.000202
		(0.7197 ± 0.0065)	(1060.1873 ± 45.5578)	(0.008446 ± 0.000153)
RS67	[0.00, 0.32)	0.7383 ± 0.0044	4144.5377 ± 77.2141	0.018992 ± 0.000431
		(0.6824 ± 0.0062)	(4557.6537 ± 84.3385)	(0.020298 ± 0.000441)
RS67	[0.32, 0.49)	0.7406 ± 0.0044	4400.6172 ± 80.1012	0.018741 ± 0.000389
		(0.6845 ± 0.0063)	(4860.7424 ± 87.6234)	(0.019066 ± 0.000392)
RS67	[0.49, 0.63)	0.7356 ± 0.0044	4053.8929 ± 77.2620	0.017840 ± 0.000378
		(0.6813 ± 0.0062)	(4472.4684 ± 84.3330)	(0.017807 ± 0.000378)
RS67	[0.63, 0.77)	0.7347 ± 0.0045	3853.3000 ± 76.7429	0.016834 ± 0.000354
		(0.6805 ± 0.0062)	(4242.3711 ± 83.7600)	(0.017477 ± 0.000357)
RS67	[0.77, 0.95)	0.7287 ± 0.0045	4398.3809 ± 83.4655	0.015321 ± 0.000296
		(0.6759 ± 0.0063)	(4829.2597 ± 90.9895)	(0.015424 ± 0.000297)
RS67	[0.95, 1.18)	0.7229 ± 0.0047	3719.5086 ± 80.3108	0.013341 ± 0.000255
		(0.6711 ± 0.0064)	(4069.2524 ± 87.2014)	(0.013143 ± 0.000249)
RS67	[1.18, 1.80)	0.7129 ± 0.0053	3509.4895 ± 85.0441	0.009213 ± 0.000160
		(0.6635 ± 0.0066)	(3843.3789 ± 92.1741)	(0.008446 ± 0.000153)
RS70	[0.00, 0.32)	0.7050 ± 0.0061	442.5388 ± 25.5311	0.018640 ± 0.000566
		(0.6657 ± 0.0058)	(468.6783 ± 27.0391)	(0.020298 ± 0.000441)
RS70	[0.32, 0.49)	0.7218 ± 0.0061	495.9520 ± 27.3583	0.018456 ± 0.000511
		(0.6924 ± 0.0064)	(517.0795 ± 28.5237)	(0.019066 ± 0.000392)
RS70	[0.49, 0.63)	0.7085 ± 0.0060	464.3488 ± 26.2914	0.017477 ± 0.000496
		(0.6702 ± 0.0059)	(490.8712 ± 27.7931)	(0.017807 ± 0.000378)
RS70	[0.63, 0.77)	0.6984 ± 0.0062	463.8876 ± 27.3161	0.016688 ± 0.000465
		(0.6740 ± 0.0059)	(480.7470 ± 28.3089)	(0.017477 ± 0.000357)
RS70	[0.77, 0.95)	0.6955 ± 0.0063	488.8491 ± 28.3212	0.014926 ± 0.000387
		(0.6792 ± 0.0058)	(500.5848 ± 29.0011)	(0.015424 ± 0.000297)
RS70	[0.95, 1.18)	0.6840 ± 0.0067	416.6742 ± 27.2343	0.012947 ± 0.000333
		(0.6980 ± 0.0059)	(408.3257 ± 26.6887)	(0.013143 ± 0.000249)
RS70	[1.18, 1.80)	0.6885 ± 0.0078	318.0774 ± 26.5040	0.008756 ± 0.000206
		(0.7621 ± 0.0068)	(287.3750 ± 23.9457)	(0.008446 ± 0.000153)