

CH-230-A

Programming in C and C++

C/C++

Tutorial 11

Dr. Kinga Lipskoch

Fall 2019

C++ References (1)

A reference is a constant pointer which is automatically dereferenced and that has to be initialized when it is created

- ▶ Constant means that it cannot be modified to reference a different entity
 - ▶ But you can of course modify what it is pointing to
- ▶ Cannot reference NULL

```
1  int a = 3;
2  int &reference = a;
3  reference++;
4  cout << a;           // prints 4
```

C++ References (2)

- ▶ References create a synonym (alias)
 - ▶ Previous example: acting on a reference is the same that acting on the variable `a`
- ▶ The first use of references is for creating functions and methods having out parameters
 - ▶ Indeed C++ references can be used even if you do not exploit the object-oriented capabilities of the language
- ▶ `outparameters.cpp`

outparameters.cpp

```
1  #include <iostream>
2  using namespace std;
3  /* This function takes two parameters. Only modifications
4     done on the first one are visible outside. */
5  void oldStyle(int *outval, int inval)
6  {
7     cout << "Inside oldStyle" << endl;
8     inval++;
9     (*outval)++;           // need to dereference
10 }
11 /* Also this function takes two parameters. Again, only
12    modifications done on the first one are visible outside. */
13 void newStyle(int &outval, int inval)
14 {
15     cout << "Inside newStyle" << endl;
16     inval++;
17     outval++;              // no need to dereference
18 }
19 int main(int argc, char** argv)
20 {
21     int a = 0, b = 0;
22     cout << a << " " << b << endl;
23     oldStyle(&a, b);       // needs to take the address
24     cout << a << " " << b << endl;
25     a = b = 0;             // reset to initial values
26     newStyle(a, b);        // no specific syntax to pass the parameter
27     cout << a << " " << b << endl;
28     return 0;
29 }
```

Passing const Object References

The usual way to pass an input parameter to a function or method, is to pass it as a `const` reference

- ▶ Improved efficiency + cannot modify
 - ▶ No need to create a temporary copy of the object
- ▶ No need to define a copy constructor (more soon)

```
1 void method(const string& byvaluepar) {  
2     // use it as a constant object  
3 }
```

- ▶ All previous examples should be rewritten according to this indication

Passing Objects by Reference

- ▶ Another case: use a reference when you wish to pass an object by reference, i.e., if modifications have to be seen outside

```
1 void modifyString(string& tomod) {  
2     tomod.assign("new value");  
3     // non const as modification has to be seen  
4 }
```

- ▶ The use is consistent with basic data types

Dynamic Memory Allocation

- ▶ C++ has an operator for dynamic memory allocation
 - ▶ It replaces the use of the C `malloc` function
 - ▶ Easier and safer
- ▶ The operator is called `new`
 - ▶ It can be applied both to user defined types (classes) and to native types

Using `new` for Predefined Data Types

- ▶ The operator returns a pointer to a specified type
- ▶ It automatically calculates the amount of memory necessary
 - ▶ It only requires the type and the number of "objects" to hold
- ▶ `newarrays.cpp`
- ▶ Note: same syntax for pointers to different types (no casting needed)

Dynamic Memory Deallocation

- ▶ As `malloc` has the companion function `free`, the operator `new` is coupled with the operator `delete`, which removes an object from memory
- ▶ `delete` requires the address of the object(s) to be deleted from the memory

```
1  int *a, *b;  
2  a = new int;  
3  b = new int[40];  
4  delete a;  
5  delete []b;
```

More on delete

- ▶ When `delete` is called to remove an object, the destructor is invoked before removing it
- ▶ Calling `delete` twice (or more) on the same object will result in an undefined behavior
- ▶ Calling `delete` on a `NULL` pointer will do nothing
 - ▶ Thus it could be advisable to set a pointer to `NULL` after calling `delete` (further `delete` will have no effect)
- ▶ Do not mix calls to `new` / `delete` with `malloc` / `free` – similar purpose, but predictably very bad result

new and delete for Arrays of Objects

- ▶ It is possible to dynamically create arrays of objects (instances of classes)
 - ▶ There must be a default (empty) constructor for the class (which will be called for every element of the array)
 - ▶ An array of objects must be explicitly deleted, by using the following syntax
`delete []ptr;`
 - ▶ In this way the compiler is able to call the destructor for every element before freeing memory
 - ▶ There is no need to specify how many elements
- ▶ `studentsrevised.cpp`

Even More on delete

- ▶ When you create objects via `new`, you should destroy them via `delete`
 - ▶ All the memory you get from the operating system should be returned
 - ▶ Again, your programs must avoid memory leaks
- ▶ Most of the bugs in early stage are due to bad / misplaced calls of `delete`
 - ▶ Many memory related errors cause severe problems

Constants (1)

- ▶ As in C, the keyword `const` is used to define values that do not change
- ▶ In C++ the use of constants is wider
 - ▶ Constants should be used instead of the preprocessor `#define` directive

```
1  // avoid #define SIZE 100
2  const int SIZE = 100;
3  // use this instead
```

- ▶ Why? Preprocessor directives can hide bugs which are nasty to find
- ▶ Constants can be inserted into header files, name clashes will be detected by the compiler

Constants (2)

- ▶ Methods or method parameters can be declared as `const`
 - ▶ Does not add information to the outside, but rather force the compiler to check that no modifications are attempted
 - ▶ Useful when dealing with temporarily generated objects
 - ▶ Useful for efficient parameter passing (more soon)
- ▶ `constantparameters.cpp`

const Objects

- ▶ Again, as classes are types, it is possible to declare `const` objects or to declare a method which accepts a `const` object
 - ▶ The syntax is the same
- ▶ For a `const` object it is not possible to modify its public data members

Constant Methods

- ▶ A constant method is a method which does not alter the object. Thus
 - ▶ It cannot modify data members
 - ▶ It may call only other `const` methods
- ▶ Constant methods are the only methods which can be called for constant objects
- ▶ `constclass.cpp`

Multiple Inclusions

- ▶ Class declarations go to header files
- ▶ Header files will be included in all the .cpp files that need their declarations
- ▶ What if a header file is included twice?
 - ▶ A repeated class declaration is an error
 - ▶ But a repeated function declaration is not (as long as the declarations are the same)
- ▶ Should the programmer take care of not including the file twice?
 - ▶ Almost impossible in big projects

Conditional Compilation

- ▶ The preprocessor can be used to avoid multiple inclusions
- ▶ The `#ifdef`, `#ifndef`, `#else`, `#endif` directives allow to exclude some parts of the code according to specified conditions
- ▶ They are to be used with the `#define` that you already know

The Structure of a Header File

```
1  /* Student.h */
2  #ifndef _STUDENT_H
3  #define _STUDENT_H
4  class student {
5      /* your class declaration */
6  };
7  #endif // this matches the initial #ifndef
```

How Does This Work?

- ▶ The first time the header is included the symbol `_STUDENT_H` is not defined
 - ▶ Then the class declaration is compiled and then the symbol is defined
- ▶ In all the subsequent inclusions the symbol is already defined and then the class declaration is skipped
- ▶ You must always protect (or guard) your header files with this mechanism