

1. “The register/sign-in form will open into a modal”

This means that when the user clicks **Register** or **Sign In**, the form appears in a small window layered over the current page instead of opening a separate webpage.

A modal normally:

- Appears in the center of the screen.
- Displays over the existing page.
- Places a dark or transparent overlay behind it.
- Keeps the user on the same page.
- Can be closed with an **X**, a Cancel button, or sometimes by clicking outside it.

For example, the user is viewing the home page:

Home | Products | About | Sign In

After clicking **Sign In**, a modal appears:

```
+-----+
| Sign In           X |
|                     |
| Email:  [          ] |
| Password: [         ] |
|                     |
|           [Sign In]  |
+-----+
```

The page remains visible behind the form.

A typical structure is:

```
<button id="openModal">Sign In</button>

<div id="signInModal" class="modal">
  <div class="modal-content">
    <button id="closeModal">&times;</button>

    <h2>Sign In</h2>

    <form>
      <label for="email">Email</label>
      <input type="email" id="email">

      <label for="password">Password</label>
      <input type="password" id="password">

      <button type="submit">Sign In</button>
    </form>
  </div>
</div>
```

JavaScript controls whether the modal is visible:

```
const modal = document.getElementById("signInModal");
const openButton = document.getElementById("openModal");
const closeButton = document.getElementById("closeModal");

openButton.addEventListener("click", function () {
```

```
modal.style.display = "block";
});

closeButton.addEventListener("click", function () {
    modal.style.display = "none";
});
```

The statement would be clearer as:

The registration and sign-in forms will open in modal windows.

The correct preposition is usually **in a modal**, not “onto a modal.”

2. “The site is responsive at standard breakpoints”

A **responsive website** automatically adjusts its layout to fit different screen sizes, such as:

- Desktop computers
- Laptops
- Tablets
- Mobile phones

A **breakpoint** is a screen width at which the page layout changes.

For example, a desktop navigation bar may display all links horizontally:

Home | Products | About | Contact | Sign In

On a smaller mobile screen, it may change to a menu button:



Similarly, three product cards displayed in one row on a desktop may become one card per row on a phone.

Common breakpoint ranges

There is no single mandatory set, but common breakpoints include:

```
/* Mobile-first base styles */
.container {
    width: 100%;
}

/* Tablet */
@media (min-width: 768px) {
    .container {
        width: 750px;
    }
}

/* Desktop */
@media (min-width: 1024px) {
    .container {
        width: 960px;
    }
}
```

```

}

/* Large desktop */
@media (min-width: 1200px) {
  .container {
    width: 1140px;
  }
}

```

The @media rules tell the browser to apply different CSS when the viewport reaches a particular width.

Example: responsive product cards

```

.products {
  display: grid;
  grid-template-columns: 1fr;
  gap: 20px;
}

```

On small screens, this creates one column:

```

[Product 1]

[Product 2]

[Product 3]

```

At the tablet breakpoint:

```

@media (min-width: 768px) {
  .products {
    grid-template-columns: repeat(2, 1fr);
  }
}

```

The layout changes to two columns:

```

[Product 1] [Product 2]

[Product 3]

```

At the desktop breakpoint:

```

@media (min-width: 1024px) {
  .products {
    grid-template-columns: repeat(3, 1fr);
  }
}

```

It changes to three columns:

```

[Product 1] [Product 2] [Product 3]

```

Therefore, the statement:

The site is responsive at standard breakpoints.

means that the site has been designed and tested so its navigation, text, images, forms, cards, and other components reorganize appropriately at commonly used mobile, tablet, and desktop screen widths.

A more precise requirement would be:

The website must provide responsive layouts for mobile, tablet, desktop, and large-desktop viewports, using appropriate CSS media-query breakpoints.