

Lab 1: Packet analysis at application layer using Wireshark

SCSR1213 Network Communications

Universiti Teknologi Malaysia

Objective:

1. Understanding of network protocols by observing the sequence of messages exchanged between two protocol entities, delving down into the details of protocol operation, and causing protocols to perform certain actions and then observing these actions and their consequences.
2. To introduce student with Wireshark software tool for packet analyzer.
3. To analyze protocol used in application layer such as http and dns.

Reference material: Computer Networking: A Top-Down Approach, 7th ed., J.F. Kurose and K.W. Ross.

Name : SABRINA HENG WEI QI

Metric No : A23CS0265

Section : 12

Name : CHAU YING JIA

Metric No : A23CS0213

Section : 12



Mark

PART A: Wireshark Getting Started

1.0 Introduction

The basic tool for observing the messages exchanged between executing protocol entities is called a **packet sniffer**. As the name suggests, a packet sniffer captures (“sniffs”) messages being sent/received from/by your computer; it will also typically store and/or display the contents of the various protocol fields in these captured messages. A packet sniffer itself is passive. It observes messages being sent and received by applications and protocols running on your computer, but never sends packets itself. Similarly, received packets are never explicitly addressed to the packet sniffer. Instead, a packet sniffer receives a *copy* of packets that are sent/received from/by application and protocols executing on your machine.

Figure A.1 shows the structure of a packet sniffer. At the right of Figure 1 are the protocols (in this case, Internet protocols) and applications (such as a web browser or ftp client) that normally run on your computer. The packet sniffer, shown within the dashed rectangle in Figure A.1 is an addition to the usual software in your computer, and consists of two parts. The **packet capture library** receives a copy of every link-layer frame that is sent from or received by your computer. In Figure A.1, the assumed physical media is an Ethernet, and so all upper-layer protocols are eventually encapsulated within an Ethernet frame. Capturing all link-layer frames thus gives you all messages sent/received from/by all protocols and applications executing in your computer.




Figure A.1: Packet sniffer structure

The second component of a packet sniffer is the **packet analyzer**, which displays the contents of all fields within a protocol message. In order to do so, the packet analyzer must “understand” the structure of all messages exchanged by protocols. The packet analyzer understands the format of Ethernet frames, and so can identify the IP datagram within an Ethernet frame. It also understands the IP datagram format, so that it can extract the TCP segment within the IP datagram. Finally, it understands the TCP segment structure, so it can extract the HTTP message contained in the TCP segment. Finally, it understands the HTTP protocol and so, for example, knows that the first bytes of an HTTP message will contain the string “GET,” “POST,” or “HEAD”.

2.0 Getting Wireshark Ready

- Download and install the Wireshark software
- Run Wireshark. Wireshark startup screen shown in Figure A.2.




Figure A.2: Initial Wireshark startup screen

- The Wireshark interface has five major components as shown in Figure A.3.




Figure A.3: Wireshark Graphical User Interface, during packet capture and

- The **command menus** are standard pulldown menus located at the top of the window.
- The **packet display filter field**, into which a protocol name or other information can be entered in order to filter the information displayed in the packet-listing window.
- The **packet-listing window** displays a one-line summary for each packet captured, including the packet number, the time at which the packet was captured, the packet's source and destination addresses, the protocol type, and protocol-specific information contained in the packet.
- The **packet-header details window** provides details about the packet selected (highlighted) in the packet-listing window. These details include information about the Ethernet frame and IP datagram that contains this packet. The amount of Ethernet and IP-layer detail displayed can be expanded or minimized by clicking on the plus minus boxes to the left of the Ethernet frame or IP datagram line in the packet details window. If the packet has been carried over TCP or UDP, TCP or UDP details will also be displayed, which can similarly be expanded or minimized. Finally, details about the highest-level protocol that sent or received this packet are also provided.
- The **packet-contents window** displays the entire contents of the captured frame, in both ASCII and hexadecimal format.

3.0 Test Run Wireshark

- Start up the Wireshark software.
- To begin packet capture, select the Capture pull down menu and pick Options menu. Select appropriate interfaces on your compute and click Start button to begin packet capture. Refer to Figure A.4




Figure A.4: Capture and Options Menu

- Once you begin packet capture, result will be shown as in Figure A.5.




Figure A.5: Wireshark packet capture result

- By selecting Capture pulldown menu and selecting Stop, you can stop packet capture.

- Type “arp” in packet display filter field and press Enter key. This will cause only ARP message to be displayed in the packet-listing window as shown in Figure A.6.




Figure A.6: ARP packet capture

- To save the trace result, use File pulldown menu and select Save function as shown in Figure A.7.





Figure A.7: Save Wireshark trace result

PART B: HTTP Trace

In this part, we'll explore several aspects of the HTTP protocol: the basic GET/response interaction, HTTP message formats and retrieving HTML files with embedded objects. Before beginning these labs, you might want to review Section 2.2 of the textbook.

B.1 The Basic HTTP GET/response interaction

- Open packet trace file **lab1-http-B01.pcapng**.
- Enter “**http**” (just the letters, not the quotation marks) in the **packet display filter field**, so that only captured HTTP messages will be displayed later in the packet-listing window. Refer to figure below:



packet display filter

- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. What version of HTTP is the server running?

No.	Time	Source	Destination	Protocol	Length	Info
10	4.694850	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-1.html HTTP/1.1
12	4.718993	128.119.245.12	192.168.1.102	HTTP	439	HTTP/1.1 200 OK (text/html)
13	4.724332	192.168.1.102	128.119.245.12	HTTP	541	GET /favicon.ico HTTP/1.1
14	4.750366	128.119.245.12	192.168.1.102	HTTP	1395	HTTP/1.1 404 Not Found (text/html)

HTTP 1.1

2. What is the IP address of the client computer?

No.	Time	Source	Destination	Protocol	Length	Info
10	4.694850	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-1.html HTTP/1.1
12	4.718993	128.119.245.12	192.168.1.102	HTTP	439	HTTP/1.1 200 OK (text/html)
13	4.724332	192.168.1.102	128.119.245.12	HTTP	541	GET /favicon.ico HTTP/1.1
14	4.750366	128.119.245.12	192.168.1.102	HTTP	1395	HTTP/1.1 404 Not Found (text/html)

192.168.1.102

3. What is the IP address of the gaia.cs.umass.edu server?

No.	Time	Source	Destination	Protocol	Length	Info
10	4.694850	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-1.html HTTP/1.1
12	4.718993	128.119.245.12	192.168.1.102	HTTP	439	HTTP/1.1 200 OK (text/html)
13	4.724332	192.168.1.102	128.119.245.12	HTTP	541	GET /favicon.ico HTTP/1.1
14	4.750366	128.119.245.12	192.168.1.102	HTTP	1395	HTTP/1.1 404 Not Found (text/html)

128.119.245.12

4. How many bytes of content are being returned to client browser?

✓ Hypertext Transfer Protocol

```
> HTTP/1.1 200 OK\r\n
  Date: Tue, 23 Sep 2003 05:29:50 GMT\r\n
  Server: Apache/2.0.40 (Red Hat Linux)\r\n
  Last-Modified: Tue, 23 Sep 2003 05:29:00 GMT\r\n
  ETag: "1bfed-49-79d5bf00"\r\n
  Accept-Ranges: bytes\r\n
  > Content-Length: 73\r\n
  Keep-Alive: timeout=10, max=100\r\n
  Connection: Keep-Alive\r\n
  Content-Type: text/html; charset=ISO-8859-1\r\n
  \r\n
  [Request in frame: 10]
  [Time since request: 0.024143000 seconds]
  [Request URI: /ethereal-labs/lab2-1.html]
```

73 bytes

✓ Hypertext Transfer Protocol

```
> HTTP/1.1 404 Not Found\r\n
  Date: Tue, 23 Sep 2003 05:29:50 GMT\r\n
  Server: Apache/2.0.40 (Red Hat Linux)\r\n
  Vary: accept-language\r\n
  Accept-Ranges: bytes\r\n
  > Content-Length: 1071\r\n
  Keep-Alive: timeout=10, max=99\r\n
  Connection: Keep-Alive\r\n
  Content-Type: text/html; charset=ISO-8859-1\r\n
  \r\n
  [Request in frame: 13]
  [Time since request: 0.026034000 seconds]
  [Request URI: /favicon.ico]
```

1071 bytes

5. What is the status code returned from the server to client browser?

No.	Time	Source	Destination	Protocol	Length	Info
10	4.694850	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-1.html HTTP/1.1
12	4.718993	128.119.245.12	192.168.1.102	HTTP	439	HTTP/1.1 200 OK (text/html)
13	4.724332	192.168.1.102	128.119.245.12	HTTP	541	GET /favicon.ico HTTP/1.1
14	4.750366	128.119.245.12	192.168.1.102	HTTP	1395	HTTP/1.1 404 Not Found (text/html)

200 OK and 404 Not Found

B.2 The HTTP CONDITIONAL GET/response interaction

- Open packet trace file **lab1-http-B02.pcapng**.
- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. Inspect the contents of the first HTTP GET request from your browser to the server. Do you see an “IF-MODIFIED-SINCE” line in the HTTP GET?

```
▼ Hypertext Transfer Protocol
  > GET /ethereal-labs/lab2-2.html HTTP/1.1\r\n
    Host: gaia.cs.umass.edu\r\n
    User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.0.2) Gecko/20021120 Netscape/7.01\r\n
    Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,video/x-mng,:\n
    Accept-Language: en-us, en;q=0.50\r\n
    Accept-Encoding: gzip, deflate, compress;q=0.9\r\n
    Accept-Charset: ISO-8859-1, utf-8;q=0.66, *;q=0.66\r\n
    Keep-Alive: 300\r\n
    Connection: keep-alive\r\n
    \r\n
    [Response in frame: 10]
    [Full request URI: http://gaia.cs.umass.edu/ethereal-labs/lab2-2.html]
```

There is no “IF-MODIFIED-SINCE” line in the first HTTP GET.

2. Inspect the contents of the server response after the first GET request from client. Did the server explicitly return the contents of the file? How can you tell?

No.	Time	Source	Destination	Protocol	Length	Info
8	2.331268	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-2.html HTTP/1.1
10	2.357902	128.119.245.12	192.168.1.102	HTTP	739	HTTP/1.1 200 OK (text/html)
14	5.517390	192.168.1.102	128.119.245.12	HTTP	668	GET /ethereal-labs/lab2-2.html HTTP/1.1
15	5.540216	128.119.245.12	192.168.1.102	HTTP	243	HTTP/1.1 304 Not Modified

The status code 200 OK show the server explicitly return the contents of the file.

```
▼ Line-based text data: text/html (10 lines)
  \n
  <html>\n
  \n
  Congratulations again! Now you've downloaded the file lab2-2.html. <br>\n
  This file's last modification date will not change. <p>\n
  Thus if you download this multiple times on your browser, a complete copy <br>\n
  will only be sent once by the server due to the inclusion of the IN-MODIFIED-SINCE<br>\n
  field in your browser's HTTP GET request to the server.\n
  \n
  </html>\n
```

This is the content of the server response after the first GET request from client.

- Now inspect the contents of the second HTTP GET request from your browser to the server. Do you see an “IF-MODIFIED-SINCE:” line in the HTTP GET? If so, what information follows the “IF-MODIFIED-SINCE:” header?

```

v Hypertext Transfer Protocol
  > GET /ethereal-labs/lab2-2.html HTTP/1.1\r\n
    Host: gaia.cs.umass.edu\r\n
    User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.0.2) Gecko/20021120 Netscape/7...
    Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,video/x-...
    Accept-Language: en-us, en;q=0.50\r\n
    Accept-Encoding: gzip, deflate, compress;q=0.9\r\n
    Accept-Charset: ISO-8859-1, utf-8;q=0.66, *;q=0.66\r\n
    Keep-Alive: 300\r\n
    Connection: keep-alive\r\n
    If-Modified-Since: Tue, 23 Sep 2003 05:35:00 GMT\r\n
    If-None-Match: "1bfef-173-8f4ae900"\r\n
    Cache-Control: max-age=0\r\n
    \r\n
    [Response in frame: 15]
    [Full request URI: http://gaia.cs.umass.edu/ethereal-labs/lab2-2.html]

```

Yes. The “IF-MODIFIED-SINCE” line is shown in the second HTTP GET. The information follows is “Tue, 23 Sep 2003 05:35:00”.

- What is the HTTP status code and phrase returned from the server in response to this second HTTP GET? Did the server explicitly return the contents of the file? Explain.

No.	Time	Source	Destination	Protocol	Length	Info
8	2.331268	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-2.html HTTP/1.1
10	2.357902	128.119.245.12	192.168.1.102	HTTP	739	HTTP/1.1 200 OK (text/html)
14	5.517390	192.168.1.102	128.119.245.12	HTTP	668	GET /ethereal-labs/lab2-2.html HTTP/1.1
15	5.540216	128.119.245.12	192.168.1.102	HTTP	243	HTTP/1.1 304 Not Modified

303 Not Modified. The server did not explicitly return contents of file as it shown “Not Modified”. This means the server did not send the updated content of the file.

B.3 HTML Documents with Embedded Objects

- Open packet trace file **lab1-http-B03.pcapng**.
- By looking at the information in the HTTP GET and response messages, answer the following questions:

1. How many HTTP GET request messages did client browser send?

No.	Time	Source	Destination	Protocol	Length	Info
10	7.236929	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-4.html HTTP/1.1
12	7.260813	128.119.245.12	192.168.1.102	HTTP	1057	HTTP/1.1 200 OK (text/html)
17	7.305485	192.168.1.102	165.193.123.218	HTTP	625	GET /catalog/images/pearson-logo-footer.gif HTTP/1.1
20	7.308803	192.168.1.102	134.241.6.82	HTTP	609	GET /~kurose/cover.jpg HTTP/1.1
25	7.333054	165.193.123.218	192.168.1.102	HTTP	912	HTTP/1.1 200 OK (GIF89a)
54	7.589877	134.241.6.82	192.168.1.102	HTTP	1096	HTTP/1.0 200 Document follows (JPEG JFIF image)

3 HTTP GET request messages sent

2. To which Internet addresses were these GET requests sent?

No.	Time	Source	Destination	Protocol	Length	Info
10	7.236929	192.168.1.102	128.119.245.12	HTTP	555	GET /ethereal-labs/lab2-4.html HTTP/1.1
12	7.260813	128.119.245.12	192.168.1.102	HTTP	1057	HTTP/1.1 200 OK (text/html)
17	7.305485	192.168.1.102	165.193.123.218	HTTP	625	GET /catalog/images/pearson-logo-footer.gif HTTP/1.1
20	7.308803	192.168.1.102	134.241.6.82	HTTP	609	GET /~kurose/cover.jpg HTTP/1.1
25	7.333054	165.193.123.218	192.168.1.102	HTTP	912	HTTP/1.1 200 OK (GIF89a)
54	7.589877	134.241.6.82	192.168.1.102	HTTP	1096	HTTP/1.0 200 Document follows (JPEG JFIF image)

128.119.245.12, 165.193.123.218, 134.241.6.82

3. How many bytes of content are being returned to client browser for the **pearson-logo-footer.gif** image file?

```
> Frame 25: 912 bytes on wire (7296 bits), 912 bytes captured (7296 bits) on interface unknown, id 0
> Ethernet II, Src: LinksysGroup_da:af:73 (00:06:25:da:af:73), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
> Internet Protocol Version 4, Src: 165.193.123.218, Dst: 192.168.1.102
> Transmission Control Protocol, Src Port: 80, Dst Port: 4308, Seq: 2761, Ack: 572, Len: 858
> [3 Reassembled TCP Segments (3618 bytes): #22(1380), #23(1380), #25(858)]
✓ Hypertext Transfer Protocol
  > HTTP/1.1 200 OK\r\n
    Server: Netscape-Enterprise/3.6 SP3\r\n
    Date: Sun, 21 Sep 2003 06:00:35 GMT\r\n
    Content-type: image/gif\r\n
    Etag: "6fc149-d1d-3ef0b3f8"\r\n
    Last-modified: Wed, 18 Jun 2003 18:48:24 GMT\r\n
  > Content-length: 3357\r\n
    Accept-ranges: bytes\r\n
    Connection: keep-alive\r\n
```

3357 bytes

4. How many bytes of content are being returned to client browser for the **cover.jpg** image file?

No.	Time	Source	Destination	Protocol	Length	Details
54	7.589877	134.241.6.82	192.168.1.102	HTTP	1096	HTTP/1.0 200 Document follows (JPEG JFIF image)
55	7.589918	192.168.1.102	134.241.6.82	TCP	54	4309 → 80 [ACK] Seq=556 Ack=15829 Win=64240 Len=0
56	7.601393	192.168.1.102	134.241.6.82	TCP	54	4309 → 80 [FIN, ACK] Seq=556 Ack=15829 Win=64240 Len=0
57	7.620277	134.241.6.82	192.168.1.102	TCP	60	80 → 4309 [ACK] Seq=15829 Ack=557 Win=49151 Len=0
58	9.055897	192.168.1.102	192.168.1.104	SNMP	92	get-request 1.3.6.1.4.1.11.2.3.9.4.2.1.2.2.2.1.0


```

> Frame 54: 1096 bytes on wire (8768 bits), 1096 bytes captured (8768 bits) on interface unknown, id 0
> Ethernet II, Src: LinksysGroup_da:af:73 (00:06:25:da:af:73), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
> Internet Protocol Version 4, Src: 134.241.6.82, Dst: 192.168.1.102
> Transmission Control Protocol, Src Port: 80, Dst Port: 4309, Seq: 14786, Ack: 556, Len: 1042
> [18 Reassembled TCP Segments (15827 bytes): #29(31), #30(37), #32(20), #33(46), #35(26), #36(23), #38
  > Hypertext Transfer Protocol
    > HTTP/1.0 200 Document follows\r\n
      Date: Tue, 23 Sep 2003 05:38:44 GMT\r\n
      Server: NCSA/1.5.2\r\n
      Last-modified: Tue, 23 Sep 2003 04:56:38 GMT\r\n
      Content-type: image/jpeg\r\n
      Content-length: 15642\r\n
  > Frame 54: 1096 bytes on wire (8768 bits), 1096 bytes captured (8768 bits) on interface unknown, id 0
> Ethernet II, Src: LinksysGroup_da:af:73 (00:06:25:da:af:73), Dst: Dell_4f:36:23 (00:08:74:4f:36:23)
> Internet Protocol Version 4, Src: 134.241.6.82, Dst: 192.168.1.102
> Transmission Control Protocol, Src Port: 80, Dst Port: 4309, Seq: 14786, Ack: 556, Len: 1042
> [18 Reassembled TCP Segments (15827 bytes): #29(31), #30(37), #32(20), #33(46), #35(26), #36(23), #38
  > Hypertext Transfer Protocol
    > HTTP/1.0 200 Document follows\r\n
      Date: Tue, 23 Sep 2003 05:38:44 GMT\r\n
      Server: NCSA/1.5.2\r\n
      Last-modified: Tue, 23 Sep 2003 04:56:38 GMT\r\n
      Content-type: image/jpeg\r\n
      Content-length: 15642\r\n
  
```


15642 bytes

PART C: DNS Trace

1.0 nslookup

nslookup tool allows the host running the tool to query any specified DNS server for a DNS record. The queried DNS server can be a root DNS server, a top-level-domain DNS server, an authoritative DNS server, or an intermediate DNS server. To accomplish this task, nslookup sends a DNS query to the specified DNS server, receives a DNS reply from that same DNS server, and displays the result.

- To run it in Windows, open the Command Prompt (cmd) and run nslookup on the command line as shown in Figure C.1 and Figure C.2



```
C:\WINDOWS\system32\cmd.exe

C:\Users\pc-vastro220>nslookup yahoo.com
Server: ns1.utm.my
Address: 161.139.250.2


Non-authoritative answer:
Name: yahoo.com
Addresses: 2001:4998:58:1836::11
           2001:4998:c:1023::4
           2001:4998:44:41d::4
           2001:4998:44:41d::3
           2001:4998:58:1836::10
           2001:4998:c:1023::5
           72.30.35.10
           98.137.246.7
           98.137.246.8
           98.138.219.231
           98.138.219.232
           72.30.35.9

C:\Users\pc-vastro220>nslookup -type=any yahoo.com
Server: jlb.utm.my
Address: 161.139.250.2

Non-authoritative answer:
yahoo.com      MX preference = 1, mail exchanger = mta5.am0.yahoodns.net
yahoo.com      MX preference = 1, mail exchanger = mta6.am0.yahoodns.net
yahoo.com      MX preference = 1, mail exchanger = mta7.am0.yahoodns.net
yahoo.com      AAAA IPv6 address = 2001:4998:c:1023::4
yahoo.com      AAAA IPv6 address = 2001:4998:44:41d::4
yahoo.com      AAAA IPv6 address = 2001:4998:44:41d::3
yahoo.com      AAAA IPv6 address = 2001:4998:58:1836::10
yahoo.com      AAAA IPv6 address = 2001:4998:c:1023::5
yahoo.com      AAAA IPv6 address = 2001:4998:58:1836::11
yahoo.com      nameserver = ns5.yahoo.com
yahoo.com      nameserver = ns2.yahoo.com
yahoo.com      nameserver = ns4.yahoo.com
yahoo.com      nameserver = ns1.yahoo.com
yahoo.com      nameserver = ns3.yahoo.com
yahoo.com      internet address = 98.137.246.7
yahoo.com      internet address = 98.137.246.8
yahoo.com      internet address = 98.138.219.231
yahoo.com      internet address = 98.138.219.232
yahoo.com      internet address = 72.30.35.9
yahoo.com      internet address = 72.30.35.10

C:\Users\pc-vastro220>
```

Figure C.1: nslookup result



```
C:\WINDOWS\system32\cmd.exe

C:\Users\pc-vastro220>nslookup google.com ns1.time.net.my
Server: ns1.test.time.net.my
Address: 203.121.16.85


Non-authoritative answer:
Name: google.com
Addresses: 2404:6800:4001:804::200e
           172.217.24.174

C:\Users\pc-vastro220>
```

Figure C.2: nslookup result


1. Run nslookup to obtain the IP address of a www.microsoft.com server. What is the IP address of that server? Add screenshot to your answer.

```
C:\Users\chaury>nslookup www.microsoft.com
Server: ns1.utm.my
Address: 161.139.250.2
Non-authoritative answer:
Name: e13678.dscb.akamaiedge.net
Addresses: 2600:1413:a000:7b3::356e
           2600:1413:a000:790::356e
           2600:1413:a000:7ad::356e
           2600:1413:a000:78d::356e
           2600:1413:a000:7b9::356e
           184.25.249.172
Aliases: www.microsoft.com
          www.microsoft.com-c-3.edgekey.net
          www.microsoft.com-c-3.edgekey.net.globalredir.akadns.net
```



2. Run nslookup to determine the non-authoritative DNS servers for domain microsoft.com. Add screenshot to your answer.


```
C:\Users\chaury>nslookup www.microsoft.com
Server: ns1.utm.my
Address: 161.139.250.2
Non-authoritative answer:
Name: e13678.dscb.akamaiedge.net
Addresses: 2600:1413:a000:7b3::356e
           2600:1413:a000:790::356e
           2600:1413:a000:7ad::356e
           2600:1413:a000:78d::356e
           2600:1413:a000:7b9::356e
           184.25.249.172
Aliases: www.microsoft.com
          www.microsoft.com-c-3.edgekey.net
          www.microsoft.com-c-3.edgekey.net.globalredir.akadns.net
```



2.0 ipconfig

ipconfig can be used to show your current TCP/IP information, including your address, DNS server addresses, adapter type and so on.

- Information about host, use the following command: ipconfig /all



```
C:\WINDOWS\system32\cmd.exe
Description . . . . . : TAP-ProtonVPN Windows Adapter V9
Physical Address. . . . . : 00-FF-AA-18-73-0D
DHCP Enabled. . . . . : Yes
Autoconfiguration Enabled . . . . : Yes

Ethernet adapter Ethernet:


    Connection-specific DNS Suffix  . : utm.my
    Description . . . . . : Realtek PCIe GbE Family Controller
    Physical Address. . . . . : 00-24-E8-23-E3-3A
    DHCP Enabled. . . . . : Yes
    Autoconfiguration Enabled . . . . : Yes
    Link-local IPv6 Address . . . . . : fe80::b8c5:7857:8b37:ddfe%4(Preferred)
    IPv4 Address. . . . . : 10.60.82.216(Preferred)
    Subnet Mask . . . . . : 255.255.252.0
    Lease Obtained. . . . . : Tuesday, September 18, 2018 6:08:09 AM
    Lease Expires . . . . . : Thursday, September 20, 2018 6:08:10 AM
    Default Gateway . . . . . : 10.60.80.1
    DHCP Server . . . . . : 10.60.80.1
    DHCPv6 IAID . . . . . : 33563880
    DHCPv6 Client DUID. . . . . : 00-01-00-01-1F-D8-2F-7E-00-24-E8-23-E3-3A
    DNS Servers . . . . . : 161.139.250.2
                           161.139.168.168
    NetBIOS over Tcpip. . . . . : Enabled

Ethernet adapter Ethernet 2:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :
    Description . . . . . : TAP-Windows Adapter V9
```

Figure C.3: ipconfig /all result

- ipconfig is also very useful for managing the DNS information stored in your host. Each entry shows the remaining Time to Live (TTL) in seconds.
Command: ipconfig /displaydns



```
C:\WINDOWS\system32\cmd.exe
Record Name . . . . . : wpad.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 5917
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.163.188

-----
Record Name . . . . . : aimswb.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 16483
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.18.215

-----
Record Name . . . . . : my.utm.my
Record Type . . . . . : 1
Time To Live . . . . . : 16484
Data Length . . . . . : 4
Section . . . . . : Answer
A (Host) Record . . . : 161.139.20.240

C:\Users\pc-vastro220>
```

Figure C.4: ipconfig /displaydns result

- Flushing the DNS cache clears all entries and reloads the entries from the hosts file.

Command: ipconfig /flushdns



```
C:\WINDOWS\system32\cmd.exe
C:\Users\pc-vastro220>ipconfig /flushdns
Windows IP Configuration
Successfully flushed the DNS Resolver Cache.
C:\Users\pc-vastro220>
```

Figure C.5: ipconfig /flushdns result

3.0 Tracing DNS with Wireshark

- Open packet trace file dns-trace-1. Answer the following questions.
- 1. Locate the DNS query and response messages. Are then sent over UDP or TCP? Add screenshots in your answer.

▼ Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.23

- 0100 = Version: 4
- 0101 = Header Length: 20 bytes (5)
- > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
- Total Length: 58
- Identification: 0x229e (8862)
- > 000. = Flags: 0x0
- ...0 0000 0000 0000 = Fragment Offset: 0
- Time to Live: 128
- Protocol: UDP (17)
- Header Checksum: 0xd281 [validation disabled]
- [Header checksum status: Unverified]
- Source Address: 128.238.38.160
- Destination Address: 128.238.29.23
- [Stream index: 1]

UDP (Query)

2. What is the destination port for the DNS query message? What is the source port of DNS response message? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A w
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0

> Frame 8: 72 bytes on wire (576 bits), 72 bytes captured (576 bits)

▼ Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-HSRP-routers_00 (00:00:0c:07:ac:00)

> Destination: All-HSRP-routers_00 (00:00:0c:07:ac:00)

> Source: IBM_10:60:99 (00:09:6b:10:60:99)

Type: IPv4 (0x0800)

[Stream index: 5]

▼ Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.23

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 58

Identification: 0x229e (8862)

> 000. = Flags: 0x0

...0 0000 0000 0000 = Fragment Offset: 0

Time to Live: 128

Protocol: UDP (17)

Header Checksum: 0xd281 [validation disabled]

[Header checksum status: Unverified]

Source Address: 128.238.38.160

Destination Address: 128.238.29.23

[Stream index: 1]

> User Datagram Protocol, Src Port: 3163, Dst Port: 53

> Domain Name System (query)

Destination port : 53

No.	Time	Source	Destination	Protocol	Length	Info
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A w
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0

> Frame 9: 104 bytes on wire (832 bits), 104 bytes captured (832 bits)

> Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:99 (00:09:6b:10:60:99)

> Internet Protocol Version 4, Src: 128.238.29.23, Dst: 128.238.38.160

▼ User Datagram Protocol, Src Port: 53, Dst Port: 3163

Source Port: 53

Destination Port: 3163

Length: 70

Checksum: 0xb0ba [unverified]

[Checksum Status: Unverified]

Source port : 53

3. To what IP address is the DNS query message sent? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A www.ietf.org
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0x006e A www.ietf.org A 132.151.6.75 A 65.246.255.51

128.238.29.23

4. Examine the DNS query message. What “Type” of DNS query is it? Does the query message contain any “answers”? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A www.ietf.org
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0x006e A www.ietf.org


```

> Frame 8: 72 bytes on wire (576 bits), 72 bytes captured (576 bits)
> Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-HSRP-routers_00 (00:00:0c:07:ac:00)
> Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.23
> User Datagram Protocol, Src Port: 3163, Dst Port: 53
▼ Domain Name System (query)
  Transaction ID: 0x006e
  > Flags: 0x0100 Standard query
  Questions: 1
  Answer RRs: 0
  Authority RRs: 0
  Additional RRs: 0
  ▼ Queries
    > www.ietf.org: type A, class IN
    [Response In: 9]
  
```

There is no any answer (0 answer)

Type A

5. Examine the DNS response message. How many “answers” are provided? What do each of these answers contain? Add screenshots in your answer.

✓ Domain Name System (response)

Transaction ID: 0x006e

> Flags: 0x8180 Standard query response, No error

Questions: 1

Answer RRs: 2

Authority RRs: 0

Additional RRs: 0

> Queries

✓ Answers

> www.ietf.org: type A, class IN, addr 132.151.6.75

> www.ietf.org: type A, class IN, addr 65.246.255.51

[\[Request In: 8\]](#)

[Time: 0.000844000 seconds]

2 answers

Answer

✓ Answers

✓ www.ietf.org: type A, class IN, addr 132.151.6.75

Name: www.ietf.org

Type: A (1) (Host Address)

Class: IN (0x0001)

Time to live: 1678 (27 minutes, 58 seconds)

Data length: 4

Address: 132.151.6.75

✓ www.ietf.org: type A, class IN, addr 65.246.255.51

Name: www.ietf.org

Type: A (1) (Host Address)

Class: IN (0x0001)

Time to live: 1678 (27 minutes, 58 seconds)

Data length: 4

Address: 65.246.255.51

Answer content

6. Consider the subsequent TCP SYN packet sent by your host. Does the destination IP address of the SYN packet correspond to any of the IP addresses provided in the DNS response message? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
5	1.999786	Cisco_fc:f0:de	Spanning-tree-(for-...	STP	60	Conf. Root = 32768/0/00:01:96:45:05:9a Cost =
6	2.031956	128.238.38.2	224.0.0.2	HSRP	62	Hello (state Active)
7	2.527474	Cisco_83:e4:54	Broadcast	ARP	60	Who has 128.238.38.38? Tell 128.238.38.2
8	3.075845	128.238.38.160	128.238.29.23	DNS	72	Standard query 0x006e A www.ietf.org
9	3.076689	128.238.29.23	128.238.38.160	DNS	104	Standard query response 0x006e A www.ietf.org A
10	3.078479	128.238.38.160	132.151.6.75	TCP	62	3369 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460
11	3.096413	132.151.6.75	128.238.38.160	TCP	62	80 → 3369 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1460
12	3.096463	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=1 Ack=1 Win=64860 Len=0
13	3.096708	128.238.38.160	132.151.6.75	HTTP	429	GET / HTTP/1.1
14	3.111678	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK] Seq=1 Ack=376 Win=6432 Len=0
15	3.120640	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=1 Ack=376 Win=6432 Len=1380
16	3.128893	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=1381 Ack=376 Win=6432 Len=1
17	3.128148	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=2761 Win=64860 Len=0
18	3.148016	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=2761 Ack=376 Win=6432 Len=1

Yes there are correspond IP address

7. This web page contains images. Before retrieving each image, does your host issue new DNS queries?

No.	Time	Source	Destination	Protocol	Length	Info
10	3.078479	128.238.38.160	132.151.6.75	TCP	62	3369 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
11	3.096413	132.151.6.75	128.238.38.160	TCP	62	80 → 3369 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM
12	3.096463	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=1 Ack=1 Win=64860 Len=0
13	3.096708	128.238.38.160	132.151.6.75	HTTP	429	GET / HTTP/1.1
14	3.111678	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK] Seq=1 Ack=376 Win=6432 Len=0
15	3.120640	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=1 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
16	3.128893	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=1381 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
17	3.128148	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=2761 Win=64860 Len=0
18	3.148016	132.151.6.75	128.238.38.160	TCP	1434	80 → 3369 [ACK] Seq=2761 Ack=376 Win=6432 Len=1380 [TCP PDU reassembled in 20]
19	3.148069	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=4141 Win=64860 Len=0
20	3.153211	132.151.6.75	128.238.38.160	HTTP	1055	HTTP/1.1 200 OK (text/html)
21	3.153293	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [ACK] Seq=376 Ack=5143 Win=63859 Len=0
22	3.161867	128.238.38.160	132.151.6.75	TCP	54	3369 → 80 [FIN, ACK] Seq=376 Ack=5143 Win=63859 Len=0
23	3.174716	132.151.6.75	128.238.38.160	TCP	60	80 → 3369 [ACK] Seq=5143 Ack=377 Win=6432 Len=0
24	3.178159	128.238.38.160	132.151.6.75	TCP	62	3370 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
25	3.179283	128.238.38.160	132.151.6.75	TCP	62	3371 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM
26	3.191649	132.151.6.75	128.238.38.160	TCP	62	80 → 3370 [SYN, ACK] Seq=0 Ack=1 Win=5840 Len=0 MSS=1380 SACK_PERM
27	3.191726	128.238.38.160	132.151.6.75	TCP	54	3370 → 80 [ACK] Seq=1 Ack=1 Win=64860 Len=0
28	3.191998	128.238.38.160	132.151.6.75	HTTP	320	GET /images/ietflogo2e.gif HTTP/1.1

No, DNS query will only appear once in the entire tracing. There is no new DNS queries issue by host between line 10 and 27 before retrieving image in line 28.

- Open packet trace file dns-trace-2 for nslookup.
- We see from Wireshark that nslookup actually sent three DNS queries and received three DNS responses. For the purpose of this lab, ignore the first two sets of queries/responses, as they are specific to nslookup and are not normally generated by standard Internet applications. You should instead focus on the last query and response messages.
- Answer the following questions.

8. What is the destination port for the DNS query message? What is the source port of DNS response message? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
15	4.951232	128.238.38.160	128.238.29.22	DNS	86	Standard query 0x0001 PTR
16	4.951638	128.238.29.22	128.238.38.160	DNS	118	Standard query response 0
17	4.952571	128.238.38.160	128.238.29.22	DNS	80	Standard query 0x0002 A w
18	4.952953	128.238.29.22	128.238.38.160	DNS	139	Standard query response 0
19	4.953172	128.238.38.160	128.238.29.22	DNS	71	Standard query 0x0003 A w
20	4.969929	128.238.29.22	128.238.38.160	DNS	196	Standard query response 0

> Frame 19: 71 bytes on wire (568 bits), 71 bytes captured (568 bits)
 > Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-HSRP-routers_00 (00:00:0c:07:ac:00)
 > Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.22
 > User Datagram Protocol, Src Port: 3742, Dst Port: 53
 > Domain Name System (query)

Destination port for query message

No.	Time	Source	Destination	Protocol	Length	Info
15	4.951232	128.238.38.160	128.238.29.22	DNS	86	Standard query 0x0001 PTR
16	4.951638	128.238.29.22	128.238.38.160	DNS	118	Standard query response 0:
17	4.952571	128.238.38.160	128.238.29.22	DNS	80	Standard query 0x0002 A w
18	4.952953	128.238.29.22	128.238.38.160	DNS	139	Standard query response 0:
19	4.953172	128.238.38.160	128.238.29.22	DNS	71	Standard query 0x0003 A w
20	4.969929	128.238.29.22	128.238.38.160	DNS	196	Standard query response 0:

> Frame 20: 196 bytes on wire (1568 bits), 196 bytes captured (1568 bits)
 > Ethernet II, Src: Cisco_83:e4:54 (00:b0:8e:83:e4:54), Dst: IBM_10:60:99 (00:09:6b:10:60:99)
 > Internet Protocol Version 4, Src: 128.238.29.22, Dst: 128.238.38.160
 > User Datagram Protocol, Src Port: 53, Dst Port: 3742
 > Domain Name System (response)

Source port for response message

9. To what IP address is the DNS query message sent? Is this the IP address of your default local DNS server? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
15	4.951232	128.238.38.160	128.238.29.22	DNS	86	Standard query 0x0001 PTR 22.29.238.128.in-addr.arpa
16	4.951638	128.238.29.22	128.238.38.160	DNS	118	Standard query response 0x0001 PTR 22.29.238.128.in-addr.arpa
17	4.952571	128.238.38.160	128.238.29.22	DNS	80	Standard query 0x0002 A www.mit.edu.poly.edu
18	4.952953	128.238.29.22	128.238.38.160	DNS	139	Standard query response 0x0002 No such name A www.mit.edu
19	4.953172	128.238.38.160	128.238.29.22	DNS	71	Standard query 0x0003 A www.mit.edu
20	4.969929	128.238.29.22	128.238.38.160	DNS	196	Standard query response 0x0003 A www.mit.edu A 18.7.22.1

DNS query send to this IP address

```

*** ns1.utm.my can't find ipconfig/all: Non-existent domain
> ipconfig/displaydns
Server: ns1.utm.my
Address: 161.139.250.2
  
```

The destination IP address is different IP address with my default local DNS server.

10. Examine the DNS query message. What “Type” of DNS query is it? Does the query message contain any “answers”? Add screenshots in your answer.

No.	Time	Source	Destination	Protocol	Length	Info
15	4.951232	128.238.38.160	128.238.29.22	DNS	86	Standard query 0x0001 PTR
16	4.951638	128.238.29.22	128.238.38.160	DNS	118	Standard query response 0x0001 PTR
17	4.952571	128.238.38.160	128.238.29.22	DNS	80	Standard query 0x0002 A www
18	4.952953	128.238.29.22	128.238.38.160	DNS	139	Standard query response 0x0002 A www
19	4.953172	128.238.38.160	128.238.29.22	DNS	71	Standard query 0x0003 A www
20	4.969929	128.238.29.22	128.238.38.160	DNS	196	Standard query response 0x0003 A www

```

> Frame 19: 71 bytes on wire (568 bits), 71 bytes captured (568 bits) on interface 0
> Ethernet II, Src: IBM_10:60:99 (00:09:6b:10:60:99), Dst: All-HSRP-routers_00 (00:00:0c:07:ac:00)
> Internet Protocol Version 4, Src: 128.238.38.160, Dst: 128.238.29.22
> User Datagram Protocol, Src Port: 3742, Dst Port: 53
  
```

Domain Name System (query)

Transaction ID: 0x0003

Flags: 0x0100 Standard query

Questions: 1

Answer RRs: 0

Authority RRs: 0

Additional RRs: 0

Queries

> www.mit.edu: type A, class IN

[Response In: 20]

There is no any answer
(0 answer)

Type A queries

11. Examine the DNS response message. How many “answers” are provided? What do each of these answers contain? Add screenshots in your answer.

The screenshot displays a DNS response message structure. A red dashed box highlights the 'Questions' and 'Answers' sections. A blue box labeled '1 answer' has a red arrow pointing to the 'Answer RRs: 1' line. Another blue box labeled 'Answer content' has a red arrow pointing to the 'Address: 18.7.22.83' line.

```

Domain Name System (response)
  Transaction ID: 0x0003
  > Flags: 0x8580 Standard query response, No error
  Questions: 1
  Answer RRs: 1
  Authority RRs: 3
  Additional RRs: 3
  > Queries
  > Answers
    > www.mit.edu: type A, class IN, addr 18.7.22.83
      Name: www.mit.edu
      Type: A (1) (Host Address)
      Class: IN (0x0001)
      Time to live: 60 (1 minute)
      Data length: 4
      Address: 18.7.22.83

```