

Jay Ambe PG Live Server + MySQL Setup Guide

Required Stack

- Node.js
- React
- MySQL 8+
- Bootstrap
- Tailwind CSS

Frontend Build

1. Open terminal in 'payingguest'.
2. Install dependencies:
 'npm install'
3. Build React:
 'npm run build'
4. Upload the 'build' folder to your live hosting panel or serve it using Node/Nginx/Apache.

MySQL Setup

1. Create a MySQL database on the live server.
2. Recommended database name: 'jay_ambe_pg'.
3. Import this SQL file:
 'database/mysql/jay_ambe_pg_schema.sql'
4. Confirm these important tables exist:
 'students', 'admissions', 'buildings', 'floors', 'rooms', 'room_items', 'allocations',
 'payments', 'expenses', 'inquiries', 'support_tickets', 'invoices', 'calendar_events',
 'staff', 'roles', 'admins'.

Environment Variables

Create '.env' from '.env.example'.

Required values:

- 'REACT_APP_API_BASE_URL'
- 'MYSQL_HOST'
- 'MYSQL_PORT'
- 'MYSQL_DATABASE'
- 'MYSQL_USER'
- 'MYSQL_PASSWORD'

Optional payment/message values:

- 'RAZORPAY_KEY_ID'
- 'RAZORPAY_KEY_SECRET'
- 'WHATSAPP_PROVIDER'
- 'WHATSAPP_ACCESS_TOKEN'
- 'WHATSAPP_PHONE_NUMBER_ID'

Login

Frontend local-storage demo login:

- Username: 'superadmin'
- Password: 'admin123'

Live backend login should use the 'admins' table with bcrypt password hashes.

Important URLs

- '/' redirects to '/pg/login'
- '/pg/login' is the PG login page
- '/pg' is the main dashboard

Deployment Notes

- Browser React code must not connect directly to MySQL.
- Create a Node.js API between React and MySQL.
- Replace localStorage helper functions in 'src/pgadmin/Utils' with API calls when the backend is ready.
- Keep uploaded files outside React source, then save paths in MySQL.